



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : B41J 2/09, 2/095	A1	(11) International Publication Number: WO 00/38930 (43) International Publication Date: 6 July 2000 (06.07.00)
(21) International Application Number: PCT/JP99/07217 (22) International Filing Date: 22 December 1999 (22.12.99) (30) Priority Data: 10/369169 25 December 1998 (25.12.98) JP (71) Applicant (for all designated States except US): MAT-SUSHITA ELECTRIC INDUSTRIAL CO., LTD. [JP/JP]; 1006, Oaza Kadoma, Kadoma-shi, Osaka 571-8501 (JP). (72) Inventors; and (75) Inventors/Applicants (for US only): MATSUI, Masatomo [JP/JP]; 554-5, Oomachi, Saijo-shi, Ehime 793-0030 (JP). BANDO, Katsuhiko [JP/JP]; 1727-2, Hagyu, Niihama-shi, Ehime 792-0050 (JP). KOUYAMA, Yoshihisa [JP/JP]; 518-5, Kitadai, Toyo-shi, Ehime 799-1343 (JP). SONE, Koji [JP/JP]; 1942-33, Oojoin, Niihama-shi, Ehime 792-0060 (JP). SEO, Naoyuki [JP/JP]; 813-1, Oomachi, Saijo-shi, Ehime 793-0030 (JP). (74) Agents: IWAHASHI, Fumio et al.; Matsushita Electric Industrial Co., Ltd., 1006, Oaza Kadoma, Kadoma-shi, Osaka 571-8501 (JP).		(81) Designated States: CN, ID, KR, SG, US. Published <i>With international search report.</i>
(54) Title: INK JET RECORDING APPARATUS		
(57) Abstract		
The present invention relates to an ink jet recording apparatus that prints by ejecting ink onto recording media. The ink jet recording apparatus achieves high density recording on the recording media without narrowing the pitch of nozzle holes. The ink jet recording apparatus charges sprayed ink drops by a charging electrode (5), applies a high voltage on a deflecting electrode (29) placed in a position facing the center of a plurality of nozzle holes (10) disposed in a line, and controls flying paths of the ink drops (18). The ink drops are electrostatically deflected by the high voltage, fly through the flying path converging toward the deflecting electrode, and reach to the recording face. Thus, the ink jet recording apparatus which achieves high density recording can be provided without using narrow pitch nozzle holes, which requires a difficult machining process and is difficult to manufacture.		