

HIGH DENSITY ROW ON ROLLER CONE BIT

PRIORITY CLAIM

This application claims priority to provisional application 60/788,766, filed
5 April 3, 2006.

TECHNICAL FIELD

This invention relates in general to an earth-boring bit cone and in particular to a rolling cone earth-boring bit having a row of teeth that has a higher density than adjacent rows on other cones of the bit.

10 BACKGROUND

Figure 1 illustrates a typical prior art earth-boring bit 11. Bit 11 has a bit body 13 that is threaded at its upper end for connection into a drill string. Bit body 13 has a number of pressure compensating lubricant reservoirs 15. Bit body 13 is also provided with at least one nozzle 17, which discharges drilling fluid from down the drill string to
15 cool bit 11 and wash cuttings produced during drilling out of the borehole.

A plurality of cones 19, 21 are mounted for rotation on cantilevered bearing pins. In this prior art example, there are three cones, but only two are shown. Cones 19, 21 are shown with a plurality of teeth 23, each having a crest 25 that extends parallel with an axis of rotation of each cone 19, 21. During drilling operation, cones
20 19, 21 roll over the bottom of the borehole being drilled while teeth 23 penetrate and disintegrate the earth's formation.

Prior art bits similar to that illustrated in Figure 1 have a shortcoming that becomes particularly apparent during drilling of formations, such as shales, that behave plastically. During drilling of these formations, conventionally arranged teeth 23 tend
25 to fall into indentations made by the same or another tooth 23 on a previous revolution of bit 11. This condition is known as tracking and can seriously impair the penetration rate, life and performance of bit 11.

Another shortcoming of the prior art bit illustrated in Figure 1 is that formation material may become packed between teeth 23, preventing teeth 23 from penetrating
30 the formation deeply and thereby reducing the rate of penetration of bit 11. This condition is known as balling. Balling, like tracking, prevents the teeth 23 from penetrating to full depth, thus resulting in inefficient and costly drilling. Balling also

prevents the force on crests 25 of teeth 23 from reaching the level sufficient to fracture rock.

The characteristics of both tracking and balling are well recognized, but generally are treated as independent problems. In many cases, features that reduce tracking promote balling, and vice versa. For example, balling is more likely to occur between closely spaced teeth. Large and widely spaced teeth are more prone to tracking.

DISCLOSURE OF THE INVENTION

The bit of this invention has a plurality of cones, each having at least one intermediate row of teeth. At least one of the intermediate rows on at least one of the cones is a high density row. The high density row is spaced farther from the bit axis than a closer one of the intermediate rows on at least one of the other cones. The high density row has a lesser pitch than the pitch of the closer one of the intermediate rows.

In the preferred embodiment, each of the teeth of the high density row has a height substantially the same as the height of the teeth of the closer one of the intermediate rows. Each of the teeth of the high density row and the closer one of the intermediate rows has a leading flank and a trailing flank and an included angle therebetween. The included angle of the teeth of the high density row is preferably substantially the same as the included angle of the teeth of the closer one of the intermediate rows. Each of the teeth of the high density row has a leading flank and trailing flank. The leading flank of one tooth in the high density row intersects the trailing flank of an adjacent tooth without any circumferential gaps in the example shown.

In the example shown, at least one of the intermediate rows on one of the cones, other than the cone containing the high density row, is located farther from the bit axis than the high density row and has a pitch greater than the pitch of the high density row. The high density row has more teeth than the closer one of the intermediate rows and the farther one of the intermediate rows. Inner and outer grooves adjoin inner and outer sides of the high density row. Preferably, each groove has a width at least equal to a width of the high density row measured at bases of the teeth of the high density row.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a side elevational view of a prior art earth-boring bit.

Figure 2 is a bottom view of an earth-boring bit constructed in accordance with this invention.

5 Figure 3 is a layout of the earth-boring bit of Figure 2.

BEST MODE(S) FOR CARRYING OUT THE INVENTION

Referring to Figures 2 and 3, cones 27, 29 and 31 are suitable for mounting to an earth-boring bit as shown in Figure 1 in place of the cones illustrated in Figure 1.

10 Cones 27, 29 and 31 have rows of cutting elements, which in this embodiment comprise teeth 32 that are integrally formed in the supporting metal of each cone, such as by milling. In this example, cone 27 has teeth 32 arranged in rows in a conventional manner. These rows include a heel row 33 located adjacent gage surface 35 of cone 27. One or more intermediate rows 37 (only one shown) are spaced inward from heel row

15 33. A spear point 39 defines an innermost row of teeth 32, spear point 39 being formed at the apex or nose of cone 27.

Similarly, cone 29 has teeth 32 arranged in a conventional manner in this example. The rows on cone 29 include a heel row 41, at least one intermediate row 43 (only one shown) and an inner row 45. As shown in the layout of Figure 3,

20 intermediate row 43, also termed farther intermediate row, is located farther from bit axis 30 than intermediate row 37, which is referred to herein as closer intermediate row 37. Inner row 45 is also located farther from bit axis 30 than spear point 39 of cone 27.

In this embodiment, cone 31 is configured in accordance with this invention. Cone 31 has a heel row 47, at least one intermediate row 49 (only one shown), also

25 referred to as high density row 49, and an inner row 51 located in the nose area of the cone. High density row 49 is located closer to bit axis 30 than farther intermediate row 43 and farther from bit axis 30 than closer intermediate row 37. Heel row 47 and inner row 51 may be conventional and constructed as in the prior art. Preferably, high density row 49 differs from the prior art in that it has more teeth 32 than the

30 intermediate row of a comparable prior art bit. Preferably, high density row 49 has more teeth 32 than farther intermediate row 43 and than closer intermediate row 37 and its teeth are more closely spaced to each other.

Each tooth 32 of the intermediate rows 37, 43 and 49 has a base 52 where it joins the supporting metal of the particular cone 27, 29 or 31. In a transverse cross-

section of each tooth 32 where it joins the supporting metal, base 52 would appear to be generally rectangular in this embodiment. Each tooth 32 has an inner side or flank 53 and an outer flank 55 on its inner and outer sides, relative to bit axis 30. Inner and outer flanks 53, 55 converge toward each other from opposite edges of base 52 to a blunt crest 54. As shown in Figure 2, each tooth 32 has a leading flank 57 and a trailing flank 59, considering the direction of rotation of each cone 27, 29, or 31. Leading and trailing flanks 57, 59 converge toward each other from opposite edges of base 52 (Fig. 3) to crest 54. The angle of convergence, or included angle between leading and trailing flanks 57 of each tooth 32 is preferably substantially the same for all of the intermediate rows 37, 43 and 49.

The height H (Fig. 3) of each tooth 32 is considered herein to be the length of a line extending normal to base 52 and intersecting crest 54. Preferably, the heights H of each tooth 32 of the intermediate rows 37, 43 and 49 are substantially the same.

An outer groove 61 joins the outer side of high density row 49 and an inner groove 63 joins the inner side of high density row 49. Inner and outer grooves 61, 63 are conical sections of supporting metal extending around cone 31. Base 52 of each tooth 32 of high density row 49 is substantially flush with inner and outer grooves 61, 63, thus height H for high density row 49 extends from the level of inner and outer grooves 61, 63 to crest 54. The width of each groove 61, 63 is preferably at least equal to the maximum thickness of each tooth 32 of high density row 49. The maximum thickness is the distance at base 52 between inner and outer flanks 53, 55. As shown in Figure 3, high density row 49 of cone 31 intermeshes between intermediate row 37 of cone 27 and intermediate row 43 of cone 29. Farther intermediate row 43 intermeshes within outer groove 61 between heel row 47 and high density row 49 of cone 31. Closer intermediate row 37 intermeshes within inner groove 63 between inner row 51 and high density row 49 of cone 31.

Leading and trailing flanks 57, 59 of adjacent teeth 32 of high density row 49 intersect or join each other, creating a V-shaped valley between adjoining teeth 32. There are no circumferentially extending spaces or gaps between where the leading and trailing flanks 57, 59 of adjacent teeth 32 of high density row 49 join the supporting metal of cone 31. Stated another matter, the bases 52 of adjacent teeth 32 in high density row 49 substantially adjoin each other, without any spaces between. By contrast, bases 52 of adjacent teeth 32 in intermediate rows 37 and 43 of cones 27 and 29 are circumferentially spaced apart from each other. Intermediate row 37 of cone 27

has a circumferentially extending gap between where the leading flank 57 of one tooth 32 and the trailing flank 59 of an adjacent tooth 32 join the supporting metal. Intermediate row 43 of cone 29 has an even larger circumferential gap between each leading flank 57 and trailing flank 59 of adjacent teeth where flanks 57, 59 join the supporting metal.

The pitch P3 is the distance from the center of crest 54 of one tooth 32 to the center of the crest of the adjacent tooth 32 of high density row 49. Pitch P3 is in the range from 25 to 75 percent of pitch P2 of farther intermediate row 43 and 25 to 75 percent of pitch P1 of closer intermediate row 37. In the embodiment shown, pitch P3 is 50 percent of pitch P2 and 50 percent of pitch P1. In cones 27 and 29, there are more teeth in farther intermediate row 43 than closer intermediate row 37 because the diameter of cone 29 is greater at farther intermediate row 43 than the diameter of cone 27 at closer intermediate row 37. Because of the smaller pitch P3, even though the diameter of cone 31 at high density row 49 is less than at the diameter of cone 29 at farther intermediate row 43, there are more teeth 32 in high density row 49 than in farther intermediate row 43. There are more teeth in high density row 49 than closer intermediate row 37 because of the smaller pitch P3 and the greater diameter of cone 31 at high density row 49 than the diameter of cone 27 at closer intermediate row 37. The additional number of teeth 32 in high density row 49 may be up to twice the amount of intermediate rows 37 or 43, depending upon the difference in pitches P1, P2 and P3.

Hardfacing 65 is shown schematically on teeth 32 in the layout of Figure 3 to illustrate the intermeshing engagement of the intermediate rows 37, 43 and 49. During operation, high density row 49 helps to break up tracking or buildup of rock formation occurring between the widely spaced teeth within intermediate rows 37 and 43. The wide inner and outer grooves 61, 63 allow for the sideways displacement of cuttings and resist balling in high density row 49.

While the invention has been shown in only one of its forms, it should be apparent to those skilled in the art that it is not so limited but is susceptible to various changes without departing from the scope of the invention. For example, although each cone is shown with only one intermediate row, the invention is applicable to cones that have more than one intermediate row. In addition, more than one high density row may be employed. The invention is also applicable to bits having tungsten carbide inserts pressed into mating holes in the cones, rather than integrally formed metal teeth.

CLAIMS

1. An earth-boring bit, comprising:
a plurality of cones, each having at least one intermediate row of cutting
5 elements;
at least one of the intermediate rows on at least one of the cones being a high
density row, the high density row being spaced farther from the bit axis than a closer
one of the intermediate rows on at least one of the other cones; and
the high density row having a lesser pitch than a pitch of the closer one of the
10 intermediate rows.
2. The bit according to claim 1, wherein:
each of the cutting elements of the high density row has a height substantially
the same as a height of the cutting elements of the closer one of the intermediate rows.
15
3. The bit according to claim 1, wherein:
each of the cutting elements of the high density row and the closer one of the
intermediate rows has a leading flank and a trailing flank and an included angle
therebetween; and
20 the included angle of the cutting elements of the high density row is
substantially the same as the included angle of the cutting elements of the closer one of
the intermediate rows.
4. The bit according to claim 1, wherein:
25 each of the cutting elements of the high density row has a leading flank and
trailing flank; and
the leading flank of at least one cutting element of the high density row
intersects the trailing flank of an adjacent cutting element.
- 30 5. The bit according to claim 1, wherein:
the pitch of the high density row is in the range from 25 to 75 percent of the
pitch of the closer one of the intermediate rows.

6. The bit according to claim 1, wherein

at least one of the intermediate rows on one of the cones other than the cone containing the high density row is located farther from the bit axis than the high density row and has a pitch greater than the pitch of the high density row.

5

7. The bit according to claim 1, wherein:

a farther one of the intermediate rows on one of the cones other than the cone containing the high density row is located farther from the bit axis than the high density row; and

10 the high density row has more cutting elements than the farther one of the intermediate rows.

8. The bit according to claim 1, wherein:

15 a farther one of the intermediate rows on one of the cones other than the cone containing the high density row is located farther from the bit axis than the high density row and has a pitch greater than the pitch of the high density row; and

the high density row has more cutting elements than the closer one of the intermediate rows and the farther one of the intermediate rows.

20 9. The bit according to claim 1, wherein:

inner and outer grooves adjoin inner and outer sides of the high density row; and

each groove has a width at least equal to a width of the high density row measured at bases of the cutting elements of the high density row.

25

10. An earth-boring bit, comprising:

a plurality of cones, each having at least one intermediate row of cutting elements;

30 at least one of the intermediate rows on at least one of the cones being a high density row, the high density row being spaced closer to the bit axis than a farther one of the intermediate rows on at least one of the other cones; and

the high density row having more cutting elements than the farther one of the intermediate rows.

11. The bit according to claim 10, wherein:

each of the cutting elements of the high density row has a height substantially the same as the height of the cutting elements of the farther one of the intermediate rows.

5

12. The bit according to claim 10, wherein:

each of the cutting elements of the high density row and the farther one of the intermediate rows has a leading flank and a trailing flank and an included angle therebetween; and

10 the included angle of the cutting elements of the high density row is substantially the same as the included angle of the cutting elements of the farther one of the intermediate rows.

13. The bit according to claim 10, wherein:

15 each of the cutting elements of the high density row has a leading flank and trailing flank; and

the leading flank of at least one cutting element intersects the trailing flank of an adjacent cutting element without any circumferential gap therebetween.

20 14. The bit according to claim 10, wherein

at least one of the intermediate rows on one of the cones other than the cone containing the high density row is located closer to the bit axis than the high density row and has a pitch greater than a pitch of the high density row.

25 15. An earth-boring bit, comprising:

three rotatable cones, each having a nose area and a gage area with a heel row of cutting elements adjacent the gage area;

a farther intermediate row of cutting elements between the heel row and the nose area on at least one of the cones;

30 a closer intermediate row of cutting elements between the heel row and the nose area on another one of the cones and located closer to an axis of rotation of the bit than the farther intermediate row;

a high density row of cutting elements located between the heel row and the nose area of still another of the cones, the high density row being located closer to the

axis of rotation of the bit than the farther intermediate row and farther from the axis of rotation of the bit than the closer intermediate row; and

the high density row having more cutting elements than the closer intermediate row and the farther intermediate row.

5

16. The bit according to claim 15, wherein:

each cutting element of the farther intermediate row, the closer intermediate row, and the high density row has a base where it joins supporting metal of the cone, a crest at its tip, and a height measured from the base to the crest; and

10 the heights of each of the cutting elements of the farther intermediate row, the closer intermediate row and the high density row are substantially the same.

17. The bit according to claim 15, wherein:

15 each cutting element of the high density row has a base where it joins supporting metal of the cone and a thickness measured between an outer side and an inner side of the cutting element at the base; and

inner and outer grooves adjoin inner and outer sides of the high density row, each of the grooves having a width at least equal to the thickness of each of the cutting elements of the high density row.

20

18. The bit according to claim 15, wherein:

each of the cutting elements of the closer intermediate row, the farther intermediate row, and the high density row has a leading flank and a trailing flank and an included angle therebetween; and

25 the included angle of the cutting elements of the high density row is substantially the same as the included angle of the cutting elements of the closer and farther intermediate rows.

19. The bit according to claim 15, wherein:

30 each of the cutting elements of the high density row has a leading flank and a trailing flank; and

the leading flank and trailing flanks of adjacent cutting elements of the high density row join each other without any circumferential gaps therebetween.

20. The bit according to claim 14, wherein:

the high density row has a smaller pitch between its cutting elements than a pitch of the closer intermediate row and a pitch of the farther intermediate row.