

MECHANICAL LOCKING SYSTEM FOR BUILDING PANELS

Technical field

The disclosure relates to the field of mechanical locking systems for building
5 panels, especially furniture components with mechanical locking systems, which
are intended to lock perpendicularly or in parallel to each other.

Field of application of the invention

Embodiments of the present invention are particularly suitable for use in furniture
components, which are preferably formed of sheet shaped panels and which are
10 joined mechanically with a locking system integrated with the panel, i.e. mounted
at the factory, The following description of known technology, problems of known
systems and objects and features of the invention will therefore, as a non
restrictive example, be aimed above all at this field of application and in
particular at furniture components formed as rectangular or square panels
15 intended to be mechanically joined on one pair of opposite edges
perpendicularly or parallel to other adjacent panels.

It should be emphasised that the invention can be applied to any type of sheet
shaped panel such as for example wood based HDF, particle board and
plywood, plastic sheet shaped materials, mineral fibre and metal based
20 materials, stone and ceramics and similar. It may be used to assemble and
disassemble furniture components, floor panels and elements for packaging
boxes and similar. It may also be used to lock and unlock components, which for
example have a cylinder form such as table legs.

Background of the invention

25 Furniture such as kitchen cabinets, bookshelves, drawers, tables and similar are
generally supplied as flat components in order to save transportation costs. The
customer must assemble them. Several methods are used to assemble such
furniture components for example glue, spikes, screws and similar. Snapping
connections comprising plastic components are widely used to connect for
30 example drawers. It is an advantage if assembled furniture components may be
disassembled partly or completely again in a simple way. Mistakes during
assembly may be corrected and furniture may be dissembled again to flat
components in connection with transportation from one apartment to another. A

simple and easy disassembly is an advantage even in the case when furniture components are factory assembled.

Known technology and problems thereof

It is known from WO 2012/154113 that furniture components may be locked mechanically with a perpendicular snap action. Figure 1a shows a first 1 and a second 2 panel. The first panel 1 comprises a groove 6, formed in the panel core 7. An insertion groove 4 formed in one of the groove walls comprises a flexible tongue 3 that locks into a tongue groove 5 when an edge of the second panel 2 is displaced into the groove 6. Figure 1b shows a known flexible bristle tongue 3, which is used to connect floor panels. Such a tongue is also used to connect furniture components. The tongue 3 comprises flexible protrusions 8 that bend in the length direction of the tongue and that displace the tongue in the insertion groove 4 during the snap action. Figure 1b shows the tongue 3 in the outer locked position.

Figure 1c and 1d show that the locking system may be disassembled. A rod shaped stick 9 is inserted into the tongue groove 3 sideways. The flexible tongue 3 is pushed back into the insertion groove 4 and the second panel 2 may be released from the first panel 1.

The main problem with such disassembly is that the rod shaped stick 9 must be turned in a correct position and must be inserted precisely into the tongue groove 5. A disassembly is not possible if the rod shaped stick is inserted into the insertion groove 4.

Summary of the invention

A basic objective of embodiments of the present invention is to simplify disassembly of panels that are locked perpendicularly to each other with a flexible tongue.

The above objects of embodiments of the invention are achieved wholly or partly by a mechanical locking system and panels, according to the independent claims that provide a stronger and easier locking and unlocking. Embodiments of the invention are evident from the dependent claims and from the description and drawings.

A first aspect of the invention is a set of panels comprising a first and a second panel. A panel edge of the second panel is insertable into a core groove of the first panel to obtain a mechanical connection between the first and the second panel. The panel edge is insertable into the core groove by an essentially linear
5 relative displacement of the first and second panel when the first and second panel are arranged essentially perpendicularly to each other. The panel edge comprising a separate and flexible tongue and the core groove comprising a tongue groove, or the panel edge comprising a tongue groove and the core groove comprising a separate and flexible tongue. The separate and flexible
10 tongue is insertable into the tongue groove for connecting the panels to each other in a first direction, which is perpendicular to a main plane (MP-1) of the first panel. The panel edge of the second panel is configured to cooperate with the core groove of the first panel for connecting the panels to each other in a second direction, which is perpendicular to a main plane (MP-2) of the second panel. A
15 longitudinal direction of the separate and flexible tongue extends parallel with the panel edge and/or core groove. The separate and flexible tongue is arranged in an insertion groove and the separate and flexible tongue being displaceable inwardly towards a bottom of the insertion groove and outwardly into the tongue groove during a locking of the first and second panel. The separate and flexible
20 tongue comprises a guiding protrusion at a short edge of the separate and flexible tongue and the guiding protrusion is configured such that its shape changes during the locking and/or unlocking of the first and second panel.

By means of the inventive concept, the panels may be disassembled in an improved and simple manner.

25 Preferably, the panels in the set of panels are essentially formed as parallelepipeds or, more specifically, as rectangular parallelepipeds.

Each of the panels, in particular the first and the second panel, may comprise a lower side and an upper side. Preferably, the lower and upper sides are shaped as rectangles or squares and are planar. The lower side and the upper side may
30 be parallel. In one example, the panel has a uniform thickness. In another example, the panel has a non-uniform thickness. In yet another example, the panel comprises two or more sections, each having a uniform thickness. The lower side and the upper side of the panel may be parallel with the main plane of

the panel. In particular, the main plane of the panel may coincide with the lower or the upper side of the panel. Moreover, each panel may comprise side edges which may connect the upper and lower sides. In the case of a panel formed as a parallelepiped, there may be two pairs of side edges. Preferably, at least
5 portions of the two side edges in each pair of side edges are parallel.

In one example, a density of the panel is uniform. In another example, the density of the panel is higher closer to the upper and/or lower sides than in a center part of the panel.

The first direction may be parallel to the main plane of the second panel.
10 Moreover, the second direction may be parallel to the main plane of the first panel.

The panel edge of a panel may comprise at least a portion of a side edge of the panel. Additionally, the panel edge may comprise a portion of the lower side and a portion of the upper side of the panel close to the side edge. A shape of the
15 panel edge may substantially correspond to a shape of the core groove. Thereby, the second panel may engage with the first panel in a tightly fit manner. In particular, the panel edge and the core groove may be essentially U-shaped. Optionally, corners of the panel edge and/or the core groove may be bevelled.

By a short edge of the separate and flexible tongue is here meant an edge of the
20 tongue in a longitudinal direction of the separate and flexible tongue.

The separate and flexible tongue may comprise an outer edge part that is formed as a guiding protrusion.

The guiding protrusion may be in contact with an inner part of the insertion groove during the locking.

25 In particular, in a locked position of the first and the second panel, the guiding protrusion may be in contact with the inner part of the insertion groove.

Alternatively, there may be a space between the inner part of the insertion groove and the guiding protrusion in a locked position of the first and the second panel. The space is preferably smaller than the displacement of the separate
30 and flexible tongue during locking along a direction towards the inner part of the insertion groove.

The guiding protrusion may be curve shaped and configured to guide a rod shaped tool into the tongue groove when the rod shaped tool is inserted into the insertion groove. By curve shaped is here meant that at least a portion of the guiding protrusion is shaped as a curve. The curve may have a non-zero curvature. In particular, as seen from a top view, an outer side of the guiding protrusion may be shaped as a curve. The curvature is preferably such that an angle formed between a tangential direction of the outer side of the guiding protrusion and a longitudinal direction of the rod shaped tool is acute. In particular, the angle may be between 1° and 89°. Since the guiding protrusion is curve shaped, the acute angle may vary along the guiding protrusion in a direction towards a tip of the guiding protrusion. For example, the acute angle may increase towards the tip of the guiding protrusion.

According to an alternative embodiment, the guiding protrusion comprises at least one straight portion. As seen from a top view, each straight portion may be inclined with respect to a longitudinal direction of the tongue. In one example, the guiding protrusion comprises one straight portion. In another example, the guiding protrusion comprises at least two straight portions. In the latter example, the straight portions are preferably juxtaposed. The angle with respect to the longitudinal direction of the tongue may be different between the different straight portions. For example, the angle may increase by each straight portion towards the tip of the guiding protrusion.

In one example, a cross section of the guiding protrusion along a direction towards the tip of the guiding protrusion is constant. In another example, the cross section of the guiding protrusion is tapering. Moreover, in non-limiting examples, the cross section of the guiding protrusion along a direction towards its tip may be shaped as a circle, an oval, a polygon, a rectangle, a square, or a triangle.

The guiding protrusion may be flexible. More generally, at least portions of the guiding protrusion may be flexible.

The rod shaped tool may comprise an essentially round cross section. In particular, the cross-section may be shaped as a circle or an oval. By having a rotationally symmetric cross-section, such as a circle, the precise orientation of

the rod shaped tool when inserting it into the insertion groove may become immaterial, which may further simplify the disassembly of the panels.

The separate and flexible tongue may comprise several flexible protrusions extending in the length direction of the tongue.

- 5 The insertion groove may be formed in the core groove of the first panel.

When the panel edge comprises the tongue groove and the core groove comprises the separate and flexible tongue, the tongue groove may be arranged in the lower side or in the upper side of the second panel. In particular, the tongue groove may be arranged in the lower side or in the upper side of the
10 second panel, close to a side edge of the second panel.

Moreover, when the panel edge comprises the tongue groove and the core groove comprises the separate and flexible tongue, the insertion groove may be formed in the core groove. The core groove may comprise two side walls and a bottom wall. The two side walls of the core groove may be parallel. According to
15 one embodiment, the insertion groove may be arranged in a side wall of the core groove. A shape of at least a part of the flexible tongue may substantially correspond to a shape of the insertion groove. In particular, the flexible tongue and the insertion groove may be essentially U-shaped. The insertion groove may comprise two side walls and a bottom wall. The side walls of the insertion groove
20 may be parallel. In a first example, the bottom wall of the insertion groove is planar. In a second example, the bottom wall of the insertion groove is rounded. The insertion groove may be inclined with respect to the lower side and/or the upper side of the first panel. In a non-limiting example, the angle between a side wall of the insertion groove and the lower side and/or the upper side of the first
25 panel may be between 5° and 45°.

The tongue groove may comprise two side walls and a bottom wall. The side walls of the tongue groove may be parallel. In a first example, the bottom wall of the tongue groove is planar. In a second example, the bottom wall of the tongue groove is rounded. The tongue groove may be inclined with respect to the lower
30 side and/or the upper side of the second panel. In a non-limiting example, the angle between a side wall of the tongue groove and the lower side and/or the upper side of the second panel may be between 45° and 85°. The inclination of

the tongue groove may correspond to an inclination of the insertion groove so that in a connected state of the first and second panel, parallel side walls of the tongue groove and parallel side walls of the insertion groove are essentially aligned with each other.

- 5 A second aspect of the invention is a locking system for locking of panels comprising a first and a second panel. A panel edge of the second panel is insertable into a core groove of the first panel to obtain a mechanical connection between the first and the second panel. The panel edge is insertable into the core groove by an essentially linear relative displacement of the first and second
- 10 panel when the first and second panel are arranged essentially perpendicularly to each other. The locking system comprises a separate and flexible tongue arranged in an insertion groove which is formed in the core groove and a tongue groove at the panel edge. The tongue groove is adapted to accommodate a part of the separate and flexible tongue. The separate and flexible tongue comprises
- 15 a guiding protrusion at a short edge of the separate and flexible tongue. The guiding protrusion is configured such that its shape changes when a rod shaped tool is inserted into at least a part of the tongue groove.

The rod shaped tool may comprise an essentially round cross section.

- The invention provides the advantages that a rod shaped tool may be inserted
- 20 sideways into the insertion groove that generally is larger than the tongue groove and the tool will be automatically guided by the guiding protrusion into the tongue groove. The rod shaped tool may have a simple round cross section and a precise orientation of the tool during insertion into the groove may be avoided. This facilitates an easy and simple disassembly of locked panels.

- 25 According to a third aspect of the invention, there is provided a set of panels comprising a first and a second panel. A panel edge of the second panel is insertable into a core groove of the first panel to obtain a mechanical connection between the first and the second panel, the panel edge being insertable into the core groove by an essentially linear relative displacement of the first and second
- 30 panel when the first and second panel are arranged essentially perpendicularly to each other. Moreover, the panel edge comprises a separate and flexible tongue and the core groove comprises a tongue groove, wherein the separate

and flexible tongue is insertable into the tongue groove for connecting the panels to each other in a first direction, which is perpendicular to a main plane of the first panel. The panel edge of the second panel is configured to cooperate with the core groove of the first panel for connecting the panels to each other in a second direction, which is perpendicular to a main plane of the second panel. A longitudinal direction of the separate and flexible tongue extends parallel with the panel edge and/or core groove. The separate and flexible tongue is arranged in an insertion groove and is displaceable inwardly towards a bottom of the insertion groove and outwardly into the tongue groove during a locking of the first and second panel. An engagement portion of the core groove is arranged to engage with the separate and flexible tongue during locking of the first and second panel for displacing the separate and flexible tongue inwardly towards the bottom of the insertion groove, wherein the engagement portion is bevelled.

The bevelled engagement portion may be an upper bevelled engagement portion, provided close to, or at, an upper or lower side of the second panel.

The bevelled engagement portion may be provided in an upper part of the first panel, the upper part having a higher density than a center part of the first panel.

The bevelled engagement portion may be provided between a side wall of the core groove and a lower or upper side of the first panel. In particular, the bevelled engagement portion may join the side wall of the core groove and the upper or lower side of the first panel.

The second panel may comprise an overlapping portion, which engages with the bevelled engagement portion in a locked position of the first and second panel.

A thickness of the second panel may be smaller at the panel edge than in a visible part of the second panel which is visible in a locked position of the first and the second panel.

A distance between a lower edge side and a parallel upper edge side of the panel edge may be smaller than a distance between a lower side and a parallel upper side, the lower and upper edge sides being located closer to a side edge of the second panel than the lower and upper sides.

The insertion groove may be provided in the lower edge side or in the upper edge side of the panel edge. Alternatively, the insertion groove may be provided in the lower side or in the upper side of the second panel.

According to a fourth aspect of the invention, there is provided a set of panels comprising a first and a second panel. A panel edge of the second panel is insertable into a core groove of the first panel to obtain a mechanical connection between the first and the second panel, and the panel edge is insertable into the core groove by an essentially linear relative displacement of the first and second panel when the first and second panel are arranged essentially in the same plane MP-1. Moreover, the panel edge comprises a separate and flexible tongue and the core groove comprises a tongue groove, or the panel edge comprises a tongue groove and the core groove comprises a separate and flexible tongue. The separate and flexible tongue is insertable into the tongue groove for connecting the panels to each other in a first direction, which is parallel to a main plane of the first panel. The panel edge of the second panel is configured to cooperate with the core groove of the first panel for connecting the panels to each other in a second direction, which is perpendicular to the main plane of the panels. A longitudinal direction of the separate and flexible tongue extends parallel with the panel edge and/or core groove. Moreover, the separate and flexible tongue is arranged in an insertion groove and is displaceable inwardly towards a bottom of the insertion groove and outwardly into the tongue groove during a locking of the first and second panel. The separate and flexible tongue comprises a guiding protrusion at a short edge of the separate and flexible tongue, and the guiding protrusion is configured such that its shape changes during the locking and/or unlocking of the first and second panel.

The guiding protrusion may be further configured to be in contact with an inner part of the insertion groove during the locking.

The guiding protrusion may be curve shaped and configured to guide a rod shaped tool into the tongue groove when the rod shaped tool is inserted into the insertion groove.

The rod shaped tool may comprise an essentially round cross section.

Brief Description of the Drawings

Figs 1a-d illustrate known technology;

Figs 2a-d illustrate disassembly of locked panels according to an embodiment;

5 Figs 3a-d illustrate embodiments of separate flexible tongues;

Figs 4a-c illustrate assembly and disassembly of panels according to an alternative embodiment;

Figs 5a-d illustrate assembly and disassembly of panels located in the same main plane according to an embodiment.

10 Description of Embodiments of the Invention

To facilitate understanding, several locking systems in the figures are shown schematically. It should be emphasised that improved or different functions can be achieved using combinations of the preferred embodiments.

15 Figs. 2a-d illustrate a first panel 1 and a second panel 2 which are connected to each other in accordance with an embodiment. The first panel 1 comprises a core groove 6 which is arranged in an upper side 1b of the first panel 1. The core groove 6 comprises two opposing side walls 6a, 6b and a bottom wall 6c. The opposing side walls 6a, 6b are parallel. The second panel 2 comprises a panel edge 12 which in a locked position of the panels 1, 2 is arranged in the core groove 6. More specifically, a portion of a lower side 2a, a portion of an upper side 2b, and a side edge 2c of the second panel 2 are arranged in the core groove 6. The panels 1, 2 may be locked to each other by means of a separate and flexible tongue 3.

25 Figures 2a shows a top view of the flexible tongue 3 in a locked position. A part of the flexible tongue 3 comprising flexible protrusions 8 is located in an insertion groove 4. An opposite part is located in the tongue groove 5 according to known technology. The flexible tongue 3 comprises an outer edge part 3a that is formed as a guiding protrusion 10 that automatically guides a rod shaped tool 9 into a tongue groove 5 when the tool 9 is inserted sideways into the insertion groove 4.

30 The guiding protrusion 10 is arranged at a short edge of the tongue 3. It is

understood that there may be a corresponding guiding protrusion 10 arranged at the other short edge of the tongue 3 (not shown).

Figure 2b shows that the flexible guiding protrusion is deformed when the rod shaped tool 9 is displaced sideways parallel to the length direction of the tongue 3 such that the tongue 3 is pressed into the insertion groove 4. It is an advantage if the flexible guiding protrusion 10 is in contact with an inner part of the insertion groove 4 during locking and when the tongue is pressed into the insertion groove. The guiding protrusion 10 is preferably flexible and is preferably also formed as a curved edge part.

Figure 2c shows a side view of the locking system. According to the present embodiment, a main plane MP-1 of the first panel 1 coincides with the upper side 1b of the first panel 1. Moreover, a main plane MP-2 of the second panel 2 coincides with the lower side 2a of the first panel 2, which is situated to the left, as shown in Fig. 2c. The rod shaped tool 9 preferably comprises an essentially round cross section. According to the present embodiment, the cross section of the rod shaped tool 9 is circular. Moreover, a width of the rod shaped tool 9 corresponds to a width of the tongue groove 5 between two parallel side walls 5a, 5b thereof. According to the present embodiment, a bottom wall 5c of the tongue groove 5, connecting the two side walls, is rounded. The curvature of the rounded bottom wall 5c substantially corresponds to the curvature of the rod shaped tool 9. Thereby, an improved guiding of the rod shaped tool 9 may be provided. In the present embodiment, the rod shaped tool 9 is adapted to be fitted inside the tongue groove 5 so that essentially no portion of the rod shaped tool 9 extends outside the lower side 2a of the second panel 2. Thereby, the panels 1, 2 may be easily disassembled, since the rod shaped tool 9 may be fitted inside the tongue groove 5 while the tongue 3 is displaced into the insertion groove 4, thereby releasing the mechanical connection between the first 1 and the second panel 2. Figure 2d shows disassembly of the first 1 and the second panel 2 according to the present embodiment.

It is clear that other shapes of the rod shaped tool 9 and the tongue groove 5 are equally conceivable. For example, the cross-section of the rod shaped tool 9 may be shaped as a polygon, a rectangle, a square, an oval, a triangle or a star. Additionally, according to alternative embodiments, the shape of the bottom wall

may not correspond to the shape of the rod shaped tool 9. For example, the cross-section of the rod shaped tool 9 may be circular and the cross-section of the tongue groove 5 may be U-shaped, for example comprising a planar bottom wall.

- 5 The insertion groove 4 may also be formed in the second panel 2 and the tongue groove 5 may be formed in the core groove 6 of the first panel 1. This will be described in more detail below.

The above-described embodiment provides the advantages that the insertion of the tool 9 may be made into the whole cross section comprising the insertion
10 groove 4 and the tongue grooves 5. A symmetric tool cross section may be used that eliminates a precise orientation of the tool 9 prior to insertion into the grooves.

The guiding of the rod shaped tool 9 is illustrated in Fig. 2a and Fig. 2c. The broken lines illustrate the position of the rod shaped tool 9 when inserted into the
15 insertion groove 4 and the arrows indicate that the rod shaped tool 9 is guided into the tongue groove 5 in the shown direction.

Figure 3a shows a tongue blank 11 comprising several thermoplastic injection-moulded flexible tongues 3. The tongues are preferably separated from the blank 11 at a separation portion S located inwardly and at a distance from the outer
20 edge of the tongue 3.

Figure 3b shows that the guiding protrusion 10 may replace one of the flexible protrusions 8 such that all flexible protrusions 8 are located along the tongue in the length direction of the tongue and spaced in the length direction from the guiding protrusion 10.

25 Figure 3c shows that the principles of the invention may be used to improve disassembly when other types of tongues are used for example flexible tongues comprising a snap tab 13 at the outer part. The locking system comprising a flexible snap tab 13 may be formed such that a tool 9 with an essentially round cross section may be used to release the first 1 and the second 2 panels.

30 Figure 3d shows that such tongue 3 comprising a snap tab 13 may comprise a symmetric cross section in inner parts and an edge portion that may be cut or

formed to a wedge shaped edge part 14. The flexible tongue may comprise a flexible snap tab and an asymmetric cross section along its length direction.

In particular, the flexible tongue 3 may be tapering towards an edge of the flexible tongue 3 in a longitudinal direction. Thereby, an area of the cross section of the flexible tongue 3 may decrease towards the edge. Additionally, a maximal horizontal distance from an inner part of the cross section to an outer part of the cross section may decrease towards the edge. Here, the horizontal distance is measured in a direction along which the flexible tongue 3 is adapted to contract and expand. For example, the horizontal distance may be measured in a direction along which the flexible snap tab 13 is adapted to contract and expand. As shown in the embodiment according to Fig. 3d, the cross section of the flexible snap tab 13 decreases towards the edge. A portion 13a of the flexible snap tab 13 has been cut out from the flexible tongue 3 for providing the tapering edge.

Next, an alternative embodiment will be described with respect to Figs. 4a-c. Figs. 4a and 4b show a side view of a first panel 1 and a second panel 2 which are being assembled. It is understood that, in Figs. 4a-c, the first panel 1 extends horizontally and that the second panel 2 extends vertically and that only a connecting region of the first 1 and second 2 panel is shown. The first 1 and second 2 panels are arranged essentially perpendicularly to each other.

According to the present embodiment, the first panel 1 comprises three parts: an upper part 30, a center part 32, and a lower part 34. The upper part 30 and the lower part 34 are located close to the upper 1b and lower 1a sides, respectively, and have a higher density than the center part 32.

The core groove 6 comprises two opposing side walls 6a, 6b and a bottom wall 6c. The core groove 6 comprises a tongue groove 5. The tongue groove 5 is provided in the side wall 6a of the tongue groove 5. Thus, the tongue groove 5 is provided in a left part 21a of the first panel 1 which is located to the left of core groove 6. Moreover, the tongue groove 5 comprises two parallel side walls 5a, 5b and a bottom wall 5c. As seen from the side view in Figs. 4a-c, a linear extension E of the lower side wall 5a is located at or above a right part 21b of the first panel 1, which is located to the right of core groove 6. Thereby, a tool, such

as a cutting tool, may easily provide the tongue groove 5 by means of a linear displacement of the tool.

5 An engagement portion 20 of the core groove 6 is bevelled. The bevelled engagement portion 20 is provided between an upper part of the side wall 6a and the upper side 1b of the first panel 1, thereby joining them. Alternatively, the engagement portion 20 of the core groove 6 may be rounded off.

Moreover, the panel edge 12 of the second panel 2 has a smaller thickness than an inner part of the second panel 2, wherein the inner part is located farther from a side edge 2c of the second panel 2 than the panel edge 12. More specifically,
10 the panel edge 12 comprises a lower edge side 22a and an upper side edge 22b which are parallel to each other and are located closer to the side edge 2c of the second panel 2 than a lower side 2a and an upper side 2b of the second panel 2. As displayed in Fig. 4c, the distance d_1 between the lower edge side 22a and the upper side edge 22b is smaller than the distance d_2 between the lower side 2a
15 and the upper side 2b.

The lower edge side 22a is joined to the lower side 2a by means of an overlapping portion 24. According to the present embodiment, there is a corresponding upper edge side 22b which is joined to the upper side 2b of the second panel 2 by means of an overlapping portion 25. By means of the
20 overlapping portions 24, 25, which in an assembled state, or locked position, of the first 1 and second 2 panels engage with the bevelled engagement portion 20 and a bevelled surface 27 of the core groove 6, respectively, the panel edge 12 and/or the core groove 6 may be concealed in an improved manner.

The panel edge 12 comprises a separate and flexible tongue 3. The separate
25 and flexible tongue 3 may assume a contracted state and an expanded state and has a tendency to assume the expanded state when no forces are acting on it. The separate and flexible tongue 3 is arranged in an insertion groove 4 which is provided in lower edge side 22a of the panel edge 12. The separate and flexible tongue 3 comprises a chamfered portion 23 which is pointing downwards when
30 the separate and flexible tongue 3 is inserted into the insertion groove 4.

When the first 1 and second 2 panels are assembled, the panel edge 12 of the second panel 2 is inserted into the core groove 6 of the first panel 1 by a relative

vertical displacement of the first 1 and second 2 panels. The displacement is linear. The separate and flexible tongue 3 is partly inserted into the insertion groove 4 and is further displaced into the insertion groove 4 when the chamfered portion 23 engages with the bevelled engagement portion 20 during the vertical displacement. By means of the bevelled engagement portion 20, the chamfered portion 23 engages with a smooth surface during the assembly. Thereby, the chamfered portion 23 may avoid engaging with any sharp edges during assembly. When displaced further into the insertion groove 4, the separate and flexible tongue 3 may become contracted. When the side walls 4a, 4b of the insertion groove 4 are aligned with the side walls 5a, 5b of the tongue groove 5, the separate and flexible tongue 3 may expand and may be displaced out from the insertion groove 4 and into the tongue groove 5 for obtaining a locking of the first 1 and second 2 panels in a direction which is perpendicular to the main plane MP-1 of the first panel.

The core groove 6 comprises an inclined portion 16 between the side wall 6a and the bottom wall 6c as well as between the side wall 6b and the bottom wall 6c. Moreover, the panel edge 12 comprises a bevel 26 between the lower edge side 22a and the side edge 2c of the second panel 2 and a bevel 26 between the upper edge side 22b and the side edge 2c of the second panel 2. A shape of the inclined portion 16 may substantially correspond to a shape of the bevel 26. For example, the inclination of the inclined portion 16 and the bevel 26 may be substantially the same. The bevels 26 may remove sharp corners between the edge sides 22a, 22b and the side edge 2c. Moreover, the bevels 26 may guide the second panel 2 into a proper locking position.

In a locked position of the panels 1, 2, the panel edge 12 cooperates with the core groove 6 for connecting the panels to each other in a second direction, which is perpendicular to a main plane MP-2 of the second panel 2.

From Fig. 4b it is clear that the visible outer parts of the first 1 and second 2 panels have a uniform thickness in a locked position of the first 1 and second 2 panel.

It is understood that according to an alternative embodiment, the second panel 2 may have a uniform thickness.

Fig. 4c shows a side view of a first panel 1 and a second panel 2 which are being disassembled. This is analogous to the disassembly described above in relation to Figs. 2a-d. In particular, when disassembling, the rod shaped tool 9 is inserted sideways into the insertion groove 4 and is guided into a proper position in the tongue groove 5 by means of a guiding protrusion 10 which is provided at a short edge of the separate and flexible tongue 3. When the rod shaped tool 9 is inserted into the tongue groove 5, the separate and flexible tongue 3 is displaced into insertion groove 4. Thereby, the second panel 2 becomes unlocked and the panel edge 12 may be removed from the core groove 6 by a relative linear vertical displacement of the first 1 and second 2 panel.

Figures 5a – 5d show a locking system that may be used to lock and unlock a first 1 and a second 2 panel that, in a locked position, are located in the same main plane MP-1. In other words, the panels are arranged essentially in parallel with each other. Such a locking system may be used to lock two or several furniture components with, for example, a length of 0.6 m and that after locking form a part of a book shelf with a length of, for example, 1.2 or 1.8 m. An advantage of providing this type of locking system is that smaller components are easier to transport, assemble and disassemble. It is clear than other lengths of the furniture components are equally conceivable. In non-limiting examples, the length may be between 0.1 m and 1.0 m.

In the present embodiment, the first panel 1 and the second panel 2 have a uniform thickness.

The first panel 1 comprises a core groove 6 and a tongue groove 5 and the second panel 2 comprises a panel edge 12 that is insertable into the core groove 6 with a displacement parallel with the main plane MP-1 of the first and the second panel. The panel edge 12 comprises a separate and flexible tongue 3 which is provided in an insertion groove 4. In a locked position of the panels, the separate and flexible tongue 3 locks into the tongue groove 5.

According to an alternative embodiment (not shown), the tongue groove 5 may be provided in the second panel 2 and the separate and flexible tongue 3 may be provided in the first panel 1.

It is essential that the locking system is strong in order to provide sufficient rigidity to the locked components. Preferably, an upper edge 30a and a lower edge 31a of the first panel 1 and an upper edge 31b and a lower edge 31b of the second panel 2 are in contact with each other when the panels 1, 2 are locked.

- 5 According to the present embodiment, a side face of the panel edge 12 engages with a bottom wall of the core groove 6 in a locked position of the first 1 and second 2 panel. This may be seen in Fig. 5c. In addition, in a locked position, an upper and a lower face of the panel edge 12 engage with a respective one of two opposing side walls of the core groove 6. According to an alternative
10 embodiment (not shown), however, the side face of the panel edge 12 may be separated from the bottom wall of the core groove 6 in a locked position of the first 1 and second 2 panel.

- The first panel 1 comprises an engagement portion 40 which is arranged to engage with the separate and flexible tongue 3 during locking of the first 1 and
15 second 2 panel for displacing the separate and flexible tongue 3 inwardly towards the bottom of the insertion groove 4. The engagement portion 40 is inclined with respect to the main plane MP-1 of the first 1 and second 2 panel. Moreover, the engagement portion 40 is bevelled at a portion 42 which is adjacent to the tongue groove 5.

- 20 Figure 5d shows unlocking of the first 1 and second 2 panels with a rod shaped tool 9 according to the above-described methods. The separate and flexible tongue 3 comprises an outer edge part 3a that is formed as a guiding protrusion 10 that automatically guides the rod shaped tool 9 into the tongue groove 5 when the tool 9 is inserted sideways into the insertion groove 4.

25

CLAIMS

1. A set of panels (1,2) comprising a first (1) and a second panel (2), a panel edge (12) of the second panel (2) being insertable into a core groove (6) of the first panel (1) to obtain a mechanical connection between the first and the second panel, the panel edge (12) being insertable into the core groove (6) by an essentially linear relative displacement of the first and second panel when the first and second panel are arranged essentially perpendicularly to each other,
- said panel edge (12) comprising a separate and flexible tongue (3) and said core groove (6) comprising a tongue groove (5), or said panel edge (12) comprising a tongue groove (5) and said core groove (6) comprising a separate and flexible tongue (3),
- wherein the separate and flexible tongue (3) is insertable into the tongue groove (5) for connecting said panels to each other in a first direction, which is perpendicular to a main plane (MP-1) of the first panel,
- wherein the panel edge (12) of the second panel (2) is configured to cooperate with the core groove (6) of the first panel (1) for connecting said panels to each other in a second direction, which is perpendicular to a main plane (MP-2) of the second panel,
- wherein a longitudinal direction of the separate and flexible tongue (3) extends parallel with said panel edge and/or core groove, and
- wherein the separate and flexible tongue (3) is arranged in an insertion groove (4), said separate and flexible tongue (3) being displaceable inwardly towards a bottom of the insertion groove (4) and outwardly into the tongue groove (5) during a locking of the first and second panel,
- characterized in that the separate and flexible tongue (3) comprises a guiding protrusion (10) at a short edge of the separate and flexible tongue (3), and that the guiding protrusion (10) is configured such that its shape changes during the locking and/or unlocking of the first and second panel, and in that the guiding protrusion (10) is curve shaped and configured to guide a rod shaped tool (9) into the tongue groove (5) when the rod shaped tool (9) is inserted into the insertion groove (4).

2. The set of panels as claimed in claim 1, wherein the guiding protrusion (10) is further configured to be in contact with an inner part of the insertion groove (4) during the locking.

5 3. The set of panels as claimed in claim 1, wherein there is a space between an inner part of the insertion groove (4) and the guiding protrusion (10) in a locked position of the first (1) and the second (2) panel.

 4. The set of panels as claimed in anyone of the preceding claims,
10 wherein the rod shaped tool (9) comprises an essentially round cross section.

 5. The set of panels as claimed in anyone of the preceding claims, wherein the separate and flexible tongue (3) comprises several flexible protrusions (8, 10) extending in the length direction of the tongue (3).

15

 6. The set of panels as claimed in any of the preceding claims, wherein, when said panel edge (12) comprises the tongue groove (5) and said core groove (6) comprises the separate and flexible tongue (3), said tongue groove (5) is arranged in a lower side (2a) or in an upper side (2b) of the second panel
20 (2).

 7. The set of panels as claimed in any of the preceding claims, wherein, when said panel edge (12) comprises the tongue groove (5) and said core groove (6) comprises the separate and flexible tongue (3), said insertion groove
25 (4) is formed in said core groove (6) of the first panel (1).

 8. The set of panels according to claim 7, wherein said insertion groove (4) is arranged in a side wall (6a) of said core groove (6).

30 9. A locking system for locking of panels (1, 2) comprising a first (1) and a second panel (2), wherein a panel edge (12) of the second panel (2) is insertable into a core groove (6) of the first panel (1) to obtain a mechanical connection between the first and the second panel, the panel edge (12) being insertable into

the core groove (6) by an essentially linear relative displacement of the first and second panel when the first and second panel are arranged essentially perpendicularly to each other, wherein the locking system comprises:

5 a separate and flexible tongue (3) arranged in an insertion groove (4) which is formed in the core groove (6); and

a tongue groove (5) at the panel edge (12), said tongue groove (5) being adapted to accommodate a part of the separate and flexible tongue (3),

10 characterized in that the separate and flexible tongue (3) comprises a guiding protrusion (10) at a short edge of the separate and flexible tongue (3), and that the guiding protrusion is configured such that its shape changes when a rod shaped tool (9) is inserted into at least a part of the tongue groove (5), and in that the guiding protrusion (10) is curve shaped and configured to guide a rod shaped tool (9) into the tongue groove (5) when the rod shaped tool (9) is inserted into the insertion groove (4).

15

10. A locking system as claimed in claim 11, wherein the rod shaped tool (9) comprises an essentially round cross section.

11. A set of panels (1,2) comprising a first (1) and a second panel (2), a panel edge (12) of the second panel (2) being insertable into a core groove (6) of the first panel (1) to obtain a mechanical connection between the first and the second panel, the panel edge (12) being insertable into the core groove (6) by an essentially linear relative displacement of the first and second panel when the first and second panel are arranged essentially perpendicularly to each other,

25 said panel edge (12) comprising a separate and flexible tongue (3) and said core groove (6) comprising a tongue groove (5),

wherein the separate and flexible tongue (3) is insertable into the tongue groove (5) for connecting said panels to each other in a first direction, which is perpendicular to a main plane (MP-1) of the first panel,

30 wherein the panel edge (12) of the second panel (2) is configured to cooperate with the core groove (6) of the first panel (1) for connecting said panels to each other in a second direction, which is perpendicular to a main plane (MP-2) of the second panel,

wherein a longitudinal direction of the separate and flexible tongue (3) extends parallel with said panel edge and/or core groove, and

wherein the separate and flexible tongue (3) is arranged in an insertion groove (4), said separate and flexible tongue (3) being displaceable inwardly
5 towards a bottom of the insertion groove (4) and outwardly into the tongue groove (5) during a locking of the first and second panel,

characterized in that an engagement portion (20) of the core groove (6) is arranged to engage with said separate and flexible tongue (3) during locking of the first and second panel for displacing the separate and flexible tongue (3)
10 inwardly towards the bottom of the insertion groove (4), wherein said engagement portion (20) is bevelled.

12. The set of panels as claimed in claim 11, wherein the bevelled engagement portion (20) is provided in an upper part (30) of the first panel (1),
15 said upper part (30) having a higher density than a center part (32) of the first panel (1).

13. The set of panels as claimed in claim 11 or 12, wherein the bevelled engagement portion (20) is provided between a side wall (6a) of said core
20 groove (6) and a lower (1a) or upper side (1b) of the first panel (1).

14. The set of panels as claimed in any of claims 11 to 13, wherein the second panel (2) comprises an overlapping portion (24), which engages with the bevelled engagement portion (20) in a locked position of the first (1) and second
25 (2) panel.

15. The set of panels as claimed in any of claims 11 to 14, wherein a thickness of the second panel (2) is smaller at the panel edge (12) than in a visible part of the second panel (2) which is visible in a locked position of the first
30 (1) and the second (2) panel.

16. The set of panels as claimed in any of claims 11 to 15, wherein a distance between a lower edge side (22a) and a parallel upper edge side (22b)

of the panel edge (12) is smaller than a distance between a lower side (2a) and a parallel upper side (2b), the lower and upper edge sides (22a, 22b) being located closer to a side edge (2c) of the second panel (2) than the lower and upper sides (2a, 2b).

5

17. The set of panels as claimed in claim 16, wherein the insertion groove (4) is provided in said lower edge side (22a) or in said upper edge side (22b) of the panel edge (12).

10 18. A set of panels (1,2) comprising a first (1) and a second panel (2), a panel edge (12) of the second panel (2) being insertable into a core groove (6) of the first panel (1) to obtain a mechanical connection between the first and the second panel, the panel edge (12) being insertable into the core groove (6) by an essentially linear relative displacement of the first and second panel when the
15 first and second panel are arranged essentially in the same plane (MP-1)

said panel edge (12) comprising a separate and flexible tongue (3) and said core groove (6) comprising a tongue groove (5), or said panel edge (12) comprising a tongue groove (5) and said core groove (6) comprising a separate and flexible tongue (3),

20 wherein the separate and flexible tongue (3) is insertable into the tongue groove (5) for connecting said panels to each other in a first direction, which is parallel to a main plane (MP-1) of the first panel,

wherein the panel edge (12) of the second panel (2) is configured to cooperate with the core groove (6) of the first panel (1) for connecting said
25 panels to each other in a second direction, which is perpendicular to the main plane (MP-1) of the panels (1, 2),

wherein a longitudinal direction of the separate and flexible tongue (3) extends parallel with said panel edge (12) and/or core groove (6), and

wherein the separate and flexible tongue (3) is arranged in an insertion
30 groove (4), said separate and flexible tongue (3) being displaceable inwardly towards a bottom of the insertion groove (4) and outwardly into the tongue groove (5) during a locking of the first and second panel,

characterized in that the separate and flexible tongue (3) comprises a

guiding protrusion (10) at a short edge of the separate and flexible tongue (3), and that the guiding protrusion (10) is configured such that its shape changes during the locking and/or unlocking of the first and second panel, and in that the guiding protrusion (10) is curve shaped and configured to guide a rod shaped tool (9) into the tongue groove (5) when the rod shaped tool (9) is inserted into the insertion groove (4).

19. The set of panels as claimed in claim 18, wherein the guiding protrusion (10) is further configured to be in contact with an inner part of the insertion groove (4) during the locking.

20. The set of panels as claimed in claim 18 or 19, wherein the rod shaped tool (9) comprises an essentially round cross section.