

CLAIMS

1. A delivery device for delivering an instrument into a catheter assembly, comprising:
a housing having a proximal end, a distal end, and a slot;
a guide feature disposed within the housing, wherein the guide feature extends through the slot, wherein the guide feature comprises a channel, wherein the channel is generally U-shaped;
and
an instrument disposed within the housing and extending through the channel, wherein in response to movement of the guide feature along the slot in a distal direction, the instrument moves through the channel and a first end of the instrument is advanced in the distal direction, wherein a second end of the instrument is stationary with respect to the housing.
2. The delivery device of claim 1, wherein in response to movement of the guide feature along the slot in the distal direction a first distance, the first end of the instrument is advanced in the distal direction a second distance, wherein the second distance is greater than the first distance.
3. The delivery device of claim 1, wherein the first end of the instrument is advanced in the distal direction beyond the distal end of the housing in response to the guide feature being fully advanced along the slot in the distal direction.
4. The delivery device of claim 1, wherein the housing further comprises extension tubing extending outwardly from a distal portion of the housing, wherein the second end of the instrument is coupled to the extension tubing, wherein the instrument comprises a catheter.
5. The delivery device of claim 1, wherein the instrument comprises a catheter, further comprising a guidewire disposed within the catheter, wherein in response to movement of

the guide feature along the slot in the distal direction, the guidewire and the catheter move through the channel.

6. The delivery device of claim 5, wherein the first end of the guidewire is advanced in the distal direction beyond the distal end of the housing in response to the guide feature being fully advanced along the slot in the distal direction.
7. The delivery device of claim 5, wherein in response to movement of the guide feature along the slot in the distal direction a first distance, the first end of the guidewire is advanced in the distal direction a second distance, wherein the second distance is greater than the first distance.
8. The delivery device of claim 1, further comprising support tubing extending from the guide feature and coupled to the guide feature, wherein in response to movement of the guide feature along the slot in the distal direction a first distance, the instrument moves through the support tubing and the first end of the support tubing is advanced in the distal direction the first distance.
9. The delivery device of claim 1, wherein the channel is horizontally oriented within the housing.
10. The delivery device of claim 1, wherein the channel is vertically oriented within the housing.
11. The delivery device of claim 1, wherein a portion of the instrument between the second end of the instrument and the guide feature is generally parallel with a longitudinal axis of the delivery device.

12. The delivery device of claim 1, wherein a portion of the instrument between the second end of the instrument and the guide feature is angled with respect to a longitudinal axis of the delivery device.
13. The delivery device of claim 1, wherein a portion of the instrument between the first end and the guide feature is parallel with a longitudinal axis of the delivery device.
14. The delivery device of claim 1, wherein a portion of the instrument between the first end and the guide feature is angled with respect to a longitudinal axis of the delivery device.
15. The delivery device of claim 1, wherein the guide feature further comprises an advancement tab configured to be moved by a hand of a user.
16. A delivery device for delivering an instrument into a catheter assembly, comprising:
 - a housing having a proximal end, a distal end, and a slot;
 - a guide feature disposed within the housing, wherein the guide feature extends through the slot; and
 - an instrument disposed within the housing and extending through the guide feature, wherein a second end of the instrument is stationary with respect to the housing, wherein in response to movement of the guide feature along the slot in a distal direction a first distance, the first end of the instrument is advanced in the distal direction a second distance, wherein the second distance is greater than the first distance.
17. The delivery device of claim 16, wherein the first end of the instrument is advanced in the distal direction beyond the distal end of the housing in response to the guide feature being fully advanced along the slot in the distal direction.
18. The delivery device of claim 16, wherein the instrument comprises a catheter.

19. The delivery device of claim 16, wherein the guide feature comprises a channel, further comprising a guidewire disposed within the catheter, wherein in response to movement of the guide feature along the slot in the distal direction, the guidewire moves through the channel.
20. A catheter system, comprising:
a delivery device, comprising:
a housing having a proximal end, a distal end, and a slot;
a guide feature disposed within the housing, wherein the guide feature extends through the slot; and
an instrument disposed within the housing and extending through the guide feature, wherein a second end of the instrument is stationary with respect to the housing, wherein in response to movement of the guide feature along the slot in a distal direction a first distance, the first end of the instrument is advanced in the distal direction a second distance, wherein the second distance is greater than the first distance; and
a catheter assembly coupled to the distal end of the housing, the catheter assembly comprising a catheter adapter and a catheter extending distally from the catheter adapter, wherein the first end of the instrument is advanced in the distal direction beyond the distal end of the housing or a distal end of the catheter in response to the guide feature being fully advanced along the slot in the distal direction.