

ABSTRACT OF THE DISCLOSURE:

Provided is a system for treating moisture in exhaust gas that can prevent, even in a case where there is not a space for disposing a pipe having a water sealing function, the exhaust gas from leaking to outside when the moisture or the like contained in the exhaust gas is removed, while preventing backflow of water resulting from liquefaction of the moisture in the removal process. Whether or not water stored in a tank exceeds a higher water level is determined by a valve control unit. Upon determining that the higher water level is exceeded, the valve control unit transmits an open signal to a drain valve to open the drain valve. Thus, the water in the tank is drained. As the drainage proceeds, the water level gradually lowers, and whether or not the water level is not higher than a lower water level set by the valve control unit is determined by the valve control unit. Upon determining that the water level is not higher than the lower water level, the valve control unit transmits a close signal to the drain valve to close the drain valve. Due to the setting of the lower water level, the exhaust gas is unlikely to enter a drain pipe.

FIG. 1

EXHAUST (TO FACTORY EXHAUST EQUIPMENT)

5 DRY PUMP

81 VALVE CONTROL UNIT

DRAINAGE (NATURAL DRAINAGE)

FIG. 6

GAS

DRAINAGE

FIG. 7

EXHAUST (TO FACTORY EXHAUST EQUIPMENT)

5 DRY PUMP

81 VALVE CONTROL UNIT

DRAINAGE (NATURAL DRAINAGE)

FIG. 10

1 PROCESS CHAMBER

10 COMBUSTION-TYPE DETOXIFICATION DEVICE

11 CENTRAL SCRUBBER