

**AUDIO RECORDING MEDIUM, METHODS FOR RECORDING DATA ON
AND REPRODUCING DATA FROM THE RECORDING MEDIUM, AND
RECORDING AND REPRODUCING APPARATUSES THEREFOR**

BACKGROUND OF THE INVENTION

5 1. Field of the Invention

The present invention relates to the audio data related field, and more particularly, to an audio recording medium including a plurality of tracks which audio data are recorded on and reproduced from, methods for recording data on and reproducing data from the audio recording medium, and recording and reproducing apparatuses therefor.

10 2. Description of the Related Art

As for conventional digital audio recording media, such as midi discs (MDs), separate music files are continuously recorded on tracks, as shown in FIG. 1, by a digital audio recording apparatus. Accordingly, when such music files are reproduced from the tracks, the start and ending of each file can be indistinct if no pause period exists between the tracks.

For this reason, conventional compact discs (CDs) are provided with the mute data area assigned with Index 0. In other words, when a conventional digital audio recording apparatus receives digital audio data through a digital interface from a CD player and records the digital audio data in such a recording medium, mute data are also written to the mute data area having Index 0 of each track, such that the mute period exists between each of the tracks. As a result, although the audio data are continuously reproduced from the tracks, each of the tracks can be identified due to the presence of the mute periods.

25 When the conventional digital audio recording apparatus records mute data in the area with Index 0 and audio data in other index areas of a CD, the mute data and the audio data are recorded within a single write unit. Data recording and erasure from such digital audio media are performed in write units. Thus, it is almost impossible to erase only mute data from the tracks while audio data written within the same write unit remain on the recording medium.

30

SUMMARY OF THE INVENTION

To solve the above problems, it is an objective of the present invention to provide an audio recording medium which mute data can be easily recorded on and deleted from, methods for recording data on and reproducing data from the audio recording medium, and recording and reproducing apparatuses therefor.

It is another objective of the present invention to provide an audio recording medium in which a mute period can be easily adjusted, methods for recording data on and reproducing data from the audio recording medium, and recording and reproducing apparatuses therefor.

It is still another objective of the present invention to provide a method for recording data received from a CD player, in which mute data from a mute period with Index 0 can be recorded such that the mute data can be reproduced for the corresponding mute period in a reproduction mode.

According to an aspect of the present invention, there is provided an audio recording medium in which audio data are recorded in a plurality of tracks and identification data for indicating the start position of each of the tracks are recorded in write units segregated from the audio data.

It is preferable that the identification data are recorded in at least one write unit at the start of each of the tracks, and the audio data are recorded in at least one write unit, following the identification data recorded in the at least one write unit. It is more preferable that the write unit may include an audio object unit (AOBU), and the identification data includes mute data.

It is preferable that a mute period for the mute data is equal to or shorter than the duration of a single AOBU, and the mute period includes a duration from a track start point to the end of the AOBU with mute data, and the mute period is varied by moving the location of the track start point. If a mute period for the mute data is longer than the duration of a single AOBU, the number of the AOBUs with mute data can be determined such that the sum of the duration of each of the AOBUs is equal to or slightly longer than the mute period. In this case, the mute period may include a period from a track start point to the end of the last AOBU among the plurality of the AOBUs with mute data, and the mute period may be varied by moving the

location of the track start point. It is preferable that information on the mute period is recorded in a reproduction control information area, and the mute data are indexed with Index 0.

According to another aspect of the present invention, there is provided a method for recording data in a plurality of tracks of a recording medium, and reproducing data from the recording medium, the method comprising: recording identification data for indicating the start position of each of the tracks in predetermined write units; and recording audio data in write units segregated from the predetermined write units of the identification data.

It is preferable that the recording and reproduction method further comprises: reading and reproducing the identification data recorded in the predetermined write units; and reading and reproducing the audio data recorded in the write units segregated from the predetermined write units of the identification data.

According to another aspect of the present invention, there is provided a method for reproducing data recorded in a plurality of tracks of a recording medium, the method comprising: reading and reproducing identification data for indicating the start position of each of the tracks, the identification data being recorded in predetermined write units; and reading and reproducing audio data recorded in write units segregated from the predetermined write units of the identification data.

According to another aspect of the present invention, there is also provided a method for reproducing data recorded in a plurality of tracks of a recording medium in which identification data for indicating the start position of each of the tracks are recorded in predetermined write units, and audio data are recorded in write units segregated from the predetermined write units of the identification data, the method comprising: once a reproduction command for a track is input, searching for the write units with audio data in the corresponding track; and reading and reproducing the audio data from the found write units.

According to another aspect of the present invention, there is provided a method for recording data in a plurality of tracks of a recording medium, and reproducing data from the recording medium, the method comprising: determining whether there is a need to record identification data for indicating the start position of each of the tracks in a particular track; if recording of the identification data is

needed, recording the identification data in the particular track in at least one write unit; and recording audio data in the particular track in at least one write unit segregated from the at least one write unit of the identification data.

It is preferable that the recording and reproduction method further comprises:
5 reading and reproducing the identification data recorded in the at least one write unit at the start of each of the tracks; and successively reading the audio data recorded in the at least one write unit, following the identification data, and reproducing the read audio data.

It is preferable that the identification data are recorded in at least one write
10 unit at the start of each of the tracks, and the audio data are recorded in at least one write unit, following the identification data recorded in the at least one write unit. The write unit may include an audio object unit (AOBU), and the identification data may include mute data.

It is preferable that a mute period for the mute data is equal to or shorter than
15 the duration of a single AOBU, and the mute period includes a duration from a track start point to the end of the AOBU with mute data, and the mute period is varied by moving the location of the track start point. If a mute period for the mute data is longer than the duration of a single AOBU, the number of the AOBUs with mute data can be determined such that the sum of the duration of each of the AOBUs is equal
20 to or slightly longer than the mute period. In this case, the mute period may include a period from a track start point to the end of the last AOBU among the plurality of the AOBUs with mute data, and the mute period may be varied by moving the location of the track start point. It is preferable that information on the mute period is recorded in a reproduction control information area, and the mute data are
25 indexed with Index 0.

According to another aspect of the present invention, there is provided an apparatus for recording data in a plurality of tracks of a recording medium, in which identification data for indicating the start position of each of the tracks are recorded in predetermined write units, and audio data are recorded in a track in write units
30 segregated from the predetermined write units of the identification data.

It is preferable that the identification data are recorded in at least one write unit at the start of each of the tracks, and the audio data are recorded in at least one write unit, following the identification data recorded in the at least one write unit.

It is preferable that the recording apparatus comprises: a write unit generator for generating the at least one write unit with the audio data, and the at least one write unit with the identification data; a write portion for writing each of the at least one write unit with the audio data and the identification data in the corresponding tracks; and a controller for outputting a command to instruct generation of the at least one write unit with the identification data to the write portion.

According to another aspect of the present invention, there is provided an apparatus for reproducing data recorded in a plurality of tracks of a recording medium, in which identification data recorded in predetermined write units to indicate the start position of each of the tracks are read and reproduced, and audio data recorded in write units segregated from the predetermined write units of the identification data are read and reproduced.

It is preferable that the identification data recorded in at least one write unit at the start of each of the tracks are read and reproduced, and the audio data recorded following the identification data in at least one write unit segregated from the at least one write unit of the identification data are read and reproduced.

It is preferable that the reproducing apparatus comprises: a controller for outputting a command to instruct reading of the identification data or audio data recorded in the corresponding at least one write unit; a reading portion for reading the identification data or audio data recorded in the corresponding at least one write unit, according to the command from the controller; and a reproduction portion for receiving and reproducing the identification data or the audio data from the reading portion.

BRIEF DESCRIPTION OF THE DRAWINGS

The above objectives and advantages of the present invention will become more apparent by describing in detail preferred embodiments thereof with reference to the attached drawings in which:

FIG. 1 is a schematic view illustrating the configuration of tracks in a conventional audio recording medium;

FIG. 2 is a block diagram of a preferred embodiment of a recording and reproducing apparatus according to the present invention;

5 FIG. 3 illustrates an embodiment of an audio recording medium according to the present invention, in which mute data and digital audio data are written on a track of the audio recording medium;

FIG. 4 illustrates another embodiment of the audio recording medium according to the present invention, in which mute data and digital audio data are written on a track of the audio recording medium;

10 FIG. 5 is a flowchart illustrating an embodiment of a digital audio data recording method according to the present invention; and

FIG. 6 is a flowchart illustrating an embodiment of a digital audio data reproduction method according to the present invention.

15 DETAILED DESCRIPTION OF THE INVENTION

In recording audio data in a plurality of tracks of a recording medium, a recording and reproducing apparatus according to the present invention writes identification data for track identification to a corresponding track in predetermined write units, and externally input audio data in another write units. A preferred embodiment of the recording and reproducing apparatus according to the present invention is shown in FIG. 2. Referring to FIG. 2, the recording and reproducing apparatus 1, which records audio data, and mute data as identification data, includes a controller 11, a write unit generator 12, a writing/reading portion 13, and a reproduction portion 14.

25 In particular, the write unit generator 12 generates an audio object unit (AOBU) as a write unit. In the present invention, the AOBU includes an audio AOBU with audio data and a mute AOBU with mute data. The audio AOBU is created by processing audio data received from the outside and then adding a header information to the resulting audio data. In the present embodiment, a mute AOBU with mute data is pre-created, and output from the write unit generator 12 when a mute data generation command is input from the controller 11 to the write

30

unit generator 12. The number of the mute AOBUs is determined such that the sum of the duration of each of the mute AOBUs is equal to or slightly longer than a mute period in a reproduction mode. A predetermined number of the mute AOBUs may be directly transferred from the controller 11 to the writing/reading portion 13.

Alternatively, the number of the mute AOBUs can be determined by the write unit generator 12 to correspond to a desired mute period informed from the controller 11.

The writing/reading portion 13 receives AOBUs from the write unit generator 12 and records the AOBUs in corresponding tracks, or reads AOBUs from predetermined tracks of a recording medium 100. The writing/reading portion 13 also writes a track start point received from the controller 11, which indicates the start of a track from which data to be read, to a reproduction control information area of the recording medium 100, or reads the track start point from the reproduction control information area.

The controller 11 provides a mute AOBU generation command to the write unit generator 12, and provides an AOBU write command to the writing/reading portion 13 in a record mode. The controller 11 provides a track start point, which indicates the start of track from which data are to be read, to the writing/reading portion 13 in a reproduction or record mode. In the reproduction mode, the controller 11 provides an AOBU read command to the writing/reading portion 13.

The controller 11 also provides a reproduction control information including the track start point of a track, from which data is to be read, to the writing/reading portion 13. Mute data are read from the track start point by the writing/reading portion 13, so that the duration from the track start point to the last mute AOBU of the track is referred to as a mute period. The mute period can be varied by moving the location of the track start point. When a track start point exists a single mute AOBU, or when a mute AOBU is encountered during reproduction of audio AOBUs from a track start point, the controller 11 outputs a mute command to the reproduction portion 14 such that the reproduction portion 14 performs a mute operation until all mute data ranging from the track start point to the last mute AOBU is read.

The reproduction portion 14 reproduces audio data from the AOBUs output from the writing/reading portion 13. When mute AOBUs are input, the reproduction

portion 14 performs a mute operation according to the mute command from the controller 11.

In an audio recording medium according to the present invention, digital audio data are recorded in a plurality of tracks. Mute data as track identification data are recorded in at least one mute AOBU in each track, and digital audio data is recorded in at least one audio AOBU, following the mute data in the same track. The mute AOBU and the audio AOBU are segregate. In other word, the mute AOBU contains no audio data. Each of the mute AOBU and the audio AOBU has approximately the same duration. For convenience of explanation, it is assumed that the duration of each AOBU is 1 second long. The duration of each AOBU can be varied as needed.

FIG. 3 illustrates an embodiment of the audio recording medium according to the present invention, in which mute data and audio data are written to a track with a target mute period not longer than the duration of a single AOBU. Referring to FIG. 3, in recording digital audio data in a track, if there is a need to define a mute period in the track, mute data are recorded at the start of the track in units of AOBU. In the present embodiment, the mute period is shorter than or equal to the 1-second duration of the AOBU, and thus one mute AOBU is long enough to record the mute data therein. As shown in FIG. 3, the mute period is equivalent to the duration from the start of the track, at which reproduction starts, to the end of the mute AOBU. It will be appreciated that the mute period can be varied by changing the location of the track start point. Here, the location of the track start point can be optionally moved by users. On the other hand, input audio data to be recorded are processed and packed in units of AOBU segregated from the mute AOBUs, and then recorded following the mute data in the track.

FIG. 4 illustrates another embodiment of the audio recording medium according to the present invention, in which mute data and audio data are written to a track with a mute period longer than the duration of a single AOBU. Since the mute period exceeds the 1-second duration of the AOBU, mute data are recorded in successive mute AOBUs at the start of the track. It is preferable that the number of mute AOBUs is determined such that the sum of the duration of each of the mute AOBUs is equal to or slightly longer than a target mute period.

For example, if the duration of each AOBU is set at 1 second and a target mute period is set at 1.5 seconds, the mute data are recorded in two mute AOBUs in a corresponding track. In particular, the duration of a single AOBU is multiplied by the smallest integer which gives a product that is slightly longer than the mute period. In this example, the product that satisfies this condition is 2 AOBU durations. Accordingly, the mute data are recorded in 2 mute AOBUs. The location of the track start point is set such that a total duration for the mute data ranging from the track start point to the last mute AOBU is equal to the mute period. Like the embodiment described with reference to FIG. 3, input audio data to be recorded are processed and packed as AOBUs segregated from the mute AOBUs, and then recorded following the mute data in the track.

As described with reference to FIGS. 3 and 4, in the audio recording media according to the present invention, mute data and audio data are recorded in segregated AOBUs, unlike a conventional recording medium in which mute data and audio data are recorded within the same write unit. Accordingly, the mute data can be removed by deleting mute AOBUs as needed. This is because such structure of the inventive audio recording media allows a recording/reproducing apparatus to record, edit or delete data in write units.

On the other hand, like CDs, Index 0 is appended to the mute period. Information on the mute period, Index 0, is written to a reproduction control information area. When digital audio data having the mute period (Index 0) at the start of each track are received from a recorder-equipped CD player (so-called CD recording/reproducing apparatus) through a digital audio interface (not shown) of the recording and reproducing apparatus 1 shown in FIG. 2, and recorded by the recording and reproducing apparatus 1, the recording and reproducing apparatus 1 records mute data in units of AOBUs to correspond to the mute period. The recording and reproducing apparatus sets the location of the track start point such that the period from the track start point to the start point of audio data area is equal to the mute period, and assigns Index 0 to the period from the track start point to the start point of audio data area. The recording and reproducing apparatus 1 records the mute period with Index 0 in a reproduction control information area of the recording medium 100. When successive tracks are reproduced from the recording

medium 100 by the recording and reproducing apparatus 1, the sound are muted for the mute period with Index 0 when the reproduction moves from the current track to the next track, and then audio data of the next track following the mute period are reproduced.

5 FIG. 5 is a flowchart illustrating an embodiment of a digital audio data recording method according to the present invention. Referring to FIG. 5, in a record mode, the controller 11 of the recording and reproducing apparatus 1 checks whether a mute period is required in recording a new data track (step S1). If a mute period is required, the controller 11 transfers a mute AOBU generation command to the write unit generator 12. At this time, information on the number of mute AOBUs to be generated, or the mute period is also provided to the write unit generator 12. The write unit generator 12 generates mute AOBUs according to the information on the number of the mute AOBUs or the mute period, which has been received from the controller 11, and provides the mute AOBU to the writing/reading portion 13. 10 The writing/reading portion 13 writes the mute AOBU to a corresponding track (step S2). If the mute period is equal to or shorter than the duration of a single AOBU, the number of the mute AOBUs to be written is 1. As described above, the mute period can be adjusted by moving the location of the track start point. The controller 11 assigns Index 0 to the mute period, and outputs a write command to the writing/reading portion 13 such that the writing/reading portion 13 writes Index 0 to a reproduction control information area. Next, the recording and reproducing apparatus 1 writes an audio AOBU following the mute AOBU (step S3). 20

 FIG. 6 is a flowchart illustrating an embodiment of a digital audio data reproduction method according to the present invention. Referring to FIG. 6, in a reproduction mode, the controller 11 of the recording and reproducing apparatus 13 transfers reproduction control information corresponding to user's input to the writing/reading portion 13, and then the writing/reading portion 13 searches for an AOBU having the track start point in a corresponding track (step S11). Next, the writing/reading portion 13 searches for the track start point in the selected AOBU (step S12). 25

 The writing/reading portion 13 reads mute data having Index 0, which are recorded in units of AOBU, from the track start point, and transfers the read mute 30

data to the reproduction portion 14. The reproduction portion 14 mutes the operation for the duration of the mute data (step S13). The content and format of mute data can be varied as long as the intrinsic function of the mute data, i.e., to mute the operation for the mute period, can be achieved. Muting the output from the recording unit 14 can be achieved in many different ways. For example, unlike step S13, once the writing/reading portion 13 reads mute data, the controller 11 outputs a mute command to the reproduction portion 14, and then the reproduction portion 14 performs mute operation in response to the mute command.

After a lapse of the mute period, the writing/reading portion 13 reads audio data having Index 1 in units of AOBUs, and outputs the read audio data to the reproduction portion 14. The reproduction portion 14 reproduces audio data by decoding the audio data received in units of AOBUs (step S14).

Although recording and reproduction of audio data have been described with reference to the recording and reproducing apparatus 1, i.e., which has both recording and reproducing units, separate recording and reproducing apparatuses can be applied. A recording-only apparatus can be constructed by removing the reproduction portion 14 from the recording and reproducing apparatus 1 of FIG. 2. In this case, reading of data by the writing/reading portion 13, and the control operation for reproduction by the controller 11 are not required. A reproduction-only apparatus can be constructed by removing the write unit generator 12 from the recording and reproducing apparatus 1 of FIG. 2. In a similar way, writing of data by the writing/reading portion 13, and the control operation for writing of data by the controller are unnecessary.

The recording and reproducing apparatus according to the present invention can seek for and reproduce just audio data, i.e., digital audio data in the embodiments of the present invention, recorded in a particular track, without reproducing mute data as needed. The audio recording medium according to the present invention stores mute data and audio data in segregated AOBUs, and thus the start point of audio data a user desires to reproduce can be simply found by searching for the location of the audio AOBUs. In other words, when audio data are reproduced from a conventional recording medium by a conventional reproducing apparatus, two stages of searching are required: for the location of an AOBUs

containing target audio data throughout the recording medium, and then for the location of the audio data within the AOBUs. In contrast, as for the recording medium, and the recording and reproducing apparatus according to the present invention, target audio data can be reproduced by searching for just the location of the start AOBUs of the audio data. Thus, searching time can be shortened.

As previously mentioned, according to the present invention, mute data that serve as track identification data for a plurality of tracks to which audio data are recorded, are recorded in write units segregated from audio data. Thus, mute data can be easily removed if a user desires to reproduce just audio data without mute period. In addition, by moving the location of the track start point in a target track, length of the period of Index 0, i.e., the duration of mute period, can be easily adjusted. According to the present invention, when digital audio data being reproduced from a conventional CD by a CD player are recorded, the periods of Index 0 allocated to tracks of the CD can be recorded.

While this invention has been particularly shown and described with reference to preferred embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made to the described embodiments without departing from the spirit and scope of the invention as defined by the appended claims.



What is claimed is:

1 1. An audio recording medium in which audio data are recorded in a
2 plurality of tracks and identification data for indicating the start position of each of
3 the tracks are recorded in write units segregated from the audio data.

1 2. The audio recording medium of claim 1, wherein the identification data
2 are recorded in at least one write unit at the start of each of the tracks.

1 3. The audio recording medium of claim 2, wherein the audio data are
2 recorded in at least one write unit, following the identification data recorded in the at
3 least one write unit.

1 4. The audio recording medium of claim 1, wherein the write unit includes
2 an audio object unit (AOBU), and the identification data includes mute data.

1 5. The audio recording medium of claim 4, wherein a mute period for the
2 mute data is equal to or shorter than the duration of a single AOBU.

1 6. The audio recording medium of claim 5, wherein the mute period
2 includes a duration from a track start point to the end of the AOBU with mute data,
3 and the mute period is varied by moving the location of the track start point.

1 7. The audio recording medium of claim 4, wherein a mute period for the
2 mute data is longer than the duration of a single AOBU, and the number of the
3 AOBUs with mute data is determined such that the sum of the duration of each of
4 the AOBUs is equal to or slightly longer than the mute period.

1 8. The audio recording medium of claim 7, wherein the mute period
2 includes a period from a track start point to the end of the last AOBU among the
3 plurality of the AOBUs with mute data, and the mute period is varied by moving the
4 location of the track start point.



1 9. The audio recording medium of claim 4, wherein information on the
2 mute period is recorded in a reproduction control information area.

1 10. The audio recording medium of claim 4, wherein the mute data are
2 indexed with Index 0.

1 11. A method for recording data in a plurality of tracks of a recording
2 medium, and reproducing data from the recording medium, the method comprising:
3 recording identification data for indicating the start position of each of the
4 tracks in predetermined write units; and
5 recording audio data in write units segregated from the predetermined write
6 units of the identification data.

1 12. The method of claim 11, further comprising:
2 reading and reproducing the identification data recorded in the predetermined
3 write units; and
4 reading and reproducing the audio data recorded in the write units
5 segregated from the predetermined write units of the identification data.

1 13. The method of claim 12, wherein the identification data are recorded in
2 at least one write unit at the start of each of the tracks.

1 14. The method of claim 13, wherein the write unit includes an audio
2 object unit (AOBU), and the identification data includes mute data.

1 15. The method of claim 14, wherein a mute period for the mute data is
2 equal to or shorter than the duration of a single AOBU.

1 16. The method of claim 15, wherein the mute period includes a duration
2 from a track start point to the end of the AOBU with mute data, and the mute period
3 is varied by moving the location of the track start point.



1 17. The method of claim 14, wherein a mute period for the mute data is
2 , longer than the duration of a single AOBU, and the number of the AOBUs with mute
3 data is determined such that the sum of the duration of each of the AOBUs is equal
4 to or slightly longer the mute period.

1 18. The method of claim 7, wherein the mute period includes a duration
2 from a track start point to the end of the last AOBU among the plurality of the
3 AOBUs with mute data, and the mute period is varied by moving the location of the
4 track start point.

1 19. The method of claim 14, wherein information on the mute period is
2 recorded in a reproduction control information area.

1 20. The method of claim 14, wherein the mute data are indexed with Index
2 0.

1 21. A method for reproducing data recorded in a plurality of tracks of a
2 recording medium, the method comprising:
3 reading and reproducing identification data for indicating the start position of
4 each of the tracks, the identification data being recorded in predetermined write
5 units; and
6 reading and reproducing audio data recorded in write units segregated from
7 the predetermined write units of the identification data.

1 22. The method of claim 21, wherein the identification data are recorded in
2 at least one write unit at the start of each of the tracks.

1 23. The method of claim 22, wherein the write unit includes an audio
2 object unit (AOBU), and the identification data includes mute data.

1 24. The method of claim 23, wherein a mute period for the mute data is
2 equal to or shorter than the duration of a single AOBU.



1 25. The method of claim 24, wherein the mute period includes a duration
2 from a track start point to the end of the AOBU with mute data, and the mute period
3 is varied by moving the location of the track start point.

1 26. The method of claim 23, wherein a mute period for the mute data is
2 longer than the duration of a single AOBU, and the number of the AOBUs with mute
3 data is determined such that the sum of the duration of each of the AOBUs is equal
4 to or slightly longer than the mute period.

1 27. The method of claim 26, wherein the mute period includes a duration
2 from a track start point to the end of the last AOBU among the plurality of the
3 AOBUs with mute data, and the mute period is varied by moving the location of the
4 track start point.

1 28. A method for reproducing data recorded in a plurality of tracks of a
2 recording medium in which identification data for indicating the start position of each
3 of the tracks are recorded in predetermined write units, and audio data are recorded
4 in write units segregated from the predetermined write units of the identification
5 data, the method comprising:

6 once a reproduction command for a track is input, searching for the write
7 units with audio data in the corresponding track; and
8 reading and reproducing the audio data from the found write units.

1 29. The method of claim 28, wherein the identification are recorded in at
2 least one write unit at the start of each of the tracks.

1 30. The method of claim 29, wherein the write unit includes an audio
2 object unit (AOBU), and the identification data includes mute data.

1 31. A method for recording data in a plurality of tracks of a recording
2 medium, and reproducing data from the recording medium, the method comprising:



3 determining whether there is a need to record identification data for indicating
4 the start position of each of the tracks in a particular track;
5 if recording of the identification data is needed, recording the identification
6 data in the particular track in at least one write unit; and
7 recording audio data in the particular track in at least one write unit
8 segregated from the at least one write unit of the identification data.

1 32. The method of claim 31, wherein the identification data are recorded in
2 at least one write unit at the start of each of the tracks.

1 33. The method of claim 32, wherein the audio data are recorded in at
2 least one write unit, following the identification data recorded in the at least one
3 write unit.

1 34. The method of claim 33, further comprising:
2 reading and reproducing the identification data recorded in the at least one
3 write unit at the start of each of the tracks; and
4 successively reading the audio data recorded in the at least one write unit,
5 following the identification data, and reproducing the read audio data.

1 35. The method of claim 34, wherein the write unit includes an audio
2 object unit (AOBU), and the identification data includes mute data.

1 36. An apparatus for recording data in a plurality of tracks of a recording
2 medium, in which identification data for indicating the start position of each of the
3 tracks are recorded in predetermined write units, and audio data are recorded in a
4 track in write units segregated from the predetermined write units of the
5 identification data.

1 37. The apparatus of claim 36, wherein the identification data are recorded
2 in at least one write unit at the start of each of the tracks.



1 38. The apparatus of claim 37, wherein the audio data are recorded in at
2 , least one write unit, following the identification data recorded in the at least one
3 write unit.

1 39. The apparatus of claim 38, comprising:
2 a write unit generator for generating the at least one write unit with the audio
3 data, and the at least one write unit with the identification data;
4 a write portion for writing each of the at least one write unit with the audio
5 data and the identification data in the corresponding tracks; and
6 a controller for outputting a command to instruct generation of the at least
7 one write unit with the identification data to the write portion.

1 40. The apparatus of claim 39, wherein the write unit includes an audio
2 object unit (AOBU), and the identification data includes mute data.

1 41. The apparatus of claim 40, wherein the controller outputs a track start
2 point to the writing portion, the track start point allowing a mute period for the mute
3 data to be equal to or shorter than the duration of a single AOBU with the mute data;
4 and the write portion writes the track start point from the controllers in a reproduction
5 control information area of the recording medium.

1 42. The apparatus of claim 42, wherein the mute period includes a
2 duration from the track start point to the end of the AOBU with mute data, and the
3 mute period is varied by moving the location of the track start point.

1 43. The apparatus of claim 42, wherein if a mute period for the mute data
2 is longer than the duration of a single AOBU, the controller outputs information on
3 the number of the AOBUs with mute data corresponding to the mute period to the
4 write unit generator, and the write unit generator generates a number of AOBUs with
5 mute data according to the information from the controller.



1 44. The apparatus of claim 43, wherein the mute period includes a
2 duration from the track start point to the end of the last AOBUs among the AOBUs
3 with mute data, and the mute period is varied by moving the location of the track
4 start point.

1 45. The apparatus of claim 44, wherein the number of the AOBUs with
2 mute data generated by the write unit generator is determined such that the sum of
3 the duration of each of the AOBUs with mute data is equal to or slightly longer than
4 the mute period.

1 46. An apparatus for reproducing data recorded in a plurality of tracks of a
2 recording medium, in which identification data recorded in predetermined write units
3 to indicate the start position of each of the tracks are read and reproduced, and
4 audio data recorded in write units segregated from the predetermined write units of
5 the identification data are read and reproduced.

1 47. The apparatus of claim 46, wherein the identification data recorded in
2 at least one write unit at the start of each of the tracks are read and reproduced.

1 48. The apparatus of claim 47, wherein the audio data recorded following
2 the identification data in at least one write unit segregated from the at least one
3 write unit of the identification data are read and reproduced.

1 49. The apparatus of claim 48, comprising:
2 a controller for outputting a command to instruct reading of the identification
3 data or audio data recorded in the corresponding at least one write unit;
4 a reading portion for reading the identification data or audio data recorded in
5 the corresponding at least one write unit, according to the command from the
6 controller; and
7 a reproduction portion for receiving and reproducing the identification data or
8 the audio data from the reading portion.



1 50. The apparatus of claim 49, wherein the write unit includes an audio
2 object unit (AOBU), and the identification data includes mute data.

1 51. The apparatus of claim 50, wherein the controller outputs a
2 reproduction control information corresponding to a user's input to the reading
3 portion; and the reading portion searches for the AOBU having a track start point in
4 a corresponding track, finds the location of the track start point in the found AOBU,
5 read data from the track start point in the corresponding track, and outputs the read
6 data to the reproduction portion.

1 52. The apparatus of claim 51, wherein a mute period for the mute data
2 includes a duration from the track start point to the end of the AOBU with mute data,
3 and the mute period is varied by moving the location of the track start point.

1 53. The apparatus of claim 52, wherein once the reading portion reads the
2 AOBU with the mute data and outputs the read AOBU to the reproduction portion,
3 the reproduction portion mutes the outputs for the mute period.

1 54. The apparatus of claim 53, wherein once the AOBU with mute data is
2 read by the reading portion, the controller outputs a mute command to the
3 reproduction portion, and the reproduction portion performs a mute operation
4 according to the mute command from the controller.