

GRINDING AND EXTRACTION APPARATUS FOR COFFEE BEANS

1. Field of the invention

5 The present invention relates to an apparatus for grinding coffee beans and for extracting a beverage from said grinded coffee, and to an associated method for grinding and extracting a beverage.

2. Technical background

10

In all domains of food and beverage preparation, the quality of the prepared food or beverage requires, at least: adequate quality of the raw product; right tools (machines, devices, etc.) and knowledge and skills to ensure the right preparation processes.

15

Hot beverage preparation, more particularly coffee preparation and its derivatives, also obey the same rules.

20

Since the very first invention of a coffee extraction machine, the associated techniques have heavily evolved during the last decades. It is known in the state of the art that the first machine for making espresso was built and patented in 1884 by Angelo Moriondo of Turin, Italy. An improved design was later patented on April 28, 1903, by Luigi Bezzera. The founder of the La Pavoni company bought the patent and from 1905 produced espresso machines commercially on a small scale in Milan. Multiple machine designs have been created to produce espresso. Several machines share some common elements, such as a group head and a portafilter. An espresso machine may also have a steam wand which is used to steam and froth liquids (such as milk) for coffee drinks such as cappuccino and caffè latte.

25

30

Fully Automatic machines using roasted beans to prepare a coffee beverage are widely known in the state of the art. In the 80's fully automated machines of diverse brands (Jura, Saeco, etc.) have followed the trend of automation. Consequently, they have grouped all the functions done by a Barista (skilled person preparing coffee beverages) in a single machine, including grinding of coffee beans, dosing, tamping, as well as

extraction of the coffee beverage. As a consequence, in these machines, the operator only needs to fill the bean hopper and, if the machine is not connected to a water line, add water to a reservoir. The rest is automatically done by the machine itself.

5 Fully Automatic machines are growing in the market as they simplify the extraction steps and can be used by a non-skilled person. However, they are bulky and complex, and more importantly, they are considered to be a compromise between preparation quality and convenience.

10 Fully automatic machines take away the ability to manually tamping and grinding the coffee, which may affect the quality of the espresso, as this setting cannot be changed from a beverage to another.

15 Typically, the grinder can be adjustable to get the right grind size for the desired beverage: however once adjusted, the same grind size is used for all the beverages. And most importantly, the machine is never adjusted by the user according to the different coffee beans used. This results in a compromise of quality and convenience of the final beverage delivered.

The system of the invention comes to solve these limitations, as it will be further explained.

20 The main object of the present invention is to achieve similar end results of the coffee beverage delivered than those obtained when using a capsule system without the need of using any single serve packaging, and without any specific skills being needed. The invention achieves this by building a system comprising several main-devices that communicate between themselves via accessory-devices, that transfer/communicate the required parameters in order to replace a Barista know-how by an artificial intelligence (AI) system.

25 The system of the invention adjusts the parameters of each main-device (the inputs), according to the outputs of the main-device used in the previous phase. The goal is to ensure the integrity of the procedure and the information by communicating the right parameters to be used.

30 Fully automatic beverage preparation machines are known in the state of the art and are widely used for preparing coffee beverages. These automatic machines provide a fully automatic process, starting with storing the roasted coffee beans and ending with the delivery of the coffee beverage into a cup. Patent Application EP2314188A1

describes an apparatus for refilling the filter-holders provided with a code of an espresso coffee machine with selected doses of ground coffee. The operator can take the filter-holder with the ground coffee and move it to the dispensing unit of the machine which recognises the filter-holder via a sensor able only to recognize the presence of the filter-holder or type of the filter-holder, via the code of the same.

Differently to a fully automated machine, the system of the invention allows more flexibility by using different accessory-devices, tailored to the right preparation, between the main-devices. Typically, these accessory-devices are devices for espresso, drip coffee, soluble coffee, etc.

Differently to single serve systems (typically those using capsules), the system of the present invention does not use a single packaging for each beverage preparation, but a multipack, and uses accessory-devices for extraction/processing.

These and other objects, which become apparent upon reading the following description, are solved by the subject matter of the independent claim. The dependent claims refer to preferred embodiments of the invention.

These and other objects, which become apparent upon reading the following description, are solved by the subject matter of the independent claim. The dependent claims refer to preferred embodiments of the invention.

3. Summary of the invention

According to a first aspect, the invention relates to a grinding and extraction apparatus for roasted coffee beans comprising a grinding device and an associated extraction device. The grinding device comprises one or more housings for receiving one or more beans containers with roasted coffee beans of the same or different types: the grinding device comprises a reader to obtain the information of the product parameters of the roasted coffee beans of the one or more beans containers and it further comprises a control unit configured to adapt the grinding size and the quantity of roasted coffee beans for obtaining a certain coffee blend from each beans container to be grinded according to these product parameters and/or according to a recipes database comprising the beverage information associated to the beverage to be prepared. The grinding device of the invention further comprises an encoder to encode the beverage

information on programmable identification means on a product holder in the grinding device, to where the grinded coffee is sent. The extraction device is configured for receiving the product holder and comprises reading means to identify the beverage information in the said product holder identification means, the extraction device further comprising a control unit to extract the beverage according to the beverage information retrieved and/or from the beverage information retrieved from a beverage database in this control unit.

Preferably, in the grinding and extraction apparatus for roasted coffee beans of the invention, the beverage information comprises one or a plurality of the following data: beverage type, beverage volume, brewing temperature and/or brewing pump profile, brewing profile according to time.

In the apparatus of the invention, typically, the characteristics of the coffee beans are one or a plurality of the following: coffee beans type, coffee beans origin, batch volume, recommended roasting level or levels, date of harvest, date of production, production data, farmer data, date of expiration, company and or marketing info.

According to a preferred embodiment, the product holder in the grinding and extraction apparatus of the invention comprises plugging means to be quickly plugged and/or unplugged onto the grinding device and onto the extraction device so it is freely exchangeable.

Preferably, the product holder in the apparatus of the invention is locked on the grinding device and on the extraction device to allow firm fix of it during the grinding and the extraction operations, respectively.

Typically, the coffee beans received by the grinding device comprise identification means with the characteristics of these roasted coffee beans, to be read by the reading means in the grinding device, these identification means being optical, such as a barcode, OID and/or a QR code, and/or electromagnetically read identification means such as a RFID tag.

In the apparatus of the invention, preferably, the quantity of coffee to be grinded, the grinding size and the blend in the grinding device are adapted as a function of the type of beverage to be prepared from the roasted and grinded coffee beans in combination of the product parameters of the roasted coffee beans of the one or plurality of beans containers connected to the grinding device.

Typically, the one or plurality of coffee beans containers have an embedded dosing device to dose only the needed quantity of roasted coffee beans in the grinding device.

In the grinding and extraction apparatus for roasted coffee beans of the invention, typically, the grinding device comprises a motor and a drive to control the embedded dosing device of the one or plurality of coffee beans containers to dose only the needed dose of roasted coffee beans to the grinding device.

According to a preferred embodiment of the invention, the grinding device comprises a RFID tag reader to obtain the information of the product parameters of the roasted coffee beans of the one or more beans containers connected to it.

According to a second aspect, the invention further relates to a method for grinding roasted coffee beans and preparing a beverage from them using a grinding and extraction apparatus as described. The method of the invention comprises the following steps:

- reading the product parameters in the coffee beans containers;
- adapting the grinding size according to the product parameters read and/or according to a recipes database;
- dispensing a certain quantity of roasted coffee beans from a beans container in the grinding device;
- carrying out the grinding as to grinding size and quantity according to the product parameters read and/or according to a recipes database;
- encoding the beverage information on the product holder in the grinding device;
- transferring the product holder to the extraction device manually or automatically;
- reading the beverage information from the product holder by the extraction device and extracting the beverage according to the beverage information retrieved and/or from the beverage information retrieved from a beverage database.

Preferably, in the method of the invention, where a certain coffee blend is produced in the grinding device and is put in the product holder, the method comprises the following further steps:

- attaching a plurality of coffee beans containers into the grinding device;
- reading the product parameters in each of the plurality of the coffee beans containers;
- carrying out the grinding as to grinding size and quantity of each of the coffee beans containers according to the product parameters read for each and to the type of

beverage to be prepared from the recipes database from the roasted and grinded coffee beans.

Yet according to a third aspect, the invention further relates to the use of a grinding and extraction apparatus as the one described for delivering a certain beverage from roasted coffee beans.

Further features, advantages and objects of the present invention will become apparent for a skilled person when reading the following detailed description of non-limiting embodiments of the present invention, when taken in conjunction with the appended drawings.

4. Description of a preferred embodiment

In the following, the invention is described exemplarily with reference to the enclosed figures, in which

Figure 1 is an exemplary functional diagram of a roasting, grinding, extraction system according to an embodiment of the invention.

Figure 2 is an exemplary functional diagram of a dosing, extraction system according to an embodiment of the invention.

Figure 3 is a schematic view of a dispensing, extraction system according to an embodiment of the invention.

Figure 4 is a schematic view of a roasting, grinding, extraction system according to an embodiment of the invention.

Figure 5 is a schematic view of a roasting, grinding system according to an embodiment of the invention.

Figure 6 is a schematic representative view of a roasting, grinding, extraction system according to an embodiment of the invention.

Figure 7 is a schematic representative view of a roasting, grinding, extraction system according to an embodiment of the invention, showing the different elements belonging to it.

5 Figure 8 is a schematic representative view of the roasting, grinding, extraction system in Figure 7, showing the reading of identification means in the container comprising the coffee beans.

Figure 9 is a schematic representative view of the roasting, grinding, extraction system in Figure 7, showing the delivery of the coffee beans into the roasting device.

10 Figure 10 is a schematic representative view of the roasting, grinding, extraction system in Figure 7, showing the process of roasting the coffee beans in the roasting device.

Figure 11 is a schematic representative view of the roasting, grinding, extraction system in Figure 7, showing the plugging of a container in the grinding or dispensing device.

15 Figure 12 is a schematic representative view of the roasting, grinding, extraction system in Figure 7, showing two containers plugged in the grinding or dispensing device.

20 Figure 13 is a schematic representative view of the roasting, grinding, extraction system in Figure 7, showing the reading of identification means in the container comprising the coffee beans.

Figure 14 is a schematic representative view of the roasting, grinding, extraction system in Figure 7, showing the beverage finally dispensed in a cup.

Figure 15 is a schematic representative view of the roasting, grinding, extraction system in Figure 7, showing the dispensing of the beverage in a cup.

25 Figure 16 is a schematic representative view of the roasting, grinding, extraction system in Figure 7, showing the system prepared for dispensing a beverage.

Figure 17 is a schematic representative view of the roasting, grinding, extraction system in Figure 7, showing the dispensing of grinded coffee for the further preparation of a beverage.

Figure 18 is a schematic representative view of the roasting, grinding, extraction system in Figure 17, showing the grinded coffee arranged in the preparation device, ready to prepare a beverage.

Figure 19 is a schematic representative view of the roasting, grinding, extraction system in Figure 7, showing the possibility of plugging in the grinding device several containers comprising different types of coffee beans.

Figure 20 is a schematic representative view of the roasting, grinding, extraction system in Figure 7, showing different containers comprising different types of coffee beans that can be plugged in the grinding device in order to obtain different coffee blends.

The main goal of the present invention is to achieve similar end results as the ones achieved with a capsule system without using any single serve packaging, and without specific skills needed. The goal of the invention, as it will be explained in more detail in what follows, is to build main-devices that communicate among them via accessory-devices, that transfer/communicate parameters in order to replace the Barista (skilled person) know-how by an AI (Artificial Intelligence) system.

The system of the present invention adjusts each main-device parameters (inputs), according to the outputs of the main-device used in the previous phase. The goal is to ensure the integrity of the procedure and of the information by communicating the right parameters to be used.

In difference to fully automated machines, the system of the invention further allows more flexibility by using different accessory-devices (tailored to the right preparation: typically accessory devices for Espresso, Drip coffee, Soluble Coffee, etc.) between the main-devices.

In difference to single serve systems (typically preparing a beverage from a capsule or single-dose container), the system of the invention does not use a single packaging for each preparation, but a multipack, and uses accessory-devices for the extraction/processing.

Looking at Figure 1, it shows a roasting device 50 comprising a reader 53 and an encoder 52. The reader 53 is able to retrieve the information on the identification means 41 of a container 40 comprising coffee beans: these coffee beans can be green or partially roasted or a mixture of the two. The identification means 41 comprise the Information 0 of the coffee beans in the container 40, as represented schematically in Figure 1. This Information 0 can comprise one or a plurality of the following information: coffee beans type, coffee beans origin, batch volume, recommended roasting level, date of expiration, etc. The identification means 41 in the container 40 can be optical (barcode, QR code, OID) or electromagnetically readable codes (typically, a RFID code). The roasting device 50 further comprises a control unit configuring the roasting profile of the beans according to the characteristics retrieved from the reading means 53 and/or from the characteristics of the beans in a database 51 in this control unit and/or according to the user's input. The roasting device 50 therefore makes the roasting of the green beans, partially roasted beans or the mixture of the two based on this information, and then delivers the roasted coffee beans into a beans container 10, 20. The beans container 10, 20 comprises programmable identification means 21 where product parameters of the roasted coffee beans of a certain type are encoded on it by an encoder 52 in the roasting device. The information encoded on the beans containers 10, 20 is named as Information 1 in the schematic diagram of Figure 1, and this Information 1 comprises one or a plurality of the following information: Information 0 as explained above and roasting level, date of roasting, coffee origin, roasting profile, roasting date, etc.

The system of the invention further comprises a grinding device 60 comprising one or more housings for receiving one or more beans containers 10, 20. The grinding device 60 comprises a reader 62 to obtain the information of the product parameters (Information 1) of the roasted coffee beans of the one or more beans containers 10, 20. The grinding device 60 further comprises a control unit configured to adapt the grinding size and the quantity of roasted coffee beans to be delivered from the coffee beans containers 10, 20 for obtaining a certain coffee quantity and/or a certain coffee blend quantity from each beans container to be grinded according to these product parameters (Information 1) and/or according to a recipes database 64, and/or according to the user's input.

The grinded coffee is delivered from the grinding device 60 into a product holder 61: this product holder 61 comprises programmable identification means 65, where the encoder 63 in the grinding device 60 can encode the beverage information (called

Information 2). This information will comprise one or a plurality of the following: beverage type, volume of the beverage to prepare, beverage temperature, pump profile, etc. The product holder 61 comprising the beverage information (Information 2) with the grinded coffee, will then be transferred to a preparation or extraction device 70, where the final beverage (the coffee beverage) will be prepared and delivered into a cup. The preparation device 70 comprises reading means 72 able to retrieve the beverage information (Information 2) from the identification means 65 in the product holder 61 and therefore make the beverage preparation (beverage extraction) according to this information.

Looking now at Figure 2, an embodiment of the system of the invention is shown, particularly referring to a food product comprised in container 40 in the form of a powder. Similarly, the container 40 will be provided with identification means 41, optical (barcode, QR code, OID) or electromagnetically readable codes (typically, a RFID code) comprising the product information (Information 0 of the product type, such as coffee or milk, etc, and the date of expiration, for example). The system will comprise a dispensing device (60) comprising a reader 62 to retrieve the information on the product from the container 40 and therefore make the dosing according to this information (Information 0). The dispensing device 60 can also be a grinding device, as explained in the previous Figure. According to a preferred embodiment, the powdered product will be comprised in a container 10, 20. The dispensing device 60 further comprises a control unit configured to dispense a certain amount of powdered food or beverage product from a container (either 40 or 10, 20) according to these product parameters (Information 0) and/or according to a recipes database 64 as a function of the beverage to be prepared. The dispensing device 60 further comprises an encoder 63 to encode the beverage information (Information 2) on programmable identification means 65 on a product holder 61 in the dispensing device 60, to where the dispensed powdered food or beverage product is sent. Similarly as to the embodiment described in Figure 1, the product holder 61 will be transferable into an extraction or preparation device 70 to prepare and dispense the final food or beverage product. The preparation device 70 will comprise a reader 72 to retrieve the beverage information (Information 2) from the identification means 65 in the product holder 61, and prepare the beverage accordingly. This Information 2 will comprise one or a plurality of the following: beverage type, volume of the beverage to prepare, beverage temperature, pump profile, etc.

The embodiment represented functionally in Figure 2 is shown schematically in Figure 3: a dispensing device 60 receives a certain product container 10 comprising a certain type of a powder product (milk in powder, for example). The dosing device 60 reads the identification means in this container 10 and so retrieves the product information, therefore knowing which amount of milk powder has to be delivered into the product holder 61 for a certain beverage to be prepared (according to the user's input and/or to the information retrieved in a recipes database 64). A container 20 with another type of powdered product (coffee, for example) is plugged into the dosing device 60. The dosing device will read the information on this product and will deliver the amount needed on the product holder 61 for the beverage to be prepared (according to the user's input and/or to the information retrieved in a recipes database 64). The encoder 63 in the dosing device 60 will then encode the beverage information (Information 2) on the product holder 61 according to the user's input and/or to a recipes database 64. When the product holder 61 will be plugged in a preparation device 70, for the beverage preparation, the Information 2 for the certain beverage extraction will be retrieved by the device 70 so the preparation will be done according to certain parameters.

The functional diagram in Figure 1 is represented schematically in Figure 4. A container 40 with coffee beans (green and/or partially roasted) dispenses the beans into a roasting device 50. The Information 0 is read by the roasting device 50 so the roasting takes place according to certain parameters. The roasted coffee beans are delivered in a container 10. Similarly, a different type of coffee beans can be roasted in the roasting device 50 according to different parameters and can be delivered in a container 20. The containers 10, 20 can be plugged into a grinding device 60 where a certain amount of each one of the roasted beans from each of the containers 10, 20 can be sent into a product holder 61. This product holder 61 will be encoded with the beverage information (Information 2) so, when transferred into a dispensing or extraction device 70, the beverage preparation will take place according to certain parameters. The final beverage will be delivered into a cup 71, for example.

Still another embodiment of the system of the invention is represented in Figure 5. The roasting device 50 is configured for receiving coffee beans of a certain type from a container 40: these beans will be roasted. The roasting device 50 comprises reading means 53 to identify the characteristics of the coffee beans dispensed to it, and further comprises a control unit configuring the roasting profile of the beans according to the characteristics retrieved from the reading means and/or from the characteristics of the beans in a database in this control unit and/or according to the user input. The roasted

coffee beans are sent into a container 10 and are then transferred into a processing device 60. The processing device 60 can be a grinding device where the beans will be grinded (also another certain amount from a different container 20), sent to a product holder 61 that will then be transferred into a beverage preparation device 70 for the final beverage dispensing, or the processing device (not shown) can be a grinding device and a preparation or extraction device (functionalities of the device 60 and 70 together).

The roasting device 50 comprises a data transfer function to communicate product parameters of the roasted coffee beans of a certain type to the coffee processing device (grinding device or grinding and extraction device).

An schematic representation of the system of the invention is shown in Figure 6. The container 40 comprises coffee beans (green and/or partially roasted) that will be roasted in the device 50 and sent into containers 10, 20 for different types of coffee beans. The containers 10, 20 will be plugged in a grinding device 60 to deliver a certain blend into a product holder 61 that, when plugged in a preparation device 70, will deliver the coffee beverage into a cup 71.

Figure 7 represents the main components and connections of the system represented in Figure 6, namely the roasting device 50, the containers 10, 20, the dispensing or grinding device 60 and the preparation or extraction device 70.

Figure 8 shows the identification means 41 in the container 40 comprising the coffee beans. These identification means 41 will comprise the information on the coffee beans type and/or origin and/or the batch volume and/or date of expiration and/or recommended roasting level, amongst other information. The reading means 53 in the roasting device 50 will retrieve this information and will consequently do the roasting according to certain parameters.

Figure 9 shows the beans from the container 40 being delivered into the roasting device 50 for being roasted, before being sent to one of the containers 10, 20 and then to the grinding device 60. Figure 10 shows the roasting step of the beans (green and/or partially roasted) in the roasting device 50.

The roasting device 50 opens (Figure 12) and one of the containers 10 or 20 plugged in the grinding device 60 is unplugged from it (Figure 11) so it can receive the roasted

beans coming from the roasting device 50 (Figure 13). Typically, the roasting device 50 will comprise a removable basket to where the unroasted and/or partially roasted beans are delivered from the container 40 and where they are later roasted. The basket will be able to be removed from the roasting device 50 and then the roasted beans can be sent into a container 10 or 20 that will be later plugged into a grinding device 60 (Figure 14).

Figure 16 shows schematically the roasting step in the system of the invention. Once the roasting is finished, grinding takes place (Figure 18) and the grinded coffee (coffee blend) is sent into a product holder 61 (Figure 17) that will be then plugged into a preparation or extraction device 70: the beverage preparation in the preparation or extraction device 70 and its delivery into a cup 71 is shown in Figure 15.

Figures 19 and 20 show schematically different types of coffee beans that can be in different containers 10, 20 so different coffee blends can be prepared. The system of the invention allows a high versatility and the containers 10, 20 can be quickly plugged and unplugged in the grinding or dispensing device 60 (plug and play type system).

According to a second object, the invention relates to a method for roasting and grinding coffee beans using a roasting and grinding apparatus as the one described.

According to a third object, the invention further relates to the use of a roasting and grinding apparatus as the one described for delivering a blend of roasted and grinded coffee beans in a certain quantity.

It should be clear to a skilled person that the embodiments shown in the figures are only preferred embodiments, but that, however, also other designs of a system can be used.

Claims

1. Grinding and extraction apparatus for roasted coffee beans comprising a grinding device (60) and an associated extraction device (70);

5 the grinding device (60) comprising one or more housings for receiving one or more beans containers (10, 20) with roasted coffee beans of the same or different types; the grinding device (60) comprising a reader (62) to obtain the information of the product parameters of the roasted coffee beans of the one or more beans containers (10, 20); the grinding device (60) further comprising a control unit configured to adapt the grinding size and the quantity of roasted coffee beans for obtaining a certain coffee blend from each beans container to be grinded according to these product parameters and/or according to a recipes database (64) comprising the beverage information associated to the beverage to be prepared;

15 the extraction device (70) being configured for receiving a product holder (61) and comprising reading means (72) to identify the beverage information in a product holder identification means (65), the extraction device (70) further comprising a control unit to extract the beverage according to the beverage information retrieved and/or from the beverage information retrieved from a beverage database in this control unit;

20 the grinding and extraction apparatus for roasted coffee beans is characterized in that the grinding device (60) further comprising an encoder (62) to encode the beverage information on said programmable identification means (65) on the product holder (61) in the grinding device (60), to where the grinded coffee is sent.

25 2. Grinding and extraction apparatus for roasted coffee beans according to claim 1 wherein the beverage information comprises one or a plurality of the following data: beverage type, beverage volume, brewing temperature and/or brewing pump profile, brewing profile according to time.

30 3. Grinding and extraction apparatus for roasted coffee beans according to any of the previous claims wherein the characteristics of the coffee beans are one or a plurality of the following: coffee beans type, coffee beans origin, batch volume, recommended roasting level or levels, date of harvest, date of production, production data, farmer data, date of expiration, company and or marketing info.

35

4. Grinding and extraction apparatus for roasted coffee beans according to any of the previous claims wherein the product holder (61) comprises plugging means to be quickly plugged and/or unplugged onto the grinding device (60) and onto the extraction device (70) so it is freely exchangeable.
- 5 5. Grinding and extraction apparatus for roasted coffee beans according to any of the previous claims wherein the product holder (61) is locked on the grinding device (60) and on the extraction device (70) to allow firm fix of it during the grinding and the extraction operations, respectively.
- 10 6. Grinding and extraction apparatus for roasted coffee beans according to any of the previous claims wherein the coffee beans received by the grinding device (60) comprise identification means (21) with the characteristics of these roasted coffee beans, to be read by the reading means (62) in the grinding device, these identification means being
15 optical, such as a barcode, OID and/or a QR code, and/or electromagnetically read identification means such as a RFID tag.
- 20 7. Grinding and extraction apparatus for roasted coffee beans according to any of the previous claims wherein the quantity of coffee to be grinded, the grinding size and the blend in the grinding device (60) are adapted as a function of the type of beverage to be prepared from the roasted and grinded coffee beans in combination of the product parameters of the roasted coffee beans of the one or plurality of beans containers (10, 20) connected to the grinding device (60).
- 25 8. Grinding and extraction apparatus for roasted coffee beans according to any of the previous claims wherein the one or plurality of coffee beans containers (10, 20) have an embedded dosing device to dose only the needed quantity of roasted coffee beans in the grinding device (60).
- 30 9. Grinding and extraction apparatus for roasted coffee beans according to claim 7 wherein the grinding device (60) comprises a motor and a drive to control the embedded dosing device of the one or plurality of coffee beans containers (10, 20) to dose only the needed dose of roasted coffee beans to the grinding device (60).
- 35 10. Grinding and extraction apparatus for roasted coffee beans according to claim 7 wherein the grinding device (60) comprises a RFID tag reader (62) to obtain the information of the product parameters of the roasted coffee beans of the one or more beans containers (10, 20) connected to it.

11. Method for grinding roasted coffee beans and preparing a beverage from them using a grinding and extraction apparatus according to any of claims 1-10, comprising the following steps:

- 5 - reading the product parameters in the coffee beans container (10, 20);
- adapting the grinding size according to the product parameters read and/or according to a recipes database;
- dispensing a certain quantity of roasted coffee beans from a beans container (10, 20) in the grinding device (60);
- 10 - carrying out the grinding as to grinding size and quantity according to the product parameters read and/or according to a recipes database;
- encoding the beverage information on the product holder (61) in the grinding device (60);
- transferring the product holder (61) to the extraction device (70) manually or
- 15 automatically;
- reading the beverage information from the product holder (61) by the extraction device (70) and extracting the beverage according to the beverage information retrieved and/or from the beverage information retrieved from a beverage database.

20 12. Method for grinding roasted coffee beans and preparing a beverage from them according to claim 11 where a certain coffee blend is produced in the grinding device (60) and put in the product holder (61), the method comprising the following further steps:

- 25 - attaching a plurality of coffee beans containers (10, 20) into the grinding device (60);
- reading the product parameters in each of the plurality of the coffee beans containers (10, 20);
- carrying out the grinding as to grinding size and quantity of each of the coffee beans containers (10, 20) according to the product parameters read for each and to the
- 30 type of beverage to be prepared from the recipes database from the roasted and grinded coffee beans.

13. Use of a grinding and extraction apparatus according to any of claims 1-10 for delivering a certain beverage from roasted coffee beans.