CLAIMS

1. A mounting assembly for a door or a window, comprising:

a stile member having a first member arranged to be coupled to a door or window leaf and a second member extending from the first member, wherein the second member is arranged to at least partially conceal a hinged portion of a door or window assembly when the door or the window is an open position; and

a support structure attached to the stile member, wherein the support structure extends into a space defined by the first and second members of the stile member and is arranged to provide a surface of attachment for a hinge leaf within the space defined by the first and second members of the stile member.

2. The mounting assembly of claim 1, wherein the support structure comprises:

a first support member extending away from one of the first and second members of the stile member; and

a second support member extending from the first support member in a direction parallel to a plane of the one of the first and second members of the stile member from which the first support member extends.

3. The mounting assembly of claim 2, further comprising:

a hinge; and

a jamb,

wherein a first leaf of the hinge is attached to the second support member of the support structure and a second leaf of the hinge is attached to the jamb.

4. The mounting assembly of claim 3, wherein a width of the jamb is less than a length of the first member of the stile member.

5. The mounting assembly of claim 3 or 4, wherein the hinge is in a closed position when the door or the window is closed.

6. The mounting assembly of any one of claims 3 to 5, further comprising a cover releasably or rotatably attached to a first side of the jamb.

7. The mounting assembly of claim 6, wherein the cover is provided with one or more clips that are arranged to engage one or more protrusions on the first side of the jamb.

8. The mounting assembly of claim 6 or 7, wherein the cover is provided with a curved proximal end that is arranged to be rotatably received in a curved groove provided at the first side of the jamb.

9. The mounting assembly of any one of claims 6 to 8, wherein the second member of the stile member extends over the cover when the door or the window is closed.

10. The mounting assembly of any one of claims 6 to 9, further comprising a groove formed adjacent the first side of the jamb and a protrusion provided on the second leaf of the hinge, wherein the protrusion is arranged to be received in the groove of the jamb.

11. The mounting assembly of any one of claims 6 to 10, wherein the jamb further comprises an extended portion at a second side of the jamb, wherein the extended portion is arranged to at least partially conceal the hinged portion of the door or window assembly.

12. The mounting assembly of any one of the preceding claims, further comprising a panel attached to a surface of the stile member, wherein the surface of the stile member to which the panel is attached is parallel to a plane of the second member of the stile member.

13. A door or window assembly, comprising:

a mounting assembly according to any one of claims 3 to 8; and

a door or window leaf coupled to the first member of the stile member, wherein the door or window leaf has a thickness of between 50 millimetres (mm) and 70 mm.