

PAGING TIME DETERMINATION METHOD AND DEVICE, AND COMPUTER STORAGE MEDIUM

TECHNICAL FIELD

[0001] The present disclosure relates to the field of wireless communication, and more particularly, to a paging time determination method and device, and a computer storage medium.

BACKGROUND

[0002] In a Long Term Evolution (LTE) system, a network may send a paging to a terminal (User Equipment, UE) in an idle state and a UE in a connection state. For the UE, it receives a paging message on a paging time unit in a Paging Frame (PF) in a Discontinuous Reception (DRX) cycle.

[0003] The UE determines a position of the paging time unit belonging to itself within one DRX cycle according to its UE_ID, and then receives the paging message. However, the paging time unit has different types of time-frequency resources. When the time-frequency resource for carrying the paging message and a nominal resource of a Synchronization Signal block (SS block) are frequency division multiplexed, a minimum bandwidth capability of the UE in the system may be exceeded, which may result in that the UE cannot receive the paging.

SUMMARY

[0004] To solve the above technical problems, embodiments of the present disclosure provide a method and device for determining paging time, and a computer storage medium.

[0005] A method for determining paging time provided in an embodiment of the present disclosure includes:

[0006] receiving, by a terminal, paging configuration information;

[0007] determining, by the terminal, a type of a paging time unit corresponding to the terminal based on the paging configuration information;

[0008] determining, by the terminal, a set of paging time units based on the type of

the paging time unit; and

[0009] receiving, by the terminal, a paging message on at least one paging time in the set of paging time units,

[0010] wherein, the paging time unit includes at least one of a first type of a paging time unit and a second type of a paging time unit.

[0011] In the embodiments of the present disclosure, determining, by the terminal, the type of the paging time unit corresponding to the terminal based on the paging configuration information includes:

[0012] obtaining, by the terminal, time-frequency resource information corresponding to the paging message from the paging configuration information; and

[0013] determining, by the terminal, the type of the paging time unit corresponding to the terminal based on at least one of: the time-frequency resource information corresponding to the paging message, time-frequency resource information of an SS block, or preset bandwidth information.

[0014] In the embodiments of the present disclosure, determining, by the terminal, the type of paging time unit corresponding to the terminal based on the paging configuration information includes:

[0015] obtaining, by the terminal, paging indication information from the paging configuration information; and

[0016] determining, by the terminal, the type of the paging time unit corresponding to the terminal based on the paging indication information.

[0017] In the embodiments of the present disclosure, determining, by the terminal, the type of paging time unit corresponding to the terminal based on at least one of the time-frequency resource information corresponding to the paging message, the time-frequency resource information of the SS block, or the preset bandwidth information includes:

[0018] determining, by the terminal based on at least one of the time-frequency resource information corresponding to the paging message, the time-frequency resource information of the SS block, or the preset bandwidth information, that the type of the paging time unit corresponding to the terminal is the first type of the paging time unit or the second

type of the paging time unit;

[0019] or,

[0020] determining, by the terminal based on at least one of the time-frequency resource information corresponding to the paging message, the time-frequency resource information of the SS block, or the preset bandwidth information, that the type of the paging time unit corresponding to the terminal is the first type of paging time unit and the second type of paging time unit.

[0021] In the embodiments of the present disclosure, the preset bandwidth information is minimum bandwidth information of the terminal, or the preset bandwidth information is bandwidth information corresponding to the terminal.

[0022] In the embodiments of the present disclosure, determining, by the terminal, the type of the paging time unit corresponding to the terminal based on the paging indication information includes:

[0023] determining, by the terminal based on the paging indication information, that the type of the paging time unit corresponding to the terminal is the first type of the paging time unit or the second type of the paging time unit; or

[0024] determining, by the terminal based on the paging indication information, that the type of the paging time unit corresponding to the terminal is the first type of the paging time unit and the second type of the paging time unit.

[0025] In the embodiments of the present disclosure, the first type of the paging time unit corresponds to a first type of time-frequency resource, and the second type of the paging time unit corresponds to a second type of time-frequency resource.

[0026] In the embodiments of the present disclosure, a size of a time-frequency resource corresponding to the first type of time-frequency resource is different from a size of a time-frequency resource corresponding to the second type of time-frequency resource;

[0027] and/or,

[0028] a multiplexing manner for the first type of time-frequency resource and a time-frequency resource of the SS block is different from a multiplexing manner for the second type of time-frequency resource and the time-frequency resource of the SS block.

[0029] In the embodiments of the present disclosure, the first type of the paging time

unit being corresponding to the first type of time-frequency resource includes that:

[0030] on symbols of a nominal resource for SS block transmission, the time-frequency resource corresponding to the first type of the paging time unit and the nominal resource are frequency divided.

[0031] In the embodiments of the present disclosure, the second type of paging time unit being corresponding to the second type of time-frequency resource includes that:

[0032] on symbols of a nominal resource which is not for SS block transmission, the time-frequency resource corresponding to the second type of the paging time unit includes the time-frequency resource of the nominal resource.

[0033] In the embodiments of the present disclosure, the second type of the paging time unit being corresponding to the second type of time-frequency resource includes that:

[0034] the time-frequency resource corresponding to the second type of the paging time unit and the nominal resource are time divided.

[0035] In the embodiments of the present disclosure, the paging time unit includes a paging occasion (PO) or a part of time units in the PO.

[0036] A method for determining paging time provided in the embodiments of the present disclosure includes:

[0037] transmitting, by a network, paging configuration information, the paging configuration information being configured for determining a type of a paging time unit corresponding to a terminal; and

[0038] transmitting, by the network, a paging message on at least one paging time unit in a set of paging time units corresponding to the paging configuration information,

[0039] wherein, the paging time unit includes at least one of a first type of a paging time unit and a second type of a paging time unit.

[0040] In the embodiments of the present disclosure, the paging configuration information includes time-frequency resource information corresponding to the paging message.

[0041] In the embodiments of the present disclosure, the paging configuration information includes paging indication information.

[0042] In the embodiments of the present disclosure, the first type of the paging time

unit corresponds to a first type of time-frequency resource, and the second type of paging time unit corresponds to a second type of time-frequency resource.

[0043] In the embodiments of the present disclosure, a size of a time-frequency resource corresponding to the first type of time-frequency resource is different from a size of a time-frequency resource corresponding to the second type of time-frequency resource;

[0044] and / or,

[0045] a multiplexing manner for the first type of time-frequency resource and a time-frequency resource of the SS block is different from a multiplexing manner for the second type of time-frequency resource and the time-frequency resource of the SS block.

[0046] In the embodiments of the present disclosure, the first type of paging time unit being corresponding to the first type of time-frequency resource includes that:

[0047] on symbols of a nominal resource for SS block transmission, the time-frequency resource corresponding to the first type of the paging time unit and the nominal resource are frequency divided.

[0048] In the embodiments of the present disclosure, the second type of paging time unit being corresponding to the second type of time-frequency resource includes that:

[0049] on symbols of a nominal resource which is not for SS block transmission, the time-frequency resource corresponding to the second type of the paging time unit includes the time-frequency resource of the nominal resource.

[0050] In the embodiments of the present disclosure, the second type of the paging time unit being corresponding to the second type of time-frequency resource includes that:

[0051] the time-frequency resource corresponding to the second type of the paging time unit and the nominal resource are time divided.

[0052] In the embodiments of the present disclosure, the paging time unit includes a PO or a part of time units in the PO.

[0053] A device for determining paging time provided in the embodiments of the present disclosure includes:

[0054] a first receiving unit, configured to receive paging configuration information;

[0055] a first determining unit, configured to determine a type of a paging time unit corresponding to the terminal based on the paging configuration information

[0056] a second determining unit, configured to determine a set of paging time units based on the type of the paging time unit; and

[0057] a second receiving unit, configured to receive a paging message on at least one paging time in the set of paging time units,

[0058] wherein, the paging time unit includes at least one of a first type of a paging time unit and a second type of a paging time unit.

[0059] In the embodiments of the present disclosure, the first determining unit is configured to obtain time-frequency resource information corresponding to the paging message from the paging configuration information; and determine the type of the paging time unit corresponding to the terminal based on at least one of: the time-frequency resource information corresponding to the paging message, time-frequency resource information of an SS block, or preset bandwidth information.

[0060] In the embodiments of the present disclosure, the first determining unit is configured to obtain paging indication information from the paging configuration information; and determine the type of the paging time unit corresponding to the terminal based on the paging indication information.

[0061] In the embodiments of the present disclosure, the first determining unit is configured to determine, based on at least one of the time-frequency resource information corresponding to the paging message, the time-frequency resource information of the SS block, or the preset bandwidth information, that the type of the paging time unit corresponding to the terminal is the first type of the paging time unit or the second type of the paging time unit; or determine, based on at least one of the time-frequency resource information corresponding to the paging message, the time-frequency resource information of the SS block, or the preset bandwidth information, that the type of the paging time unit corresponding to the terminal is the first type of the paging time unit and the second type of the paging time unit.

[0062] In the embodiments of the present disclosure, the preset bandwidth information is minimum bandwidth information of the terminal, or the preset bandwidth information is bandwidth information corresponding to the terminal.

[0063] In the embodiments of the present disclosure, the first determining unit is

configured to determine, based on the paging indication information, that the type of the paging time unit corresponding to the terminal is the first type of the paging time unit or the second type of the paging time unit; or determine, based on the paging indication information, that the type of paging time unit corresponding to the terminal is the first type of paging time unit and the second type of paging time unit.

[0064] In the embodiment of the present disclosure, the first type of the paging time unit corresponds to a first type of time-frequency resource, and the second type of the paging time unit corresponds to a second type of time-frequency resource.

[0065] In the embodiments of the present disclosure, a size of a time-frequency resource corresponding to the first type of time-frequency resource is different from a size of a time-frequency resource corresponding to the second type of time-frequency resource;

[0066] and/or,

[0067] a multiplexing manner for the first type of time-frequency resource and a time-frequency resource of the SS block is different from a multiplexing manner for the second type of time-frequency resource and the time-frequency resource of the SS block.

[0068] In the embodiments of the present disclosure, the first type of the paging time unit being corresponding to the first type of time-frequency resource includes that:

[0069] on symbols of a nominal resource for SS block transmission, the time-frequency resource corresponding to the first type of the paging time unit and the nominal resource are frequency divided.

[0070] In the embodiments of the present disclosure, the second type of paging time unit being corresponding to the second type of time-frequency resource includes that:

[0071] on symbols of a nominal resource which is not for SS block transmission, the time-frequency resource corresponding to the second type of the paging time unit includes the time-frequency resource of the nominal resource.

[0072] In the embodiments of the present disclosure, the second type of paging time unit being corresponding to the second type of time-frequency resource includes that:

[0073] the time-frequency resource corresponding to the second type of the paging time unit and the nominal resource are time divided.

[0074] In the embodiments of the present disclosure, the paging time unit includes a

PO or a part of time units in the PO.

[0075] A device for determining paging time provided in the embodiments of the present disclosure includes:

[0076] a first transmitting unit, configured to transmit paging configuration information, the paging configuration information being configured for determining a type of a paging time unit corresponding to a terminal; and

[0077] a second transmitting unit, configured to transmit a paging message on at least one paging time unit in a set of paging time units corresponding to the paging configuration information;

[0078] wherein, the paging time unit includes at least one of a first type of a paging time unit and a second type of a paging time unit.

[0079] In the embodiments of the present disclosure, the paging configuration information includes time-frequency resource information corresponding to the paging message.

[0080] In the embodiments of the present disclosure, the paging configuration information includes paging indication information.

[0081] In the embodiments of the present disclosure, the first type of the paging time unit corresponds to a first type of time-frequency resource, and the second type of the paging time unit corresponds to a second type of time-frequency resource.

[0082] In the embodiments of the present disclosure, a size of a time-frequency resource corresponding to the first type of time-frequency resource is different from a size of a time-frequency resource corresponding to the second type of time-frequency resource;

[0083] and/or,

[0084] a multiplexing manner for the first type of time-frequency resource and a time-frequency resource of the SS block is different from a multiplexing manner for the second type of time-frequency resource and the time-frequency resource of the SS block.

[0085] In the embodiments of the present disclosure, the first type of the paging time unit being corresponding to the first type of time-frequency resource includes that:

[0086] on symbols of a nominal resource for SS block transmission, the time-frequency resource corresponding to the first type of the paging time unit and the

nominal resource are frequency divided.

[0087] In the embodiments of the present disclosure, the second type of paging time unit being corresponding to the second type of time-frequency resource includes that:

[0088] on symbols of a nominal resource which is not for SS block transmission, the time-frequency resource corresponding to the second type of the paging time unit includes the time-frequency resource of the nominal resource.

[0089] In the embodiments of the present disclosure, the second type of paging time unit being corresponding to the second type of time-frequency resource includes that:

[0090] the time-frequency resource corresponding to the second type of the paging time unit and the nominal resource are time divided.

[0091] In the embodiments of the present disclosure, the paging time unit includes a PO or a part of time units in the PO.

[0092] A computer storage medium provided in the embodiments of the present disclosure has stored thereon computer-executable instructions which, when executed by a processor, implement the above method for determining paging time.

[0093] In the technical solutions of the embodiments of the present disclosure, the terminal receives paging configuration information; the terminal determines a type of a paging time unit corresponding to the terminal based on the paging configuration information; the terminal determines a set of paging time units based on the type of the paging time unit; and the terminal receives the paging message on at least one paging time unit in the set of paging time units; wherein, the paging time unit includes at least one of a first type of a paging time unit and a second type of a paging time unit. With the technical solutions of the embodiments of the present disclosure, when paging configuration on the network side changes, the UE can be informed of the set of paging time units available within the cell in time, so that the paging resource can be flexibly configured on the network side.

BRIEF DESCRIPTION OF THE DRAWINGS

[0094] The drawings described herein are used to provide a further understanding of the present disclosure and constitute a part of the present application. The exemplary embodiments of the present disclosure and the descriptions thereof are used to explain the

present disclosure and do not constitute an improper limitation on the present disclosure. In the drawings:

[0095] FIG. 1 is a schematic diagram of a base station sending a wireless signal through a beam;

[0096] FIG. 2 is a schematic diagram of an SS block;

[0097] FIG. 3 is a diagram of distribution of slots in different subcarrier spacings and frequency bands;

[0098] FIG. 4 is a diagram of distribution of SS blocks in different subcarrier spacings;

[0099] FIG. 5 is a diagram of position distribution of a predefined time-frequency resource where the SS block is located, in the slots;

[00100] FIG. 6 is a diagram of distribution of a PF and a PO;

[00101] FIG. 7 is a diagram of distribution of the time-frequency resource of a PO;

[00102] FIG. 8 is a first schematic flowchart diagram of a method for determining paging time in an embodiment of the present disclosure;

[00103] FIG. 9 is a first schematic structural composition diagram of a device for determining paging time in an embodiment of the present disclosure;

[00104] FIG. 10 is a second schematic flowchart diagram of a method for determining paging time in an embodiment of the present disclosure;

[00105] FIG. 11 is a second schematic structural composition diagram of a device for determining paging time in an embodiment of the present disclosure; and

[00106] FIG. 12 is a schematic structural composition diagram of a terminal in an embodiment of the present disclosure.

DETAILED DESCRIPTION

[00107] In order to facilitate understanding of the technical solution of the embodiments of the present disclosure, key technologies involved in the embodiments of the present disclosure are explained below.

[00108] 1) Beams in 5G

[00109] Because the frequency band used in the 5G system is higher than that of the

LTE system, a path loss of the wireless signal transmission of the 5G system is also larger than that of the LTE system, resulting in a smaller coverage of the wireless signal of the 5G system. As such, in the 5G system, a beamforming technology is used by a multi-antenna system of the base station to form beams so as to improve a gain of the wireless signal, thereby compensating for the path loss. In the beamforming technology, the beams are directional, and a narrow beam can only cover a partial region of the cell, and cannot cover the entire region of the cell. As shown in FIG.1, the base station can send signals through four beams in different directions (B1, B2, B3, and B4). For the beam B2, it can only cover UE1 and cannot cover UE2.

[00110] 2) SS blocks in 5G

[00111] Common channels and common signals such as broadcast channels and synchronization signals in the 5G system need to cover the entire cell in a multi-beam scanning manner, so that UEs in the cell can receive these signals. For the synchronization signals, the transmission of the multi-beams is achieved by defining a Synchronization Signal burst set (SS burst set). One SS burst set includes one or more synchronization signal bursts (SS bursts), and one SS burst includes one or more SS blocks (also referred to as SSBs for short). One SS block is configured to carry the synchronization signal and the broadcast channel for one beam. Therefore, one SS burst set can include the synchronization signals for beams of which the number is equal to the number of the SS blocks within the range of the cell. As shown in FIG. 2, one SS block includes a Primary Synchronization Signal (PSS) of one symbol, a Secondary Synchronization Signal (SSS) of one symbol, and a Physical Broadcast Channel (PBCH) of two symbols.

[00112] The number L of SS blocks included in one SS burst set is determined according to the frequency band of the system. For example:

for the frequency band of 3GHz, L is 4;

for the frequency band of 3GHz-6GHz, L is 8; and

for the frequency band of 6GHz-52.6GHz, L is 64.

[00113] For the SS burst set, the transmission cycle is configurable. In one example, the SS burst set in one cycle is transmitted within a time window of 5 ms. In addition, the subcarrier spacing (SCS) of the system can also be configurable. The distributions of slots in

different subcarrier spacings and frequency bands are shown in FIG. 3. FIG. 3 schematically shows respectively, from top to bottom:

slot distribution of the SS burst set at 15KHz SCS and $L = 4$ (corresponding to the frequency band of 3GHz);

slot distribution of the SS burst set at 15KHz SCS and $L = 8$ (corresponding to the frequency band of 3GHz-6GHz);

slot distribution of the SS burst set at 30KHz SCS and $L = 4$ (corresponding to the frequency band of 3GHz);

slot distribution of the SS burst set at 30KHz SCS and $L = 8$ (corresponding to the frequency band of 3GHz-6GHz);

slot distribution of the SS burst set at 120KHz SCS and $L = 64$ (corresponding to the frequency band of 6GHz-52.6GHz);

Slot distribution of the SS burst set at 240KHz SCS and $L = 64$ (corresponding to the frequency band of 6GHz-52.6GHz).

[00114] Further, for the distribution of the SS blocks within one slot, one slot includes 14 symbols, and can carry two SS blocks at most. The distributions of SS blocks at different subcarrier spacings are shown in FIG. 4. FIG. 4 schematically shows respectively, from top to bottom:

distribution of the SS blocks in one slot at 15KHz SCS;

distribution I of the SS blocks in one slot at 30KHz SCS;

distribution II of the SS blocks in one slot at 30KHz SCS;

distribution of the SS blocks in one slot at 120KHz SCS;

distribution of the SS blocks in one slot at 240KHz SCS.

[00115] In the above solution, although the number L of the SS blocks is determined according to the frequency band of the system, L is only the maximum number of the SS blocks. The number of the SS blocks which are actually transmitted by the network may be less than L . The number of the SS blocks actually transmitted by the network needs to be indicated to the UE, so that the UE can perform rate matching, and locations of the time-frequency resources that do not transmit the SS block can be used for transmission of other channels, such as a Physical Downlink Shared Channel (PDSCH). Here, the

information of the SS blocks actually transmitted by the network is indicated by a RMSI.

[00116] The location distribution of the predefined time-frequency resources, in which the SS blocks are located, in the slot is shown in FIG. 5. However, due to the cycles of the SS blocks are different and the SS blocks which are actually transmitted are different, the SS blocks may not necessarily be transmitted on the predefined time-frequency resources, and thus these predefined time-frequency resources are referred to as nominal resources of the SS blocks.

[00117] 3) Paging for LTE

[00118] In the LTE system, the network may transmit a paging to a UE in the idle state and a UE in the connection state. The paging process can be triggered by a core network or the base station, and is configured to transmit a paging request to the UE in the idle state, or to notify the UE of updated system information, or to notify the UEs to receive information such as Earthquake and Tsunami Warning System (ETWS) information, Commercial Mobile Alert Service (CMAS) and the like. After receiving the paging message of the core network, the base station parses the paging message to obtain a Tracking Area identity list (TA list) of the UE, and performs an air interface paging on the cells of the tracking areas which belong to the TA list. Further, after receiving the paging message of the core network, the base station aggregates the paging messages with the same PO into one piece of paging message and transmits it to a relevant UE through a paging channel. The UE receives paging parameters through a system message, calculates the PO in conjunction with its own International Mobile Subscriber Identification Number (IMSI), and receives the paging message at the corresponding time according to the PO. Here, the paging message is carried by the PDSCH, and the UE obtains the paging indication information by detecting a Physical Downlink Control Channel (PDCCH) scrambled with P-RNTI, so as to receive the paging message in the PDSCH. Further, the UE in the idle state saves power in a DRX manner. The UE obtains DRX-related information from SIB2, and monitors the PDCCH scrambled with P-RNTI on the PO in the PF within one DRX cycle to receive the paging message.

[00119] In the above solution, the PF indicates a system frame number at which the paging message should appear, and the PO indicates a sub-frame time at which the paging message may appear. One PF frame may include one or more PO sub-frames. In each DRX

cycle or paging cycle, the UE only needs to monitor the PO sub-frame belonging thereto. The distributions of the PF and the PO are shown in the FIG. 6. The System Frame Number (SFN) that satisfies the following formula can be used as one PF frame:

$$\text{SFN mod } T = (T \text{ div } N) \times (\text{UE_ID mod } N)$$

where T represents a DRX cycle or a paging cycle of the UE. If a default paging cycle carried in SIB2 is noted as T_{sib} , if a DRX value T_{ue} of the UE has been configured, $T = \min(T_{\text{ue}}, T_{\text{sib}})$ which represents a smaller value between T_{ue} and T_{sib} ; and if T_{ue} is not configured, $T = T_{\text{sib}}$. $\text{UE_ID} = (\text{IMSI mod } 1024)$, that is, all IMSIs are divided into 1024 groups of UEs. The IMSI is unique for each user. $N = \min(T, nB)$, which represents a smaller value between T and nB , where the parameter nB represents a density of the paging. The nB is carried in SIB2, and the value range is $\{4T, 2T, T, T/2, T/4, T/8, T/16, T/32\}$, so the value range of N is $\{T, T/2, T/4, T/8, T/16, T/32\}$. Actually, N indicates how many PFs are included in each cycle.

[00120] The location of the PO sub-frame is determined by a LTE mode (FDD or TDD) and parameters N_s and i_s , where N_s represents how many paging sub-frames there are in each PF, i_s represents an index of the paging sub-frame, and $N_s = \max(1, nB / T)$, $i_s = \text{floor}(\text{UE_ID} / N) \text{ mod } N_s$. As shown in Tables 1 and 2, N_s has only three values: 1, 2, and 4. For example, if the current mode is the LTE-FDD mode, $N_s = 4$, and if $i_s = 0$, $\text{PO} = 0$ and the paging message will be transmitted in sub-frame 0; and if $i_s = 2$, $\text{PO} = 5$, and the paging message will be transmitted in sub-frame 5. Finally, the UE determines the position of the PO of its own within one cycle according to the POs in the cell and its UE_ID . In this way, the UEs are evenly assigned to different POs.

N_s	PO ($i_s=0$)	PO ($i_s=1$)	PO ($i_s=2$)	PO ($i_s=3$)
1	9	N/A	N/A	N/A
2	4	9	N/A	N/A
4	0	4	5	9

Table 1 (FDD)

Ns	PO (i _s =0)	PO (i _s =1)	PO (i _s =2)	PO (i _s =3)
1	0	N/A	N/A	N/A
2	0	5	N/A	N/A
4	0	1	5	6

Table 2 (TDD)

[00121] 4) Paging for 5G

[00122] In 5G, for definitions of time-frequency resources of a PO, one of them is to define that the nominal resources corresponding to the SS blocks are used as time-frequency resources carrying the paging message in the PO. As shown in FIG. 7, on the symbols of the nominal resource where the SS block is actually transmitted, the time-frequency resource corresponding to the PO and the time-frequency resource corresponding to the nominal resource are frequency divided. This type of time-frequency resource corresponding to the PO is referred to as a first type of time-frequency resource; on the symbols of the nominal resource where the SS block is not transmitted, the time-frequency resource corresponding to the PO may include the time-frequency resource corresponding to the nominal resource. This type of time-frequency resource corresponding to the PO is referred to as a second type of time-frequency resource.

[00123] For the two types of time-frequency resources of the PO in FIG. 7, due to different sizes of the time-frequency resources, the capabilities of carrying the paging messages thereof are also different. Especially, for the first type of time-frequency resource, because the time-frequency resource corresponding to the PO and the time-frequency resource corresponding to the nominal resource are frequency divided, and a total bandwidth is required to meet a minimum bandwidth capability of the UE, the bandwidth used for carrying the paging messages is very limited.

[00124] In actual deployment of the system, a paging time unit that the network may configure (such as the PO or a part of the time unit in the PO) includes a first type of paging time unit and a second type of paging time unit. When the time-frequency resource configured for carrying the paging message and the nominal resource of the SS block are

frequency division multiplexed, the minimum bandwidth capability of the UE in the system may be exceeded, which may result in that the UE cannot receive the paging. As such, for the two types of paging time units configured by the network, the first type of paging time unit must be excluded.

[00125] The technical solutions of embodiments of the present disclosure are described below with reference to specific embodiments.

[00126] FIG. 8 is a first schematic flowchart diagram of a method for determining paging time in an embodiment of the present disclosure. As shown in FIG. 8, the method for determining the paging time includes the following steps.

[00127] In step 801, a terminal receives paging configuration information.

[00128] In the embodiment of the present disclosure, the terminal receives the paging configuration information sent by the network.

[00129] In step 802, the terminal determines a type of a paging time unit corresponding to the terminal based on the paging configuration information.

[00130] In the embodiment of the present disclosure, the terminal determining the type of the paging time unit corresponding to the terminal according to the paging configuration information may be implemented by, but not limited to, the following manners:

[00131] In a first manner, the terminal obtains time-frequency resource information corresponding to the paging message from the paging configuration information; and the terminal determines the type of the paging time unit corresponding to the terminal based on at least one of the time-frequency resource information corresponding to the paging message, time-frequency resource information of an SS block, or preset bandwidth information.

[00132] For the first manner, determining the type of the paging time unit corresponding to the terminal includes:

1) the terminal determining that the type of paging time unit corresponding to the terminal is the first type of the paging time unit or the second type of the paging time unit based on at least one of the time-frequency resource information corresponding to the paging message, the time-frequency resource information of the SS block, or the preset bandwidth information.

2) the terminal determining that the type of the paging time unit corresponding to the terminal

is the first type of the paging time unit and the second type of the paging time unit based on at least one of the time-frequency resource information corresponding to the paging message, the time-frequency resource information of the SS block, or the preset bandwidth information.

[00133] For example, in a case where the time-frequency resource corresponding to the paging message and the nominal resource of the SS block are the frequency division multiplexed, the terminal determines bandwidth information corresponding to the paging message and the SS block based on the time-frequency resource information corresponding to the paging message and the time-frequency resource information of the SS block; the terminal compares the bandwidth information corresponding to the paging message and the SS block with preset bandwidth information; if the bandwidth information corresponding to the paging message and the SS block is greater than the preset bandwidth information, it is determined that the type of the paging time unit corresponding to the terminal is the second type of the paging time unit; and if the bandwidth information corresponding to the paging message and the SS block is less than or equal to the preset bandwidth information, it is determined that the type of the paging time unit corresponding to the terminal is the first type of the paging time unit and the second type of the paging time unit.

[00134] In another example, in a case where the time-frequency resource corresponding to the paging message includes the time-frequency resource of the nominal resource (the SS block is not transmitted on this nominal resource), the terminal compares the bandwidth information corresponding to the paging message with the preset bandwidth information; if the bandwidth information corresponding to the paging message is greater than the preset bandwidth information, it is determined that the type of the paging time unit corresponding to the terminal is the second type of the paging time unit; and if the bandwidth information corresponding to the paging message is less than or equal to the preset bandwidth information, it is determined that the type of the paging time unit corresponding to the terminal is the first type of the paging time unit and the second type of the paging time unit.

[00135] In another example, in a case where the time-frequency resource corresponding to the paging message and the nominal resource (the SS block may be or may be not transmitted on this nominal resource) are time division multiplexed, the terminal

compares the bandwidth information corresponding to the paging message with the preset bandwidth information; if the bandwidth information corresponding to the paging message is greater than the preset bandwidth information, it is determined that the type of the paging time unit corresponding to the terminal is the second type of the paging time unit; and if the bandwidth information corresponding to the paging message is less than or equal to the preset bandwidth information, it is determined that the type of the paging time unit corresponding to the terminal is the first type of the paging time unit and the second type of the paging time unit.

[00136] In the above solutions, the preset bandwidth information is minimum bandwidth information of the terminal, or the preset bandwidth information is bandwidth information corresponding to the terminal.

[00137] Herein, different terminals in the system respectively correspond to respective bandwidth capabilities (i.e., the bandwidth information). Among all the bandwidth information, there is minimum bandwidth information. That is, the bandwidth information of all the terminals in the system is greater than or equal to the minimum bandwidth information. For example, a terminal 1 corresponds to a bandwidth 1, a terminal 2 corresponds to a bandwidth 2, and a terminal 3 corresponds to a bandwidth 3. The bandwidth 1, the bandwidth 2 and the bandwidth 3 are different bandwidths, and all the three bandwidths are greater than or equal to the minimum bandwidth. It can be seen that the minimum bandwidth information of the terminals refers to the minimum bandwidth information corresponding to the system. In an application, the bandwidth information of each terminal can be obtained on the network side.

[00138] In a second manner, the terminal obtains paging indication information from the paging configuration information; and the terminal determines the type of the paging time unit corresponding to the terminal based on the paging indication information.

[00139] For the second manner, determining the type of the paging time unit corresponding to the terminal includes:

1) the terminal determining that the type of the paging time unit corresponding to the terminal is the first type of the paging time unit or the second type of the paging time unit according to the paging indication information.

2) the terminal determining that the type of the paging time unit corresponding to the terminal is the first type of the paging time unit and the second type of the paging time unit according to the paging indication information.

[00140] In the above solutions, the terminal can directly determine the type of the paging time unit based on the indication from the network side.

[00141] In an embodiment, the paging indication information includes the type of the paging time unit corresponding to the terminal.

[00142] In another embodiment, the paging indication information includes the type of the paging time unit that is needed to be excluded by the terminal.

[00143] In an example where the paging time unit is the PO, the paging indication information is configured to indicate that the terminal corresponds to the second type of PO, or the paging indication information is configured to indicate that the terminal needs to exclude the first type of PO. Regardless of the specific indication method, the terminal can determine the type of the paging time unit corresponding to the terminal by the paging indication information, that is, the terminal corresponds to the second type of PO.

[00144] In another example where the paging time unit is the PO, the paging indication information is configured to indicate that the terminal corresponds to the first type of PO and the second type of PO, or the paging indication information is configured to indicate that the terminal does not need to exclude any type of PO. Regardless of the specific indication method, the terminal can determine the type of the paging time unit corresponding to the terminal by the paging indication information, that is, the terminal corresponds to the first type of PO and the second type of PO.

[00145] In step 803, the terminal determines a set of paging time units based on the type of the paging time unit.

[00146] In the embodiment of the present disclosure, the first type of paging time unit corresponds to a first type of time-frequency resource, and the second type of paging time unit corresponds to a second type of time-frequency resource.

[00147] In the above solutions, the first type of time-frequency resource and the second type of time-frequency resource have the following relationship:

1) a size of the time-frequency resource corresponding to the first type of time-frequency

resource is different from a size of a time-frequency resource corresponding to the second type of time-frequency resource.

2) a multiplexing manner for the first type of time-frequency resource and the time-frequency resource of the SS block is different from a multiplexing manner for the second type of time-frequency resource and the time-frequency resource of the SS block.

3) the size of the time-frequency resource corresponding to the first type of time-frequency resource is different from the size of the time-frequency resource corresponding to the second type of time-frequency resource, and the multiplexing manner for the first type of time-frequency resource and the time-frequency resource of the SS block is different from the multiplexing manner for the second type of time-frequency resource and the time-frequency resource of the SS block,

[00148] Further, the first type of the paging time unit being corresponding to the first type of time-frequency resource includes that:

[00149] on symbols of a nominal resource for SS block transmission, the time-frequency resource corresponding to the first type of paging time unit and the nominal resource are frequency divided.

[00150] The second type of paging time unit being corresponding to the second type of time-frequency resource includes that:

[00151] on symbols of a nominal resource which is not for SS block transmission, the time-frequency resource corresponding to the second type of paging time unit includes the time-frequency resource of the nominal resource.

[00152] The second type of paging time unit being corresponding to the second type of time-frequency resource includes that:

[00153] the time-frequency resource corresponding to the second type of paging time unit and the nominal resource are time divided.

[00154] In the above solution, the paging time unit includes the PO, or a part of time units in the PO.

[00155] It can be seen that, when the first type of paging time unit and the nominal resource of the SS block are frequency division multiplexed, the preset bandwidth information may be exceeded (such as the minimum bandwidth information of the terminal,

which may result in that the UE cannot receive the paging). As such, the first type of paging time unit must be excluded. That is, the terminal only needs to use the set of second type of paging time units as candidate paging time units. Herein, the terminal determines a location of a paging time unit corresponding to itself among the candidate paging time units, and receives the paging message at this location of the paging time unit.

[00156] Of course, if the preset bandwidth information is not exceeded (such as the minimum bandwidth information of the terminal, which may result in that the UE cannot receive the paging), the set of the first type of paging time units and the set of the second type of paging time units can be used as the candidate paging time units. Herein, the terminal determines the location of the paging time unit corresponding to itself among the candidate paging time units, and receives the paging message at this location of the paging time unit.

[00157] In step 804, the terminal receives a paging message on at least one paging time in the set of paging time units; wherein the paging time unit include at least one of a first type of a paging time unit and a second type of a paging time unit.

[00158] In a specific application, after determining the set of paging time units, the terminal determines the location of the paging time unit (such as the PO) at which it receives the paging message according to its UE_ID, and receives the paging message at the determined location of the paging time.

[00159] FIG. 9 is a first schematic structural composition diagram of a device for determining paging time in an embodiment of the present disclosure. As shown in FIG. 9, the device for determining the paging time includes:

[00160] a first receiving unit 901, configured to receive paging configuration information;

[00161] a first determining unit 902, configured to determine a type of a paging time unit corresponding to the terminal based on the paging configuration information;

[00162] a second determining unit 903, configured to determine a set of paging time units based on the type of the paging time unit; and

[00163] a second receiving unit 904, configured to receive a paging message on at least one paging time in the set of paging time units,

[00164] where the paging time unit includes at least one of a first type of a paging time

unit and a second type of a paging time unit.

[00165] In an embodiment, the first determining unit 902 is configured to obtain time-frequency resource information corresponding to the paging message from the paging configuration information; and determine the type of the paging time unit corresponding to the terminal based on at least one of the time-frequency resource information corresponding to the paging message, time-frequency resource information of an SS block, or preset bandwidth information.

[00166] In an embodiment, the first determining unit 902 is configured to obtain paging indication information from the paging configuration information; and determine the type of the paging time unit corresponding to the terminal based on the paging indication information.

[00167] In an embodiment, the first determining unit 902 is configured to determine, based on at least one of the time-frequency resource information corresponding to the paging message, the time-frequency resource information of the SS block, or the preset bandwidth information, that the type of the paging time unit corresponding to the terminal is the first type of the paging time unit or the second type of the paging time unit; or determine, based on at least one of the time-frequency resource information corresponding to the paging message, the time-frequency resource information of the SS block, or the preset bandwidth information, that the type of the paging time unit corresponding to the terminal is the first type of the paging time unit and the second type of the paging time unit.

[00168] In an embodiment, the preset bandwidth information is minimum bandwidth information of the terminal; or the preset bandwidth information is bandwidth information corresponding to the terminal.

[00169] In an embodiment, the first determining unit 902 is configured to determine, based on the paging indication information, that the type of the paging time unit corresponding to the terminal is the first type of the paging time unit or the second type of the paging time unit; or determine, based on the paging indication information, that the type of the paging time unit corresponding to the terminal is the first type of the paging time unit and the second type of the paging time unit.

[00170] In an embodiment, the first type of the paging time unit corresponds to a first

type of time-frequency resource, and the second type of the paging time unit corresponds to a second type of time-frequency resource.

[00171] In an embodiment, a size of a time-frequency resource corresponding to the first type of time-frequency resource is different from a size of a time-frequency resource corresponding to the second type of time-frequency resource;

[00172] and/or,

[00173] a multiplexing manner for the first type of time-frequency resource and a time-frequency resource of the SS block is different from a multiplexing manner for the second type of time-frequency resource and the time-frequency resource of the SS block.

[00174] In an embodiment, the first type of the paging time unit being corresponding to the first type of time-frequency resource includes:

[00175] on symbols of a nominal resource for SS block transmission, the time-frequency resource corresponding to the first type of the paging time unit and the nominal resource are frequency divided.

[00176] In an embodiment, the second type of the paging time unit being corresponding to the second type of time-frequency resource includes:

[00177] on symbols of a nominal resource which is not for SS block transmission, the time-frequency resource corresponding to the second type of the paging time unit includes the time-frequency resource of the nominal resource.

[00178] In an embodiment, the second type of the paging time unit being corresponding to the second type of time-frequency resource includes that:

[00179] the time-frequency resource corresponding to the second type of the paging time unit and the nominal resource are time divided.

[00180] In an embodiment, the paging time unit includes the PO or a part of time units in the PO.

[00181] Those skilled in the art should understand that the functions implemented by the respective units in the device for determining the paging time shown in FIG. 9 can be understood by referring to the related description of the foregoing method for determining the paging time. The functions of the respective units in the device for determining the paging time shown in FIG. 9 may be implemented by a program running on a processor, or may be

implemented by a specific logic circuit.

[00182] FIG. 10 is a second schematic flowchart diagram of a method for determining a paging time in an embodiment of the present disclosure. As shown in FIG. 10, the method for determining the paging time includes the following steps.

[00183] In step 1001, a network transmits paging configuration information, the paging configuration information being configured for determining a type of a paging time unit corresponding to a terminal.

[00184] In an embodiment, the paging configuration information includes time-frequency resource information corresponding to the paging message.

[00185] In this way, the terminal can obtain the time-frequency resource information corresponding to the paging message from the paging configuration information; and determines the type of the paging time unit corresponding to the terminal based on at least one of the time-frequency resource information corresponding to the paging message, time-frequency resource information of an SS block, or preset bandwidth information.

[00186] In another embodiment, the paging configuration information includes paging indication information.

[00187] In this way, the terminal may obtain the paging indication information from the paging configuration information; and determines the type of the paging time unit corresponding to the terminal according to the paging indication information.

[00188] In the above solutions, the first type of the paging time unit corresponds to a first type of time-frequency resource, and the second type of the paging time unit corresponds to a second type of time-frequency resource.

[00189] Further, a size of the time-frequency resource corresponding to the first type of time-frequency resource is different from the size of the time-frequency resource corresponding to the second type of time-frequency resource; and/or, a multiplexing manner for the first type of time-frequency resource and a time-frequency resource of the SS block is different from a multiplexing manner for the second type of time-frequency resource and the time-frequency resource of the SS block.

[00190] In the above solutions, the first type of the paging time unit being corresponding to the first type of time-frequency resource includes that:

[00191] on symbols of a nominal resource for SS block transmission, the time-frequency resource corresponding to the first type of the paging time unit and the nominal resource are frequency divided.

[00192] In the above solutions, the second type of the paging time unit being corresponding to the second type of time-frequency resource includes that:

[00193] on symbols of a nominal resource which is not for SS block transmission, the time-frequency resource corresponding to the second type of the paging time unit includes the time-frequency resource of the nominal resource.

[00194] In the above solutions, the second type of the paging time unit being corresponding to the second type of time-frequency resource type includes that:

[00195] the time-frequency resource corresponding to the second type of the paging time unit and the nominal resource are time divided.

[00196] In the above solutions, the paging time unit includes the PO or a part of time units in the PO.

[00197] In step 1002, the network transmits a paging message on at least one paging time unit in a set of paging time units corresponding to the paging configuration information, where the paging time unit includes at least one of a first type of a paging time unit and a second type of a paging time unit.

[00198] Those skilled in the art should understand that the paging configuration information on the network side corresponds to the paging configuration information on the terminal side.

[00199] FIG. 11 is a second schematic structural composition diagram of a device for determining paging time in an embodiment of the present disclosure. As shown in FIG. 11, the device includes:

[00200] a first transmitting unit 1101, configured to transmit paging configuration information, the paging configuration information being configured to determine a type of a paging time unit corresponding to a terminal; and

[00201] a second transmitting unit 1102, configured to transmit a paging message on at least one paging time unit in a set of paging time units corresponding to the paging configuration information;

[00202] where the paging time unit includes at least one of a first type of a paging time unit and a second type of a paging time unit.

[00203] In an embodiment, the paging configuration information includes time-frequency resource information corresponding to the paging message.

[00204] In an embodiment, the paging configuration information includes paging indication information.

[00205] In an embodiment, the first type of the paging time unit corresponds to a first type of time-frequency resource, and the second type of the paging time unit corresponds to a second type of time-frequency resource.

[00206] In an embodiment, a size of a time-frequency resource corresponding to the first type of time-frequency resource is different from a size of a time-frequency resource corresponding to a second type of time-frequency resource;

[00207] and/or,

[00208] a multiplexing manner for the first type of time-frequency resource and a time-frequency resource of the SS block is different from a multiplexing manner for the second type of time-frequency resource and the time-frequency resource of the SS block.

[00209] In an embodiment, the first type of the paging time unit being corresponding to the first type of time-frequency resource includes that:

[00210] on symbols of a nominal resource for SS block transmission, the time-frequency resource corresponding to the first type of the paging time unit and the nominal resource are frequency divided.

[00211] In an embodiment, the second type of the paging time unit being corresponding to the second type of time-frequency resource includes that:

[00212] on symbols of a nominal resource which is not for SS block transmission, the time-frequency resource corresponding to the second type of the paging time unit includes the time-frequency resource of the nominal resource.

[00213] In an embodiment, the second type of the paging time unit being corresponding to the second type of time-frequency resource includes that:

[00214] the time-frequency resource corresponding to the second type of the paging time unit and the nominal resource are time divided.

[00215] In an embodiment, the paging time unit includes PO or a part of time units in the PO.

[00216] When the foregoing device for determining the paging time in the embodiment of the present disclosure is implemented in a form of a software functional module and sold or used as an independent product, it may also be stored in a computer-readable storage medium. Based on such an understanding, the technical solution of the embodiment of the present disclosure essentially or a part thereof that contributes to the existing technology may be embodied in a form of a software product. The computer software product is stored in a storage medium and includes pieces of instructions for causing a computer device (which may be a personal computer, a server, a network device, or the like) to perform all or part of the methods described in the embodiments of the present disclosure. The foregoing storage medium includes various media that can store program codes, such as a USB disk, a mobile hard disk, a Read Only Memory (ROM), a magnetic disk, or an optical disk. In this way, the embodiments of the present disclosure are not limited to any specific combination of hardware and software.

[00217] Accordingly, an embodiment of the present disclosure further provides a computer storage medium in which computer-executable instructions are stored. When the computer-executable instructions are executed by a processor, the method for determining the paging time according to the embodiments of the present disclosure is implemented.

[00218] FIG. 12 is a schematic structural composition diagram of a terminal in an embodiment of the present disclosure. As shown in FIG. 12, a terminal 120 can include one or more (only one is shown in the figure) processors 1202 (the processors 1202 may include, but is not limited to, a processing device such as a Micro Controller Unit (MCU) or a Field Programmable Gate Array (FPGA)), a memory 1204 for storing data, and a transmission device 1206 for communication functions. A person of ordinary skill in the art can understand that the structure shown in FIG. 12 is only for illustration, and does not limit the structure of the electronic device. For example, the terminal 120 may further include more or fewer components than those shown in FIG. 12, or have a different configuration from that shown in FIG.12.

[00219] The memory 1204 may be configured to store software programs and modules

of application software, such as program instructions/modules corresponding to the method for determining the paging time in the embodiments of the present disclosure. The processor 1202 executes the software programs and modules stored in the memory 1204, thereby performing various functional applications and data processing, that is, implementing the method described above. The memory 1204 may include a high-speed random access memory, and may further include a non-volatile memory, such as one or more magnetic storage devices, a flash memory, or other non-volatile solid-state memories. In some examples, the memory 1204 may further include memories which is set remotely with respect to the processor 1202, and these remote memories may be connected to the terminal 120 through a network. Examples of the above network include, but are not limited to, an Internet, a corporate intranet, a local area network, a mobile communication network, and a combination thereof.

[00220] The transmission device 1206 is configured to receive or transmit data via the network. The specific examples of the above network may include a wireless network provided by a communication provider of the terminal 120. In one example, the transmission device 1206 includes a Network Interface Controller (NIC), which can be connected to other network devices through a base station so as to perform communication with the Internet. In one example, the transmission device 1206 may be a Radio Frequency (RF) module, which is configured to communicate with the Internet in a wireless manner.

[00221] The technical solutions described in the embodiments of the present disclosure can be arbitrarily combined if they do not conflict.

[00222] In the embodiments provided in the present disclosure, it should be understood that the method and smart device disclosed may be implemented in other ways. The embodiments of the device described above are merely illustrative. For example, the division of the units is only a logical function division. In practice, there may be other manners of division. For example, multiple units or components may be combined or integrated into another system, or some features may be ignored or not performed. In addition, coupling, direct coupling or communication connection among the illustrated or discussed components may be indirect coupling or communication connection through some interfaces, devices or units, or may be in electrical, mechanical or other forms.

[00223] The units described as separated parts above may or may not be physically separated, and the parts shown as units may or may not be physical units, that is, they may be located in one place, or may be distributed over multiple network units. Some or all of the units may be selected according to actual requirements to achieve the objectives of the solutions in the embodiments.

[00224] In addition, the respective functional units in each of the embodiments of the present disclosure may be integrated into a second processing unit, or each of the units may be separately used as one unit, or two or more units may be integrated into one unit. The above integrated units may be implemented in the form of hardware, or may be implemented in the form of hardware plus software functional units.

[00225] Those described above are merely specific embodiments of the present disclosure, and the protection scope of the present disclosure is not limited thereto. Any person skilled in the art can easily think of changes or substitutions within the technical scope disclosed in the present disclosure, and all the changes or substitutions should be within the protection scope of the present disclosure.

WHAT IS CLAIMED IS:

1. A method for determining paging time, comprising:
receiving, by a terminal, paging configuration information;
determining, by the terminal, a type of a paging time unit corresponding to the terminal based on the paging configuration information;
determining, by the terminal, a set of paging time units based on the type of the paging time unit; and
receiving, by the terminal, a paging message on at least one paging time in the set of paging time units,
wherein, the paging time unit comprises at least one of a first type of a paging time unit or a second type of a paging time unit.
2. The method of claim 1, wherein the determining, by the terminal, the type of the paging time unit corresponding to the terminal based on the paging configuration information comprises:
obtaining, by the terminal, time-frequency resource information corresponding to the paging message from the paging configuration information; and
determining, by the terminal, the type of the paging time unit corresponding to the terminal based on at least one of: the time-frequency resource information corresponding to the paging message, time-frequency resource information of a Synchronization Signal (SS) block, or preset bandwidth information.
3. The method of claim 1, wherein the determining, by the terminal, the type of the paging time unit corresponding to the terminal based on the paging configuration information comprises:
obtaining, by the terminal, paging indication information from the paging configuration information; and
determining, by the terminal, the type of the paging time unit corresponding to the terminal based on the paging indication information.
4. The method of claim 2, wherein the determining, by the terminal, the type of the paging time unit corresponding to the terminal based on at least one of the time-frequency resource information corresponding to the paging message, the time-frequency resource

information of the SS block, or the preset bandwidth information comprises:

determining, by the terminal based on at least one of the time-frequency resource information corresponding to the paging message, the time-frequency resource information of the SS block, or the preset bandwidth information, that the type of the paging time unit corresponding to the terminal is the first type of the paging time unit or the second type of the paging time unit;

or,

determining, by the terminal based on at least one of the time-frequency resource information corresponding to the paging message, the time-frequency resource information of the SS block, or the preset bandwidth information, that the type of the paging time unit corresponding to the terminal is the first type of the paging time unit and the second type of the paging time unit.

5. The method of claim 4, wherein the preset bandwidth information is minimum bandwidth information of the terminal, or the preset bandwidth information is bandwidth information corresponding to the terminal.

6. The method of claim 3, wherein the determining, by the terminal, the type of the paging time units corresponding to the terminal based on the paging indication information comprises:

determining, by the terminal based on the paging indication information, that the type of the paging time unit corresponding to the terminal is the first type of the paging time unit or the second type of the paging time unit; or

determining, by the terminal based on the paging indication information, that the type of the paging time unit corresponding to the terminal is the first type of the paging time unit and the second type of the paging time unit.

7. The method of claim 1, wherein the first type of the paging time unit corresponds to a first type of time-frequency resource, and the second type of the paging time unit corresponds to a second type of time-frequency resource.

8. The method of claim 7, wherein a size of a time-frequency resource corresponding to the first type of time-frequency resource is different from a size of a time-frequency resource corresponding to the second type of time-frequency resource;

and/or,

a multiplexing manner for the first type of time-frequency resource and a time-frequency resource of an SS block is different from a multiplexing manner for the second type of time-frequency resource and the time-frequency resource of the SS block.

9. The method of claim 7 or 8, wherein the first type of the paging time unit corresponds to the first type of time-frequency resource where on symbols of a nominal resource for SS block transmission, the time-frequency resource corresponding to the first type of the paging time unit and the nominal resource are frequency divided.

10. The method of claim 7 or 8, wherein the second type of the paging time unit corresponds to the second type of time-frequency resource where on symbols of a nominal resource which is not for SS block transmission, the time-frequency resource corresponding to the second type of the paging time unit comprises the time-frequency resource of the nominal resource.

11. The method of claim 7 or 8, wherein the second type of the paging time unit corresponds to the second type of time-frequency resource where the time-frequency resource corresponding to the second type of the paging time unit and the nominal resource are time divided.

12. The method of any one of claims 1 to 11, wherein the paging time unit comprises a paging occasion (PO) or a part of time units in the PO.

13. A method for determining paging time, comprising:

transmitting, by a network, paging configuration information, the paging configuration information being configured for determining a type of a paging time unit corresponding to a terminal; and

transmitting, by the network, a paging message on at least one paging time unit in a set of paging time units corresponding to the paging configuration information,

wherein, the paging time unit comprises at least one of a first type of a paging time unit or a second type of a paging time unit.

14. The method of claim 13, wherein the paging configuration information comprises time-frequency resource information corresponding to the paging message.

15. The method of claim 13, wherein the paging configuration information comprises

paging indication information.

16. The method of claim 13, wherein the first type of the paging time unit corresponds to a first type of time-frequency resource, and the second type of the paging time unit is corresponding to a second type of time-frequency resource.

17. The method of claim 16, wherein a size of a time-frequency resource corresponding to the first type of time-frequency resource is different from the size of a time-frequency resource corresponding to the second type of time-frequency resource;

and/or,

a multiplexing manner for the first type of time-frequency resource and a time-frequency resource of an SS block is different from a multiplexing manner for the second type of time-frequency resource and the time-frequency resource of the SS block.

18. The method of claim 16 or 17, wherein the first type of the paging time unit corresponds to the first type of time-frequency resource type where on symbols of a nominal resource for SS block transmission, the time-frequency resource corresponding to the first type of the paging time unit and the nominal resource are frequency divided.

19. The method of claim 16 or 17, wherein the second type of the paging time unit corresponds to the second type of time-frequency resource where on symbols of a nominal resource which is not for SS block transmission, the time-frequency resource corresponding to the second type of the paging time unit comprises the time-frequency resource of the nominal resource.

20. The method of claim 16 or 17, wherein the second type of the paging time unit corresponds to the second type of time-frequency resource where the time-frequency resource corresponding to the second type of the paging time unit and the nominal resource are time divided.

21. The method of any one of claims 13 to 20, wherein the paging time unit comprises a PO or a part of time units in the PO.

22. A device for determining paging time, comprising:

a first receiving unit, configured to receive paging configuration information;

a first determining unit, configured to determine a type of a paging time unit corresponding to the terminal based on the paging configuration information;

a second determining unit, configured to determine a set of paging time units based on the type of the paging time unit; and

a second receiving unit, configured to receive a paging message on at least one paging time in the set of paging time units,

wherein, the paging time unit comprises at least one of a first type of a paging time unit and a second type of a paging time unit.

23. The device of claim 22, wherein the first determining unit is configured to obtain time-frequency resource information corresponding to the paging message from the paging configuration information; and determine the type of the paging time unit corresponding to the terminal based on at least one of: the time-frequency resource information corresponding to the paging message, time-frequency resource information of an SS block, or preset bandwidth information.

24. The device of claim 22, wherein the first determining unit is configured to obtain paging indication information from the paging configuration information; and determine the type of the paging time unit corresponding to the terminal based on the paging indication information.

25. The device of claim 23, wherein the first determining unit is configured to determine, based on at least one of the time-frequency resource information corresponding to the paging message, the time-frequency resource information of the SS block, or the preset bandwidth information, that the type of the paging time unit corresponding to the terminal is the first type of the paging time unit or the second type of the paging time unit; or determine, based on at least one of the time-frequency resource information corresponding to the paging message, the time-frequency resource information of the SS block, or the preset bandwidth information, that the type of the paging time unit corresponding to the terminal is the first type of the paging time unit and the second type of the paging time unit.

26. The device of claim 25, wherein the preset bandwidth information is minimum bandwidth information of the terminal, or the preset bandwidth information is bandwidth information corresponding to the terminal.

27. The device of claim 24, wherein the first determining unit is configured to determine, based on the paging indication information, that the type of the paging time unit

corresponding to the terminal is the first type of the paging time unit or the second type of the paging time unit; or determine, based on the paging indication information, that the type of the paging time unit corresponding to the terminal is the first type of the paging time unit and the second type of the paging time unit.

28. The device of claim 22, wherein the first type of the paging time unit corresponds to a first type of time-frequency resource, and the second type of the paging time unit corresponds to a second type of time-frequency resource.

29. The device of claim 28, wherein a size of a time-frequency resource corresponding to the first type of time-frequency resource is different from a size of a time-frequency resource corresponding to the second type of time-frequency resource;

and/or,

a multiplexing manner for the first type of time-frequency resource and a time-frequency resource of an SS block is different from a multiplexing manner for the second type of time-frequency resource and the time-frequency resource of the SS block.

30. The device of claim 28 or 29, wherein the first type of paging time unit corresponds to the first type of time-frequency resource where on symbols of a nominal resource for SS block transmission, the time-frequency resource corresponding to the first type of the paging time unit and the nominal resource are frequency divided.

31. The device of claim 28 or 29, wherein, the second type of the paging time unit corresponds to the second type of time-frequency resource where on symbols of a nominal resource which is not for SS block transmission, the time-frequency resource corresponding to the second type of the paging time unit comprises the time-frequency resource of the nominal resource.

32. The device of claim 28 or 29, wherein the second type of the paging time unit corresponds to the second type of time-frequency resource where the time-frequency resource corresponding to the second type of the paging time unit and the nominal resource are time divided.

33. The device of any one of claims 22 to 32, wherein the paging time unit comprises a PO or a part of time units in the PO.

34. A device for determining paging time, comprising:

a first transmitting unit, configured to transmit paging configuration information, the paging configuration information being configured for determining a type of a paging time unit corresponding to a terminal; and

a second transmitting unit, configured to transmit a paging message on at least one paging time unit in a set of paging time units corresponding to the paging configuration information,

wherein, the paging time unit comprises at least one of a first type of a paging time unit and a second type of a paging time unit.

35. The device of claim 34, wherein the paging configuration information comprises time-frequency resource information corresponding to the paging message.

36. The device of claim 34, wherein the paging configuration information comprises paging indication information.

37. The device of claim 34, wherein the first type of the paging time unit corresponds to a first type of time-frequency resource, and the second type of the paging time unit corresponds to a second type of time-frequency resource.

38. The device of claim 37, wherein a size of a time-frequency resource corresponding to the first type of time-frequency resource is different from a size of a time-frequency resource corresponding to the second type of time-frequency resource;

and/or,

a multiplexing manner for the first type of time-frequency resource and a time-frequency resource of an SS block is different from a multiplexing manner for the second type of time-frequency resource and the time-frequency resource of the SS block.

39. The device of claim 37 or 38, wherein the first type of the paging time unit corresponds to the first type of time-frequency resource where on symbols of a nominal resource for SS block transmission, the time-frequency resource corresponding to the first type of the paging time unit and the nominal resource are frequency divided.

40. The device of claim 37 or 38, wherein the second type of the paging time unit corresponds to the second type of time-frequency resource where on symbols of a nominal resource which is not for SS block transmission, the time-frequency resource corresponding to the second type of the paging time unit comprises the time-frequency resource of the

nominal resource.

41. The device of claim 37 or 38, wherein the second type of paging time unit corresponds to the second type of time-frequency resource where the time-frequency resource corresponding to the second type of the paging time unit and the nominal resource are time divided.

42. The device of any one of claims 34 to 41, wherein the paging time unit comprises a PO or a part of time units in the PO.

43. A computer storage medium having stored thereon computer-executable instructions which, when executed by a processor, implement steps of the method of any one of claims 1-12, or steps of the method of any one of claims 13-21.