3. The device of claim 2, wherein an extended part of the open is extended toward the bottom of the plate.

4. The device of claim 3, wherein the center part of the brush lies on the extended part of the open of the plate, and the center part of the brush is staggered with the side parts of the brush.

5. The device of claim 4, wherein parts of the lower edge of the brush are in contact with the first set of rollers.

6. The device of claim 1 further comprising a pair of blocking plates detachably mounted to the pair of side walls of the body and arranged adjacent to the fourth and fifth sets of rollers, the space between the pair of blocking plates exposes the fourth and fifth sets of rollers.

7. The device of claim 6, wherein each of the pair of blocking plates comprises a first portion and a second portion extended from the center of the edge of the first portion, the first portion has a semicircular shape.

8. The device of claim 7, wherein one of the pair of blocking plates further comprises a first sensor.

9. The device of claim 1, wherein the receiving plate of the body comprises a second sensor configured to detect whether any cards are accommodated on the receiving plate.

10. The device of claim 1, wherein one of the pair of side walls of the body comprises a third sensor configured to count the number of cards transmitted by the second roller assembly.

~~11. A card input device of a shuffling machine, the device comprising:~~

~~a body comprising:~~

~~a pair of side walls; and~~

~~a receiving plate detachably mounted between the pair of side walls,~~

~~a first roller assembly rotatably mounted between the pair of side walls of the body, the first roller assembly comprising at least:~~

~~a first set of rollers exposed by a hole formed in the receiving plate of the body, and~~

~~a filtering mechanism detachably mounted between the pair of side walls of the body and arranged over the first set of rollers.~~

11. A card input device of a shuffling machine, the device comprising:

a pair of side walls;

a receiving plate detachably mounted between the pair of side walls;

a first set of rollers rotatably mounted between the pair of side walls and exposed by a hole formed in the receiving plate; and

a filtering mechanism detachably mounted between the pair of side walls and arranged over the first set of rollers.

~~12. The device of claim 11, wherein the first roller assembly further comprises a second set of rollers and a third set of rollers arranged over the second set of rollers, the second and third sets of rollers are arranged opposite to the first set of rollers with respect to the filtering mechanism.~~

~~13.~~12. The device of claim ~~12~~11 further comprising a second roller assembly rotatably mounted between the pair of side walls of the body and arranged adjacent to the first roller assembly, the second roller assembly comprising at least a fourth and a fifth sets of rollers.

~~14.~~13. The device of claim 11, wherein the filtering mechanism comprises:

a plate comprising an open formed in the plate;

a connecting mechanism arranged on the back side of the plate close to the upper edge of the open; and

a brush detachably mounted to the plate through the connecting mechanism and extended towards the front side of the plate through the open.

~~15. The device of claim 14, wherein an extended part of the open is extended toward the bottom of the plate.~~

~~16. The device of claim 15, wherein the center part of the brush lies on the extended part of the open of the plate, the center part of the brush is staggered with the side parts of the brush, and parts of the lower edge of the brush are in contact with the first set of rollers.~~

~~17.~~14. The device of claim 11 further comprising a pair of blocking plates detachably mounted to the pair of side walls of the body and arranged adjacent to the fourth and fifth sets of rollers, the space between the pair of blocking plates exposes the fourth and fifth sets of rollers.

~~18. A card input device of a shuffling machine, the device comprising:~~

~~a pair of side walls;~~

~~a receiving plate detachably mounted between the pair of side walls;~~

~~a first set of rollers rotatably mounted between the pair of side walls and exposed by a hole formed in the receiving plate; and~~

~~a filtering mechanism detachably mounted between the pair of side walls and arranged over the first set of rollers.~~

~~19.~~15. The device of claim ~~18~~11 further comprising a second set of rollers and a third set of rollers arranged over the second set of rollers, the second and third sets of rollers are arranged opposite to the first set of rollers with respect to the filtering mechanism.

~~20.~~16. The device of claim ~~18~~11, wherein the filtering mechanism comprises:

a plate comprising an open formed in the plate; and

a brush detachably mounted to the back side of the plate close to the upper edge of the open,

wherein the brush is extended towards the front side of the plate through the open.

~~21.~~17. The device of claim ~~20~~16, wherein an extended part of the open is extended toward the bottom of the plate.

~~22.~~18. The device of claim ~~21~~17, wherein the center part of the brush lies on the extended part of the open of the plate, the center part of the brush is staggered with the side parts of the brush.

~~23.~~19. The device of claim ~~22~~18, wherein parts of the lower edge of the brush are in contact with the first set of rollers.