[Document Name] Claims

[Claim 1]

A fishing spinning reel ~~for fishing,~~ comprising:

a rotor ~~that~~ configured to rotate~~s~~ ~~in response to the~~by rotation operation of a handle rotatably supported ~~on~~ by a reel main body;

a spool ~~that~~ configured to move~~s~~ back and forth ~~in response to~~by the rotation operation of the handle; and

a fishing line guide ~~that is provided~~disposed on one of arm levers pivotably supported ~~on~~ by a pair of arms provided on the rotor ~~and~~ to guide~~s~~ ~~the~~ a fishing line to the spool~~; ~~, ~~wherein~~

wherein the fishing line guide includes:

a line roller ~~that~~ configured to guide~~s~~ ~~to the spool~~ the fishing line picked up by a bail ~~mounted on~~attached to the pair of arms to the spool~~, ~~; and

a line slider ~~that~~ configured to guide~~s~~ the fishing line from the bail to the line roller;

wherein the line slider includes:

~~a mounting portion on which~~an attachment part that the bail is integrally ~~connected~~ joined to or formed with;

a first depression configured to accommodate at least a part of a head of a screw member when the screw member is attached, wherein the screw member is inserted from a bail side and the screw member is configured to fasten the line slider to one of the arm levers;

a second depression configured to accommodate an end of the line roller and covering to cover an outer periphery of the end with a minute gap provided; and

~~and~~ a wall ~~portion that~~ configured to separate~~s~~ ~~a~~ the first ~~recess~~depression from the second depression, ~~which mounts a screw member for attaching the arm lever and houses at least a part of a head portion of the screw member, from a second recess which houses an end side of the line roller and covers the outer circumference of its edge with a tiny gap; and~~

wherein the wall ~~portion~~ and the line slider are formed of a single member; and

wherein the first depression and the second depression are formed to communicate with each other by a circular opening in the wall, wherein the circular opening is provided with a recess.

~~[Claim 2]~~

~~The spinning reel for fishing of claim 1, wherein the first recess communicates with the second recess.~~

[Claim ~~3~~2]

The fishing spinning reel ~~for fishing of~~according to claim 1~~ or 2~~, wherein the ~~mounting portion~~attachment part is formed into a hollow structure, ~~and~~ the first ~~recess~~ depression and the attachment part having a hollow ~~mounting portion~~structure are separated by a ~~plate portion~~plate-shaped part, ~~on which~~and the wall ~~portion~~ is ~~integrally formed~~integrated with the plate-shaped part.

[Claim ~~4~~3]

The fishing spinning reel ~~for fishing of~~according to claim 1~~ or 2~~, wherein the ~~mounting portion~~attachment part is formed into a hollow structure and communicates with the first ~~recess~~ depression and the second ~~recess~~depression.