

SPECIFICATION

An improved screw-and-nut unit or screw joint

5 The subject invention relates to screws and screw joints of the kind comprising a screw spindle body formed with at least one non-threaded section extending along the spindle body, and at least one nut member formed with a threaded section which matches the non-threaded section on the screw spindle body. The screw spindle body and the nut member are arranged to move axially relative to one another, during which movements the threaded nut member section travels along the non-threaded section of the screw spindle body. The screw spindle and the nut member may also be turned relative to one another to effect engagement between said nut member section and the threads of the screw spindle body.

Screw spindles and screw joints of this type permit rapid displacement of the screw spindle body and nut member axially relative to one another, thus giving a quick grip and a quick release action, and screw spindles and screw joints of this kind may be used for instance in vices or valves adapted to shut off large flows quickly.

One problem inherent in screw joints of this kind is that removal of the threads on one or several sections of the screw body and the nut member results in a considerable reduction of the strength of the screw joint. The screw spindle threads, being the weakest ones, are those most exposed to stress. Another problem is the difficulty in obtaining, in a reasonable manner, an advantageous distribution of the area of thread engagement over the periphery of the screw spindle body. The most common solution to this latter problem is to divide the threaded portion into two, three or four sections which are distributed symmetrically over the periphery. However, this arrangement adds considerably to the manufacturing costs and in addition weakens the threads further, since each screw thread in each section requires two bevelled entrances. Furthermore, additional portions of the faces of engagement of the threads cannot either be used because of the clearance that is required between the threaded sections of the screw spindle body and the nut member. Such clearance is necessary, as any dirt or dust particles that might enter between the screw spindle body and the nut member could otherwise easily interfere with the operation of the screw or screw joint. An additional disadvantage with the provision of several threaded sections is that it increases the number of angular positions in which the threads are completely out of mesh, and the consequence is a reduction of the circumferential length over which grip is possible.

The purpose of the invention is to eliminate the disadvantages outlined above in screws and screw joints of the kind referred to. The subject invention provides a screw joint possessing considerably enhanced gripping strength compared with prior-art screw joints of this type.

In accordance with the teachings of the invention, this is achieved in that the non-threaded section of the screw spindle body as well as the threaded section on the nut member extend helically along the screw spindle body and the nut member, respectively.

The invention will be described in closer detail in the following with reference to some embodiments thereof illustrated in the accompanying drawings, wherein

Figure 1 is a lateral view of a screw joint in accordance with the invention, showing a first embodiment thereof,

Figure 2 is a lateral view of the screw joint in accordance with a second embodiment, and

Figures 3 and 4 are sectional views of nut members cooperating with the screw joints shown respectively in Fig. 1 and in Fig. 2.

The screw joint of Fig. 1 consists of a screw spindle body 1 and a nut member 2 and they are illustrated in their tightened positions on either side of a work piece 3. In accordance with the invention, the screw spindle body is formed with a threaded portion 4 extending around the screw spindle along the entire length thereof, as well as with a section 5 which is not threaded and which extends helically around the screw spindle body, separating the threads thereon. The section 5 forms a helical spiral the pitch of which along the screw spindle body considerably exceeds the pitch of the individual screw threads 6. For this reason each individual screw thread 6 extends only over a part of the periphery of the screw body 1. In the two embodiments illustrated herein, the threaded portion 4 and the non-threaded section 5 have been given the same width.

The inner face of the nut member 2, most clearly illustrated in Fig. 3, is formed with screw threads 7 and with a non-threaded section 8 matching respectively the threads and the non-threaded section of the screw spindle body 1. Consequently, the nut member 2 may be applied over the tip 9 of the screw spindle, entering either the screw threads 6 or the section 5, and be moved along the screw spindle body 1, sliding in section 5, and the nut may thereafter be turned into engagement with the threads 6 in any chosen thread entrance. When the threads 6 and 7 are not in engagement, the nut member 2 can slide along the screw spindle body while performing a rotating movement, its screw threads 7 positioned in section 5 and the screw spindle threads 6 positioned in nut section 8.

Upon tightening, the shearing stress exerted on the screw threads 6 and 7 will be distributed over the cooperating faces of the two bodies, both along the periphery of the screw spindle body and in the axial direction. A strong bond is obtained in this manner. In a conventional screw joint of the kind that does not have the quick grip and quick release function referred to, the load and shearing stress will be exerted primarily on that screw joint thread with which engagement is first effected. In the screw joint in accordance with the subject invention, on the other hand, the shearing stress will be more evenly distributed in the axial direction, which enhances the general strength of the screw joint.

The screw joint in accordance with the first embodiment illustrated in Figs. 1 and 3 is formed with right-hand screw threads 6 and with a left-hand non-threaded section 5. In this embodiment, rapid displacement in the direction towards the head 10 of the screw spindle body is achieved when the nut member is turned to the left, i.e. counter-clockwise, whereafter tightening and locking is effected by turning the nut member to the right, i.e. clockwise.

The screw threads and the non-threaded section could both be either left-hand or right-hand ones, and this latter embodiment is illustrated in Figs. 2 and 4. The various details of this embodiment have been given the same numeral references as those of the previous embodiments. One advantage of this embodiment over the one shown in Figs. 1 and 2 is that, given otherwise identical conditions, that is the same width of the threaded portion 4 and the same thread pitch, the individual screw thread 6 may extend over more than half a turn around the circumferential length of the screw spindle body 1, whereas in accordance with the embodiment of Figs. 1 and 2, the screw thread extends over a circumferential length that is less than 180°.

In accordance with a further development of the invention, the nut member could consist of two or more interacting nuts. While assuming relative angular end positions, the nuts can be displaced rapidly together along the screw spindle body, their screw threads sliding in the non-threaded section 5. After the nuts have been turned relative to one another to opposite relative angular positions, the screw threads in the nuts will run in continuous engagement in the screw threads 6 of the screw body 1. Together, these screw threads then cover the entire or major portion of the periphery of the screw spindle body, such that at any one time one or several nuts will engage in the screw threads 6 of the screw spindle body.

Another possible further development is to provide one of the two cooperating nuts with a trapezoidal screw thread which is able to

slide only on the section 5. The other nut, formed like those already described herein, will be able to turn relative to the first nut into and out of engagement with the screw threads 6 of the screw spindle body.

The invention is not limited to the embodiments described and referred to in the foregoing but several modifications are possible within the scope of the appended claims. For instance, the screw spindle body 1 and the nut member 2 could serve as the cooperating members of a vice, a lifting jack, sliding valve or the like. Roller bodies could be inserted between the screw and the nut parts to reduce the frictional forces. The screw threads as well as the non-threaded sections could have a pitch that differs from that shown herein and a larger number of entrances could be provided both on the spindle and on the nut member. The threaded portions 4, 7 and the non-threaded sections 5, 8 need not have the same axial width. This might be advantageous as it adds to strength and durability, because the various screw threads on the screw body 1 and on the nut member 2 thus obtain equivalent strength characteristics.

CLAIMS

1. An improved screw-and-nut unit or screw joint, comprising a screw spindle body (1) formed with at least one non-threaded section (5) extending along the spindle body, and at least one nut member (2) formed with a threaded section (7) that matches the non-threaded section (5) on the spindle body (1), said screw spindle body (1) and said nut member (2) arranged to move axially relative to one another, during which movement the threaded section (7) travels along the non-threaded section (5) of the screw spindle body, and to be turned relative to one another to effect engagement between the threaded section (7) of the nut member and the threads (6) of the screw spindle body, characterised in that the non-threaded section (5) of the screw spindle body (1) and the threaded section (7) of the nut member (2) extend helically along the screw spindle body (1) and the nut member (1), respectively.

2. An improved screw-and-nut unit or screw joint as claimed in claim 1, characterised in that the screw threads (6) on said screw spindle body (1) are either left-hand threads or right-hand threads, and in that the non-threaded section (5) extends helically in the opposite direction to said screw threads.

3. An improved screw-and-nut unit or screw joint, as claimed in claim 1, characterised in that the screw threads (6) on said screw spindle body (1) are either left-hand threads or right-hand threads, and in that the non-threaded section (5) extends helically in the same direction as said screw threads.

4. An improved screw-and-nut unit or screw joint, as claimed in any one of the



Upon tightening, the shearing stress exerted on the screw threads 6 and 7 will be distributed over the cooperating faces of the two bodies, both along the periphery of the screw spindle body and in the axial direction. A strong bond is obtained in this manner. In a conventional screw joint of the kind that does not have the quick grip and and quick release function referred to, the load and shearing stress will be exerted primarily on that screw joint thread with which engagement is first effected. In the screw joint in accordance with the subject invention, on the other hand, the shearing stress will be more evenly distributed in the axial direction, which enhances the general strength of the screw joint.

The screw joint in accordance with the first embodiment illustrated in Figs. 1 and 3 is formed with right-hand screw threads 6 and with a left-hand non-threaded section 5. In this embodiment, rapid displacement in the direction towards the head 10 of the screw spindle body is achieved when the nut member is turned to the left, i.e. counter-clockwise, whereafter tightening and locking is effected by turning the nut member to the right, i.e. clockwise.

The screw threads and the non-threaded section could both be either left-hand or right-hand ones, and this latter embodiment is illustrated in Figs. 2 and 4. The various details of this embodiment have been given the same numeral references as those of the previous embodiments. One advantage of this embodiment over the one shown in Figs. 1 and 2 is that, given otherwise identical conditions, that is the same width of the threaded portion 4 and the same thread pitch, the individual screw thread 6 may extend over more than half a turn around the circumferential length of the screw spindle body 1, whereas in accordance with the embodiment of Figs. 1 and 2, the screw thread extends over a circumferential length that is less than 180°.

In accordance with a further development of the invention, the nut member could consist of two or more interacting nuts. While assuming relative angular end positions, the nuts can be displaced rapidly together along the screw spindle body, their screw threads sliding in the non-threaded section 5. After the nuts have been turned relative to one another to opposite relative angular positions, the screw threads in the nuts will run in continuous engagement in the screw threads 6 of the screw body 1. Together, these screw threads then cover the entire or major portion of the periphery of the screw spindle body, such that at any one time one or several nuts will engage in the screw threads 6 of the screw spindle body.

Another possible further development is to provide one of the two cooperating nuts with a trapezoidal screw thread which is able to

slide only on the section 5. The other nut, formed like those already described herein, will be able to turn relative to the first nut into and out of engagement with the screw

threads 6 of the screw spindle body.

The invention is not limited to the embodiments described and referred to in the foregoing but several modifications are possible within the scope of the appended claims. For instance, the screw spindle body 1 and the nut member 2 could serve as the cooperating members of a vice, a lifting jack, sliding valve or the like. Roller bodies could be inserted between the screw and the nut parts to reduce the frictional forces. The screw threads as well as the non-threaded sections could have a pitch that differs from that shown herein and a larger number of entrances could be provided both on the spindle and on the nut member. The threaded portions 4, 7 and the non-threaded sections 5, 8 need not have the same axial width. This might be advantageous as it adds to strength and durability, because the various screw threads on the screw body 1 and on the nut member 2 thus obtain equivalent strength characteristics.

CLAIMS

1. An improved screw-and-nut unit or screw joint, comprising a screw spindle body (1) formed with at least one non-threaded section (5) extending along the spindle body, and at least one nut member (2) formed with a threaded section (7) that matches the non-threaded section (5) on the spindle body (1), said screw spindle body (1) and said nut member (2) arranged to move axially relative to one another, during which movement the threaded section (7) travels along the non-threaded section (5) of the screw spindle body, and to be turned relative to one another to effect engagement between the threaded section (7) of the nut member and the threads (6) of the screw spindle body, characterised in that the non-threaded section (5) of the screw spindle body (1) and the threaded section (7) of the nut member (2) extend helically along the screw spindle body (1) and the nut member (1), respectively.

2. An improved screw-and-nut unit or screw joint as claimed in claim 1, characterised in that the screw threads (6) on said screw spindle body (1) are either left-hand threads or right-hand threads, and in that the non-threaded section (5) extends helically in the opposite direction to said screw threads.

3. An improved screw-and-nut unit or screw joint, as claimed in claim 1, characterised in that the screw threads (6) on said screw spindle body (1) are either left-hand threads or right-hand threads, and in that the non-threaded section (5) extends helically in the same direction as said screw threads.

4. An improved screw-and-nut unit or screw joint, as claimed in any one of the



* C L N S *

GB 2 071 801 B

3

17

3

preceding claims, characterised in that the nut member (2) consists of two or several cooperating nuts arranged to be turned relative to one another, and in that in one of their
5 angular end positions, said nuts form a single nut unit the threads of which extend around the entire periphery of said screw spindle body or over the major portion thereof.

Printed for Her Majesty's Stationery Office
by Burgess & Son (Abingdon) Ltd.—1983.
Published at The Patent Office, 25 Southampton Buildings,
London, WC2A 1AY, from which copies may be obtained.