# CLAIMS

1. A built-in washer circumcision device, comprising: a circumcision cover, a comprehensive cover and a first washer and/or a second washer, the circumcision cover and the comprehensive cover being configured to be connected with each other, wherein

the comprehensive cover is provided with a U-nail groove, and the first washer is arranged in the U-nail groove along a longitudinal outer side of the comprehensive cover at an end of the comprehensive cover facing towards the circumcision cover; wherein the first washer has a ring and a protrusion located on a bottom surface of the ring; a second ring-shaped groove is also formed at the end of the comprehensive cover towards the circumcision cover, and is located in the periphery of a first ring-shaped groove; and the protrusion is configured to be clamped in the second ring-shaped groove;

and

a U-nail seat corresponding to the U-nail groove is arranged on the circumcision cover, and the second washer is arranged on the U-nail seat, and wherein the comprehensive cover is provided with a circumcision knife; and a third washer is arranged at the end of the circumcision cover towards the comprehensive cover and corresponds to the circumcision knife.

2. The built-in washer circumcision device of claim 1, wherein a first ring-shaped groove is formed at the end of the comprehensive cover towards the circumcision cover, and is located outside the U-nail groove; and the first washer is arranged in the first ring-shaped groove.

3. The built-in washer circumcision device of claim 2, wherein the first washer is slightly wider than the first ring-shaped groove, so that the first washer is elastically clamped in the first ring-shaped groove.

4. The built-in washer circumcision device of claims 1-3, wherein a third ring-shaped groove is formed in the U-nail seat towards the U-nail groove; and the second washer is arranged in the third ring-shaped groove.

5 . The built-in washer circumcision device of claim 1, wherein the third washer has a first lateral portion surrounding the circumcision knife , a longitudinal portion perpendicular to the first lateral portion, and a second lateral portion surrounding the U-nail seat.

6 . The built-in washer circumcision device of claims 1-4, wherein the first, second and/or third washers are rubber washer(s) and/or silicone washer(s).