a first driving signal to be provided to the at least one pump to cause the generated pressure at the at least one filter membrane that exceeds an osmotic pressure associated with the at least one filter membrane and substantially maintain a first target recovery rate, the first target recovery rate being greater than a maximum non-scaling recovery rate for the at least one filter membrane and having an associated duration of time prior to when a pre-antiscalant maximum non-scaling recovery state is reached for the at least one filter membrane; determine when the pre-antiscalant maximum non-scaling recovery state is reached for the filter membrane; and in response to determining the pre-antiscalant maximum non-scaling recovery state is reached, cause one or a plurality of antiscalant doses to be provided to the filter membrane to increase an amount of time between when a post-antiscalant maximum non-scaling recovery state is reached and when subsequent scaling and/or fouling of the filter membrane occurs.

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] Various aspects and features of the present disclosure will be better understood by reading the following detailed description, taken together with the drawings wherein:

What is claimed is:

1. A filter system comprising:

at least one inlet fluidly coupled to at least one feed stream;

at least one filter membrane fluidly coupled to the at least one inlet to receive feed water from the at least one feed stream;

at least one pump to generate a pressure to displace the feed water from the at least one feed stream into the at least one filter membrane and produce an output permeate stream; and

a controller configured to:

cause a first driving signal to be provided to the at least one pump to cause the generated pressure at the at least one filter membrane that exceeds an osmotic pressure associated with the at least one filter membrane and substantially maintain a first target recovery rate, the first target recovery rate being greater than a maximum non-scaling recovery rate for the at least one filter membrane and having an associated duration of time prior to when a pre-antiscalant maximum non-scaling recovery state is reached for the at least one filter membrane; determine when the pre-antiscalant maximum non-scaling recovery state is reached for the filter membrane; and

in response to determining the pre-antiscalant maximum non-scaling recovery state is reached, cause one or a plurality of antiscalant doses to be provided to the filter membrane to increase an amount of time between when a post-antiscalant maximum non-scaling recovery state is reached and when subsequent scaling and/or fouling of the filter membrane occurs.

2. The filter system of claim 1, wherein the controller is further configured to cause a second driving signal to be provided to the at least one pump to cause the generated pressure to produce the output permeate stream at a recovery rate substantially equal to a second target recovery rate during a second period of time.

3. The filter system of claim 2, wherein the second target recovery rate is equal to or less than a maximum non-scaling recovery rate for the at least one filter.

4. The filter system of claim 2, wherein the second target recovery rate is greater than the maximum non-scaling recovery rate for the at least one filter membrane.

5. The filter system of claim 2, wherein the second target recovery rate is greater than the maximum non-scaling recovery rate for the at least one filter membrane and the first target recovery rate.

6. The filter system of claim 2, wherein the second driving signal is configured to cause at least a partial flush of the at least one filter membrane.

7. The filter system of claim 6, wherein the second target recovery rate is equal to zero such that all of the feed water of the at least one feed stream is output as reject.

8. The filter system of claim 6, wherein the second target recovery rate is less than or equal to a maximum non-scaling recovery rate for the at least one filter membrane during a portion of the second period of time and greater than the maximum non-scaling recovery rate for a portion of the second period of time.

9. The filter system of claim 6, wherein the second target recovery rate is greater than 0% and less than the maximum non-scaling recovery rate to cause a partial flush of the at least one filter membrane.

10. The filter system of claim 2, wherein the second target recovery rate is between 96-100% such that a ratio of the received feed water to output permeate stream by volume is between 0.96 and 1.0 during the second period of time.

11. The filter system of claim 2, further comprising at least one bleed valve fluidly coupled to the at least one filter membrane to output a first predetermined portion of the feed water of the at least one feed stream as reject water during the second period of time.

12. The filter system of claim 11, wherein the second target recovery rate is equal to 100%, and wherein the controller is configured to cause the at least one bleed valve to close such

that the first predetermined portion of feed water output as reject water is zero percent during the second period of time.

13. The filter system of claim 11, wherein the second target recovery rate is 100% such that 0% of the at least one feed stream is output as reject water during the second period of time.

14. The filter system of claim 11, wherein the second period of time occurs prior to or after the first period of time based on a predetermined sequence of filter operations stored in a memory.

15. The filter system of claim 2, wherein the second driving signal is further configured to cause one or a plurality of antiscalant doses to be introduced into the at least one filter membrane at a predetermined moment during the second period of time.

16. The filter system of claim 15, wherein the predetermined moment delineates the second period of time into a first induction period occurring prior to the predetermined moment and a second induction period occurring after the predetermined moment at which antiscalant is introduced, the first induction period being a period of time operating before scaling and/or fouling of the at least one filter membrane occurs, the second induction period being a period of time measured from when the antiscalant is introduced to when scaling and/or fouling of the at least one filter membrane occurs.

17. The filter system of claim 2, wherein the controller is further configured to cause a third driving signal to be provided to the at least one pump to cause at least a partial flush during a third period of time, the third period of time subsequent to the second period of time.

18. The filter system of claim 17, wherein the third driving signal is configured to cause the at least one pump to generate a pressure to produce the output permeate stream at a recovery rate that is substantially equal to a third target recovery rate during the third period of time, the third target recovery rate being different than the first and second target recovery rates.

19. The filter system of claim 17, wherein the third target recovery rate is between 0% and 80% during the third period of time to cause at least a partial flush of the at least one filter membrane.

20. The filter system of claim 18, wherein the third recovery rate is substantially 0% to cause a full flush of the at least one filter membrane.

21. The filter system of claim 2, wherein the second period of time is subsequent to the first period of time, and wherein causing the second driving signal to be provided during the second period of time occurs without causing an intervening full flush of the at least one filter membrane between the first and second periods of time.

22. The filter system of claim 2, wherein the second driving signal is configured to cause pressure generated by the at least one pump to increase to an amount exceeding osmotic pressure of the at least one filter membrane such that over the second period of time pressure increases by at least 10 psi per minute, the second period of time being at least two (2) minutes.

23. The filter system of claim 2, wherein the second driving signal is configured to cause the at least one pump to generate a substantially constant pressure such that over the second period of time the substantially constant pressure increases by a maximum of 10 pounds per square inch (psi) per hour, the second period of time being at least 6 hours.

24. The filter system of claim 1, wherein the first driving signal is configured to cause pressure generated by the at least one pump to increase to an amount exceeding osmotic pressure of the at least one filter membrane such that over the first period of time pressure increases by at least 10 psi per minute, the first period of time being at least two (2) minutes.

25. The filter system of claim 1, wherein the first driving signal is configured to cause the at least one pump to generate a substantially constant pressure such that over the first period of time the substantially constant pressure increases by a maximum of 10 pounds per square inch (psi) per hour, the first period of time being at least 6 hours.

26. The filter system of claim 1, further comprising at least one bleed valve fluidly coupled to the at least one filter membrane to output a second predetermined portion of feed water of the at least one feed stream as reject water during the first period of time.

27. The filter system of claim 26, wherein the first target recovery rate is less than or equal to 98%, the first predetermined portion of feed water being at least 2%, and wherein the controller is configured to cause the at least one bleed valve to output the first predetermined

portion of feed water of the at least one feed stream to be output as reject water during the first period of time.

28. The filter system of claim 1, wherein the controller is further configured to cause one or a plurality of antiscalant doses to be introduced into the at least one filter membrane at a predetermined moment during the first period of time.

29. The filter system of claim 28, wherein the predetermined moment delineates the first period of time into a first induction period occurring prior to the predetermined moment and a second induction period occurring after the predetermined moment at which antiscalant is introduced, the first induction period being a period of time operating before scaling and/or fouling of the at least one filter membrane occurs, the second induction period being a period of time measured from when the antiscalant is introduced to when scaling and/or fouling of the at least one filter membrane occurs.

30. The filter system of claim 29, wherein causing the first driving signal to be provided to the at least one pump further comprises causing the at least one pump to monotonically increase pressure beyond osmotic pressure of the at least one filter membrane from the predetermined moment the antiscalant is introduced to maintain the first target recovery rate during at least a portion of the second induction period.

31. The filter system of claim 1, wherein the at least one filter membrane comprises at least one high-pressure filter membrane with a pressure casing capable of withstanding at least 90 bar of pressure.

32. The filter system of claim 1, wherein the at least one filter membrane comprises at least first and second filter membranes, each of the first and second filter membranes providing at least a portion of first and second filter stages, respectively.

33. The filter system of claim 32, further comprising a filter valve arrangement to switchably fluidly couple the first and/or second filter membranes to the at least one feed stream.

34. The filter system of claim 33, wherein the controller is further configured to cause the filter valve arrangement to switchably fluidly couple the first and/or second filter membranes to the at least one feed stream during the first and/or second periods of time.

35. The filter system of claim 1, wherein the at least one inlet fluidly couples to a bleed of a filter system such that the at least one feed stream comprises concentrate from the filter system.

36. The filter system of claim 1, wherein the at least one inlet fluidly couples to an outlet of a filter system such that the at least one feed stream comprises permeate output by the filter system.