

REPLACED SHEETS		SG
☒	Description : paged 01 to paged 02	
☒	Claim(s) : paged 08 to paged 09	
☐	Drawing(s) : paged to paged	
☐	Abstract : paged to paged	

1

VALVE FOR THE FLOW CONTROL OF A FLUID COMPRISING SOLID PARTICLES

The invention relates to apparatus for operating a closure, a material handling system including such apparatus, and a method of transferring a flowable material from a material storage container.

Material handling apparatus generally consists of a storage container or silo, with a discharge aperture, and operating means therefor. Product from the silo is discharged mainly due to gravity through the aperture which is generally located at or near the bottom of the apparatus. A problem experienced with apparatus such as this is that on delivery, brittle, or friable products such as for example, tablets, can be damaged. In particular, when the aperture is closed after an amount of product has been dispensed, product trapped between the closure and the rim of the aperture may be crushed, resulting in a loss of useable product, and potential contamination by dust.

It is an object of the invention to mitigate problems such as this.

According to the invention there is provided apparatus for operating a closure for an aperture of a material storage container, comprising means to regulate the position of the closure relative to the aperture during closure thereof.

The regulating means may comprise moveable stop means adapted to abut a part of the apparatus in the closed position.

The regulating means may include adjustment means to adjust the position of the stop means relative to the closure.

The adjustment means may be operable to move the stop means from an

This Sheet Has Been Replaced



operating to a non-operating position.

The stop means may be pivotably mounted for movement between the operating and non-operating positions.

The adjustment means may comprise cylinder means.

The stop means may comprise a tapering nose part, a surface of which is disposed to contact a part of the apparatus in the closed position.

The apparatus may comprise cylinder means for operating the closure.

It is preferred that the regulating means is adapted to cooperate with a part of the cylinder means for regulation of the position of the closure. The cylinder part may comprise an elongate extension, which moves with the cylinder means when it is operated.

According to a second aspect of the invention, there is provided a material handling system including a material storage container having an aperture and a closure therefor, comprising apparatus as hereinbefore defined. The apparatus is preferably disposed outside of the container and closure.

According to a third aspect of the invention there is provided a method of transferring a flowable product from a material storage container which comprises the steps of providing apparatus to open a closure of the container, allowing material to run out of the container and then operating the apparatus to close the closure to leave a gap between the closure and the container, so that material trapped between the closure and container is not crushed.



3

Apparatus embodying the invention is hereinafter described, by way of example, with reference to the accompanying drawings.

Fig. 1 is a side view of a material storage and discharge container for use with apparatus according to the invention;

Fig. 2 is a side view of a base part including apparatus according to the invention;

Fig. 3 is a side sectional view of the apparatus of Figs. 1 and 2 in an open position;

Fig. 4 is a side view of the apparatus of Figs. 1 and 2 in a closed position;

Fig. 5 is a plan view of the apparatus of Fig. 2;

Fig. 6 is a transverse sectional view through the base part of a material storage container including apparatus according to the invention; and

Fig. 7 is an enlarged view of apparatus according to the invention in a non-operative position.

Referring to the drawings, there is shown apparatus 1 for operating a closure 2 for an aperture of a material storage container 3, comprising means 4 to regulate the position of the closure 2 relative to the aperture.

The apparatus illustrated is that generally referred to as an Intermediate Bulk Container or IBC, which usually consists of a container 3 with an inlet 5 and an outlet (not shown). The container is mounted on a base part 6 on which it is

supported. The base part 6 includes the apparatus 1 for operating a valve or closure 2 of the container, which in the illustrated embodiment is a generally conical device. Referring to Figs. 3 and 4 the device 2 generally comprises a cone-shaped stopper, the apex of which extends into the container 3. An edge seal or seals are provided around the periphery of the device 2 which sealingly engage with the mouth of the aperture of the container to prevent material escaping when the device 2 or valve is in a closed position. The device 2 is moved from the open to the closed positions by apparatus which, in the illustrated embodiment, is in the form of a lifting cylinder and piston arrangement 7, situated outside (as viewed) of the device 2 in the base part 6.

The base part 6 is further provided with a chute 8 through which product is delivered, which preferably is offset and angled away from the vertical by for example 30°, as viewed, in order to minimise damage to friable products such as tablets during their progress down the chute 8.

Referring to Figs. 3 and 4, to deliver product from the container, the cylinder 7 is operated by any suitable control means, to extend the piston upwardly (as viewed) into the device 2, thereby raising it into the IBC. An annular gap 9 is thereby created through which product can flow from the container 3 and out through the chute 8. When a sufficient amount of product has been delivered, the cylinder 7 is again actuated by appropriate control means to lower the device 2 closing the annular gap 9 and preventing further product discharge.

As will be appreciated, in prior known discharge apparatus, when the device 2 is lowered back into the closed position, product for example in the form of tablets "bridges" and often becomes trapped between the device 2 and the rim of the aperture, and is crushed. Apparatus as shown herein embodying the invention overcomes this problem by providing regulating means 4 (Figs. 2, 5,

6 and 7) which includes adjustment means 10. The adjustment means 10 is in the form of a cylinder device mounted on a part of the base 6, although any suitable device such as for example a bellows device could be used. The cylinder device 10 is operatively connected with a movable stop means 11 in the form of a substantially triangular part having a tapered nose 12. The nose 12 has an upper (in use) surface 13. The stop means 11 is pivotably mounted both to an extension part or piston 14 of the cylinder 10 and a part of the base 6. As illustrated, the regulating means 4 is mounted so as to be cooperable with an inverted T extension part 15 which extends from the bottom (in use) of the cylinder 7 and is moved upwards and downwards with the cylinder 7.

In use, the container 3 is filled with product through the aperture 5 with the device 2 in the fully closed position illustrated in Fig. 4. The cylinder 10 of the regulating means 4 is operated to extend the piston extension part 14, thus causing the tapered nose 12 of the stop means 11 to rise, away from the T-shaped extension 15, in a clockwise direction as illustrated. At this point, the T-shaped extension 15 is fully extended downwardly, as viewed.

When a batch of product is to be delivered from the IBC, a suitable receptacle is placed in communication with the chute 8 and the cylinder 7 is then operated to raise the device 2, as described above. Product then flows through the annular gap 9, down the chute 8 and into the receptacle. When delivery is complete, the adjustment means 10 is operated to withdraw the extension part 14 a preset amount. This has the effect of lowering the tapered nose 12 of the stop means 11 by the pivotal movement (counter-clockwise as illustrated) to a position below the T-shaped extension 15. The stop means 11 is thus locked into position. The cylinder 7 is then operated to lower the device 2, however the device cannot descend to the full sealing position, because the downward path of the T-shaped extension is blocked by the stop means 11, and in particular the upper surface

13 thereof. The rim of the device 2 is thus stopped short of the mouth of the aperture, by a distance which corresponds to the position of the stop means 11.

It is desirable to set the apparatus such that the annular gap which is left after the device is lowered is set to slightly larger than the average particle size of the product in the container so that the particles bridge and will not flow, nevertheless they will not be broken.

As will be appreciated, the size of the annular gap 9 is adjusted by adjusting the set position of the stop means 11.

As can be seen, the actuating mechanism 7 is underneath and outside the IBC which gives the additional ability to adjust the lift height of the cylinder 7 externally and also to provide a separately externally preset lift height. Although the IBC may be made of any suitable material, it is preferably of a moulded plastic construction. The central discharge hopper or chute 8 is also in the embodiment, made of plastic.

It is not necessary to provide any form of vibrator, such as is commonly used with apparatus of this kind although for cohesive products the cylinder 7 can be oscillated to promote flow without harsh extreme vibration which can damage powder.

Thus, the apparatus illustrated in the drawings is capable of delivering friable products such as "green" capsules, free flowing powders or like particulate material and tablets, without damage occurring due to crushing between the closure and the container. This is because the apparatus has the chute 8 which has a very shallow inclined outlet as shown which allows the product to roll down or pass along the hopper walls gently and swirl around into the offset

angled discharge pipe. The apparatus 1 is adjustable to cater for different grades and types of product and can be retro-fitted to existing material delivery systems if required.

It will be understood that the terms "crush", "crushing", "crushed" used herein cover spalling, flaking, chipping or otherwise providing physically reduced material.

CLAIMS

1. Apparatus for operating a closure for an aperture of a material storage container, comprising means to regulate the position of the closure relative to the aperture, in the closed position during closure thereof.
2. Apparatus according to Claim 1, the regulating means comprising moveable stop means adapted to abut a part of the apparatus in the closed position.
3. Apparatus according to Claim 2, the regulating means comprising adjustment means to adjust the position of the stop means relative to the closure.
4. Apparatus according to any preceding claim, the adjustment means being operable to move the stop means from an operating to a non-operating position.
5. Apparatus according to any of Claims 2 to 4, the stop means being pivotably mounted for movement between the operating and non-operating positions.
6. Apparatus according to any of Claims 3 to 5, the adjustment means comprising cylinder means.
7. Apparatus according to any of Claims 2 to 6, the stop means comprising a tapering nose part, a surface of which is disposed to contact a part of the apparatus in the closed position.
8. Apparatus according to any preceding claim, including cylinder means for operating the closure.





9. Apparatus according to Claim 8, the regulating means being adapted to cooperate with a part of the cylinder means for regulation of the position of the closure.

10. Apparatus according to Claim 9, the cylinder part comprising an elongate extension, which moves with the cylinder means when it is operated.

11. Apparatus according to any preceding claim, adapted for use with a cone closure device.

12. A material handling system, including a material storage container having an aperture and a closure therefor, comprising apparatus according to any one of claims 1 to 11.

13. A material handling system, according to Claim 12, the apparatus being disposed outside the container and closure.

14. A method of transferring a flowable product from a material storage container, comprising the steps of providing apparatus to open a closure of the container, allowing material to pass out of the container, and then operating the apparatus to close the closure to leave a gap between the closure and the container, so that material trapped between the closure and container is not crushed.

15. A method according to Claim 14, including the step of presetting the apparatus to leave a predetermined gap between the closure and the container.






FIG. 1




FIG. 2

2/5





FIG. 3



5/5




FIG. 6




FIG. 7

APPARATUS FOR OPERATING A CLOSURE

The invention relates to apparatus for operating a closure, a material handling system including such apparatus, and a method of transferring a flowable material from a material storage container.

Material handling apparatus generally consists of a storage container or silo, with a discharge aperture, and operating means therefor. Product from the silo is discharged mainly due to gravity through the aperture which is generally located at or near the bottom of the apparatus. A problem experienced with apparatus such as this is that on delivery, brittle, or friable products such as for example, tablets, can be damaged. In particular, when the aperture is closed after an amount of product has been dispensed, product trapped between the closure and the rim of the aperture may be crushed, resulting in a loss of useable product, and potential contamination by dust.


It is an object of the invention to mitigate problems such as this.

According to the invention there is provided apparatus for operating a closure for an aperture of a material storage container, comprising means for operating the closure, and means to regulate the position of the closure relative to the aperture to leave a gap therebetween, in the closed position during closure thereof.

The regulating means may comprise moveable stop means adapted to abut a part of the apparatus in the closed position.

The regulating means may include adjustment means to adjust the position of the stop means relative to the closure.

The adjustment means may be operable to move the stop means from an



CLAIMS

THIS SHEET HAS BEEN
REPLACED

1. Apparatus for operating a closure for an aperture of a material storage container, comprising means for operating the closure, and means to regulate the position of the closure relative to the aperture to leave a gap therebetween, in the closed position during closure thereof.
2. Apparatus according to Claim 1, the regulating means comprising moveable stop means adapted to abut a part of the apparatus in the closed position.
3. Apparatus according to Claim 2, the regulating means comprising adjustment means to adjust the position of the stop means relative to the closure.
4. Apparatus according to any preceding claim, the adjustment means being operable to move the stop means from an operating to a non-operating position.
5. Apparatus according to any of Claims 2 to 4, the stop means being pivotably mounted for movement between the operating and non-operating positions.
6. Apparatus according to any of Claims 3 to 5, the adjustment means comprising cylinder means.
7. Apparatus according to any of Claims 2 to 6, the stop means comprising a tapering nose part, a surface of which is disposed to contact a part of the apparatus in the closed position.
8. Apparatus according to any preceding claim, wherein the means for operating the closure comprises cylinder means.

This Sheet Has Been Replaced



AMENDED SHEET



* C L M S *

8

CLAIMS**REPLACEMENT SHEETS SG**


- ☐ Description : paged ... to paged ...
☒ Claim(s) : paged 08 to paged 09
☐ Drawing(s) : paged ... to paged ...
☐ Abstract : paged ... to paged ...

DATE OF RECEIPT 17/10/98

**THIS SHEET HAS BEEN
REPLACED**

1. Apparatus for operating a closure for an aperture of a material storage container, characterised by means (4), to regulate the position of the closure (2) relative to the aperture (9), in the closed position during closure thereof.
2. Apparatus according to Claim 1, characterised by the regulating means (4) comprising movable stop means (11) adapted to abut a part of the apparatus (1) in the closed position.
3. Apparatus according to Claim 2, characterised by the regulating means (4) comprising adjustment means (10) to adjust the position of the stop means (11) relative to the closure.
4. Apparatus according to any preceding claim, characterised by the adjustment means (10) being operable to move the stop means (11) from an operating to a non-operating position.
5. Apparatus according to any of Claims 2 to 4, characterised by the stop means (11) being pivotably mounted for movement between the operating and non-operating positions.
6. Apparatus according to any of Claims 3 to 5, characterised by the adjustment means (10) comprising cylinder means.
7. Apparatus according to any of Claims 2 to 6, characterised by the stop means (11) comprising a tapering nose part (12), and by a surface of the part (12) being disposed to contact a part (15) of the apparatus in the closed position.

This Sheet Has Been Replaced






THIS SHEET HAS BEEN
REPLACED

8. Apparatus according to Claim 7, characterised by cylinder means (7) for operating the closure (2), and by the part (15) comprising part of the cylinder means (7).
9. Apparatus according to Claim 8, characterised by the regulating means (4) being adapted to cooperate with the part (15) of the cylinder means (7) for regulation of the position of the closure (2).
10. Apparatus according to Claim 9, characterised by the cylinder part (15) comprising an elongate extension, which moves with the cylinder means when it is operated.
- 11.. A material handling system, characterised by a material storage container (3) comprising an aperture and a closure (2) therefor, and by apparatus (1) according to any one of claims 1 to 11.
12. A material handling system according to Claim 12, characterised by the apparatus (1) being disposed outside the container (3) and closure (2).
13. A method of transferring a flowable product from a material storage container (3), characterised by the steps of providing apparatus (1) to open a closure (2) of the container (3), by allowing material to pass out of the container (3), and then by operating the apparatus (1) to close the closure (2) to leave a gap (9) between the closure (2) and the container (3), so that material trapped between the closure (2) and container (3) is not crushed.
14. A method according to Claim 13, characterised by the step of presetting the apparatus (1) to leave a predetermined gap (9) between the closure (2) and the container (3).



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau




9804062-9
1105

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B65D 90/62	A1	(11) International Publication Number: WO 97/06079 (43) International Publication Date: 20 February 1997 (20.02.97)
(21) International Application Number: PCT/GB96/01674 (22) International Filing Date: 11 July 1996 (11.07.96) (30) Priority Data: 9516027.1 4 August 1995 (04.08.95) GB (71) Applicant (for all designated States except US): MATCON (R & D) LIMITED [GB/GB]; Matcon House, London Road, Moreton-in-Marsh, Glos. GL56 OHJ (GB). (72) Inventor; and (75) Inventor/Applicant (for US only): SEMENENKO, Ivan [GB/GB]; Harvey House, High Street, Moreton-in-Marsh, Glos. GL56 OHJ (GB). (74) Agent: JOHNSON, Terence, Leslie; Edward Evans & Co., Chancery House, 53-64 Chancery Lane, London WC2A 1SD (GB).	(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	

(54) Title: VALVE FOR THE FLOW CONTROL OF A FLUID COMPRISING SOLID PARTICLES



(57) Abstract

Referring to the drawings, there is shown apparatus (1) for operating a closure (2) for an aperture of a material storage container (3), comprising means (4) to regulate the position of the closure (2) relative to the aperture. The apparatus illustrated is that generally referred to as an Intermediate Bulk Container or IBC, which usually consists of a container (3) with an inlet (5) and an outlet (not shown). The container is mounted on a base part (6) on which it is supported. The base part (6) includes the apparatus (1) for operating a valve or closure (2) of the container, which in the illustrated embodiment is a generally conical device. The base part (6) is further provided with a chute (8) through which product is delivered, which preferably is offset and angled away from the vertical by, for example 30°, as viewed, in order to minimise damage to friable products such as tablets during their progress down the chute (8). There is adjustment means in the form of a piston and cylinder arrangement which has an extensible part for engaging with a detent of lifting means for the device (2) so that an annular gap through which material is discharged is adjustable in width whereby to prevent crushing of material which might be "bridged" in the gap.

**CLAIMS**

1. Apparatus (1) for operating a closure (2) for an aperture of a material storage container (3), characterised by first means (7) for operating the closure, and second means (4) to regulate the position of the closure (2) relative to the aperture by interacting with the first means (7) to leave a gap between the closure and the aperture, in the closed position.
2. Apparatus according to claim 1, the regulating means (4) comprising movable stop means (11) adapted to abut a part (15) of the aperture (1) in the closed position.
3. Apparatus according to claim 2, the regulating means (4) comprising adjustment means (10) to adjust the position of the stop means (11) relative to the closure (2).
4. Apparatus according to any preceding claim, the adjustment means (10) being operable to move the stop means (11) from an operating to a non-operating position.
5. Apparatus according to any of claims 2 to 4, the stop means (11) being pivotably mounted for movement between the operating and non-operating positions.
6. Apparatus according to any of claims 3 to 5, the adjustment means (10) comprising cylinder means.
7. Apparatus according to any of claims 2 to 6, the stop means (11) comprising a tapering nose part (12), a surface (13) of which is disposed to contact a part (15) of the apparatus in the closed position.



8. Apparatus according to any preceding claim, wherein the means (7) for operating the closure (7) comprises cylinder means.
9. Apparatus according to claim 8, the cylinder means (7) comprising an extension part (15), which moves with the cylinder means when it is operated.
10. Apparatus according to any preceding claim, adapted for use with a cone closure device.
11. A material handling system, including a material storage container (3) having an aperture and a closure (2) therefor, comprising apparatus according to any one of claims 1 to 10.
12. A material handling system according to claim 12, the apparatus (1) being disposed outside the container and closure.
13. A method of transferring a flowable product from a material storage container comprising the steps of providing operating means to open a closure of the container, allowing material to pass out of the container, operating the operating means to close the closure and operating regulating means to interact with the operating means to leave a gap between the closure and the container, so that material trapped between the closure and container is not crushed.
14. A method according to claim 13, including the step of presetting the regulating means to leave a predetermined gap between the closure and the container.