

REPLACED SHEETS		SG
☒	Description : paged ...1... to paged ...15...	
☒	Claim(s) : paged ...16... to paged ...19...	
☒	Drawing(s) : paged ...17... to paged ...17...	
☒	Abstract : paged ...20... to paged	
DATE OF RECEIPT		

1

PATENT

ATTORNEY DOCKET NO. 04476/160001

CUFF FOR BLOOD PRESSURE METER**Field Of The Invention**

This invention concerns a cuff used to measure blood pressure. More specifically, it concerns a cuff for a blood pressure meter which measures blood pressure when applied to a finger.

Background Of The Invention

Fig. 16 is a perspective view of a conventional finger blood pressure meter. Fig. 17 is a cross-sectional view of a conventional blood pressure meter finger cuff. Several types of designs of finger cuffs are currently available.

The finger cuff shown in Fig. 17 has a wrapper constituting a sheet (or membrane) made of rubber or a soft plastic which is folded over on itself. Chamber 501, which contains compressed air, is formed by welding or bonding the ends of this sheet. Generally, the outside of chamber 501 has strips of cloth around its top and bottom ends which cause it to assume the shape of a cylinder when inflated. Cylindrical cuff or chamber 501, is enclosed within cylindrical case 500.

To measure a patient's blood pressure, the patient inserts his finger into the cylindrical cuff 501. When chamber 501 is filled with compressed air via the air tube connected to it, it expands like a balloon, adhering to and pressing against the finger. The blood pressure is measured by obstructing the flow of blood in the artery of the finger.

As seen in Fig. 16, the finger 400 inserted in the cylindrical cuff does not touch anything outside of the cuff nor does it rest on a fixed member or support. A patient often bends his finger, thus not relaxing the

This Sheet Has Been Replaced



1 finger for an accurate measurement because there is no
2 support on which the patient can rest his finger. As a
3 result of the tension in the finger, inaccurate blood
4 pressure measurements are taken.

5 In the conventional blood pressure finger cuff
6 described above, the range of finger sizes to which the
7 cuff can be applied properly is limited. If a person's
8 finger size happens to match the finger cuff size,
9 pressure would be applied to the finger as the
10 cylindrical cuff or chamber is filled with compressed
11 air. If the finger to be measured does not match the
12 finger cuff size, but is, for example, thinner than the
13 finger size optimal for the finger cuff, the chamber is
14 stretched and deformed by the pressure applied by the
15 compressed air before the cuff is expanded enough to
16 cause its surface to press against the finger. The
17 tension caused by the deformation of the chamber affects
18 the pressure inside the finger cuff, and the pressure
19 applied to the finger is reduced. If pressurization were
20 continued while the chamber was deformed, the sum of the
21 pressure against the finger and the pressure required to
22 expand the cuff would equal the internal pressure of the
23 cuff. The result would be that the internal pressure in
24 the cuff would not correspond to the blood pressure
25 value. Since this type of chamber deforms when it
26 stretches, the insertion of a thin finger in the cuff
27 causes the midline cross-section to expand like a
28 balloon, while the two ends of the chamber, along the
29 path of insertion, become round. Thus, both the shape of
30 the cylindrical cuff and its length when pressed against
31 a finger vary with the diameter of the finger. This
32 variation leads to measurement errors.

33 An example of this can be seen in Fig. 17. When
34 chamber 501 expands like a balloon, the length of the
35 surface in contact with the finger, which was originally
36 l_1 , is reduced to l_2 .

This Sheet Has Been Replaced



1 Another disadvantage of this type of cuff is that
2 the material of the air containment wall or chamber is
3 limited to materials which can stretch, yet are highly
4 stable, i.e., materials capable of substantial elastic
5 deformation.

6 As seen in Fig. 18, a conventional finger cuff has
7 many parts to assemble, in this case, five pieces. In
8 this conventional finger cuff, a long, flat air chamber
9 590 is rolled into a cylinder 591a, 591b, both ends of
10 which are taped on both surfaces to form a permanent tube
11 then sealed by end pieces 592, 593. The task of winding
12 the cuff into a cylinder is extremely complicated, and
13 thus, assembling the cuff is difficult.

14 Summary Of The Invention

15 This invention provides a cuff for a blood pressure
16 meter which solves the problems described above. Such a
17 cuff is made of a material which does not stretch
18 regardless of the diameter of the object to be measured
19 (a finger, for example) and the length of the portion of
20 cuff in contact with the object to be measured does not
21 vary. As a result, the pressure within the cuff closely
22 approximates the blood pressure of the object so that an
23 accurate measurement is made.

24 A cuff for a blood pressure meter of this invention
25 is described below.

26 A cuff for a blood pressure meter according to this
27 invention includes a belt having a plurality of
28 protruding bodies disposed thereon and an air bag or
29 chamber disposed over the protruding bodies on the belt
30 for receiving compressed air. The cuff further including
31 at least one containment wall disposed on the belt,
32 forming with the belt an air bag or chamber for receiving
33 compressed air, and at least a pair of folded portions on
34 each of the containment walls which cause the surface
35 portions of the containment walls, the portions which
36



1 make contact with a patient's finger, to remain parallel
2 to the protruding bodies when the volume enclosed by the
3 belt, protruding bodies, and containment walls is filled
4 with compressed air.

5 This cuff has a number of protruding bodies which
6 protrude inwardly from the inner surface of the belt,
7 when the belt is formed into a cuff. The belt or basic
8 structure has a cylindrical shape. The containment walls
9 for compressed air, which are formed from a thin sheet,
10 are located on the surface of the basic structure, over
11 the protruding bodies. The edges of the containment
12 walls are connected to the belt. Compressed air is
13 pumped into a chamber located between the belt and the
14 protruding bodies thereon, and the containment walls.

15 The folding portions are located at either end of
16 the containment walls at right angles to the path along
17 which the finger is inserted. Ordinarily, the surfaces
18 of the containment walls which contact the object to be
19 measured touch the level horizontal surfaces of the
20 protruding bodies. To measure a patient's blood
21 pressure, one inserts the object to be measured (i.e., a
22 finger), and compressed air is pumped into the chamber.
23 The portions on either end of the containment walls which
24 are folded toward the periphery rise up (i.e., the
25 portions move toward the interior of the cuff), and as
26 these portions move, the surfaces which come in contact
27 with the finger remain parallel with the flat surfaces of
28 the protruding bodies. The folded portions assist the
29 containment walls to maintain contact with the finger.
30 As the compressed air fills the chamber, the containment
31 walls are pushed inward toward the finger. These walls
32 do not stretch when the chamber is filled with compressed
33 air. Even when the object to be measured (i.e., a
34 finger) is thinner than the cuff, the internal pressure
35 in the cuff is not increased by the force of expansion.
36 The length of the surface in contact with the finger does



1 not vary with the diameter of the finger, and the blood
2 pressure can be measured with accuracy.

3 In another aspect of this invention, a cuff for a
4 blood pressure meter includes a belt having containment
5 walls for compressed air furnished to the structure, a
6 locking device on one end, and a lock on the other end.
7 When the locking device is engaged with the lock, the
8 belt assumes a cylindrical form. In this cuff for a
9 blood pressure meter, a projection which is the locking
10 device is located on one end of the belt, while a slit
11 which is the lock into which the projection engages is
12 located on the other end of the belt. This long, flat
13 cuff is rolled into a cylinder. The cylindrical shape is
14 maintained by fitting the projection into the slit.
15 Thus, assembly of the cuff is extremely simple.

16 This cuff for a blood pressure meter can further
17 include a support, or a finger bed, located at one end of
18 the blood pressure meter finger cuff on which the patient
19 can rest his finger. The patient can then relax his
20 finger in order to obtain a more accurate blood pressure
21 measurement.

22 The cuff according to this invention has many
23 advantages:

24 (1) The upward movement of the folded portions pre-
25 vents the material of the containment walls from
26 stretching and deforming.

27 (2) The surface areas of the containment walls which
28 contact the finger do not vary with the thickness of the
29 finger.

30 (3) The shape of the contacting surface does not
31 vary due to the force of expansion.

32 (4) Additionally, because the folded portions move,
33 an expansion force does not increase the internal
34 pressure in the cuff. Thus, the internal pressure in the
35 cuff closely approximates the blood pressure in the
36 finger.

This Sheet Has Been Replaced



(5) When the cuff is pressurized, its cross-section will not assume the shape of a balloon, as in conventional cuffs.

(6) Since this design requires less air to achieve a given pressure, the signal-to-noise ratio of the pulsewave which is detected will be larger.

(7) Because the material of the containment wall does not need to stretch, it need not be limited to only those materials which can withstand substantial elastic deformation. Rather, a wide range of materials can be chosen.

(8) A cylindrical cuff is easily formed by engaging the locking device and the lock.

(9) The finger bed on the cuff ensures that the patient's finger is relaxed in order for an accurate measurement to be made.

(10) The cuff comprises three segments which allow for easy assembly and shorter assembly time, then with conventional finger cuffs.

Brief Description Of The Drawings

Fig. 1 is a cross-sectional view of a first embodiment of a cuff for a blood pressure meter;

Fig. 2 is a plan view of the first embodiment of a cuff for a blood pressure meter;

Fig. 3 is a cross-sectional view of the first embodiment of a cuff for a blood pressure meter;

Fig. 4 is a cross-sectional view showing the components of a second embodiment of the cuff for a blood pressure meter;

Fig. 5 is a cross-sectional view showing the folded portion bent out from the edge of the outer case;

Fig. 6 is a cross-sectional view showing a guard on the folded portion which is a modification of the first and second embodiments, and a finger bed at one end of the cuff which is described in a sixth embodiment;



Fig. 8 is a cross-sectional view of a fourth embodiment of the cuff for a blood pressure meter;

Fig. 9 is a plan view of a fifth embodiment of the cuff for a blood pressure meter;

Fig. 10 is a perspective view of the fifth embodiment of the cuff for a blood pressure meter;

Fig. 11 is a plan view of the fifth embodiment of the cuff for a blood pressure meter;

Fig. 12 is a perspective view of a finger bed of a sixth embodiment of the cuff for a blood pressure meter;

Fig. 13 is a exploded view of a cuff comprising three segments;

Fig. 14 is a exploded view of a cuff with a finger bed comprising three segments;

Fig. 15 is an exploded view of a cuff with a finger bed comprising three segments;

Fig. 16 is a perspective view of a conventional finger cuff blood pressure meter;

Fig. 17 is a cross-sectional view of a conventional finger cuff for a blood pressure meter; and

Fig. 18 is an exploded view of a conventional cuff comprising five elements.

Detailed Description Of The Invention

Fig. 1 is a cross-sectional view of a first embodiment of the cuff for a blood pressure meter.

The cuff for a blood pressure meter shown in this first embodiment is a finger cuff. This finger cuff comprises a belt or basic structure 1; at least one containment wall 2 located on belt 1; at least one chamber 6 for compressed air; and folded portions 3 located on containment walls 2. When compressed air is pumped into the chambers 6 formed by belt 1 and containment walls 2, the surfaces 21 of containment walls

1 2, which contact the finger are forced to remain parallel
2 to the bases of the protruding bodies by folded portions
3 3.

4 As can be seen in Figs. 1-3, belt 1 includes thin
5 panel 11 and a number of protruding bodies 12.
6 Protruding bodies 12 are formed on the inner surface of
7 panel 11 and extend toward the interior of the cuff. In
8 this embodiment, eight protruding bodies 12 are provided
9 (see Figs. 2 and 3) so that each protruding body has a
10 flat upper surface to the outside of the cuff.
11 Containment walls 2 are formed by a long strip of
12 material in the form of a sheet or membrane of specified
13 length and width. The containment walls are attached to
14 belt 1 on one side. As shown in Fig. 1, side fitting
15 segments 22 are located on either end of each containment
16 wall 2. Side fitting segments 22 are mounted to basic
17 structure 1 at the beginning and the end of the path
18 along which the finger is inserted. With this structure,
19 contacting surfaces 21 of containment walls 2 contact the
20 upper surfaces of protruding bodies 12, which are arrayed
21 next to each other. Basic structure 1 to which contain-
22 ment wall 2 is attached is rolled into a cylinder, as
23 shown in Fig. 3, and enclosed within cylindrical outer
24 case 4.

25 As shown in Fig. 1, the folded portions 3 are
26 located at either end of the containment walls at right
27 angles to the path along which the finger is inserted.
28 Each folded portion 3 includes side fitting segment 22;
29 outer curved segment 31, which starts at the tip of side
30 fitting segment 22, is attached to basic structure 1 and
31 folded until segment 31 is parallel to side fitting
32 segment 22; and an inner curved segment 32, which starts
33 at the tip of outer curved segment 31, is folded until
34 inner curved segment 32 is parallel to outer curved
35 segment 31. Compressed air is pumped into the chambers 6

This Sheet Has Been Replaced




1 located between containment walls 2 with folded portions
2 3 and basic structure 1.

3 In such a cuff for a blood pressure meter, folded
4 portions 3 are provided at right angles to the path along
5 which the finger is inserted at both the beginning and
6 the end of the path. When a finger is inserted and com-
7 pressed air is pumped into the chamber 6 formed by basic
8 structure 1 and containment walls 2, folded portions 3,
9 which are normally oriented toward the periphery on
10 either end of each containment wall 2, rise up (i.e.,
11 they move toward the interior of the cuff). In other
12 words, as shown in Figs. 1 and 3, outer curved segment 31
13 and inner curved segment 32 extend in a straight line
14 from side fitting segment 22. Contacting portions 21 of
15 the containment walls 2, which normally contact the flat
16 surfaces of the protruding bodies 12, remain parallel
17 with the flat surfaces as they are pushed inwardly when
18 the chamber 6 inflates, and the finger is compressed.
19 Containment walls 2, which are formed from a thin sheet
20 of material, are not stretched during inflation of the
21 cuff.

22 Even when the object to be measured (i.e., the
23 finger) is thin, the internal pressure in the cuff is not
24 increased by the force of expansion. The length of the
25 surface in contact with the finger does not vary with the
26 diameter of the finger, and the blood pressure can be
27 measured with acceptable accuracy.

28 In this embodiment, eight protruding bodies 12 are
29 provided on the inner surface of basic structure 1.
30 However, any number of protruding bodies 12 may be used.

31 Fig. 4 is a partial cross-sectional view of a second
32 embodiment of the cuff for a blood pressure meter. In
33 this embodiment, side fitting segments 22, which are
34 connected to folded portions 3, are thicker than the
35 folded portions. Outer curved segments 31 and inner
36 curved segments 32, which are formed by folding the



1 material back on outer curved segments 31, have the same
2 width as contacting surfaces 21, while side fitting
3 segments 22 are wider.

4 In this embodiment, side fitting segments 22, which
5 are connected to folded portions 3, are made of a hard
6 material. When compressed air is pumped into the
7 chambers 6 located between basic structure 1 and
8 containment walls 2, folded portions 3 readily move
9 inward toward the object to be measured while side
10 fitting segments 22 are prevented from expanding or
11 bending toward the edges of the cuff as they are pushed
12 by the compressed air. This helps ensure that contacting
13 surfaces 21 can only move upward i.e., toward the
14 interior of the cuff.

15 Fig. 5 shows that the side fitting segments 22 are
16 expand or bend toward the edges of the cuff as they are
17 pushed by the compressed air, particularly when the side
18 fitting segments 22 rise up over the edge of the cuff.
19 When the measurement steps start in this case, the air
20 pressure in the cuff is gradually lowered. Then, the
21 expanding or bending portion of the side fitting segment
22 22 recovers to its original shape once the air pressure
23 falls under a certain level. This causes a shock in the
24 inner pressure of the cuff, and often leads to a mistaken
25 measurement of the blood pressure.

26 Fig. 6 shows another modification of the cuff. The
27 folding guards 107, 108 located over the side fitting
28 segments 22 are provided to overcome the above problem.
29 The folding guards 107, 108 prevent the side fitting
30 segments 22 from bending toward the edges of the cuff, so
31 that the inner curved segment 32 and the outer curved
32 segment 31 smoothly move only when inflated without
33 bending the side fitting segments 22 to the sides.

34 Fig. 6 also shows projection 111 around the cuff
35 holder segment 102a and a concave space 112 around cuff
36 holder segment 102b. Cuff holder 102 comprises cuff



holder segments 102a, 102b. When cuff holder 102 is inserted into the main unit 110, it is easily positioned by engaging projection 111 and the concave spaces 112 with the corresponding engagement structures of main unit 110. This configuration reduces the assembly time for the cuff.


Fig. 7 shows a cross-sectional view of a third embodiment of the cuff for a blood pressure meter. In this cuff for a blood pressure meter, belt 1 is cylindrical, and the inner surface of its body has a number of concave portions 12a facing the interior of the cuff. Containment walls 2, which are formed from a sheet or membrane of material, are attached to basic structure 1 when side fitting segments 22 are sandwiched between cylindrical case 4 and the exterior of basic structure 1. With this design, contacting surfaces 21 of containment walls 2 are positioned so that they contact the flat bottoms of concave portions 12a in the body. Folded portions 3, which are connected to side fitting segments 22, conform to the shape of rim portions 12b, which are the curved portions on either side of the flat bottom of concave portions 12a. During inflation, folded portions 3 are folded toward the interior of the cuff.

In a cuff according to this embodiment, when compressed air is pumped via connector tube 5 into the chambers 6 formed by basic structure 1 and containment walls 2, folded portions 3, which are angled toward the interior of the cuff, rise toward the interior. Flat contacting surfaces 21 remain flat as they are inflated. In other words, surfaces 21 expand into the interior of the cuff. This design prevents containment walls 2 from stretching and deforming when the chamber 6 is filled with compressed air. As is shown in Fig. 7, since the length L_2 of the folded portions is equal to the maximum displacement L_1 , an expansion force is not generated when the finger inserted in the cuff is thinner than average.



Fig. 8 is a cross-sectional view of a fourth embodiment of the cuff for a blood pressure meter. In this cuff for a blood pressure meter, belt 1 is flat. Flat protruding bodies 12c are formed on and integrally with the flat surfaces of structure 1. Belt 1, including flat protruding bodies 12c, is rolled into a cylinder and fitted into cylindrical case 4. Containment walls 2 form sac-like chambers 6 with the belt parallel to the path along which the finger is inserted. Folded portions 3 are found at both ends of this path. Folded portions 3 comprise outer curved segments 31 and inner curved segments 32, which are connected to outer curved segments 31. The outer curved segments 31 and the inner curved segments 32 overlap each other perpendicular to the path of the finger, i.e., toward the interior of the cuff. In this design, the rear surfaces of containment walls 2, which are connected to folded portions 3, contact with flat protruding bodies 12c. Contacting surfaces 21, which are also connected to folded portions 3, are parallel to flat protruding bodies 12c.

In a cuff for a blood pressure meter according to this embodiment, when compressed air is pumped into the chambers 6 formed by basic structure 1 and containment walls 2 via connector tube 5, folded portions 3, which are folded over toward the interior of the cuff parallel to the path of the finger, rise up. In other words, outer curved segments 31 and inner curved segments 32 assume the form of straight lines extending toward the interior of the cuff, and contacting surfaces 21 remain horizontal as they are pushed upward. Thus, containment walls 2 are not stretched and deformed. As is shown in Fig. 8, the maximum displacement L_1 when the surface of the cuff is not experiencing expansion force is equal to $2 \times L_1$. Thus, the internal pressure in the cuff will not increase because of an expansion force when the finger inserted in the cuff is thinner than average.



1 Figs. 9 and 10 are a plan view and a perspective
2 view, respectively, of a fifth embodiment of the cuff for
3 a blood pressure meter. This cuff for a blood pressure
4 meter comprises basic structure 1, which is formed from a
5 membrane, and containment walls 2, which are attached to
6 one surface of basic structure 1. On the inner portion
7 of the surface to which the containment walls are
8 attached, fitting (lower cuff) 15 anchors a number of
9 protruding bodies. Belt 1 and fitting 15 are molded
10 together. Locking device (locking tab) 13 is on one end
11 of belt 1 and lock (slit) 14 is on the other end.
12 Locking tab 13 engages with lock 14 so that the belt
13 assumes a cylindrical form. Locking tab 13 becomes
14 narrow near its base to form notches 13a. The width of
15 tab 13 between the notches is substantially equal to the
16 length of slit 14.

17 Fig. 11 is a plan view of the cuff for a blood
18 pressure meter showing a modification of locking device
19 13 and lock 14. In this embodiment, locking device 13
20 comprises a notch on the inner surface of one end of
21 structure 1, while the other end of structure 1 has a
22 notch 14 cut into the opposite side so that the two
23 notches can engage with each other.

24 In a cuff of this embodiment, basic structure 1 is
25 rolled into a cylinder, and locking device 13 is fitted
26 into lock 14. This design makes it quite simple to
27 assemble the cylindrical cuff shown in Fig. 11.
28 Additionally, this cuff can easily be fitted into the
29 actual blood pressure meter.

30 Fig. 12 shows a sixth embodiment comprising finger
31 bed 109 on cuff holder segment 102b on which a patient
32 can rest his finger after it has been inserted in the
33 cuff cylinder. This ensures that the patient's finger is
34 relaxed in order to obtain an accurate blood pressure
35 reading.

This Sheet Has Been Replaced



1 Figs. 13-15 show cuffs comprising three segments,
2 cuff main unit, cuff holder, and cuff holder segment.
3 Fig. 13 shows a basic configuration of three segments.
4 The cuff main unit 120 includes basic structure,
5 protruding bodies, and containment wall. When assembling
6 the cuff, cuff main unit 120 is inserted into cuff holder
7 121 and then attached to cuff holder segment 122.
8 Projection 122a on cuff holder segment 122 engages with
9 the slit 121a on cuff holder 121 in order to assemble the
10 cuff properly. This configuration does not show a finger
11 bed.

12 Fig. 14 is another example of a cuff comprising
13 three segments. Cuff main unit 130 has a nozzle 130a.
14 Cuff holder 131 has a slot 131a to insert the nozzle
15 130a. A stopper 131b on cuff holder 131 is also provided
16 for easy assembling. This configuration also shows a
17 finger bed 132a.

18 Fig. 15 is a modification of the cuff shown in Fig.
19 14. This example has projection 142b which engages with
20 slit 141c for easy assembling.

21 The cuff for a blood pressure meter described in the
22 first through fourth embodiments has folded portions on
23 the walls of the chambers 6 which cause the contacting
24 portions of the containment walls, which contact a
25 patient's finger, to remain parallel with respect to the
26 bottoms of the chambers when those chambers, which are
27 located between the basic structure and the containment
28 walls, are filled with compressed air.

29 The cuff for a blood pressure meter described in the
30 fifth embodiment has a locking device on one end of its
31 basic structure and a lock to receive the locking device
32 on the other end of the basic structure. Thus, a
33 cylindrical cuff can easily be formed by fitting this
34 locking device into the lock. Such a cuff can easily be
35 fitted into the actual blood pressure meter.



1 The cuff for a blood pressure meter of the sixth
2 embodiment has a finger bed. The finger bed insures that
3 the finger is relaxed in order to measure the blood
4 pressure accurately.

5 The cuff for a blood pressure meter of this
6 invention has three segments. This allows for easy
7 assembly and a shorter assembly time.

This Sheet Has Been Replaced





1 What is claimed is :

2
3 1. A cuff for a blood pressure meter, said cuff
4 comprising:

5 a belt having a plurality of protruding bodies
6 disposed on one side of said belt; and

7 at least one chamber disposed on said one side
8 of said belt for receiving compressed air and
9 accommodating said protruding bodies therein.

10
11 2. A cuff for a blood pressure meter as claimed in
12 claim 1, said cuff further comprising:

13 at least one containment wall disposed on said
14 one side of said belt, said containment wall and said
15 belt forming said chamber for receiving compressed air,
16 said containment wall having ends and a surface portion,
17 said surface portion adapted to contact a patient's
18 finger; and

19 at least a pair of folded portions, each of
20 said folded portions disposed at each end of said
21 containment wall, said folded portions causing said
22 surface portion of said containment wall to remain paral-
23 lel to surfaces of said protruding bodies when said
24 chamber formed by said belt and said containment wall is
25 filled with compressed air.

26
27 3. The cuff for a blood pressure meter as claimed
28 in claim 2, wherein said protruding bodies have flat
29 surfaces, and

30 said folded portions comprise a side fitting
31 segment, an outer curved segment, and an inner curved
32 segment,

33 wherein said outer curved segment starts at the end
34 of said side fitting segment and is folded until it is
35 parallel to said side fitting segment, and said inner
36 curved segment starts at the end of said outer curved

This Sheet Has Been Replaced





1 segment and is folded until it is parallel to said outer
2 curved segment whereby said folded portions are folded
3 back upon themselves along a line parallel to a path of
4 said flat protruding bodies.

5
6 4. The cuff for a blood pressure meter as claimed
7 in claim 3, wherein said side fitting segment is thicker
8 than said folded portions, and

9 said outer curved segment and said inner curved
10 segment are the same width as said surface portions of
11 said containment walls.

12
13 5. The cuff for a blood pressure meter as claimed
14 in claim 2, wherein each of said containment walls
15 further comprise a side fitting segment, said side
16 fitting segment mounting said containment wall to said
17 belt and being thicker than said folded portions.

18
19 6. The cuff for a blood pressure meter as claimed
20 in claim 2, wherein said belt has a concave inner
21 surface, and

22 said folded portions of said containment walls bend
23 to contact a portion of said concave inner surface.

24
25 7. The cuff for a blood pressure meter as claimed
26 in claim 2, wherein said belt is a membrane and has two
27 ends,

28 said belt having a locking device disposed on one
29 end and a lock disposed on said other end,

30 said belt and said containment walls are molded
31 together, and

32 said locking device engages with said lock whereby
33 said belt assumes a cylindrical form.

34
This Sheet Has Been Replaced





1 8. The cuff for a blood pressure meter as claimed
2 in claim 7, wherein said locking device is a tab and said
3 lock is a slit.

4
5 9. The cuff for a blood pressure meter as claimed
6 in claim 7, wherein said locking device and said lock are
7 notches.

8
9 10. The cuff for blood pressure meter as claimed in
10 claim 2, said cuff further comprising at least one
11 folding guard extending from said folded portion and
12 disposed over an end of said containment wall.

13
14 11. The cuff for blood pressure meter as claimed in
15 claim 10, wherein said folding guard is disposed over
16 said side fitting segment.

17
18 12. A cuff for blood pressure meter as claimed in
19 claim 1, said cuff further comprising means for
20 supporting a patient's finger.

21
22 13. A cuff for blood pressure meter as claimed in
23 claim 12, wherein said means for supporting a patient's
24 finger is a finger bed.

25
26 14. A cuff for blood pressure meter as claimed in
27 claim 12, wherein said means for supporting a patient's
28 finger is disposed extending from an outside edge of said
29 belt.

30
31 15. The cuff for blood pressure meter as claimed in
32 claim 2, said cuff further comprising:
33 a cuff main unit;
34 a cuff holder having a slit; and
35 a cuff holder segment having a projection,





1 wherein said cuff main unit is inserted into said
2 cuff holder, and said slit of said cuff holder engages
3 with said projection of said cuff holder segment such
4 that said cuff holder and said cuff holder segment are
5 attached whereby said cuff is assembled.
6

7 16. The cuff for blood pressure meter as claimed in
8 claim 2, said cuff further comprising:

9 a cuff main unit having a nozzle;

10 a cuff holder having a slot and a stopper; and

11 a cuff holder segment,

12 wherein said nozzle of said cuff main unit engages
13 with said slot of said cuff holder for assembling said
14 cuff.
15

16 17. The cuff for blood pressure meter as claimed in
17 claim 16, wherein said cuff holder has a slit, and said
18 cuff holder segment has a projection,

19 whereby said slit of said cuff holder engages with
20 said projection of said cuff holder segment to assemble
21 said cuff.
22
23
24
25

This Sheet Has Been Replaced

