

INFORMATION TRANSMISSION METHOD, NETWORK DEVICE, AND TERMINAL DEVICE

TECHNICAL FIELD

[0001] The present application relates to the field of communications and, in particular, to an information transmission method, a network device, and a terminal device.

BACKGROUND

[0002] In a 5G system which also may be termed as a New Radio (NR) system, multiple-beam can be used to cover different directions and regions. For downlink transmission, different downlink transmitting beams of a network device may correspond to different receiving beams of a terminal device for the best match. For example, in the case where the best receiving beam for two transmitting beams of the Transmission Reception Point (TRP for short) 1 of the network device is the beam 1 of the terminal device, the receiving performance will be poor if the terminal device uses the beam 2 to receive a signal transmitted by any one of the transmitting beams of the TRP1. Similarly, in a case where the best receiving beam for two transmitting beams of the TRP2 of the network device is the beam 2 of the terminal device, the receiving performance will be poor if the terminal device uses the beam 1 to receive a signal transmitted by any one of the transmitting beams of the TRP2. Therefore, it is desirable that an indication method can indicate a beam corresponding to a downlink transmission channel, thereby improving downlink receiving performance.

SUMMARY

[0003] Embodiments of the present application provide an information

transmission method, a network device, and a terminal device, according to which the terminal device can be notified of a beam corresponding to a downlink transmission channel, thereby improving downlink receiving performance.

[0004] In a first aspect, an information transmission method is provided, including:

5 sending, by a network device, indication information to a terminal device, where the indication information indicates a beam corresponding to a downlink transmission channel determined by the network device from multiple pieces of configuration information, the beam corresponding to the downlink transmission channel is used to transmit the downlink transmission channel, and each piece of the multiple pieces of
10 configuration information includes at least one of: information of at least one transmitting beam, information of a receiving beam corresponding to the at least one transmitting beam, and resource mapping information, where the resource mapping information indicates a resource available or unavailable for downlink transmission of the at least one transmitting beam; and transmitting, by the network device, the
15 downlink transmission channel through the beam corresponding to the downlink transmission channel.

[0005] Optionally, each piece of configuration information corresponds to one beam group, and information of each transmitting beam among the information of the at least one transmitting beam includes at least one of the following:

20 **[0006]** identification information of each transmitting beam, resource occupying information specific to each transmitting beam, and a number for each transmitting beam in the beam group corresponding to each piece of configuration information.

[0007] Optionally, the information of the receiving beam corresponding to the at least one transmitting beam includes identification information of the receiving beam
25 corresponding to the at least one transmitting beam.

[0008] Optionally, the resource mapping information includes at least one piece of data transmission resource mapping information, each piece of data transmission resource mapping information indicates a resource available or unavailable for downlink transmission of the at least one transmitting beam.

30 **[0009]** Optionally, the downlink transmission channel includes a data channel, the

beam corresponding to the downlink transmission channel includes a transmitting beam corresponding to the data channel, and the sending, by the network device, the indication information to the terminal device includes: sending, by the network device, a physical downlink control channel PDCCH to the terminal device through a beam in a first beam group, where a first indication field of the PDCCH includes the indication information, the indication information includes a number for the transmitting beam corresponding to the data channel, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the first beam group, first configuration information of the multiple pieces of configuration information corresponds to the first beam group, the first configuration information is configuration information pre-configured by the network device for the terminal device to receive the data channel.

[0010] Optionally, the method further includes: sending, by the network device, a first signaling to the terminal device, where the first signaling includes first configuration indication information, and the first configuration indication information indicates that the network device sends the data channel by using the first configuration information of the multiple pieces of configuration information.

[0011] Optionally, the first signaling is a radio resource control RRC signaling or downlink control information DCI.

[0012] Optionally, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel includes a receiving beam corresponding to the data channel, and the sending, by the network device, the indication information to the terminal device includes: sending, by the network device, a PDCCH to the terminal device through a beam in a second beam group, where a second indication field of the PDCCH includes the indication information, the indication information includes identification information of the receiving beam corresponding to the data channel, the indication information specifically indicates that the terminal device receives the data channel by using a receiving beam corresponding to the identification information.

[0013] Optionally, the downlink transmission channel includes a data channel, the

beam corresponding to the downlink transmission channel includes a transmitting beam corresponding to the data channel, and the sending, by the network device, the indication information to the terminal device includes: sending, by the network device, a PDCCH to the terminal device through a beam in a third beam group, where a third indication field of the PDCCH includes the indication information, the indication information includes a number for a beam corresponding to the data channel in a fourth beam group, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the fourth beam group, second configuration information of the multiple pieces of configuration information corresponds to the fourth beam group, the second configuration information is configuration information pre-configured by the network device for the terminal device to receive the data channel.

[0014] Optionally, the method further includes: sending, by the network device, a second signaling to the terminal device, where the second signaling includes second configuration indication information, and the second configuration indication information indicates that the network device sends the data channel by using the second configuration information of the multiple pieces of configuration information.

[0015] Optionally, the second signaling is a RRC signaling or DCI.

[0016] Optionally, as an embodiment, the method further includes: sending, by the network device, a PDCCH to the terminal device, where the PDCCH includes third configuration indication information, and the third configuration indication information indicates configuration information used by the network device for sending a data channel.

[0017] That is, the third configuration indication information indicates which piece of the multiple pieces of configuration information is used by the network device.

[0018] That is, the network device may dynamically indicate, through the PDCCH, the network device uses which piece of the multiple pieces of configuration information to send the data channel.

[0019] Optionally, the at least one data transmission resource mapping

information includes multiple pieces of data transmission resource mapping information, the method further includes: sending, by the network device, a PDCCH to the terminal device, where the PDCCH includes a fourth indication field, and the fourth indication field indicates data transmission resource mapping information used
5 by the network device for transmitting the downlink transmission channel.

[0020] That is, the fourth indication field indicates which piece of the multiple pieces of data transmission resource mapping information is used by the network device.

[0021] Optionally, the downlink transmission channel includes a data channel, the
10 beam corresponding to the downlink transmission channel includes a transmitting beam corresponding to the data channel, and the sending, by the network device, the indication information to the terminal device includes: sending, by the network device, a PDCCH to the terminal device through a beam in a fifth beam group, where a fifth indication field of the PDCCH includes the indication information, the indication
15 information includes a number for a transmitting beam corresponding to the data channel in a sixth beam group, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the sixth beam group, and the fifth beam group is a beam group associated with the sixth beam group.

20 **[0022]** Optionally, the method further includes: sending, by the network device, the multiple pieces of configuration information to the terminal device.

[0023] In a second aspect, an information transmission method is provided, including: receiving, by a terminal device, indication information sent by a network device, where the indication information indicates a beam corresponding to a
25 downlink transmission channel determined by the network device from multiple pieces of configuration information, the beam corresponding to the downlink transmission channel is used to transmit the downlink transmission channel, and each piece of the multiple pieces of configuration information includes at least one of: information of at least one transmitting beam, information of a receiving beam
30 corresponding to the at least one transmitting beam, and resource mapping

information, where the resource mapping information indicates the resource available or unavailable for downlink transmission; determining, by the terminal device, a receiving beam corresponding to the downlink transmission channel according to the indication information; and receiving, by the terminal device, the downlink
5 transmission channel through the receiving beam corresponding to the downlink transmission channel.

[0024] Optionally, each piece of configuration information corresponds to one beam group, and information of each transmitting beam among the information of the at least one transmitting beam includes at least one of the following: identification
10 information of each transmitting beam, resource occupying information specific to each transmitting beam, and a number for each transmitting beam in the beam group to which each transmitting beam belongs.

[0025] Optionally, information of the receiving beam corresponding to the at least one transmitting beam includes identification information of the receiving beam
15 corresponding to the at least one transmitting beam.

[0026] Optionally, the resource mapping information includes at least one piece of data transmission resource mapping information, each piece of data transmission resource mapping information indicates a resource available or unavailable for downlink transmission of the at least one transmitting beam.

20 **[0027]** Optionally, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel includes a transmitting beam corresponding to the data channel, and the receiving, by the terminal device, the indication information sent by the network device includes: receiving, by the terminal device, a physical downlink control channel PDCCH sent by the network device
25 through a beam in a first beam group, where a first indication field of the PDCCH includes the indication information, the indication information includes a number for the transmitting beam corresponding to the data channel, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the first beam group, first
30 configuration information of the multiple pieces of configuration information

corresponds to the first beam group, the first configuration information is configuration information pre-configured by the network device for the terminal device to receive the data channel;

5 **[0028]** the determining, by the terminal device, the receiving beam corresponding to the downlink transmission channel according to the indication information includes: determining, by the terminal device, a receiving beam corresponding to the transmitting beam according to the transmitting beam corresponding to the number; and receiving the data channel through the receiving beam corresponding to the transmitting beam.

10 **[0029]** Optionally, the method further includes: receiving, by the terminal device, a first signaling sent by the network device, where the first signaling includes first configuration indication information, and the first configuration indication information indicates that the network device sends the data channel by using the first configuration information of the multiple pieces of configuration information.

15 **[0030]** Optionally, the first signaling is a radio resource control RRC signaling or downlink control information DCI.

20 **[0031]** Optionally, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel includes a receiving beam corresponding to the data channel, and the receiving, by the terminal device, the indication information sent by the network device includes: receiving, by the terminal device, a PDCCH sent by the network device through a beam in a second beam group, where a second indication field of the PDCCH includes the indication information, the indication information includes identification information of the receiving beam corresponding to the data channel, the indication information specifically indicates
25 that the terminal device receives the data channel by using a receiving beam corresponding to the identification information.

30 **[0032]** Optionally, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel includes a transmitting beam corresponding to the data channel, and the receiving, by the terminal device, the indication information sent by the network device includes: receiving, by the terminal

device, a PDCCH sent by the network device through a beam in a third beam group, where a third indication field of the PDCCH includes the indication information, the indication information includes a number for a beam corresponding to the data channel in the fourth beam group, the indication information specifically indicates
5 that the network device sends the data channel by using the transmitting beam corresponding to the number in the fourth beam group, second configuration information of the multiple pieces of configuration information corresponds to the fourth beam group, the second configuration information is configuration information pre-configured by the network device for the terminal device to receive the data
10 channel.

[0033] The determining, by the terminal device, the receiving beam corresponding to the downlink transmission channel according to the indication information includes: determining, by the terminal device, a receiving beam corresponding to the transmitting beam according to the transmitting beam corresponding to the number;
15 and receiving the data channel through the receiving beam corresponding to the transmitting beam.

[0034] Optionally, the method further includes: receiving, by the terminal device, a second signaling sent by the network device, where the second signaling includes second configuration indication information, and the second configuration indication information indicates that the network device sends the data channel by using the
20 second configuration information of the multiple pieces of configuration information.

[0035] Optionally, the second signaling is a RRC signaling or DCI.

[0036] Optionally, the method further includes: receiving, by the terminal device, a PDCCH sent by the network device, where the PDCCH includes third configuration indication information, the third configuration indication information indicates
25 configuration information used by the network device uses for sending a data channel.

[0037] That is, the third configuration indication information indicates which piece of the multiple pieces of configuration information is used by the network device to send the data channel.

[0038] Optionally, the at least one piece of data transmission resource mapping
30

information includes multiple pieces of data transmission resource mapping information, the method further includes: receiving, by the terminal device, a PDCCH sent by the network device, where the PDCCH includes a fourth indication field, and the fourth indication field indicates data transmission resource mapping information used by the network device for transmitting the downlink transmission channel.

[0039] That is, the fourth indication field indicates which piece of the multiple pieces of data transmission resource mapping information is used by the network device.

[0040] Optionally, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel includes a transmitting beam corresponding to the data channel, and the receiving, by the terminal device, the indication information sent by the network device includes: receiving, by the terminal device, a PDCCH sent by the network device through a beam in a fifth beam group, where a fifth indication field of the PDCCH includes the indication information, the indication information includes a number for a transmitting beam corresponding to the data channel in a sixth beam group, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the sixth beam group, and the fifth beam group is a beam group associated with the sixth beam group;

[0041] the determining, by the terminal device, the receiving beam corresponding to the downlink transmission channel according to the indication information includes: determining, by the terminal device, a receiving beam corresponding to the transmitting beam according to the transmitting beam corresponding to the number; and receiving the data channel through the receiving beam corresponding to the transmitting beam.

[0042] Optionally, the method further includes: receiving, by the terminal device, the multiple pieces of configuration information sent by the network device.

[0043] In a third aspect, a network device is provided, and the network device may include a unit for performing the method in the first aspect or any alternative implementation thereof.

[0044] In a fourth aspect, a terminal device is provided, and the terminal device includes a unit for performing the method in the second aspect or any alternative implementation thereof.

[0045] In a fifth aspect, a network device is provided, including a memory, a processor, and a transceiver, where the memory is configured to store a program, the processor is configured to execute the program, and when the program is executed, the processor performs the method in the first aspect and any alternative implementation thereof based on the transceiver.

[0046] In a sixth aspect, a terminal device is provided, including a memory, a processor, and a transceiver, where the memory is configured to store a program, the processor is configured to execute the program, and when the program is executed, the processor performs the method in the second aspect and any alternative implementation thereof based on the transceiver.

[0047] In a seventh aspect, a computer readable medium is provided, where the computer readable medium is configured to store program codes for execution by a terminal device, and the program codes include instructions for performing the method in the first aspect or various implementations thereof.

[0048] In an eighth aspect, a computer readable medium is provided, where the computer readable medium is configured to store program codes for execution by a network device, and the program codes include instructions for performing the method in the second aspect or various implementations thereof.

[0049] Based on the foregoing technical solution, according to the information transmission method in the embodiments of the present application, a network device may send indication information to a terminal device, where the indication information indicates a beam corresponding to a downlink transmission channel determined by the network device from multiple pieces of configuration information, so that the network device may send the downlink transmission channel over the beam corresponding to the downlink transmission channel. After the terminal device learns that the network device sends the beam corresponding to the downlink transmission channel, the terminal device may select a corresponding receiving beam to receive the

downlink transmission channel, thereby improving downlink receiving performance.

BRIEF DESCRIPTION OF THE DRAWINGS

[0050] FIG. 1 is a schematic diagram of a communication system according to an embodiment of the present application.

5 [0051] FIG. 2 is a schematic flowchart of an information transmission method according to an embodiment of the present application.

[0052] FIG. 3 is a schematic flowchart of an information transmission method according to an embodiment of the present application.

10 [0053] FIG. 4 is a schematic block diagram of a network device according to an embodiment of the present application.

[0054] FIG. 5 is a schematic block diagram of a terminal device according to an embodiment of the present application.

[0055] FIG. 6 is a schematic block diagram of a network device according to an embodiment of the present application.

15 [0056] FIG. 7 is a schematic block diagram of a terminal device according to an embodiment of the present application.

DETAILED DESCRIPTION OF THE EMBODIMENTS

[0057] The technical solution in the embodiments of the present application will be described below with reference to the accompanying drawings in the embodiments
20 of the present application.

[0058] The technical solution in the embodiments of the present application can be applied to various communication systems, for example, a Global System of Mobile communication (“GSM” for short) system, a Code Division Multiple Access (“CDMA” for short) system, a Wideband Code Division Multiple Access (“WCDMA”
25 for short) system, a General Packet Radio Service (“GPRS” for short), a Long Term Evolution (“LTE” for short) system, an LTE Frequency Division Duplex (“FDD” for

short) system, an LTE Time Division Duplex (“TDD” for short), a Universal Mobile Telecommunication System (“UMTS” for short), a Worldwide Interoperability for Microwave Access (“WiMAX” for short) communication system, or a future 5G system.

5 **[0059]** FIG. 1 shows a wireless communication system 100 applied in an embodiment of the present application. The wireless communication system 100 may include a network device 110. The network device 100 may be a device that communicates with a terminal device. The network device 100 may provide a particular geographic area with communication coverage and may communicate with
10 terminal devices (e.g., UE) located within the coverage. Optionally, the network device 100 may be a base station (Base Transceiver Station, BTS) in the GSM system or the CDMA system, or a base station (NodeB, NB) in the WCDMA system, or an evolved base station (Evolutional Node B, eNB or eNodeB) in the LTE system, or a wireless controller in a Cloud Radio Access Network (CRAN), alternatively, the
15 network device can be a relay station, an access point, a vehicle-mounted device, a wearable device, a network side device in a future 5G network or a network device in a future evolutionary Public Land Mobile Network (PLMN).

[0060] The wireless communication system 100 also includes at least one terminal device 120 located within the coverage of the network device 110. The terminal
20 device 120 can be mobile or fixed. Optionally, the terminal device 120 may refer to an access terminal, User Equipment (UE), a subscriber unit, a subscriber station, a mobile station, a mobile platform, a remote station, a remote terminal, a mobile device, a user terminal, a terminal, a wireless communication device, a user agent, or a user device. The access terminal may be a cellular phone, a cordless phone, a Session
25 Initiation Protocol (SIP) phone, a Wireless Local Loop (WLL) station, a Personal Digital Assistant (PDA), a handheld device with wireless communication functions, a computing device or other processing devices connected to a wireless modem, a vehicle-mounted device, a wearable device, a terminal device in the future 5G network, or a terminal device in the future evolutionary PLMN.

30 **[0061]** Optionally, the 5G system or network may also be referred to as a New

Radio (NR) system or network.

[0062] FIG. 1 exemplarily shows one network device and two terminal devices. Optionally, the wireless communication system 100 may include a plurality of network devices and other numbers of terminal devices may be included within the coverage of each network device, which is not limited in the embodiment of the present application.

[0063] Optionally, the wireless communication system 100 may further include other network entities, such as a network controller, a mobility management entity, and the like, which is not limited in the embodiment of the present application.

10 [0064] It should be understood that the terms such as “system” and “network” are used interchangeably herein. The term such as “and/or” herein is merely used to describe an association between associated objects, indicating that there may be three relationships, for example, A and/or B may indicate three situations that A exists separately, both A and B exist, B exists separately. In addition, the character “/” herein generally indicates that contextual objects are in an “or” relationship.

[0065] FIG. 2 is a schematic flowchart of an information transmission method 200 according to an embodiment of the present application. As shown in FIG. 2, the method 200 includes:

[0066] S201, a network device sends indication information to a terminal device, where the indication information indicates a beam corresponding to a downlink transmission channel determined by the network device from multiple pieces of configuration information, the beam corresponding to the downlink transmission channel is used to transmit the downlink transmission channel, and each piece of the multiple pieces of configuration information includes at least one of: information of at least one transmitting beam, information of a receiving beam corresponding to the at least one transmitting beam, and resource mapping information, where the resource mapping information indicates a resource available or unavailable for downlink transmission of the at least one transmitting beam; and

[0067] S202, the network device transmits the downlink transmission channel through the beam corresponding to the downlink transmission channel.

[0068] Specifically, a network device may send indication information to a terminal device, where the indication information indicates a beam corresponding to a downlink transmission channel determined by the network device from the multiple pieces of configuration information, so that the network device may send the downlink transmission channel over the beam corresponding to the downlink transmission channel. After learning that the network device sends the beam corresponding to the downlink transmission channel, the terminal device may select a corresponding receiving beam to receive the downlink transmission channel. Therefore, it is possible to avoid the problem that there is poor receiving performance resulting from mismatch of the transmitting beam of the network device and the receiving beam of the terminal device.

[0069] Optionally, each piece of the configuration information corresponds to one beam group, and information of each transmitting beam among the information of the at least one transmitting beam includes at least one of the following:

[0070] identification information of each transmitting beam, resource occupying information specific to each transmitting beam, and a number for each transmitting beam in the beam group corresponding to each piece of configuration information.

[0071] The resource occupying information specific to each transmitting beam may indicate information of a temporarily occupied time domain resource and/or frequency domain resource of each transmitting beam, for example, a first beam is temporarily used for a certain period to send a measurement signal, therefore, during this period, the first beam cannot be used for transmitting data, so that the terminal device may not receive the data during this period.

[0072] Optionally, the information of the receiving beam corresponding to the at least one transmitting beam includes identification information of the receiving beam corresponding to the at least one transmitting beam.

[0073] Optionally, the resource mapping information includes at least one piece of data transmission resource mapping information, each piece of data transmission resource mapping information indicates a resource available or unavailable for downlink transmission of the at least one transmitting beam.

[0074] It should be understood that each piece of data transmission resource mapping information may be a piece of data transmission resource mapping information for the entire beam group, at this point, each transmitting beam in the beam group has the same data transmission resource mapping information, or may be
5 a piece of data transmission resource mapping information for each transmitting beam.

[0075] Optionally, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel includes a transmitting beam corresponding to the data channel, and the sending, by the network device, the
10 indication information to the terminal device includes:

[0076] sending, by the network device, a physical downlink control channel PDCCH to the terminal device through a beam in a first beam group, where a first indication field of the PDCCH includes the indication information, the indication information includes a number for the transmitting beam corresponding to the data
15 channel, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the first beam group, first configuration information of the multiple pieces of configuration information corresponds to the first beam group, the first configuration information is configuration information pre-configured by the network device for the
20 terminal device to receive the data channel.

[0077] Specifically, in this embodiment, the network device sends a control channel and a data channel through beams in the same beam group, and the network device may notify the terminal device in advance that the network device uses first configuration information of the multiple pieces of configuration information to send
25 the data channel, where the first configuration information is corresponding to the first beam group, and then the network device may send a Physical Downlink Control Channel (PDCCH for short) through a beam in a first beam group, and notify the terminal device, through a case that a first indication field of the PDCCH includes a number for the transmitting beam corresponding to the data channel, that the network
30 device sends the data channel by using the transmitting beam corresponding to the

number in the first beam group, so that the terminal device may determine a corresponding receiving beam according to the transmitting beam and then receives the data channel by using the receiving beam

[0078] In other words, in this embodiment, the network device may not need to notify the terminal device every time which piece of configuration information is used by the network device, after the network device notifies the terminal device which piece of configuration information is used by the network device, if the network device does not change the configuration information, the terminal device considers that the network device uses the configuration information. Also, by sending the PDCCH, the terminal device may be notified a transmitting beam corresponding to which number from the configuration information is used by the network device to send the data channel.

[0079] Optionally, the method further includes:

[0080] sending, by the network device, a first signaling to the terminal device, where the first signaling includes first configuration indication information, and the first configuration indication information indicates that the network device sends the data channel by using the first configuration information of the multiple pieces of configuration information.

[0081] That is, by sending the first signaling to the terminal device and including the first configuration indication information in the first signaling, the network device may indicate which piece of configuration information is used by the network device. For the foregoing embodiment, by sending the first signaling, the network device may notify the terminal device that the network device sends the data channel by using the first configuration information, and before the network device changes the configuration, the terminal device always considers that the network device sends the data channel by using the first configuration information. By sending the PDCCH, the terminal device may be notified a transmitting beam corresponding to which number from the first configuration information is used by the network device to send the data channel.

[0082] That is, the network device may semi-statically configure the transmitting

beam corresponding to the data channel of the network device, firstly it is pre-configured through high-layer signaling that a transmitting beam in which piece of configuration information is used, and then it is dynamically indicated, through the PDCCH, a transmitting beam corresponding to which number from the configuration information is used.

[0083] Optionally, the first signaling is Radio Resource Control (RRC for short) signaling or downlink control information (DCI for short).

[0084] In general, the network device sends both a control channel and a data channel by using beams in the first beam group, and the network device pre-configures that the first configuration information is used to send the data channel, that is, a transmitting beam in the first beam group is used to send the data channel, the network device may send a PDCCH by using the beam in the first beam group, and dynamically indicate, through indication information in the PDCCH, a transmitting beam of which number in the first beam group is specifically used.

[0085] For example, the multiple pieces of configuration information include two pieces of configuration information, as follows:

[0086] Beam group 1, including a transmitting beam B1 and a transmitting beam B2, and intra-group numbers are 0 and 1, respectively;

[0087] Beam group 2, including a transmitting beam B2, a transmitting beam B3, and a transmitting beam B4, and intra-group numbers are 0, 1, and 2, respectively.

[0088] If the network device pre-configures that a beam in the beam group 1 is used to send the data channel, the terminal device receives a PDCCH from B1, and if a first indication field of the PDCCH may include 1 bit, the 1 bit may be indicated as follows:

[0089] 0, indicating that the transmitting beam used by the data channel is the transmitting beam B1;

[0090] 1, indicating that the transmitting beam used by the data channel is the transmitting beam B2.

[0091] Or, if the network device pre-configures that a beam in the beam group 2 is used to send the data channel, the terminal device receives a PDCCH from B3, and if

a first indication field of the PDCCH may include 2 bits, the 2 bits may be indicated as follows:

[0092] 0, indicating that the transmitting beam used by the data channel is the transmitting beam B2;

5 **[0093]** 1, indicating that the transmitting beam used by the data channel is the transmitting beam B3;

[0094] 2, indicating that the transmitting beam used by the data channel is the transmitting beam B4.

10 **[0095]** Optionally, as another embodiment, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel includes a receiving beam corresponding to the data channel, and the sending, by the network device, the indication information to the terminal device includes:

[0096] sending, by the network device, a PDCCH to the terminal device through a beam in a second beam group, where a second indication field of the PDCCH includes the indication information, the indication information includes identification information of the receiving beam corresponding to the data channel, the indication information specifically indicates that the terminal device receives the data channel by using a receiving beam corresponding to the identification information.

20 **[0097]** Specifically, the network device may send a PDCCH to the terminal device through a beam in the second beam group, through the case that a second indication field of the PDCCH includes the indication information, the indication information directly indicates that the terminal device receives a receiving beam corresponding to the data channel, such that the terminal device may receive the data channel by using the receiving beam corresponding to the data channel.

25 **[0098]** For example, the multiple pieces of configuration information include two pieces of configuration information, as follows:

[0099] Beam group 1, a receiving beam Beam1, and one piece of data transmission resource mapping information;

30 **[0100]** Beam group 2, a receiving beam Beam2, and one piece of data transmission resource mapping information.

[0101] The terminal device receives a PDCCH sent by the network device, if an indication field of the PDCCH can be indicated as follows:

[0102] 0, indicating configuration information of the beam group 1;

[0103] 1, indicating configuration information of the beam group 1.

5 **[0104]** In this embodiment, each piece of configuration information corresponds to one receiving beam and one piece of data transmission resource mapping information, so the determination of which piece of configuration information to use is equivalent to the determination of which receiving beam and which piece of data transmission resource mapping information to use.

10 **[0105]** Optionally, as another embodiment, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel includes a transmitting beam corresponding to the data channel, and the sending, by the network device, the indication information to the terminal device includes:

[0106] sending, by the network device, a PDCCH to the terminal device through a
15 beam in a third beam group, where a third indication field of the PDCCH includes the indication information, the indication information includes a number for a transmitting beam corresponding to the data channel in a fourth beam group, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the fourth
20 beam group, second configuration information of the multiple pieces of configuration information corresponds to the fourth beam group, the second configuration information is configuration information pre-configured by the network device for the terminal device to receive the data channel.

[0107] In this embodiment, the network device sends a control channel and a data
25 channel through beams in different beam groups, for example, the network device sends the control channel by using a beam in a third beam group, and sends the data channel by using a beam in a fourth beam group. The network device may notify the terminal device in advance that the network device sends the data channel by using second configuration information of the multiple pieces of configuration information,
30 where the second configuration information corresponds to the fourth beam group,

and then the network device may send a PDCCH through the beam in the third beam group, and notify the terminal device, through a case that a third indication field of the PDCCH includes a number for a transmitting beam corresponding to the data channel, that the network device sends the data channel by using the transmitting beam
5 corresponding to the number in the fourth beam group, so that the terminal device may determine a corresponding receiving beam according to the transmitting beam, and then receive the data channel by using the receiving beam.

[0108] Optionally, the method for the network device to notify the terminal device in advance which piece of configuration information is used by the network device
10 may include:

[0109] sending, by the network device, a second signaling to the terminal device, where the second signaling includes second configuration indication information, and the second configuration indication information indicates that the network device sends the data channel by using the second configuration information of the multiple
15 pieces of configuration information.

[0110] Optionally, the second signaling is a RRC signaling or DCI.

[0111] Different from the foregoing embodiments, the network device sends a control channel and a data channel by using beams in different beam groups, and the network device pre-configures that second configuration information is used to send
20 the data channel, that is, a transmitting beam in a fourth beam group is used to send the data channel, the network device may send a PDCCH by using a beam in a third beam group, and dynamically indicate, through indication information in the PDCCH, a transmitting beam of which number in the fourth beam group is specifically used.

[0112] For example, the multiple pieces of configuration information include two
25 pieces of configuration information, as follows:

[0113] Beam group 1, including a transmitting beam B1 and a transmitting beam B2, and intra-group numbers are 0 and 1, respectively;

[0114] Beam group 2, including a transmitting beam B2, a transmitting beam B3, and a transmitting beam B4, and intra-group numbers are 0, 1, and 2, respectively.

[0115] The network device pre-configures that a beam in the beam group 1 is used
30

to send the data transmission channel, and the terminal device receives a PDCCH from B3. If a third indication field of the PDCCH may include 1 bit, the 1 bit may be indicated as follows:

5 [0116] 0, indicating that the transmitting beam used by the data channel is the transmitting beam B1;

[0117] 1, indicating that the transmitting beam used by the data channel is the transmitting beam B2.

[0118] Optionally, as an embodiment, the method further includes:

10 [0119] sending, by the network device, a PDCCH to the terminal device, where the PDCCH includes third configuration indication information, and the third configuration indication information indicates configuration information used by the network device for sending a data channel.

[0120] That is, the third configuration indication information may indicate which piece of the multiple pieces of configuration information is used by the network device for sending the data channel.

[0121] That is, the network device may dynamically indicate, through the PDCCH, the network device uses which piece of the multiple pieces of configuration information to send the data channel.

20 [0122] Optionally, the at least one data transmission resource mapping information includes multiple pieces of data transmission resource mapping information, the method further includes:

[0123] sending, by the network device, a PDCCH to the terminal device, where the PDCCH includes a fourth indication field, and the fourth indication field indicates data transmission resource mapping information used by the network device for transmitting the downlink transmission channel.

[0124] That is, the fourth indication field indicates which piece of the multiple pieces of data transmission resource mapping information is used by the network device.

30 [0125] Specifically, each piece of configuration information may further include multiple pieces of data transmission resource mapping information, where each piece

of data transmission resource mapping information may indicate a resource available or unavailable for downlink transmission of each transmitting beam, and the network device may notify the terminal device, through a fourth indication field of the PDCCH, which piece of the multiple pieces of data transmission resource mapping information is used by the network device, so that the terminal device receives data according to the indicated data transmission resource mapping information. For example, the data transmission resource mapping information indicates a resource unavailable for downlink transmission, the terminal device may not perform data reception on the resource, and thus it is possible to saving time-frequency resources of the terminal device.

[0126] For example, the multiple pieces of configuration information include two pieces of configuration information, as follows:

[0127] Beam group 1, a receiving beam Beam1, four pieces of data transmission resource mapping information;

[0128] Beam group 2, a receiving beam Beam2, four pieces of data transmission resource mapping information.

[0129] The network device pre-configures that configuration information of the beam group 1 is used, and the terminal device receives a PDCCH. If an indication field of the PDCCH may include 1 bit, the 1 bit may be indicated as follows:

[0130] 0, indicating that the data channel uses the first piece of data transmission resource mapping information;

[0131] 1, indicating that the data channel uses the second piece of data transmission resource mapping information;

[0132] 2, indicating that the data channel uses the third piece of data transmission resource mapping information;

[0133] 3, indicating that the data channel uses the fourth piece of data transmission resource mapping information.

[0134] Optionally, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel includes a transmitting beam corresponding to the data channel, and the sending, by the network device, the

indication information to the terminal device includes:

[0135] sending, by the network device, a PDCCH to the terminal device through a beam in a fifth beam group, where a fifth indication field of the PDCCH includes the indication information, the indication information includes a number for a transmitting beam corresponding to the data channel in a sixth beam group, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the sixth beam group, and the fifth beam group is a beam group associated with the sixth beam group.

[0136] Specifically, the fifth beam group and the sixth beam group may be associated beam groups, for example, the network device uses beams in the fifth and sixth beam groups to perform the same service. The network device may send a PDCCH through a beam in the fifth beam group, and indicate, through a case that the indication information is included in the fifth indication field of the PDCCH, a number for a transmitting beam corresponding to the data channel in a sixth beam group, so that the terminal device may determine that the network device sends the data channel by using the transmitting beam corresponding to the number in the sixth beam group, and then the terminal device may determine a receiving beam corresponding to the transmitting beam, and then receive the data channel by using the receiving beam.

[0137] Optionally, the method further includes:

[0138] the network device sends the multiple pieces of configuration information to the terminal device.

[0139] The information transmission method according to the embodiment of the present application is described above in detail from the perspective of the network device with reference to FIG. 2, and an information transmission method according to an embodiment of the present application is described below in detail from the perspective of a terminal device with reference to FIG. 3. It should be understood that the description on the terminal device side corresponds to the description on the network device side. For a similar description, reference may be made to the above, and will not be described herein again to avoid repetition.

[0140] FIG. 3 is a schematic flowchart of an information transmission method 300 according to an embodiment of the present application. As shown in FIG. 3, the method 300 includes the following:

[0141] S301, a terminal device receives indication information sent by a network device, where the indication information indicates a beam corresponding to a downlink transmission channel determined by the network device from multiple pieces of configuration information, the beam corresponding to the downlink transmission channel is used to transmit the downlink transmission channel, and each piece of the multiple pieces of configuration information includes at least one of:
information of at least one transmitting beam, information of a receiving beam corresponding to the at least one transmitting beam, and resource mapping information, where the resource mapping information indicates a resource available or unavailable for downlink transmission;

[0142] S302, the terminal device determines a receiving beam corresponding to the downlink transmission channel according to the indication information; and

[0143] S303, the terminal device receives the downlink transmission channel through the receiving beam corresponding to the downlink transmission channel.

[0144] Specifically, the terminal device may receive indication information sent by the network device, where the indication information indicates a beam corresponding to a downlink transmission channel determined by the network device from the multiple pieces of configuration information, and optionally, the beam corresponding to the downlink transmission channel is a transmitting beam or a receiving beam, and the terminal device may then determine, according to the indication information, a receiving beam corresponding to the downlink transmission channel, for example, if the beam corresponding to the downlink transmission channel is a transmitting beam corresponding to the downlink transmission channel, the terminal device may determine a receiving beam corresponding to the transmitting beam, and then the receiving beam is used to receive the downlink transmission channel. Alternatively, if the beam corresponding to the downlink transmission channel is a receiving beam corresponding to the downlink transmission channel, the

terminal device may directly receive the downlink transmission channel by using the receiving beam corresponding to the downlink transmission channel.

[0145] Optionally, each piece of configuration information corresponds to one beam group, and information of each transmitting beam among the information of the at least one transmitting beam includes at least one of the following:

[0146] identification information of each transmitting beam, resource occupying information specific to each transmitting beam, and a number for each transmitting beam in the beam group corresponding to each piece of configuration information.

[0147] Optionally, the information of the receiving beam corresponding to the at least one transmitting beam includes identification information of the receiving beam corresponding to the at least one transmitting beam.

[0148] Optionally, the resource mapping information includes at least one piece of data transmission resource mapping information, where each piece of data transmission resource mapping information indicates a resource available or unavailable for downlink transmission of the at least one transmitting beam.

[0149] Optionally, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel includes a transmitting beam corresponding to the data channel, and the receiving, by the terminal device, the indication information sent by the network device includes:

[0150] receiving, by the terminal device, a physical downlink control channel PDCCH sent by the network device through a beam in a first beam group, where a first indication field of the PDCCH includes the indication information, the indication information includes a number for the transmitting beam corresponding to the data channel, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the first beam group, first configuration information of the multiple pieces of configuration information corresponds to the first beam group, the first configuration information is configuration information pre-configured by the network device for the terminal device to receive the data channel;

[0151] the determining, by the terminal device, the receiving beam corresponding

to the downlink transmission channel according to the indication information includes:

[0152] determining, by the terminal device, a receiving beam corresponding to the transmitting beam according to the transmitting beam corresponding to the number;

5 and

[0153] receiving the data channel through the receiving beam corresponding to the transmitting beam.

[0154] Specifically, in this embodiment, the network device sends a control channel and a data channel by using beams in the same beam group, and the terminal device defaults that the network device sends the data channel using first configuration information of the multiple pieces of configuration information, where the first configuration information corresponds to the first beam group. The indication information includes a number for a transmitting beam corresponding to the data channel, the terminal device receives a PDCCH that is sent by the network device using a beam in the first beam group, and the terminal device is notified, through a case that a first indication field of the PDCCH includes the indication information, that the network device sends the data channel using the transmitting beam corresponding to the number in the first beam group, so that the terminal device may determine a corresponding receiving beam according to the transmitting beam, and then receive the data channel using the receiving beam.

10
15
20

[0155] Optionally, the method further includes:

[0156] receiving, by the terminal device, a first signaling sent by the network device, where the first signaling includes first configuration indication information, and the first configuration indication information indicates that the network device sends the data channel by using the first configuration information of the multiple pieces of configuration information.

25

[0157] That is, the network device may notify the terminal device, through the first signaling, which piece of the multiple pieces of configuration information is used by the network device. Optionally, the first signaling is a radio resource control RRC signaling or downlink control information DCI.

30

[0158] That is, the network device may semi-statically configure the transmitting beam corresponding to the data channel of the network device, firstly it is pre-configured through high-layer signaling that a transmitting beam in which piece of configuration information is used, and then it is dynamically indicated, through the PDCCH, a transmitting beam corresponding to which number from the configuration information is used.

[0159] Optionally, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel includes a receiving beam corresponding to the data channel, and the receiving, by the terminal device, the indication information sent by the network device includes:

[0160] receiving, by the terminal device, a PDCCH sent by the network device through a beam in a second beam group, where a second indication field of the PDCCH includes the indication information, the indication information includes identification information of the receiving beam corresponding to the data channel, the indication information specifically indicates that the terminal device receives the data channel by using a receiving beam corresponding to the identification information.

[0161] In this embodiment, the terminal device may receive a PDCCH that is sent by the network device using a beam in a second beam group, and through a case that a second indication field of the PDCCH includes the indication information, the indication information indicates that the terminal device receives a receiving beam corresponding to the data channel, so that the terminal device can directly receive the data channel by using the receiving beam corresponding to the data channel.

[0162] Optionally, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel includes a transmitting beam corresponding to the data channel, and the receiving, by the terminal device, the indication information sent by the network device includes:

[0163] receiving, by the terminal device, a PDCCH sent by the network device through a beam in a third beam group, where a third indication field of the PDCCH includes the indication information, the indication information includes a number for

a transmitting beam corresponding to the data channel in a fourth beam group, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the fourth beam group, second configuration information of the multiple pieces of configuration information corresponds to the fourth beam group, the second configuration information is configuration information pre-configured by the network device for the terminal device to receive the data channel;

[0164] the determining, by the terminal device, the receiving beam corresponding to the downlink transmission channel according to the indication information includes:

[0165] determining, by the terminal device, a receiving beam corresponding to the transmitting beam according to the transmitting beam corresponding to the number; and

[0166] receiving the data channel through the receiving beam corresponding to the transmitting beam.

[0167] In this embodiment, the network device notifies the terminal device in advance that the network device sends a PDCCH through a beam in a third beam group, and sends a data channel through a beam in a fourth beam group, that is, the network device sends the data channel and the control channel by using beams in different beam groups, so that the terminal device receives the PDCCH sent by the network device through the beam in the third beam group, and then determines, according to the indication information included in the third indication field in the PDCCH, the network device uses which beam in the fourth group to send the data channel.

[0168] Optionally, as an embodiment, the method further includes:

[0169] receiving, by the terminal device, a second signaling sent by the network device, where the second signaling includes second configuration indication information, and the second configuration indication information indicates that the network device sends the data channel by using the second configuration information of the multiple pieces of configuration information.

[0170] That is to say, by sending second signaling, the network device may notify the terminal device in advance which group of configuration information is used by the network device to send the data channel. Optionally, the second signaling is a RRC signaling or DCI.

5 **[0171]** Optionally, as an embodiment, the method further includes:

[0172] receiving, by the terminal device, a PDCCH sent by the network device, where the PDCCH includes third configuration indication information, and the third configuration indication information indicates configuration information used by the network device for sending a data channel.

10 **[0173]** That is, the third configuration indication information indicates which piece of the multiple pieces of configuration information is used by the network device to send the data channel.

[0174] That is to say, the network device may dynamically indicate, through the third configuration indication information in the PDCCH, which piece of the multiple
15 pieces of configuration information is used by the network device to send the data channel.

[0175] Optionally, the at least one piece of data transmission resource mapping information includes multiple pieces of data transmission resource mapping information, the method further includes:

20 **[0176]** receiving, by the terminal device, a PDCCH sent by the network device, where the PDCCH includes a fourth indication field, and the fourth indication field indicates data transmission resource mapping information used by the network device for transmitting the downlink transmission channel.

[0177] That is, the fourth indication field indicates which piece of the multiple
25 pieces of data transmission resource mapping information is used by the network device.

[0178] Optionally, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel includes a transmitting beam corresponding to the data channel, and the receiving, by the terminal device, the
30 indication information sent by the network device includes:

[0179] receiving, by the terminal device, a PDCCH sent by the network device through a beam in a fifth beam group, where a fifth indication field of the PDCCH includes the indication information, the indication information includes a number for a transmitting beam corresponding to the data channel in a sixth beam group, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the sixth beam group, and the fifth beam group is a beam group associated with the sixth beam group;

[0180] the determining, by the terminal device, the receiving beam corresponding to the downlink transmission channel according to the indication information includes:

[0181] determining, by the terminal device, a receiving beam corresponding to the transmitting beam according to the transmitting beam corresponding to the number; and

[0182] receiving the data channel through the receiving beam corresponding to the transmitting beam.

[0183] Optionally, the method further includes:

[0184] receiving, by the terminal device, the multiple pieces of configuration information sent by the network device.

[0185] The method embodiments of the present application are described in detail above with reference to FIG. 2 and FIG. 3, and device embodiments of the present application will be described in detail below with reference to FIG. 4 to FIG. 7. It should be understood that the device embodiments correspond to the method embodiments, for a similar description, reference may be made to the method embodiments.

[0186] FIG. 4 is a schematic block diagram of a network device according to an embodiment of the present invention. The network device 400 of FIG. 4 includes a transceiving unit 410.

[0187] The transceiving unit 410 is configured to: send indication information to a terminal device, where the indication information indicates a beam corresponding to a

downlink transmission channel determined by the network device from multiple pieces of configuration information, the beam corresponding to the downlink transmission channel is used to transmit the downlink transmission channel, and each piece of the multiple pieces of configuration information includes at least one of:

- 5 information of at least one transmitting beam, information of a receiving beam corresponding to the at least one transmitting beam, and resource mapping information, where the resource mapping information indicates a resource available or unavailable for downlink transmission of the at least one transmitting beam; and transmit the downlink transmission channel through the beam corresponding to the
10 downlink transmission channel.

[0188] Optionally, in some embodiments, each piece of configuration information corresponds to one beam group, and information of each transmitting beam among the information of the at least one transmitting beam includes at least one of the following:

- 15 **[0189]** identification information of each transmitting beam, resource occupying information specific to each transmitting beam, and a number for each transmitting beam in the beam group corresponding to each piece of configuration information.

- [0190]** Optionally, in some embodiments, the information of the receiving beam corresponding to the at least one transmitting beam includes identification information
20 of the receiving beam corresponding to the at least one transmitting beam.

- [0191]** Optionally, in some embodiments, the resource mapping information includes at least one piece of data transmission resource mapping information, each piece of data transmission resource mapping information indicates a resource available or unavailable for downlink transmission of the at least one transmitting
25 beam.

[0192] Optionally, in some embodiments, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel includes a transmitting beam corresponding to the data channel, and the transceiving unit 410 is further configured to:

- 30 **[0193]** send a physical downlink control channel PDCCH to the terminal device

through a beam in a first beam group, where a first indication field of the PDCCH includes the indication information, the indication information includes a number for the transmitting beam corresponding to the data channel, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the first beam group, first configuration information of the multiple pieces of configuration information corresponds to the first beam group, the first configuration information is configuration information pre-configured by the network device for the terminal device to receive the data channel.

10 **[0194]** Optionally, in some embodiments, the transceiving unit 410 is further configured to:

[0195] send a first signaling to the terminal device, where the first signaling includes first configuration indication information, and the first configuration indication information indicates that the network device sends the data channel by using the first configuration information of the multiple pieces of configuration information.

[0196] Optionally, in some embodiments, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel includes a receiving beam corresponding to the data channel, and the transceiving unit 410 is further configured to:

[0197] send a PDCCH to the terminal device through a beam in a second beam group, where a second indication field of the PDCCH includes the indication information, the indication information includes identification information of the receiving beam corresponding to the data channel, the indication information specifically indicates that the terminal device receives the data channel by using a receiving beam corresponding to the identification information.

[0198] Optionally, in some embodiments, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel includes a transmitting beam corresponding to the data channel, and the transceiving unit 410 is further configured to:

[0199] send a PDCCH to the terminal device through a beam in a third beam group, where a third indication field of the PDCCH includes the indication information, the indication information includes a number for a transmitting beam corresponding to the data channel in a fourth beam group, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the fourth beam group, second configuration information of the multiple pieces of configuration information corresponds to the fourth beam group, the second configuration information is configuration information pre-configured by the network device for the terminal device to receive the data channel.

[0200] Optionally, in some embodiments, the transceiving unit 410 is further configured to:

[0201] send a second signaling to the terminal device, where the second signaling includes second configuration indication information, and the second configuration indication information indicates that the network device sends the data channel by using the second configuration information of the multiple pieces of configuration information.

[0202] Optionally, in some embodiments, the second signaling is a RRC signaling or DCI.

[0203] Optionally, in some embodiments, the transceiving unit 410 is further configured to:

[0204] send a PDCCH to the terminal device, where the PDCCH includes third configuration indication information, and the third configuration indication information indicates configuration information used by the network device for sending a data channel.

[0205] That is, the third configuration indication information indicates which piece of the multiple pieces of configuration information is used by the network device to send the data channel.

[0206] Optionally, in some embodiments, the at least one piece of data transmission resource mapping information includes multiple pieces of data

transmission resource mapping information, and the transceiving unit 410 is further configured to:

5 [0207] send a PDCCH to the terminal device, where the PDCCH includes a fourth indication field, and the fourth indication field indicates data transmission resource mapping information used by the network device for transmitting the downlink transmission channel.

[0208] That is, the fourth indication field indicates which piece of the multiple pieces of data transmission resource mapping information is used by the network device.

10 [0209] Optionally, in some embodiments, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel includes a transmitting beam corresponding to the data channel, and the transceiving unit 410 is further configured to:

[0210] send a PDCCH to the terminal device through a beam in a fifth beam group, where a fifth indication field of the PDCCH includes the indication information, the indication information includes a number for a transmitting beam corresponding to the data channel in a sixth beam group, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the sixth beam group, and the fifth beam group is a beam group associated with the sixth beam group.

[0211] Optionally, in some embodiments, the transceiving unit 410 is further configured to:

[0212] send the multiple pieces of configuration information to the terminal device.

25 [0213] It should be understood that the network device 400 may correspond to the network device in the method 200, and corresponding functions of the network device may be implemented and are not described herein again for brevity.

[0214] FIG. 5 is a schematic block diagram of a terminal device according to an embodiment of the present application. The terminal device 500 of FIG. 5 includes:

30 [0215] a receiving unit 510, configured to receive indication information sent by a

network device, where the indication information indicates a beam corresponding to a downlink transmission channel determined by the network device from multiple pieces of configuration information, the beam corresponding to the downlink transmission channel is used to transmit the downlink transmission channel, and each
5 piece of the multiple pieces of configuration information includes at least one of: information of at least one transmitting beam, information of a receiving beam corresponding to the at least one transmitting beam, and resource mapping information, where the resource mapping information indicates the resource available or unavailable for downlink transmission; and

10 **[0216]** a determining unit 520, configured to determine a receiving beam corresponding to the downlink transmission channel according to the indication information;

[0217] the receiving unit 510 is further configured to: receive the downlink transmission channel through the receiving beam corresponding to the downlink
15 transmission channel.

[0218] Optionally, in some embodiments, each piece of configuration information corresponds to one beam group, and information of each transmitting beam among the information of the at least one transmitting beam includes at least one of the following:

20 **[0219]** identification information of each transmitting beam, resource occupying information specific to each transmitting beam, and a number for each transmitting beam in the beam group to which each transmitting beam belongs.

[0220] Optionally, in some embodiments, the information of the receiving beam corresponding to the at least one transmitting beam includes identification information
25 of the receiving beam corresponding to the at least one transmitting beam.

[0221] Optionally, in some embodiments, the resource mapping information includes at least one piece of data transmission resource mapping information, each piece of data transmission resource mapping information indicates a resource available or unavailable for downlink transmission of the at least one transmitting
30 beam.

[0222] Optionally, in some embodiments, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel includes a transmitting beam corresponding to the data channel, and the receiving unit 510 is further configured to:

5 **[0223]** receive a physical downlink control channel PDCCH sent by the network device through a beam in a first beam group, where a first indication field of the PDCCH includes the indication information, the indication information includes a number for the transmitting beam corresponding to the data channel, the indication information specifically indicates that the network device sends the data channel by
10 using the transmitting beam corresponding to the number in the first beam group, first configuration information of the multiple pieces of configuration information corresponds to the first beam group, the first configuration information is configuration information pre-configured by the network device for the terminal device to receive the data channel;

15 **[0224]** the determining unit 520 is specifically configured to:

[0225] determine a receiving beam corresponding to the transmitting beam according to the transmitting beam corresponding to the number;

[0226] the receiving unit 510 is specifically configured to:

[0227] receive the data channel through the receiving beam corresponding to the
20 transmitting beam.

[0228] Optionally, in some embodiments, the receiving unit 510 is further configured to:

[0229] receive a first signaling sent by the network device, where the first signaling includes first configuration indication information, and the first
25 configuration indication information indicates that the network device sends the data channel by using the first configuration information of the multiple pieces of configuration information.

[0230] Optionally, in some embodiments, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel
30 includes a receiving beam corresponding to the data channel, and the receiving unit

510 is further configured to:

[0231] receive a PDCCH sent by the network device through a beam in a second beam group, where a second indication field of the PDCCH includes the indication information, the indication information includes identification information of the receiving beam corresponding to the data channel, the indication information specifically indicates that the terminal device receives the data channel by using a receiving beam corresponding to the identification information.

[0232] Optionally, in some embodiments, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel includes a transmitting beam corresponding to the data channel, and the receiving unit 510 is further configured to:

[0233] receive a PDCCH sent by the network device through a beam in a third beam group, where a third indication field of the PDCCH includes the indication information, the indication information includes a number for a transmitting beam corresponding to the data channel in a fourth beam group, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the fourth beam group, second configuration information of the multiple pieces of configuration information corresponds to the fourth beam group, the second configuration information is configuration information pre-configured by the network device for the terminal device to receive the data channel.

[0234] Optionally, in some embodiments, the receiving unit 510 is further configured to:

[0235] receive a second signaling sent by the network device, where the second signaling includes second configuration indication information, and the second configuration indication information indicates that the network device sends the data channel by using the second configuration information of the multiple pieces of configuration information.

[0236] Optionally, in some embodiments, the second signaling is a RRC signaling or DCI.

[0237] Optionally, in some embodiments, the transceiving unit is further configured to:

[0238] receive a PDCCH sent by the network device, where the PDCCH includes third configuration indication information, and the third configuration indication information indicates configuration information used by the network device for sending a data channel.

[0239] That is, the third configuration indication information indicates which piece of the multiple pieces of configuration information is used by the network device to send the data channel.

10 [0240] Optionally, in some embodiments, the at least one piece of data transmission resource mapping information includes multiple pieces of data transmission resource mapping information, and the receiving unit 510 is further configured to:

[0241] receive a PDCCH sent by the network device, where the PDCCH includes a fourth indication field, and the fourth indication field indicates data transmission resource mapping information used by the network device for transmitting downlink transmission channel.

[0242] That is, the fourth indication field indicates which piece of the multiple pieces of data transmission resource mapping information is used by the network device to transmit the downlink transmission channel.

[0243] Optionally, in some embodiments, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel includes a transmitting beam corresponding to the data channel, and the receiving unit 510 is further configured to:

25 [0244] receive a PDCCH sent by the network device through a beam in a fifth beam group, where a fifth indication field of the PDCCH includes the indication information, the indication information includes a number for a transmitting beam corresponding to the data channel in a sixth beam group, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the sixth beam group, and the fifth

30

beam group is a beam group associated with the sixth beam group.

[0245] Optionally, in some embodiments, the receiving unit 510 is further configured to:

5 [0246] receive the multiple pieces of configuration information sent by the network device.

[0247] It should be understood that the terminal device 500 may correspond to the terminal device in the method 300, and corresponding functions of the terminal device may be implemented and are not described herein again for brevity.

10 [0248] FIG. 6 is a schematic block diagram of a network device according to an embodiment of the present invention. The network device 600 of FIG. 6 includes a memory 610, a processor 620 and a transceiver 630, where the memory is configured to store a program, the processor 620 is configured to execute the program, when the program is executed, the processor 620 is configured to control the transceiver 630 to send indication information to the terminal device, where the indication information
15 indicates a beam corresponding to a downlink transmission channel determined by the network device from multiple pieces of configuration information, the beam corresponding to the downlink transmission channel is used to transmit the downlink transmission channel, and each piece of the multiple pieces of configuration information includes at least one of: information of at least one transmitting beam,
20 information of a receiving beam corresponding to the at least one transmitting beam, and resource mapping information, where the resource mapping information indicating resources available or unavailable for downlink transmission of the at least one transmitting beam; and transmit the downlink transmission channel through the beam corresponding to the downlink transmission channel.

25 [0249] Optionally, in some embodiments, each piece of configuration information corresponds to one beam group, and information of each transmitting beam among the information of the at least one transmitting beam includes at least one of the following:

[0250] identification information of each transmitting beam, resource occupying
30 information specific to each transmitting beam, and a number for each transmitting

beam in the beam group corresponding to each piece of configuration information.

[0251] Optionally, in some embodiments, the information of the receiving beam corresponding to the at least one transmitting beam includes identification information of the receiving beam corresponding to the at least one transmitting beam.

5 **[0252]** Optionally, in some embodiments, the resource mapping information includes at least one piece of data transmission resource mapping information, each piece of data transmission resource mapping information indicates a resource available or unavailable for downlink transmission of the at least one transmitting beam.

10 **[0253]** Optionally, in some embodiments, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel includes a transmitting beam corresponding to the data channel, and the transceiver 630 is further configured to:

[0254] send a physical downlink control channel PDCCH to the terminal device
15 through a beam in a first beam group, where a first indication field of the PDCCH includes the indication information, the indication information includes a number for the transmitting beam corresponding to the data channel, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the first beam group, first
20 configuration information of the multiple pieces of configuration information corresponds to the first beam group, the first configuration information is configuration information pre-configured by the network device for the terminal device to receive the data channel.

[0255] Optionally, in some embodiments, the transceiver 630 is further configured
25 to:

[0256] send a first signaling to the terminal device, where the first signaling includes first configuration indication information, and the first configuration indication information indicates that the network device sends the data channel by using the first configuration information of the multiple pieces of configuration
30 information.

[0257] Optionally, in some embodiments, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel includes a receiving beam corresponding to the data channel, and the transceiver 630 is further configured to:

- 5 **[0258]** send a PDCCH to the terminal device through a beam in a second beam group, where a second indication field of the PDCCH includes the indication information, the indication information includes identification information of the receiving beam corresponding to the data channel, the indication information specifically indicates that the terminal device receives the data channel by using a
10 receiving beam corresponding to the identification information.

[0259] Optionally, in some embodiments, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel includes a transmitting beam corresponding to the data channel, and the transceiver 630 is further configured to:

- 15 **[0260]** send a PDCCH to the terminal device through a beam in a third beam group, where a third indication field of the PDCCH includes the indication information, the indication information includes a number for a transmitting beam corresponding to the data channel in a fourth beam group, the indication information specifically indicates that the network device sends the data channel by using the
20 transmitting beam corresponding to the number in the fourth beam group, second configuration information of the multiple pieces of configuration information corresponds to the fourth beam group, the second configuration information is configuration information pre-configured by the network device for the terminal device to receive the data channel.

- 25 **[0261]** Optionally, in some embodiments, the transceiver 630 is further configured to:

- [0262]** send a second signaling to the terminal device, where the second signaling includes second configuration indication information, and the second configuration indication information indicates that the network device sends the data channel by
30 using the second configuration information of the multiple pieces of configuration

information.

[0263] Optionally, in some embodiments, the second signaling is a RRC signaling or DCI.

5 **[0264]** Optionally, in some embodiments, the transceiver 630 is further configured to:

[0265] send a PDCCH to the terminal device, where the PDCCH includes third configuration indication information, and the third configuration indication information indicates configuration information used by the network device for sending a data channel.

10 **[0266]** That is, the third configuration indication information indicates which piece of the multiple pieces of configuration information is used by the network device to send the data channel.

[0267] Optionally, in some embodiments, the at least one piece of data transmission resource mapping information includes multiple pieces of data
15 transmission resource mapping information, and the transceiver 630 is further configured to:

[0268] send a PDCCH to the terminal device, where the PDCCH includes a fourth indication field, and the fourth indication field indicates data transmission resource mapping information used by the network device for transmitting the downlink
20 transmission channel.

[0269] That is, the fourth indication field indicates which piece of the multiple pieces of data transmission resource mapping information is used by the network device.

[0270] Optionally, in some embodiments, the downlink transmission channel
25 includes a data channel, the beam corresponding to the downlink transmission channel includes a transmitting beam corresponding to the data channel, and the transceiver 630 is further configured to:

[0271] send a PDCCH to the terminal device through a beam in a fifth beam group, where a fifth indication field of the PDCCH includes the indication
30 information, the indication information includes a number for a transmitting beam

corresponding to the data channel in a sixth beam group, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the sixth beam group, and the fifth beam group is a beam group associated with the sixth beam group.

5 **[0272]** Optionally, in some embodiments, the transceiver 630 is further configured to:

[0273] send the multiple pieces of configuration information to the terminal device.

[0274] It should be understood that the network device 600 may correspond to the
10 network device in the method 200, and corresponding functions of the network device may be implemented and are not described herein again for brevity.

[0275] FIG. 7 is a schematic block diagram of a terminal device according to an embodiment of the present application. The terminal device 700 of FIG. 7 includes a memory 710, a processor 720 and a transceiver 730, where the memory 710 is
15 configured to store a program, the processor 720 is configured to execute the program, when the program is executed, the processor 720 is configured to control the transceiver 730 to receive indication information sent by the network device, where the indication information indicates a beam corresponding to a downlink transmission channel determined by the network device from multiple pieces of configuration
20 information, the beam corresponding to the downlink transmission channel is used to transmit the downlink transmission channel, and each piece of the multiple pieces of configuration information includes at least one of: information of at least one transmitting beam, information of a receiving beam corresponding to the at least one transmitting beam, and resource mapping information, where the resource mapping
25 information indicates a resource available or unavailable for downlink transmission;

[0276] the processor 720 is further configured to determine a receiving beam corresponding to the downlink transmission channel according to the indication information;

[0277] the transceiver 730 is further configured to: receive the downlink
30 transmission channel through the receiving beam corresponding to the downlink

transmission channel.

[0278] Optionally, in some embodiments, each piece of configuration information corresponds to one beam group, and information of each transmitting beam among the information of the at least one transmitting beam includes at least one of the following:

[0279] identification information of each transmitting beam, resource occupying information specific to each transmitting beam, and a number for each transmitting beam in the beam group to which each transmitting beam belongs.

[0280] Optionally, in some embodiments, the information of the receiving beam corresponding to the at least one transmitting beam includes identification information of the receiving beam corresponding to the at least one transmitting beam.

[0281] Optionally, in some embodiments, the resource mapping information includes at least one piece of data transmission resource mapping information, each piece of data transmission resource mapping information indicates a resource available or unavailable for downlink transmission of the at least one transmitting beam.

[0282] Optionally, in some embodiments, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel includes a transmitting beam corresponding to the data channel, and the transceiver 730 is further configured to:

[0283] receive a physical downlink control channel PDCCH sent by the network device through a beam in a first beam group, where a first indication field of the PDCCH includes the indication information, the indication information includes a number for the transmitting beam corresponding to the data channel, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the first beam group, first configuration information of the multiple pieces of configuration information corresponds to the first beam group, the first configuration information is configuration information pre-configured by the network device for the terminal device to receive the data channel;

[0284] the processor 720 is specifically configured to:

[0285] determine a receiving beam corresponding to the transmitting beam according to the transmitting beam corresponding to the number;

[0286] the transceiver 730 is specifically configured to:

5 **[0287]** receive the data channel through the receiving beam corresponding to the transmitting beam.

[0288] Optionally, in some embodiments, the transceiver 730 is further configured to:

10 **[0289]** receive a first signaling sent by the network device, where the first signaling includes first configuration indication information, and the first configuration indication information indicates that the network device sends the data channel by using the first configuration information of the multiple pieces of configuration information.

15 **[0290]** Optionally, in some embodiments, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel includes a receiving beam corresponding to the data channel, and the transceiver 730 is further configured to:

20 **[0291]** receive a PDCCH sent by the network device through a beam in a second beam group, where a second indication field of the PDCCH includes the indication information, the indication information includes identification information of the receiving beam corresponding to the data channel, the indication information specifically indicates that the terminal device receives the data channel by using a receiving beam corresponding to the identification information.

25 **[0292]** Optionally, in some embodiments, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel includes a transmitting beam corresponding to the data channel, and the transceiver 730 is further configured to:

30 **[0293]** receive a PDCCH sent by the network device through a beam in a third beam group, where a third indication field of the PDCCH includes the indication information, the indication information includes a number for a transmitting beam

corresponding to the data channel in a fourth beam group, the indication information specifically indicates that the network device sends the data by using the transmitting beam corresponding to the number in the fourth beam group, second configuration information of the multiple pieces of configuration information corresponds to the fourth beam group, the second configuration information is configuration information pre-configured by the network device for the terminal device to receive the data channel.

[0294] Optionally, in some embodiments, the transceiver 730 is further configured to:

10 **[0295]** receive a second signaling sent by the network device, where the second signaling includes second configuration indication information, and the second configuration indication information indicates that the network device sends the data channel by using the second configuration information of the multiple pieces of configuration information.

15 **[0296]** Optionally, in some embodiments, the second signaling is a RRC signaling or DCI.

[0297] Optionally, in some embodiments, the transceiver 730 is further configured to:

20 **[0298]** receive a PDCCH sent by the network device, where the PDCCH includes third configuration indication information, and the third configuration indication information indicates configuration information used by the network device for sending a data channel.

[0299] That is, the third configuration indication information indicates which piece of the multiple pieces of configuration information is used by the network device to send the data channel.

[0300] Optionally, in some embodiments, the at least one piece of data transmission resource mapping information includes multiple pieces of data transmission resource mapping information, and the transceiver 730 is further configured to:

30 **[0301]** receive a PDCCH sent by the network device, where the PDCCH includes

a fourth indication field, and the fourth indication field indicates data transmission resource mapping information used by the network device for transmitting downlink transmission channel.

5 **[0302]** That is, the fourth indication field indicates which piece of the multiple pieces of data transmission resource mapping information is used by the network device to transmit the downlink transmission channel.

10 **[0303]** Optionally, in some embodiments, the downlink transmission channel includes a data channel, the beam corresponding to the downlink transmission channel includes a transmitting beam corresponding to the data channel, and the transceiver 730 is further configured to:

15 **[0304]** receive a PDCCH sent by the network device through a beam in a fifth beam group, where a fifth indication field of the PDCCH includes the indication information, the indication information includes a number for a transmitting beam corresponding to the data channel in a sixth beam group, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the sixth beam group, and the fifth beam group is a beam group associated with the sixth beam group.

20 **[0305]** Optionally, in some embodiments, the transceiver 730 is further configured to:

25 **[0306]** receive the multiple pieces of configuration information sent by the network device.

30 **[0307]** It should be understood that the terminal device 700 may correspond to the terminal device in the method 300, and corresponding functions of the terminal device may be implemented and are not described herein again for brevity.

35 **[0308]** It should be understood that the terms such as “and/or” herein is merely used to describe an association between associated objects, indicating that there may be three relationships, for example, A and/or B may indicate three situations that A exists separately, both A and B exist, B exists separately. In addition, the character “/” herein generally indicates that contextual objects are in an “or” relationship.

40 **[0309]** It should be understood that, in the various embodiments of the present

application, the size of the sequence numbers of the foregoing processes does not mean the order of execution sequence, and the order of execution of each process should be determined by its function and internal logic, and is not intended to limit the implementing process of the embodiments of the present application in any way.

5 **[0310]** Those skilled in the art may realize that the unit and algorithm processes of each example described in the embodiments disclosed herein may be implemented by electronic hardware or a combination of computer software and the electronic hardware. Whether to realize these functions by hardware or software depends to specific application and design constraints of the technical solutions. Those skilled in
10 the art may realize the described functions for each specific application by different methods, but such realization shall not be conceived as going beyond the scope of the present application.

[0311] Those skilled in the art may clearly know that, for specific working processes of the systems, devices and units described above, reference may be made
15 to the corresponding processes in the method embodiments and details will not be described herein again for the sake of convenient and brief description.

[0312] In several embodiments provided in the present application, it will be appreciated that the disclosed systems, devices and methods may be implemented in another manner. For example, the device embodiments described above are only
20 illustrative. For example, division of the units is only division of logic functions, and there may be other division manners during a practical implementation. For example, multiple units or components may be combined or integrated into another system, or some characteristics may be omitted or not executed. In addition, mutual couplings or direct couplings or communication connections shown or discussed may be
25 implemented through some interfaces. The direct couplings or communication connections between the devices or units may be implemented in electrical, mechanical or in other forms.

[0313] The units described as separate parts may or may not be physically separated. The parts displayed as units may or may not be physical units, namely, the
30 parts may be located in the same place, or may be distributed to multiple network

units. Part or all of the units may be selected, according to a practical requirement, to achieve the objectives of the schemes in the embodiments.

[0314] In addition, each function unit in each embodiment of the present application may be integrated into a processing unit, each unit may also physically
5 exist independently, and two or more units may also be integrated into a unit.

[0315] When implemented in form of software function unit and sold or used as an independent product, the functions may be stored in a computer-readable storage medium. Based on such understanding, the technical solutions of the present application substantially or the part making contributions to the prior art or part of the
10 technical solutions may be embodied by a software product, and the computer software product is stored in a storage medium, including a plurality of instructions for enabling computer equipment (which may be a personal computer, a server, network equipment or the like) to execute all or part of steps of the method in each embodiment of the present application. The abovementioned storage medium includes
15 various media capable of storing program codes such as a USB flash disk, a mobile hard disk, a Read-Only Memory (ROM), a Random Access Memory (RAM), a magnetic disk or an optical disk.

[0316] The above is only specific implementations of the present application but not intended to limit the scope of protection of the present application. Any variations
20 or replacements apparent to those skilled in the art within the technical scope disclosed in the present application shall fall into the scope of protection of the present application. Therefore, the scope of protection of the present application shall be subject to the scope of protection of the claims.

CLAIMS

1. An information transmission method, comprising:

sending, by a network device, indication information to a terminal device, wherein the indication information indicates a beam corresponding to a downlink transmission channel determined by the network device from multiple pieces of configuration information, the beam corresponding to the downlink transmission channel is used to transmit the downlink transmission channel, and each piece of the multiple pieces of configuration information comprises at least one of: information of at least one transmitting beam, information of a receiving beam corresponding to the at least one transmitting beam, and resource mapping information, wherein the resource mapping information indicates a resource available or unavailable for downlink transmission of the at least one transmitting beam; and

transmitting, by the network device, the downlink transmission channel through the beam corresponding to the downlink transmission channel.

2. The method according to claim 1, wherein each piece of configuration information corresponds to one beam group, and information of each transmitting beam among the information of the at least one transmitting beam comprises at least one of the following:

identification information of each transmitting beam, resource occupying information specific to each transmitting beam, and a number for each transmitting beam in the beam group corresponding to each piece of configuration information.

3. The method according to claim 1 or 2, wherein the information of the receiving beam corresponding to the at least one transmitting beam comprises identification information of the receiving beam corresponding to the at least one transmitting beam.

4. The method according to any one of claims 1 to 3, wherein the resource mapping information comprises at least one piece of data transmission resource mapping information, each piece of data transmission resource mapping information

indicates a resource available or unavailable for downlink transmission of the at least one transmitting beam.

5 5. The method according to any one of claims 2 to 4, wherein the downlink transmission channel comprises a data channel, the beam corresponding to the downlink transmission channel comprises a transmitting beam corresponding to the data channel, and the sending, by the network device, the indication information to the terminal device comprises:

10 sending, by the network device, a physical downlink control channel PDCCH to the terminal device through a beam in a first beam group, wherein a first indication field of the PDCCH comprises the indication information, the indication information comprises a number for the transmitting beam corresponding to the data channel, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the first beam group, first configuration information of the multiple pieces of configuration
15 information corresponds to the first beam group, the first configuration information is configuration information pre-configured by the network device for the terminal device to receive the data channel.

6. The method according to claim 5, further comprising:

20 sending, by the network device, a first signaling to the terminal device, wherein the first signaling comprises first configuration indication information, and the first configuration indication information indicates that the network device sends the data channel by using the first configuration information of the multiple pieces of configuration information.

25 7. The method according to claim 6, wherein the first signaling is a radio resource control RRC signaling or downlink control information DCI.

30 8. The method according to claim 3 or 4, wherein the downlink transmission channel comprises a data channel, the beam corresponding to the downlink transmission channel comprises a receiving beam corresponding to the data channel, and the sending, by the network device, the indication information to the terminal device comprises:

sending, by the network device, a PDCCH to the terminal device through a beam in a second beam group, wherein a second indication field of the PDCCH comprises the indication information, the indication information comprises identification information of the receiving beam corresponding to the data channel, the indication information specifically indicates that the terminal device receives the data channel by using a receiving beam corresponding to the identification information.

9. The method according to any one of claims 1 to 4, wherein the downlink transmission channel comprises a data channel, the beam corresponding to the downlink transmission channel comprises a transmitting beam corresponding to the data channel, and the sending, by the network device, the indication information to the terminal device comprises:

sending, by the network device, a PDCCH to the terminal device through a beam in a third beam group, wherein a third indication field of the PDCCH comprises the indication information, the indication information comprises a number for a transmitting beam corresponding to the data channel in a fourth beam group, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the fourth beam group, second configuration information of the multiple pieces of configuration information corresponds to the fourth beam group, the second configuration information is configuration information pre-configured by the network device for the terminal device to receive the data channel.

10. The method according to claim 9, further comprising:

sending, by the network device, a second signaling to the terminal device, wherein the second signaling comprises second configuration indication information, and the second configuration indication information indicates that the network device sends the data channel by using the second configuration information of the multiple pieces of configuration information.

11. The method according to claim 10, wherein the second signaling is a RRC signaling or DCI.

12. The method according to any one of claims 1 to 4, further comprising:

sending, by the network device, a PDCCH to the terminal device, wherein the PDCCH comprises third configuration indication information, and the third configuration indication information indicates configuration information used by the network device for sending a data channel.

- 5 13. The method according to any one of claims 4 to 12, wherein the at least one piece of data transmission resource mapping information comprises multiple pieces of data transmission resource mapping information, the method further comprises:

 sending, by the network device, a PDCCH to the terminal device, wherein the PDCCH comprises a fourth indication field, and the fourth indication field indicates
10 data transmission resource mapping information used by the network device for transmitting the downlink transmission channel.

14. The method according to any one of claims 2 to 4, wherein the downlink transmission channel comprises a data channel, the beam corresponding to the downlink transmission channel comprises a transmitting beam corresponding to the
15 data channel, and the sending, by the network device, the indication information to the terminal device comprises:

 sending, by the network device, a PDCCH to the terminal device through a beam in a fifth beam group, wherein a fifth indication field of the PDCCH comprises the indication information, the indication information comprises a number for a
20 transmitting beam corresponding to the data channel in a sixth beam group, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the sixth beam group, and the fifth beam group is a beam group associated with the sixth beam group.

15. The method according to any one of claims 1 to 14, wherein the method
25 further comprises:

 sending, by the network device, the multiple pieces of configuration information to the terminal device.

16. An information transmission method, comprising:

 receiving, by a terminal device, indication information sent by a network device,
30 wherein the indication information indicates a beam corresponding to a downlink

transmission channel determined by the network device from multiple pieces of configuration information, the beam corresponding to the downlink transmission channel is used to transmit the downlink transmission channel, and each piece of the multiple pieces of configuration information comprises at least one of: information of
5 at least one transmitting beam, information of a receiving beam corresponding to the at least one transmitting beam, and resource mapping information, wherein the resource mapping information indicates the resource available or unavailable for downlink transmission; determining, by the terminal device, a receiving beam corresponding to the downlink transmission channel according to the indication
10 information; and

receiving, by the terminal device, the downlink transmission channel through the receiving beam corresponding to the downlink transmission channel.

17. The method according to claim 16, wherein each piece of configuration information corresponds to one beam group, and information of each transmitting
15 beam among the information of the at least one transmitting beam comprises at least one of the following:

identification information of each transmitting beam, resource occupying information specific to each transmitting beam, and a number for each transmitting beam in the beam group corresponding to each piece of configuration information.

20 18. The method according to claim 16 or 17, wherein the information of the receiving beam corresponding to the at least one transmitting beam comprises identification information of the receiving beam corresponding to the at least one transmitting beam.

19. The method according to any one of claims 16 to 18, wherein the resource
25 mapping information comprises at least one piece of data transmission resource mapping information, each piece of data transmission resource mapping information indicates a resource available or unavailable for downlink transmission of the at least one transmitting beam.

20. The method according to any one of claims 17 to 19, wherein the downlink
30 transmission channel comprises a data channel, the beam corresponding to the

downlink transmission channel comprises a transmitting beam corresponding to the data channel, and the receiving, by the terminal device, the indication information sent by the network device comprises:

receiving, by the terminal device, a physical downlink control channel PDCCH
5 sent by the network device through a beam in a first beam group, wherein a first indication field of the PDCCH comprises the indication information, the indication information comprises a number for the transmitting beam corresponding to the data channel, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in
10 the first beam group, first configuration information of the multiple pieces of configuration information corresponds to the first beam group, the first configuration information is configuration information pre-configured by the network device for the terminal device to receive the data channel;

the determining, by the terminal device, the receiving beam corresponding to the
15 downlink transmission channel according to the indication information comprises:

determining, by the terminal device, a receiving beam corresponding to the transmitting beam according to the transmitting beam corresponding to the number;
and

receiving the data channel through the receiving beam corresponding to the
20 transmitting beam.

21. The method according to claim 20, further comprising:

receiving, by the terminal device, a first signaling sent by the network device, wherein the first signaling comprises first configuration indication information, and the first configuration indication information indicates that the network device sends
25 the data channel by using the first configuration information of the multiple pieces of configuration information.

22. The method according to claim 21, wherein the first signaling is a radio resource control RRC signaling or downlink control information DCI.

23. The method according to claim 18 or 19, wherein the downlink transmission
30 channel comprises a data channel, the beam corresponding to the downlink

transmission channel comprises a receiving beam corresponding to the data channel, and the receiving, by the terminal device, the indication information sent by the network device comprises:

receiving, by the terminal device, a PDCCH sent by the network device through
5 a beam in a second beam group, wherein a second indication field of the PDCCH comprises the indication information, the indication information comprises identification information of the receiving beam corresponding to the data channel, the indication information specifically indicates that the terminal device receives the data channel by using a receiving beam corresponding to the identification
10 information.

24. The method according to any one of claims 16 to 19, wherein the downlink transmission channel comprises a data channel, the beam corresponding to the downlink transmission channel comprises a transmitting beam corresponding to the data channel, and the receiving, by the terminal device, the indication information sent
15 by the network device comprises:

receiving, by the terminal device, a PDCCH sent by the network device through a beam in a third beam group, wherein a third indication field of the PDCCH comprises the indication information, the indication information comprises a number for a transmitting beam corresponding to the data channel in a fourth beam group, the
20 indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the fourth beam group, second configuration information of the multiple pieces of configuration information corresponds to the fourth beam group, the second configuration information is configuration information pre-configured by the network device for the
25 terminal device to receive the data channel;

the determining, by the terminal device, the receiving beam corresponding to the downlink transmission channel according to the indication information comprises:

determining, by the terminal device, a receiving beam corresponding to the transmitting beam according to the transmitting beam corresponding to the number;
30 and

receiving the data channel through the receiving beam corresponding to the transmitting beam.

25. The method according to claim 24, further comprising:

receiving, by the terminal device, a second signaling sent by the network device,
5 wherein the second signaling comprises second configuration indication information, and the second configuration indication information indicates that the network device sends the data channel by using the second configuration information of the multiple pieces of configuration information.

26. The method according to claim 25, wherein the second signaling is no
10 signaling or DCI.

27. The method according to any one of claims 16 to 19, further comprising:

receiving, by the terminal device, a PDCCH sent by the network device, wherein the PDCCH comprises third configuration indication information, and the third configuration indication information indicates configuration information used by the
15 network device for sending a data channel.

28. The method according to any one of claims 19 to 27, wherein the at least one piece of data transmission resource mapping information comprises multiple pieces of data transmission resource mapping information, the method further comprises:

receiving, by the terminal device, a PDCCH sent by the network device, wherein
20 the PDCCH comprises a fourth indication field, and the fourth indication field indicates data transmission resource mapping information used by the network device for transmitting the downlink transmission channel.

29. The method according to any one of claims 17 to 19, wherein the downlink transmission channel comprises a data channel, the beam corresponding to the
25 downlink transmission channel comprises a transmitting beam corresponding to the data channel, and the receiving, by the terminal device, the indication information sent by the network device comprises:

receiving, by the terminal device, a PDCCH sent by the network device through a beam in a fifth beam group, wherein a fifth indication field of the PDCCH
30 comprises the indication information, the indication information comprises a number

for a transmitting beam corresponding to the data channel in a sixth beam group, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the sixth beam group, and the fifth beam group is a beam group associated with the sixth beam group;

the determining, by the terminal device, the receiving beam corresponding to the downlink transmission channel according to the indication information comprises:

determining, by the terminal device, a receiving beam corresponding to the transmitting beam according to the transmitting beam corresponding to the number; and

receiving the data channel through the receiving beam corresponding to the transmitting beam.

30. The method according to any one of claims 16 to 29, further comprising:

receiving, by the terminal device, the multiple pieces of configuration information sent by the network device.

31. A network device, comprising:

a transceiving unit, configured to send indication information to a terminal device, wherein the indication information indicates a beam corresponding to a downlink transmission channel determined by the network device from multiple pieces of configuration information, the beam corresponding to the downlink transmission channel is used to transmit the downlink transmission channel, and each piece of the multiple pieces of configuration information comprises at least one of: information of at least one transmitting beam, information of a receiving beam corresponding to the at least one transmitting beam, and resource mapping information, wherein the resource mapping information indicates a resource available or unavailable for downlink transmission of the at least one transmitting beam; and

the transceiving unit is further configured to: transmit the downlink transmission channel through the beam corresponding to the downlink transmission channel.

32. The network device according to claim 31, wherein each piece of configuration information corresponds to one beam group, and information of each

transmitting beam among the information of the at least one transmitting beam comprises at least one of the following:

identification information of each transmitting beam, resource occupying information specific to each transmitting beam, and a number for each transmitting beam in the beam group corresponding to each piece of configuration information.

33. The network device according to claim 31 or 32, wherein the information of the receiving beam corresponding to the at least one transmitting beam comprises identification information of the receiving beam corresponding to the at least one transmitting beam.

34. The network device according to any one of claims 31 to 33, wherein the resource mapping information comprises at least one piece of data transmission resource mapping information, each piece of data transmission resource mapping information indicates a resource available or unavailable for downlink transmission of the at least one transmitting beam.

35. The network device according to any one of claims 32 to 34, wherein the downlink transmission channel comprises a data channel, the beam corresponding to the downlink transmission channel comprises a transmitting beam corresponding to the data channel, and the transceiving unit is further configured to:

send a physical downlink control channel PDCCH to the terminal device through a beam in a first beam group, wherein a first indication field of the PDCCH comprises the indication information, the indication information comprises a number for the transmitting beam corresponding to the data channel, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the first beam group, first configuration information of the multiple pieces of configuration information corresponds to the first beam group, the first configuration information is configuration information pre-configured by the network device for the terminal device to receive the data channel.

36. The network device according to claim 35, wherein the transceiving unit is further configured to:

send a first signaling to the terminal device, wherein the first signaling comprises first configuration indication information, and the first configuration indication information indicates that the network device sends the data channel by using the first configuration information of the multiple pieces of configuration information.

5 37. The network device according to claim 36, wherein the first signaling is a radio resource control RRC signaling or downlink control information DCI.

38. The network device according to claim 33 or 34, wherein the downlink transmission channel comprises a data channel, the beam corresponding to the downlink transmission channel comprises a receiving beam corresponding to the data
10 channel, and the transceiving unit is further configured to:

send a PDCCH to the terminal device through a beam in a second beam group, wherein a second indication field of the PDCCH comprises the indication information, the indication information comprises identification information of the receiving beam corresponding to the data channel, the indication information specifically indicates
15 that the terminal device receives the data channel by using a receiving beam corresponding to the identification information.

39. The network device according to any one of claims 31 to 34, wherein the downlink transmission channel comprises a data channel, the beam corresponding to the downlink transmission channel comprises a transmitting beam corresponding to
20 the data channel, and the transceiving unit is further configured to:

send a PDCCH to the terminal device through a beam in a third beam group, wherein a third indication field of the PDCCH comprises the indication information, the indication information comprises a number for a transmitting beam corresponding to the data channel in a fourth beam group, the indication information specifically
25 indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the fourth beam group, second configuration information of the multiple pieces of configuration information corresponds to the fourth beam group, the second configuration information is configuration information pre-configured by the network device for the terminal device to receive the data
30 channel.

40. The network device according to claim 39, wherein the transceiving unit is further configured to:

send a second signaling to the terminal device, wherein the second signaling comprises second configuration indication information, and the second configuration indication information indicates that the network device sends the data channel by using the second configuration information of the multiple pieces of configuration information.

41. The network device according to claim 40, wherein the second signaling is a RRC signaling or DCI.

42. The network device according to any one of claims 31 to 34, wherein the transceiving unit is further configured to:

send a PDCCH to the terminal device, wherein the PDCCH comprises third configuration indication information, and the third configuration indication information indicates configuration information used by the network device for sending a data channel.

43. The network device according to any one of claims 34 to 42, wherein the at least one piece of data transmission resource mapping information comprises multiple pieces of data transmission resource mapping information, and the transceiving unit is further configured to:

send a PDCCH to the terminal device, wherein the PDCCH comprises a fourth indication field, and the fourth indication field indicates data transmission resource mapping information used by the network device for transmitting the downlink transmission channel.

44. The network device according to any one of claims 32 to 34, wherein the downlink transmission channel comprises a data channel, the beam corresponding to the downlink transmission channel comprises a transmitting beam corresponding to the data channel, and the transceiving unit is further configured to:

send a PDCCH to the terminal device through a beam in a fifth beam group, wherein a fifth indication field of the PDCCH comprises the indication information, the indication information comprises a number for a transmitting beam corresponding

to the data channel in a sixth beam group, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the sixth beam group, and the fifth beam group is a beam group associated with the sixth beam group.

5 45. The network device according to any one of claims 31 to 44, wherein the transceiving unit is further configured to:

send the multiple pieces of configuration information to the terminal device.

46. A terminal device, comprising:

10 a receiving unit, configured to receive indication information sent by a network device, wherein the indication information indicates a beam corresponding to a downlink transmission channel determined by the network device from multiple pieces of configuration information, the beam corresponding to the downlink transmission channel is used to transmit the downlink transmission channel, and each piece of the multiple pieces of configuration information comprises at least one of:
15 information of at least one transmitting beam, information of a receiving beam corresponding to the at least one transmitting beam, and resource mapping information, wherein the resource mapping information indicates the resource available or unavailable for downlink transmission; and

20 a determining unit, configured to determine a receiving beam corresponding to the downlink transmission channel according to the indication information;

the receiving unit is further configured to: receive the downlink transmission channel through the receiving beam corresponding to the downlink transmission channel.

25 47. The terminal device according to claim 46, wherein each piece of configuration information corresponds to one beam group, and information of each transmitting beam among the information of the at least one transmitting beam comprises at least one of the following:

30 identification information of each transmitting beam, resource occupying information specific to each transmitting beam, and a number for each transmitting beam in the beam group to which each transmitting beam belongs.

48. The terminal device according to claim 46 or 47, wherein the information of the receiving beam corresponding to the at least one transmitting beam comprises identification information of the receiving beam corresponding to the at least one transmitting beam.

5 49. The terminal device according to any one of claims 46 to 48, wherein the resource mapping information comprises at least one piece of data transmission resource mapping information, each piece of data transmission resource mapping information indicates a resource available or unavailable for downlink transmission of the at least one transmitting beam.

10 50. The terminal device according to any one of claims 47 to 49, wherein the downlink transmission channel comprises a data channel, the beam corresponding to the downlink transmission channel comprises a transmitting beam corresponding to the data channel, and the receiving unit is further configured to:

15 receive a physical downlink control channel PDCCH sent by the network device through a beam in a first beam group, wherein a first indication field of the PDCCH comprises the indication information, the indication information comprises a number for the transmitting beam corresponding to the data channel, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the first beam group, first
20 configuration information of the multiple pieces of configuration information corresponds to the first beam group, the first configuration information is configuration information pre-configured by the network device for the terminal device to receive the data channel;

 the determining unit is specifically configured to:

25 determine a receiving beam corresponding to the transmitting beam according to the transmitting beam corresponding to the number; and

 the receiving unit is specifically configured to:

 receive the data channel through the receiving beam corresponding to the transmitting beam.

30 51. The terminal device according to claim 50, wherein the receiving unit is

further configured to:

receive a first signaling sent by the network device, wherein the first signaling comprises first configuration indication information, and the first configuration indication information indicates that the network device sends the data channel by using the first configuration information of the multiple pieces of configuration information.

52. The terminal device according to claim 51, wherein the first signaling is a radio resource control RRC signaling or downlink control information DCI.

53. The terminal device according to claim 48 or 49, wherein the downlink transmission channel comprises a data channel, the beam corresponding to the downlink transmission channel comprises a receiving beam corresponding to the data channel, and the receiving unit is further configured to:

receive a PDCCH sent by the network device through a beam in a second beam group, wherein a second indication field of the PDCCH comprises the indication information, the indication information comprises identification information of the receiving beam corresponding to the data channel, the indication information specifically indicates that the terminal device receives the data channel by using a receiving beam corresponding to the identification information.

54. The terminal device according to any one of claims 46 to 49, wherein the downlink transmission channel comprises a data channel, the beam corresponding to the downlink transmission channel comprises a transmitting beam corresponding to the data channel, and the receiving unit is further configured to:

receive a PDCCH sent by the network device through a beam in a third beam group, wherein a third indication field of the PDCCH comprises the indication information, the indication information comprises a number for a transmitting beam corresponding to the data channel in a fourth beam group, the indication information specifically indicates that the network device sends the data channel by using the transmitting beam corresponding to the number in the fourth beam group, second configuration information of the multiple pieces of configuration information corresponds to the fourth beam group, the second configuration information is

configuration information pre-configured by the network device for the terminal device to receive the data channel.

55. The terminal device according to claim 54, wherein the receiving unit is further configured to:

5 receive a second signaling sent by the network device, wherein the second signaling comprises second configuration indication information, and the second configuration indication information indicates that the network device sends the data channel by using the second configuration information of the multiple pieces of configuration information.

10 56. The terminal device according to claim 55, wherein the second signaling is a RRC signaling or DCI.

57. The terminal device according to any one of claims 46 to 49, wherein the transceiving unit is further configured to:

15 receive a PDCCH sent by the network device, wherein the PDCCH comprises third configuration indication information, and the third configuration indication information indicates configuration information used by the network device for sending a data channel.

20 58. The terminal device according to any one of claims 49 to 57, wherein the at least one piece of data transmission resource mapping information comprises multiple pieces of data transmission resource mapping information, and the receiving unit is further configured to:

25 receive a PDCCH sent by the network device, wherein the PDCCH comprises a fourth indication field, and the fourth indication field indicates data transmission resource mapping information used by the network device for transmitting downlink transmission channel.

59. The terminal device according to any one of claims 47 to 49, wherein the downlink transmission channel comprises a data channel, the beam corresponding to the downlink transmission channel comprises a transmitting beam corresponding to the data channel, and the receiving unit is further configured to:

30 receive a PDCCH sent by the network device through a beam in a fifth beam

group, wherein a fifth indication field of the PDCCH comprises the indication information, the indication information comprises a number for a transmitting beam corresponding to the data channel in a sixth beam group, the indication information specifically indicates that the network device sends the data channel by using the
5 transmitting beam corresponding to the number in the sixth beam group, and the fifth beam group is a beam group associated with the sixth beam group.

60. The terminal device according to any one of claims 46 to 59, wherein the receiving unit is further configured to:

receive the multiple pieces configuration information sent by the network device.