

## **CONNECTOR**

### **TECHNICAL FIELD**

The present invention relates to the art of connectors and, particularly to an electrical connector adapted for mounting on a printed circuit board.

### **5 BACKGROUND**

A printed circuit board (PCB) connector (e.g. a receptacle) may be directly soldered (also known as surface mounting) to a surface of the PCB to provide a connectable interface between the PCB and another device with an opposing mating connector (e.g. a plug).

10 A surface mount receptacle typically includes a housing with a mating face for mating with an opposing mating plug and a board-mounting end from which a plurality of terminals exit the housing for termination to circuit traces on the PCB. The surface mount receptacle may further include a plurality of mounting posts at the base of the housing for the purpose of aiding the alignment  
15 of the surface mount receptacle to the PCB during mounting.

The terminals normally include mating portions for mating with the terminals of the opposing mating plug and tail portions (or 'solder tails') projecting from the housing for interconnection, as by soldering, to circuit traces on the PCB or in holes in the PCB into which the tails are inserted. The solder  
20 tails when soldered to the PCB often become the only points of attachment and the only means of securing the surface mount receptacle onto the PCB other than the mounting posts.

A common practice to connect cables to a PCB is by terminating the cables at a plug connector (jointly referred to as cable assembly) and then mating  
25 the plug connector to a surface mount receptacle on the PCB. The plug connector

typically includes a printed circuit card that has a projecting edge that is received within a mating slot in the surface mount receptacle.

High speed data transfer systems require electrical connectors in which the electrical impedance can be controlled in order to maintain the required data transfer rate of the electrical system. Shielding cages are typically utilised with such connectors to control the emission of electromagnetic interference. These cages often serve as a secondary housing for the connector in that they will substantially enclose the connectors. U.S. Publ No. 2006/0040556 discloses one such shield housing.

With the miniaturisation of electronic equipment, small-sized surface mount receptacles with very fine solder tails are desired because the footprint allocated for each internal component is reduced to accommodate the limited internal space within the electronic equipment. U.S. Publ. No. 2006/0009080 and U.S. Publ No. 2006/0014438 disclose one such surface mount receptacle.

The small size of the surface mount receptacle makes it difficult to guide the opposing mating plug into mating with the surface mount receptacle as well as increases the difficulty of ensuring the opposing mating plug mates properly with the surface mount receptacle, especially in a blind mating application.

Because the solder contacts at the solder tails are the only means of attachment between the surface mount receptacle and the PCB other than the mounting posts, any failed attempt in aligning and mating the opposing mating plug to the surface mount receptacle can cause mechanical stress at these points of attachment causing the solder contacts to loosen and ultimately breaking signal pathways and causing connection to the PCB to fail. In addition, the repeated unsuccessful engagement of the opposing mating plug with the surface mount receptacle together with the cable's weight and movement can cause the

surface mount receptacle to lift off the PCB, further stressing and breaking the points of attachment.

The present invention is directed at preventing the breakage of signal pathways due to the lifting of the surface mount receptacle by providing an  
5 improved structure for anchoring and holding the receptacle to a PCB without substantially increasing the footprint required to mount the receptacle.

## SUMMARY

It would be desirable to provide a connector with an improved structure that can hold the connector to a printed circuit board without increasing the footprint required to mount the connector.

5 In accordance with one embodiment of the present invention, there is provided a connector, comprising:

an insulative housing that has a top, a bottom, a first side, a second side wherein all four sides are connected to form a mating face and a board-mounting end;

10 a plurality of terminals supported in the housing and terminating at the board-mounting end wherein each terminal further comprises a contact portion configured to establish electrical contact with a complementary mating connector, a solder tail that extends out of the housing at the board-mounting end, a body portion that is disposed intermediate the contact portion and the  
15 solder tail and which interconnect them together; and

at least one solder bracket coupled to the housing wherein a major portion of the solder bracket lies within the profile of the housing.

In accordance with another embodiment of the present invention, there is provided an electrical connector configured to be mounted on a printed circuit  
20 board comprising:

an insulative housing that has a top, a bottom, a first side, a second side, all four sides connected to form a mating face and a board-mounting end wherein at the mating face, there is at least one mating slot extending into the housing;

a plurality of terminals supported in the housing and terminating at the  
25 board-mounting end wherein the terminals are grouped into a first set and a

second set and each terminal in the first set and the second set further comprises a contact portion that extends into the mating slot, a solder tail that extends out of the housing at the board-mounting end, a body portion that is disposed intermediate the contact portion and the solder tail and which interconnect them  
5 together; and

at least one solder bracket coupled to the housing wherein a major portion of the solder bracket lies within the profile of the housing.

## BRIEF DESCRIPTION OF THE DRAWINGS

An exemplary form of the present invention will now be described with reference to the accompanying drawings in which:

**Figure 1** shows a perspective view of a commercially available opposing mating plug aligned to mate with a prior art surface mount receptacle mounted on a printed circuit board, the wires of the opposing mating plug having been removed for clarity;

**Figure 2A** shows a prior art circuit board with two arrangements of conductive contact pads disposed thereon and with a surface mount receptacle mounted to one of the two contact pad arrangements and a shield housing cum guide aligned to enclose the surface mount receptacle;

**Figure 2B** shows the circuit board of Figure 2A with two surface mount receptacles enclosed within two shield housing cum guides mounted on the circuit board and with two opposing mating plug connectors aligned to mate with their respective surface mount receptacles;

**Figure 3A** is an exploded perspective view of an exemplary connector of the present invention;

**Figure 3B** is a perspective view of the assembled exemplary connector of Figure 3A;

**Figure 4** is a front view of a housing of the exemplary connector of Figure 3B looking towards a mating face of the housing;

**Figure 5A** shows the perspective shape of the solder bracket removed from the exemplary connector of Figure 3B;

**Figure 5B** shows the front view of the solder bracket of Figure 5A;

**Figure 5C** is a schematic perspective view showing an exemplary intermediate for fabricating the solder bracket of Figure 5A;

**Figure 5D** shows the perspective shape of the solder bracket of Figure 5A after it has been bent prior to fitting on the housing of the exemplary connector of  
5 Figure 3B;

**Figure 6** shows a perspective view of the housing of the exemplary connector of Figure 3B;

**Figure 7A** is a bottom view of the housing of the exemplary connector of Figure 3B with a solder bracket placed in the recess of the housing awaiting to be  
10 fitted;

**Figure 7B** is a bottom view of the housing of the exemplary connector of Figure 3B with the solder bracket fitted in the recess of the housing;

**Figure 8A** is a perspective view of another exemplary connector;

**Figure 8B** is a bottom view of the exemplary connector of Figure 8A;

**Figure 9A** is an exploded perspective view of another exemplary  
15 connector;

**Figure 9B** is a bottom view of the exemplary connector of Figure 9A wherein the solder bracket is coupled to the housing; and

**Figure 9C** is a bottom view of the exemplary connector of Figure 9A  
20 wherein the solder bracket is coupled to the housing and bent along a plurality of predefined bend lines.

While the above-identified figures set forth several embodiments of the invention, other embodiments are also contemplated, as noted in the detailed description. In all cases, this disclosure presents aspects of the invention by way

of representation and not limitation. It should be understood that numerous other modifications and embodiments can be devised by those skilled in the art, which fall within the scope and spirit of the principles of the invention. The figures may not be drawn to scale. Like reference numbers have been used throughout the

5 figures to denote like parts.

## DETAILED DESCRIPTION

Figure 1 shows a prior art plug connector **10** aligned and ready to mate with a receptacle connector **2** that is mounted by soldering on a printed circuit board **4**. The receptacle connector **2** comprises a housing **201** with a top **202**, a bottom **203**, a mating face **207**, a board-mounting end **208** and a plurality of terminals **220** grouped into a first set **221** and a second set **222** (as shown in Figure 3A) supported in the housing **201** of the receptacle connector **2**.

The plug connector **10** has an insulative plug housing **11** into which a plurality of wires or cables (not shown) are fed and the wires or cables thereof terminate at a plurality of conductive traces **13** or contact pads disposed on two major surfaces of a circuit card **12**. The circuit card **12** has a forward edge **12A** that is received within a mating slot **210** (as shown in Figure 2A) provided at the mating face **207** of the housing **201** of the receptacle connector **2** when the two connectors mate. The plug housing **11** includes an upper flange **14** and a lower flange **15**, both flanges **14**, **15** spaced apart from each other thereby defining an intervening space that surrounds or encloses the projection portion of the circuit card **12**. During mating, the lower flange **15** of the plug connector **10** is received within a cavity or recess beneath the mating slot **210** of the receptacle connector **2** and between two side walls thereof. Both the upper and lower flanges **14**, **15** which are formed from an insulative material extend for a defined distance over the first set **221** and the second set **222** of terminals to prevent electrostatic discharges from occurring during the mating of the two connectors.

Figure 2A shows a prior art shield housing **8** formed from a sheet metal blank through a suitable process, such as a stamping and forming process. The shield housing comprises a top wall **8A**, two side walls **8C**, **8D**, a back wall **8E** and a bottom wall **8B**, all combined to collectively define a bottom opening (not shown) that leads to a hollow interior cavity while the top wall **8A**, two side walls **8C**, **8D** and bottom wall **8B** cooperate to define an entrance **9** that leads to

the hollow interior cavity. The shield housing **8** further comprises a series of flanges **6** formed along the side walls **8C**, **8D** that are bent at an angle to provide a mounting surface for attachment to the PCB **4**. The shield housing **8** when mounted on the PCB **4** encloses the receptacle connector **2** and provides a shield  
5 for the receptacle connector **2** and the plug connector **10** against electromagnetic interference. Figure 2B shows a plurality of plug connectors **10** aligned and ready to mate with a plurality of receptacle connectors **2** shielded by their respective shield housings **8**.

As the shield housing **8** extends beyond the footprint of the receptacle  
10 connector **2**, it takes up valuable real estate on the PCB **4** which is a limited resource especially for small electronic equipment. In addition, due to the shield housing **8** enclosing the receptacle connector **2** beyond its mating face **207**, it is difficult to accurately mate the plug connector **10** with the receptacle connector **2** thereby increasing the chances of a mating failure and increasing the number of  
15 times needed to correctly couple the two connectors.

Referring to Figure 1, the receptacle connector **2** is attached to the PCB **4** via a plurality of solder tails **226**. As the solder tails **226** for a small receptacle connector are very fine, the solder contact at the points of attachment where the solder tails **226** of the receptacle connector **2** are soldered to the PCB **4** is limited.  
20 For every mating failure that occurred, mechanical stress can be generated at the points of attachment. Repeated mechanical stress at the points of attachment can cause the solder contact to loosen and the receptacle connector **2** to lift off the PCB **4** resulting in a breakage of the signal pathways thereby causing the connection to the PCB **4** to fail.

25 The present invention is directed at preventing the breakage of signal pathways due to the lifting of the receptacle connector by providing an improved structure for anchoring and holding the receptacle connector to a PCB without substantially increasing the footprint required to mount the receptacle connector.

Referring to Figures 3A and 3B, an exemplary connector **200** in accordance with the present invention comprises an insulative housing **201** that has a top **202**, a bottom **203**, a first side **204**, a second side **205**, all four sides connected to form a mating face **207** and a board-mounting end **208**; a first set  
5 **221** and a second set **222** of terminals supported in the housing **201** and terminating at the board-mounting end **208** and at least one solder bracket **300** coupled to the housing **201**. The housing **201** may further comprise a plurality of mounting posts **206** at the bottom **203** which may be used for positioning the connector **200** on the PCB **4**.

10 Referring to Figure 4, in one embodiment of the present invention, at the mating face **207** of the housing **201**, there is a mating slot **210** which receives the plug connector **10** of a cable assembly **11** when the plug connector **10** mates with the connector **200**; wherein the mating slot **210** bounded by a top wall **212**, a bottom wall **213**, two side walls **214**, **215** and a rear wall (not shown) extends  
15 into the interior of the housing **201**.

It should be noted that the arrangement of the two connectors in this description (i.e. a receptacle connector on the PCB and a plug connector at an end of a cable assembly) has been presented for the purpose of illustration and description. It is not intended to be exhaustive or to limit the invention to the  
20 precise forms disclosed, since many modifications or variations (e.g. a plug connector on the PCB and a receptacle connector at an end of a cable assembly) thereof are possible in light of the above teaching. All such modifications and variations are within the scope of the invention.

The first set of terminals **221** and the second set of terminals **222** extend  
25 into the mating slot **210** and provide an electrical transmission path from the cable assembly **11** to the PCB **4**. The first set of terminals **221** is similar to the second set of terminals **222** in that each terminal in the two sets further comprises a contact portion **225** that extends into the mating slot **210** and a solder tail **226**

that extends out of the housing **201** for attachment to the PCB **4** on which the connector **200** is to be mounted. Each terminal also includes a body portion **227** that is disposed intermediate the contact portion **225** and the solder tail **226** and which interconnect them. Each terminal may further comprise a retention portion

5    **229** which primarily serve to retain the terminal in place within the housing **201**.

The first set of terminals **221** are inserted into a plurality of slots that are formed in the top wall **212** of the housing **201** which include openings that communicate with the mating slot **210** and are positioned so that the contact portions **225** of the first set of terminals **221** may at least partially extend into the

10    mating slot **210**. The second set of terminals **222** are inserted into a plurality of slots that are formed in the bottom wall **213** of the housing **201** which include openings that communicate with the mating slot **210** and are positioned so that the contact portions **225** of the second set of terminals **222** may at least partially extend into the mating slot **210**.

15        In one embodiment of the present invention, there is at least one solder bracket **300** coupled to the housing **201** of the connector **200**. With reference to Figures 5A, 5B, 5C and 5D, the solder bracket **300** may further comprise a bracket body **320** having a first side **304** with a thickness **t1**, a second side **305** with a thickness **t2** and a bridge portion **302** with a thickness **tb** connecting the

20    first side **304** to the second side **305**; and a plurality of solder contact portions **310** extending from the first side **304** and the second side **305** of the bracket body **320**.

Preferably, the first side **304** and the second side **305** further comprise a plurality of locking devices **330** and/or a plurality of support tabs **340** extending

25    from the first side **304** and/or the second side **305** contiguous to the board-mounting end **208**. The locking device **330** may include, but is not limited to, a hook **333** wherein preferably, there is a plurality of engagement barbs **335** coupled to at least one edge of the hook **333**. The engagement barbs **335** anchor

the solder bracket **300** to the housing **201** as the hook **333** latches on the housing **201** thereby preventing the solder bracket **300** from disengaging from the housing **201**.

The solder bracket **300** may be made of an intermediate **300A** such as shown in Figure 5C, which is prepared by the steps of blanking a piece of metal sheet by means of a press, and bending it at required portions into shape. In Figure 5C, portions **304P**, **302P** and **305P** define the first side **304**, the bridge portion **302** and the second side **305** respectively. A plurality of solder contact portions **310**, locking devices **330** and/or support tabs **340** are defined on the intermediate **300A**. The intermediate **300A** is bent along the bend lines **B1** using known methods such as with a stamping die to give the initial shape of the solder bracket **300** as shown in Figure 5D before the solder bracket **300** is coupled to the housing **201**. Figures 5A and 5B illustrate the final shape of the solder bracket **300** after the solder bracket **300** is coupled to the housing **201** and bent along the bend lines **B2** using known methods such as with a bending jig. It should be noted that the above process description is just one of the ways of producing and coupling the solder bracket **300** to the housing **201** and that the solder bracket **300** may also be assembled, bent and coupled to the housing **201** using other methods including manual, semi-automated and automated processes.

Referring to Figure 6, in one embodiment of the present invention, there is at least one recessed portion **202A** at the top **202**, at least one recessed portion **204A** at the first side **204** and at least one recessed portion **205A** at the second side **205** of the housing **201**. Preferably, the recessed portion **202A** has a depth **db** equal or more than the thickness **tb** of the bridge portion **302**, the recessed portion **204A** has a depth **d1** equal or more than the thickness **t1** of the first side **304** and the recessed portion **205A** has a depth **d2** equal or more than the thickness **t2** of the second side **305** of the solder bracket **300**.

When a solder bracket **300** with thickness **t1**, **t2** and **tb** is coupled to a connector housing **201** with recesses of respective depths **d1**, **d2** and **db**, the outer surfaces of the first side **304**, the second side **305** and the bridge portion **302** of the solder bracket **300** will be on the same plane as the outer surfaces of the first side **204**, the second side **205** and the top **202** of the connector housing **201** if **t1** is equal to **d1**, **t2** is equal to **d2** and **tb** is equal to **db**. If the outer surfaces of the first side **304**, the second side **305** and the bridge portion **302** of the solder bracket **300** are on the same plane as the outer surfaces of the first side **204**, the second side **205** and the top **202** of the connector housing **201**, the external profile of the connector **200** remains unchanged after the solder bracket **300** is coupled to the housing **201** and therefore the exemplary connector **200** will be able to mate with existing plug connectors **10** without any modification.

When a solder bracket **300** with thickness **t1**, **t2** and **tb** is coupled to a connector housing **201** with recesses of respective depths **d1**, **d2** and **db**, the outer surfaces of the first side **304**, the second side **305** and the bridge portion **302** of the solder bracket **300** will be at a lower plane than the outer surfaces of the first side **204**, the second side **205** and the top **202** of the connector housing **201** if **t1** < **d1**, **t2** < **d2** and **tb** < **db**. If the outer surfaces of the first side **304**, the second side **305** and the bridge portion **302** of the solder bracket **300** are at a lower plane than the outer surfaces of the first side **204**, the second side **205** and the top **202** of the connector housing **201**, in addition to the solder bracket **300** being fixed in its position within the recess thereby limiting the lateral movement of the solder bracket **300** relative to the housing **201**, existing plug connectors **10** are also able to mate with the connector **200** without any modification.

In one embodiment of the present invention, the housing **201** further comprises a plurality of grooves **209** at the recessed portions **204A** and **205A** of the first side **204** and the second side **205** of the housing **201** contiguous to the board-mounting end **208**. The grooves **209** may either extend from the top **202** to the bottom **203** of the housing **201** or may extend from either the top **202** or the

bottom **203** and terminating midway into the housing **201**. As illustrated in Figure 3B, in one embodiment of the present invention, the locking devices **330** may hang over the top edges of the recessed portions **204A** and **205A** of the first side **204** and the second side **205** before terminating in the grooves **209**.

5           Figure 7A is a bottom view of the exemplary connector **200** with the solder bracket **300** of Figure 5D coupled to the housing **201**. Figure 7B is a bottom view of the exemplary connector **200** with the solder contact portions **310** and the support tabs **340** of the solder bracket **300** bent along the bend lines **B2** after the solder bracket **300** is coupled to the housing **201**. Figure 5A shows the  
10       perspective view and 5B shows the front view of the solder bracket **300** when the solder bracket **300** in Figure 7B is decoupled from the housing **201**.

          In this embodiment, the solder bracket **300** is further held in place relative to the connector housing **201** by the hooks **333**, the engagement barbs **335** (both the hooks **333** and the engagement barbs **335** are not shown in Figures 7A and  
15       7B but represented in Figures 5A and 5B), the bending of support tabs **340** and solder contact portions **310** around the bottom edges of the recessed portions **204A** and **205A** of the first side **204** and the second side **205** of the housing **201**.

          Figures 8A and 8B illustrate another embodiment of the present invention wherein a plurality of solder contact portions **310** are bent away from the housing  
20       **201** and a plurality of locking devices **330** are bent to hook around the bottom edges of the recessed portions **204A** and **205A** of the first side **204** and the second side **205** of the housing **201**. This embodiment provides additional real estate for soldering the connector **200** to the PCB **4**.

          Figures 9A, 9B and 9C illustrate another embodiment of the present  
25       invention wherein the connector **200** further comprises a plurality of latching devices **350** on the solder bracket **300** and a plurality of engagement portions **250** on the housing **201** of the connector **200**. When the solder bracket **300** is coupled

to the housing **201**, the latching devices **350** latches to the engagement portions **250** thereby further keeping the solder bracket **300** secured to the housing **201** of the connector **200**.

The foregoing description of the preferred embodiment of the invention  
5 has been presented for purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise forms disclosed, since many modifications or variations thereof are possible in light of the above teaching. All such modifications and variations are within the scope of the invention. The embodiments described herein were chosen and described in order  
10 to best explain the principles of the invention and its practical application, thereby to enable others skilled in the art to utilise the invention in various embodiments and with various modifications as are suited to the particular use contemplated thereof. It is intended that the scope of the invention be defined by the claims appended hereto, when interpreted in accordance with the full breadth  
15 to which they are legally and equitably suited.

## CLAIMS

1. An electrical connector comprising:

an insulative housing that has a top, a bottom, a first side, a second side wherein all four sides are connected to form a mating face and a board-

5 mounting end;

a plurality of terminals supported in the housing and terminating at the board-mounting end wherein each terminal further comprises a contact portion configured to establish electrical contact with a complementary mating connector, a solder tail that extends out of the housing at the board-mounting  
10 end, a body portion that is disposed intermediate the contact portion and the solder tail and which interconnect them together; and

at least one solder bracket coupled to the housing wherein a major portion of the solder bracket lies within the profile of the housing.

2. The electrical connector as claimed in claim 1 wherein the housing  
15 further comprises a plurality of mounting posts at the bottom of the housing.

3. The electrical connector as claimed in claim 1 or claim 2 wherein the housing further comprises at least one recessed portion with depth of  $d_1$  at the first side, at least one recessed portion with depth of  $d_b$  at the top and at least one recessed portion with depth of  $d_2$  at the second side of  
20 the housing.

4. The electrical connector as claimed in any one of claims 1 to 3 wherein the housing further comprises a plurality of grooves at the recessed portions of the first side and the second side of the housing.

5. The electrical connector as claimed in any one of claims 1 to 4 wherein the solder bracket further comprises:

a bracket body having a first side of thickness  $t_1$ , a second side of thickness  $t_2$  and a bridge portion of thickness  $t_b$  connecting the first side to the second side; and

a plurality of solder contact portions extending from the first side and the second side of the bracket body.

6. The electrical connector as claimed in claim 5 wherein the solder bracket further comprises a plurality of locking devices extending from at least one side of the bracket body.

7. The electrical connector as claimed in claim 6 wherein the locking device is a hook with a plurality of engagement barbs coupled to at least one edge of the hook.

8. The electrical connector as claimed in any one of claims 5 to 7 wherein the solder bracket further comprises a plurality of support tabs extending from at least one side of the bracket body.

9. The electrical connector as claimed in any one of claims 5 to 8 wherein the solder contact portions extend away from the housing.

10. The electrical connector as claimed in any one of claims 5 to 8 wherein the solder contact portions engulf a portion of the bottom of the housing.

11. The electrical connector as claimed in any one of claims 3 to 10 wherein thickness  $t_1$  is less than recess depth  $d_1$  or thickness  $t_2$  is less than recess depth  $d_2$  or thickness  $t_b$  is less than recess depth  $d_b$ .

12. The electrical connector as claimed in any one of claims 3 to 10 wherein thickness  $t_1$  is equal to the recess depth  $d_1$  or thickness  $t_2$  is equal to the recess depth  $d_2$  or thickness  $t_b$  is equal to the recess depth  $d_b$ .
- 5 13. The electrical connector as claimed in any one of claims 1 to 12 wherein the housing further comprises a plurality of engagement portions and the solder bracket further comprises a plurality of latching devices configured to latch on the engagement portions on the housing.
14. An electrical connector comprising:
- 10 an insulative housing that has a top, a bottom, a first side, a second side, all four sides connected to form a mating face and a board-mounting end wherein at the mating face, there is at least one mating slot extending into the housing;
- a plurality of terminals supported in the housing and terminating at the
- 15 board-mounting end wherein the terminals are grouped into a first set and a second set and each terminal in the first set and the second set further comprises a contact portion that extends into the mating slot, a solder tail that extends out of the housing at the board-mounting end, a body portion that is disposed intermediate the contact portion and the solder tail and which
- 20 interconnect them together; and
- at least one solder bracket coupled to the housing wherein a major portion of the solder bracket lies within the profile of the housing.