

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
21 December 2000 (21.12.2000)

PCT

(10) International Publication Number
WO 00/77429 A1

(51) International Patent Classification: F16K 15/14,
7/02, 7/04, 7/07, B60C 29/00, B32B 3/24

(74) Agent: GRIFFITH HACK; 168 Walker Street, North
Sydney, NSW 2001 (AU).

(21) International Application Number: PCT/AU00/00659

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE,
DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU,
ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS,
LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO,
NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR,
TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(22) International Filing Date: 14 June 2000 (14.06.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PQ 4713 15 June 1999 (15.06.1999) AU
PQ 2387 23 August 1999 (23.08.1999) AU

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG,
CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): IP. ONE
PTY. LTD. [AU/AU]; Level 2, 154 Elizabeth Street, Syd-
ney, NSW 2000 (AU).

Published:


— With international search report.

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): HORTON, David
[US/AU]; 35 Alexandra Street, Drummoyne, NSW 2047
(AU).

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: A NON-RETURN VALVE



WO 00/77429 A1

(57) Abstract: A non-return valve (10), typically of commonly called duckbill valve shape, comprising a valve body (12) and a valve membrane (14). The valve body (12) is generally tubular and includes an elongate passageway (16) with inlet (18) and outlet (20) at opposing ends. The valve membrane (14) is of a generally conical-shaped diaphragm formed integrally with the valve body (12). The diaphragm (14) has a collapsible opening or aperture (22) located at or adjacent the cones apex. The conical diaphragm (14) is oriented with its apex pointing downstream. The resiliently flexible material from which the diaphragm (14) is constructed, ensures that the diaphragm (14) in a collapsed condition obstructs or closes the aperture (22) to prevent fluid flowing in a reverse direction, i.e. backflow towards the inlet. Pressurisation of fluid within the passageway (16) on the inlet (18) side of the diaphragm (14), deflects the diaphragm to open the aperture (22) so that fluid can flow through the passageway from the inlet (18) to the outlet (20) only. A membrane permeable in one direction only can also be made from a panel or sheeting incorporating many such collapsible non-return duckbill valves on the surface of the panel or sheet.