



(51) International Patent Classification:
C10G 3/00 (2006.01) *C10G 65/04* (2006.01)

(21) International Application Number:
PCT/US2009/006695

(22) International Filing Date:
23 December 2009 (23.12.2009)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/203,627 24 December 2008 (24.12.2008) US
12/653,459 15 December 2009 (15.12.2009) US

(71) Applicant (for all designated States except US):
EXXONMOBIL RESEARCH AND ENGINEERING COMPANY [US/US]; 1545 Route 22 East, P.O. Box 900, Annandale, NJ 08801-0900 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **COLE, Kathryn, Y.** [US/US]; 26 North 14th Street, Easton, PA 18042 (US). **LEWIS, William, E.** [US/US]; 6933 East Fieldgate Court, Baton Rouge, LA 70808 (US).

(74) Agents: **WEISBERG, David, M.** et al.; Exxonmobil Research And Engineering Company, 1545 Route 22 East, P.O. Box 900, Annandale, NJ 08801-0900 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(88) Date of publication of the international search report:
26 May 2011

(54) Title: CO-PROCESSING OF DIESEL BIOFEED AND HEAVY OIL




FIG. 1

(57) Abstract: Processes are provided for producing a diesel fuel product having a sulfur content of 10 ppm by weight or less from feed sources that include up to 50% by weight of a biocomponent feedstock. The biocomponent feedstock is co-processed with a heavy oil feed in a severe hydro treating stage. The product from the severe hydrotreatment stage is fractionated to separate out a diesel boiling range fraction, which is then separately hydrotreated.