

DESCRIPTION

DETERIORATION DETERMINATION DEVICE OF LIQUID PUMPING APPARATUS, AND LIQUID PUMPING APPARATUS

5

TECHNICAL FIELD

[0001]

The present application relates to a deterioration determination device that determines the degree of deterioration of a liquid pumping apparatus.

10

BACKGROUND ART

[0002]

A liquid pumping apparatus that recovers liquid generated in a steam system and pumps the liquid to a utilization side under a pressure of working gas has been known as disclosed by, for example, Patent Document 1. The liquid pumping apparatus of Patent Document 1 includes a hermetic container which stores a drain generated in and flowed from the steam system, a float contained in the hermetic container, a feed valve for supplying steam, and an exhaust valve for releasing the steam. The float is connected to the feed valve and the exhaust valve via a valve operating mechanism (a float arm and a snap mechanism). In this liquid pumping apparatus, the float moves up and down according to the level of the drain, and the feed valve and the exhaust valve are operated in response to the upward and downward movement of the float. When the float moves up to a predetermined high level, the feed valve is opened, and the exhaust valve is closed. Then, the steam is introduced into the hermetic container, and the drain is pumped from the hermetic

15

20

25

container under the pressure of the steam (pumping stroke). When the float moves down to a predetermined low level, the feed valve is closed, and the exhaust valve is opened. Then, the drain flows into the hermetic container to be stored therein, and the steam is released from the hermetic container (inflow stroke).

5

CITATION LIST

PATENT DOCUMENT

[0003]

[Patent Document 1] Japanese Unexamined Patent Publication No. H08-145290

10

SUMMARY OF THE INVENTION

TECHNICAL PROBLEM

[0004]

In the above-described liquid pumping apparatus, internal components of the valve operating mechanism are inevitably deteriorated due to wear or foreign matters (such as rust and scale) attached or deposited thereon. The internal components, if left deteriorated, eventually make the feed valve and the exhaust valve unable to be opened or closed, and the drain (liquid) cannot be pumped. To avoid such pumping failure, it is important to detect the degree of deterioration of the internal components to estimate the life of the liquid pumping apparatus in advance. So far, the life of the liquid pumping apparatus has been estimated based on the number of operations of the liquid pumping apparatus (e.g., the number of opening and closing of the feed valve and the exhaust valve). However, this estimation method has been disadvantageous because the degree of deterioration of the internal components differs depending on the type and state of the liquid used, and the life cannot always

be estimated accurately.

[0005]

Under these circumstances, the present disclosure has been achieved to determine the degree of deterioration of the liquid pumping apparatus.

5 SOLUTION TO THE PROBLEM

[0006]

The present disclosure is directed to a deterioration determination device of a liquid pumping apparatus including a casing, a feed valve, an exhaust valve, and a valve operating mechanism. The casing forms a reservoir space for storing liquid
10 flowed thereto. The feed valve introduces working gas into the reservoir space. The exhaust valve releases the working gas from the reservoir space. The valve operating mechanism has a float arranged in the reservoir space. Further, the valve operating mechanism performs a pumping stroke in which the liquid is pumped from the reservoir space under a pressure of the working gas by opening the feed valve and
15 closing the exhaust valve when the float moves up to a predetermined high level, and performs an inflow stroke in which the liquid flows into the reservoir space and the working gas is released from the reservoir space by closing the feed valve and opening the exhaust valve when the float moves down to a predetermined low level.

[0007]

20 The deterioration determination device includes a first pressure sensor, and a deterioration determination unit. The first pressure sensor is arranged to communicate with a lower portion of the reservoir space to detect a pressure of a liquid layer in the reservoir space. The deterioration determination unit determines a degree of deterioration of the valve operating mechanism based on a change in the
25 pressure detected by the first pressure sensor.

[0008]

The present disclosure is also directed to a liquid pumping apparatus including the above-described deterioration determination device.

ADVANTAGES OF THE INVENTION

5 [0009]

The deterioration determination device and liquid pumping apparatus of the present application can determine the degree of deterioration of the liquid pumping apparatus.

10 BRIEF DESCRIPTION OF DRAWINGS

[0010]

[FIG. 1] FIG. 1 is a cross-sectional view illustrating a schematic configuration of a liquid pumping apparatus according to an embodiment.

15 [FIG. 2] FIG. 2 is a cross-sectional view illustrating a schematic configuration of a feed valve and an exhaust valve in an enlarged scale.

[FIG. 3] FIG. 3 is a graph showing a change in pressure of a storage space over time according to an embodiment.

[FIG. 4] FIG. 4 is a view corresponding to FIG. 3, illustrating a change in pressure of a reservoir space over time according to a variation of an embodiment.

20

DESCRIPTION OF EMBODIMENTS

[0011]

Embodiments of the present application will be described below with reference to the drawings. The embodiments below are merely exemplary ones in
25 nature, and are not intended to limit the scope, applications, or use of the present

disclosure.

[0012]

A liquid pumping apparatus 1 of the present embodiment is provided for a steam system, for example, and recovers a drain (condensation) generated as a result of condensation of steam to pump the drain to a boiler or a waste heat utilization system. Specifically, in the present embodiment, the drain corresponds to liquid recited in the claims of the present application. As shown in FIG. 1, the liquid pumping apparatus 1 includes a casing 10 which is a hermetic container, a feed valve 20, an exhaust valve 30, a valve operating mechanism 40, and a deterioration determination device 70.

[0013]

The casing 10 has a body 11 and a lid 12 connected together with bolts, and forms a reservoir space 13 for storing the drain (liquid) flowed thereto. The lid 12 is provided with a liquid inlet 14 into which the drain flows, a liquid outlet 15 from which the drain is pumped (released), a gas inlet 16 into which the steam is introduced, and a gas outlet 17 from which the steam is released. In this embodiment, the steam corresponds to working gas recited in the claims of the present application. The liquid inlet 14 is formed close to an upper portion of the lid 12, and the liquid outlet 15 is formed in a lower portion of the lid 12. Both of the gas inlet 16 and the gas outlet 17 are formed in the upper portion of the lid 12. All these ports such as the liquid inlet 14 communicate with the reservoir space 13.

[0014]

As also shown in FIG. 2, the gas inlet 16 is provided with the feed valve 20, and the gas outlet 17 is provided with the exhaust valve 30. The feed valve 20 opens and closes the gas inlet 16, and the exhaust valve 30 opens and closes the gas outlet

17. The feed valve 20 introduces the steam from the gas inlet 16 into the reservoir space 13 to pump the drain from the reservoir space 13 through the liquid outlet 15. The exhaust valve 30 releases the steam that has introduced into the reservoir space 13 from the gas outlet 17.

5 [0015]

The feed valve 20 has a valve case 21, a valve body 22, and a hoisting rod 23. The valve case 21 has a through hole penetrating in an axial direction thereof, and a valve seat 24 formed at the top of the through hole. An opening 25 that allows the through hole to communicate with the outside is formed in a middle portion of the
10 valve case 21. The valve body 22 is formed in a spherical shape, and integrally provided at a top end of the hoisting rod 23. The hoisting rod 23 is inserted in the through hole of the valve case 21 to be movable up and down. When the hoisting rod 23 moves up, the valve body 22 of the feed valve 20 is separated from the valve seat 24 to open the gas inlet 16. When the hoisting rod 23 moves down, the valve body 22
15 is seated on the valve seat 24 to close the gas inlet 16.

[0016]

The exhaust valve 30 has a valve case 31, a valve body 32, and a hoisting rod 33. The valve case 31 has a through hole penetrating in an axial direction thereof, and a valve seat 34 formed in a slightly upper portion of the through hole. An
20 opening 35 that allows the through hole to communicate with the outside is formed in the valve case 31. The valve body 32 is formed in a substantially hemispherical shape, and integrally provided at a top end of the hoisting rod 33. The hoisting rod 33 is inserted in the through hole of the valve case 31 to be movable up and down. When the hoisting rod 33 moves up, the valve body 32 of the exhaust valve 30 is
25 seated on the valve seat 34 to close the gas outlet 17. When the hoisting rod 33

moves down, the valve body 32 is separated from the valve seat 34 to open the gas outlet 17.

[0017]

A valve operating rod 36 is coupled to a bottom end of the hoisting rod 33 of the exhaust valve 30. Specifically, the hoisting rod 33 of the exhaust valve 30 moves up and down as the valve operating rod 36 moves up and down. To the valve operating rod 36, a connector plate 37 extending to a region below the hoisting rod 23 of the feed valve 20 is attached. When the valve operating rod 36 moves up, the connector plate 37 lifts the hoisting rod 23 of the feed valve 20 up. When the valve operating rod 36 moves down, the connector plate 37 also moves down, and the valve operating rod 36 also moves down under its own weight. Specifically, when the valve operating rod 36 moves up, the feed valve 20 is opened (valve opening), and the exhaust valve 30 is closed (valve closing). When the valve operating rod 36 moves down, the feed valve 20 is closed (valve closing), and the exhaust valve 30 is opened (valve opening).

[0018]

The valve operating mechanism 40 is arranged in the casing 10, and allows the valve operating rod 36 to move up and down to open and close the feed valve 20 and the exhaust valve 30. The valve operating mechanism 40 has a float 41 and a snap mechanism 50.

[0019]

The float 41 is formed in a spherical shape, and has a lever 42 attached thereto. The lever 42 is rotationally supported by an axis 43 provided for a bracket 44. The lever 42 has an axis 45 provided at an end opposite to the float 41. The snap mechanism 50 has a float arm 51, a sub-arm 52, a coil spring 53, and two receiving

members 54, 55. The float arm 51 has one end rotatably supported by an axis 58 provided for a bracket 59. The brackets 44, 59 are connected together with screws, and attached to the lid 12. The other end of the float arm 51 has a groove 51a, in which the axis 45 of the lever 42 fits. This configuration allows the float arm 51 to swing about the axis 58 as the float 41 moves up and down.

[0020]

The float arm 51 has an axis 56. The sub-arm 52 has a top end rotatably supported by the axis 58, and a bottom end provided with an axis 57. The receiving member 54 is rotatably supported by the axis 56 of the float arm 51, and the receiving member 55 is rotatably supported by the axis 57 of the sub-arm 52. The coil spring 53 in a compressed state is attached between the receiving members 54, 55. The sub-arm 52 is provided with an axis 61, to which a bottom end of the valve operating rod 36 is coupled.

[0021]

The valve operating mechanism 40 configured in this manner is displaced as the float 41 moves up and down, and allows the valve operating rod 36 to move up and down to open and close the feed valve 20 and the exhaust valve 30. More specifically, in the liquid pumping apparatus 1, the float 41 is positioned at the bottom of the reservoir space 13 when no drain is stored in the reservoir space 13. In this state, the valve operating rod 36 has moved down, the feed valve 20 is closed, and the exhaust valve 30 is open. When generated in the steam system, the drain flows into the liquid inlet 14 to be stored in the reservoir space 13 (inflow stroke). In the inflow stroke, the float 41 moves up as the amount of drain stored in the reservoir space 13 increases. In addition, the steam is released from the gas outlet 17 as the amount of drain stored in the reservoir space 13 increases. Then, when the float 41

moves up to a predetermined high level (upper reversal position), the snap mechanism 50 causes the valve operating rod 36 to move up. As a result, the feed valve 20 is opened, the exhaust valve 30 is closed, the inflow stroke ends, and a pumping stroke starts.

5 [0022]

When the feed valve 20 is opened, the steam (high-pressure steam) in the steam system is introduced into an upper portion of the reservoir space 13 (space above the drain) through the gas inlet 16. The drain stored in the reservoir space 13 is then pushed downward by the pressure of the introduced gas, and pumped from the liquid outlet 15 (pumping stroke). The drain pumped by the liquid pumping apparatus 1 is supplied to a boiler or a waste heat utilization system. When the drain is pumped (released) out and the level of the drain in the reservoir space 13 is lowered, the float 41 moves down. Then, when the float 41 moves down to a predetermined low level (lower reversal position), the snap mechanism 50 causes the valve operating rod 36 to move down. As a result, the feed valve 20 is closed, the exhaust valve 30 is opened, the pumping stroke ends, and the inflow stroke restarts. That is, again, the drain flows into the liquid inlet 14 to be stored in the reservoir space 13, and the steam is released from the reservoir space 13 through the gas outlet 17.

[0023]

20 In this manner, the valve operating mechanism 40 in the liquid pumping apparatus 1 opens and closes the feed valve 20 and the exhaust valve 30 to alternately perform the inflow stroke and the pumping stroke.

[0024]

25 The deterioration determination device 70 is configured to determine the degree of deterioration of the liquid pumping apparatus 1 (valve operating

mechanism 40). The deterioration determination device 70 includes a first pressure sensor 71, a second pressure sensor 72, and a device body 73.

[0025]

The two pressure sensors 71, 72 detect the pressure of the reservoir space 13.

5 The first pressure sensor 71 is provided at a lower portion of the body 11 of the casing 10, and communicates with an almost lowermost portion of the reservoir space 13. Specifically, the first pressure sensor 71 detects the pressure of a liquid layer in the reservoir space 13, i.e., the pressure of a region of the reservoir space 13 where the drain, which is one of the drain (liquid) or the steam (working gas), is
10 present. The second pressure sensor 72 is provided at an upper portion of the body 11 of the casing 10, and communicates with an almost uppermost portion of the reservoir space 13. Specifically, the second pressure sensor 72 detects the pressure of a gaseous layer in the reservoir space 13, i.e., the pressure of a region of the reservoir space 13 where the steam, which is one of the drain (liquid) or the steam
15 (working gas), is present.

[0026]

The device body 73 includes a state determination unit 74 and a deterioration determination unit 75. The state determination unit 74 is configured to determine an operating state of the liquid pumping apparatus 1, i.e., which of the inflow stroke and
20 the pumping stroke is performed.

[0027]

The state determination unit 74 determines whether the liquid pumping apparatus 1 is in an operating state of performing the inflow stroke or the pumping stroke based on the pressure detected by the second pressure sensor 72. The state
25 determination unit 74 successively receives the pressure detected by the second

pressure sensor 72. More specifically, the state determination unit 74 determines that the pumping stroke is performed from when a predetermined amount of pressure rise is detected to when a predetermined amount of pressure drop is detected by the second pressure sensor 72. Further, the state determination unit 74 determines that the pumping stroke is performed from when a predetermined amount of pressure drop is detected to when a predetermined amount of pressure rise is detected by the second pressure sensor 72.

[0028]

Referring to FIG. 3, how the state determination unit 74 makes the determination will be described in detail below. The pressure detected by the second pressure sensor 72 (pressure of the gaseous layer in the reservoir space 13) changes over time as indicated by a solid line A shown in FIG. 3. In the inflow stroke, the drain flows into the reservoir space 13 and the steam is released from the reservoir space 13, and thus, the pressure detected by the second pressure sensor 72 remains at a substantially constant value. When the float 41 moves up to the predetermined high level (upper reversal position), the inflow stroke is switched to the pumping stroke (upper reversal point t_a). When the stroke is switched to the compression stroke, high-pressure steam is introduced into the reservoir space 13, and the pressure of the high-pressure steam pumps the drain out. Thus, the pressure detected by the second pressure sensor 72 becomes higher than that detected in the inflow stroke. Specifically, the second pressure sensor 72 detects the pressure instantaneously increased by a predetermined amount at the upper reversal point t_a . In the pumping stroke, the pressure detected by the second pressure sensor 72 remains at a substantially constant value.

[0029]

When the float 41 moves down to the predetermined low level (lower reversal position), the pumping stroke is switched again to the inflow stroke (lower reversal point tb). When the stroke is switched to the inflow stroke, the high-pressure steam is not introduced any more, and again, the drain flows into the reservoir space and the steam is released from the reservoir space as described above. Thus, the pressure detected by the second pressure sensor 72 becomes lower than that detected in the pumping stroke. Specifically, the second pressure sensor 72 detects the pressure instantaneously decreased by a predetermined amount at the lower reversal point tb.

[0030]

Thus, the state determination unit 74 can determine that the pumping stroke is performed from when a predetermined amount of pressure rise is detected to when a predetermined amount of pressure drop is detected by the second pressure sensor 72. Further, the state determination unit 74 can determine that the inflow stroke is performed from when a predetermined amount of pressure drop is detected to when a predetermined amount of pressure rise is detected by the second pressure sensor 72. In addition, the state determination unit 74 can determine that a point of time when the predetermined amount of pressure rise is detected by the second pressure sensor 72 is the upper reversal point ta, and a point of time when the predetermined amount of pressure drop is detected by the second pressure sensor 72 is the lower reversal point tb. In this way, the operating state of the liquid pumping apparatus 1 can be determined.

[0031]

For example, when the operating state of the liquid pumping apparatus 1 is monitored to detect signs of failure or abnormality of the liquid pumping apparatus 1 before the failure or abnormality actually occurs, criteria for detecting the signs

differ depending on the operating state. Thus, if the operating state can be determined in the above-described manner, the signs can be detected accurately based on the criteria appropriate for the operating states.

[0032]

5 The second pressure sensor 72, which is configured to detect the pressure of the gaseous layer in the reservoir space 13, can detect the pressure without being influenced by, for example, a shake of the drain (liquid) in the reservoir space 13. Therefore, determination can be performed with high accuracy.

[0033]

10 The deterioration determination unit 75 is configured to determine the degree of deterioration of the valve operating mechanism 40 based on a change in the pressure detected by the first pressure sensor 71. Specifically, the deterioration determination unit 75 determines the degree of deterioration of the valve operating mechanism 40 based on a differential pressure ΔP obtained by subtracting the
15 pressure detected by the second pressure sensor 72 from the pressure detected by the first pressure sensor 71.

[0034]

 Referring to FIG. 3, how the deterioration determination unit 75 performs the determination will be described in detail below. The first pressure sensor 71
20 communicates with the drain (liquid) in the reservoir space 13. Thus, as indicated by a rough broken line B in FIG. 3, the first pressure sensor 71 detects a pressure higher by a head of the drain than the pressure detected by the second pressure sensor 72. In the inflow stroke, the drain flows into the reservoir space to be stored therein, which gradually raises the head of the drain and the pressure detected by the first pressure
25 sensor 71. In the pumping stroke, the drain is pumped (released) from the reservoir

space, which gradually lowers the head of the drain and the pressure detected by the first pressure sensor 71. Just like the second pressure sensor 72, the first pressure sensor 71 detects the pressure instantaneously increased by a predetermined amount at the upper reversal point t_a , and the pressure instantaneously decreased by a predetermined amount at the lower reversal point t_b .

[0035]

In the compression stroke, the head reaches the maximum head H_{max} at the upper reversal point t_a , and the minimum head H_{min} at the lower reversal point t_b . Also in the inflow stroke, the head reaches the maximum head H_{max} at the upper reversal point t_a , and the minimum head H_{min} at the lower reversal point t_b . The maximum head H_{max} and the minimum head H_{min} in the compression stroke are respectively equal to the maximum head H_{max} and the minimum head H_{min} in the inflow stroke.

[0036]

In the valve operating mechanism 40, if a joint or any other portion of the float 41 or snap mechanism 50 is deteriorated due to wear or foreign matters (such as rust and scale) attached or deposited thereon, the displacement of the components decreases. For example, the upward and downward movements of the float 41 in accordance with the level of the drain in the reservoir space 13 decrease, or the movement of the float arm 51 of the snap mechanism 50 in response to the upward and downward movements of the float 41 decreases. This delays the opening (or closing) of the feed valve 20 and the exhaust valve 30 by the valve operating mechanism 40. Specifically, the upper reversal position at which the feed valve 20 is opened and the exhaust valve 30 is closed is shifted to a position higher than the predetermined high level, and the lower reversal position at which the feed valve 20

is closed and the exhaust valve 30 is opened is shifted to a position lower than the predetermined low level. The amount of shift increases with the increase in the degree of deterioration of the valve operating mechanism 40.

[0037]

5 Thus, when the valve operating mechanism 40 is deteriorated, the pressure detected by the first pressure sensor 71 varies as indicated by a fine broken line Bx shown in FIG. 3. Specifically, the head (maximum head Hmax) at the upper reversal point t_a is raised, and the head (minimum head Hmin) at the lower reversal point t_b is lowered. Therefore, due to the deterioration of the valve operating mechanism 40,
10 the pressure detected by the first pressure sensor 71 at the upper reversal point t_a increases, and the pressure detected by the first pressure sensor 71 at the lower reversal point t_b decreases.

[0038]

 The deterioration determination unit 75 determines that the valve operating
15 mechanism 40 has been deteriorated when at least one of the following conditions is met. The conditions include: a condition that the differential pressure ΔP (pressure detected by the first pressure sensor 71 – pressure detected by the second pressure sensor 72) is larger than a differential pressure ΔP at the time when the inflow stroke is normally switched to the pumping stroke; and a condition that the differential
20 pressure ΔP is smaller than a differential pressure ΔP at the time when the pumping stroke is normally switched to the inflow stroke. The differential pressure ΔP at the time when the inflow stroke is normally switched to the pumping stroke is a differential pressure ΔP at the upper reversal point t_a in a normal state, i.e., the maximum head Hmax in the normal state. The differential pressure ΔP at the time
25 when the pumping stroke is normally switched to the inflow stroke is a differential

pressure ΔP at the lower reversal point t_b in the normal state, i.e., the minimum head H_{min} in the normal state.

[0039]

As indicated by the broken line Bx in FIG. 3, when the valve operating mechanism 40 is deteriorated, the differential pressure ΔP is larger than the maximum head H_{max} in the normal state for a certain period of time, and is smaller than the minimum head H_{min} in the normal state for a certain period of time. In the normal state, the differential pressure ΔP does not exceed the maximum head H_{max} , or falls below the minimum head H_{min} , at any time. Therefore, the valve operating mechanism 40 can be determined to be deteriorated when the differential pressure ΔP is detected to be larger than the maximum head H_{max} , or smaller than the minimum head H_{min} . Note that the deterioration determination unit 75 stores the values of the maximum head H_{max} and the minimum head H_{min} in the normal state in advance.

[0040]

As can be seen in the foregoing, when the valve operating mechanism 40 is deteriorated, the head at the upper reversal point t_a is raised and the head at the lower reversal point t_b is lowered, which changes the pressure detected by the first pressure sensor 71. Therefore, the valve operating mechanism 40 can be determined (detected) to be deteriorated based on the change in the pressure detected by the first pressure sensor 71.

[0041]

(Variations of Embodiment)

In the present disclosure, the deterioration determination unit 75 of the above embodiment may be configured in the following manner.

[0042]

The deterioration determination unit 75 of the above embodiment has been configured to determine the degree of deterioration of the valve operating mechanism 40 based on the difference between the differential pressure ΔP and the maximum head $H_{\max}$ or the minimum head $H_{\min}$ in the normal state, irrespective of the operating state such as the upper reversal point t_a and the lower reversal point t_b . Alternatively, the deterioration determination unit 75 may be configured to determine that the valve operating mechanism 40 is deteriorated when the differential pressure ΔP at the upper reversal point t_a is larger than the maximum head $H_{\max}$ in the normal state, or the differential pressure ΔP at the lower reversal point t_b is smaller than the minimum head $H_{\min}$ in the normal state. The upper and lower reversal points t_a and t_b are determined by the state determination unit 74. In this case, the differential pressure ΔP may be calculated only at the upper and lower reversal points t_a and t_b .

[0043]

As another variation, as shown in FIG. 4, the deterioration determination unit 75 may be configured to determine that the valve operating mechanism 40 is deteriorated when an amount of change ΔP_x in the pressure detected by the first pressure sensor 71 in the entire inflow stroke or pumping stroke is larger than an amount of change ΔP_b in the normal state. The amount of change ΔP_x is a value obtained by subtracting the pressure P_{x2} detected by the first pressure sensor 71 at the lower reversal point t_b from the pressure P_{x1} detected by the first pressure sensor 71 at the upper reversal point t_a . The amount of change ΔP_b is a value obtained by subtracting the pressure P_{b2} detected by the first pressure sensor 71 at the lower reversal point t_b from the pressure P_{b1} detected by the first pressure sensor 71 at the upper reversal point t_a in the normal state. In this case, the state determination unit

74 determines the upper reversal point t_a and the lower reversal point t_b .

[0044]

As another variation, as shown in FIG. 4, the deterioration determination unit 75 may be configured to determine that the valve operating mechanism 40 is deteriorated when the pressure P_{x1} detected by the first pressure sensor 71 at the upper reversal point t_a is larger than the pressure value P_{b1} detected in the normal state at the upper reversal point t_a , or when the pressure P_{x2} detected by the first pressure sensor 71 at the lower reversal point t_b is smaller than the pressure value P_{b2} in the normal state at the lower reversal point t_b . Also in this case, the state determination unit 74 determines the upper and lower reversal points t_a and t_b .

[0045]

The variations described above can also provide the same advantages as those of the embodiment.

[0046]

In the embodiment and variations described above, it has been described that the working gas is the steam. However, as a matter of course, any other types of gas may be used in the present disclosure.

[0047]

In the embodiment and variations described above, it has been described that the liquid to be pumped is the drain. However, any other types of liquid may be used in the present disclosure.

INDUSTRIAL APPLICABILITY

[0048]

The present application is useful for a deterioration determination device that

determines the degree of deterioration of a liquid pumping apparatus.

DESCRIPTION OF REFERENCE CHARACTERS

[0049]

- 5 1 Liquid pumping apparatus
- 10 Casing
- 13 Reservoir space
- 20 Feed valve
- 30 Exhaust valve
- 10 40 Valve Operating Mechanism
- 41 Float
- 70 Deterioration determination device
- 71 First pressure sensor
- 72 Second pressure sensor
- 15 74 State determination unit
- 75 Deterioration determination unit
- ΔP Differential pressure
- $\Delta P_b, \Delta P_x$ Amount of change

CLAIMS

1. A deterioration determination device for a liquid pumping apparatus comprising:

5 a casing that forms a reservoir space for storing liquid flowed thereto;
a feed valve that introduces working gas into the reservoir space;
an exhaust valve that releases the working gas from the reservoir space; and
a valve operating mechanism having a float arranged in the reservoir space, and
performing a pumping stroke in which the liquid is pumped from the reservoir space
10 under a pressure of the working gas by opening the feed valve and closing the exhaust
valve when the float moves up to a predetermined high level, and an inflow stroke in
which the liquid flows into the reservoir space and the working gas is released from
the reservoir space by closing the feed valve and opening the exhaust valve when the
float moves down to a predetermined low level, wherein

15 the deterioration determination device comprising:

a first pressure sensor arranged to communicate with a lower portion of the
reservoir space to detect a pressure of a liquid layer in the reservoir space;

a deterioration determination unit that determines a degree of deterioration of
the valve operating mechanism based on a change in the pressure detected by the first
20 pressure sensor; and

a second pressure sensor arranged to communicate with an upper portion of the
reservoir space to detect a pressure of a gaseous layer in the reservoir space, wherein

the deterioration determination unit determines the degree of deterioration of
the valve operating mechanism based on a differential pressure obtained by
25 subtracting the pressure detected by the second pressure sensor from the pressure
detected by the first pressure sensor.

2. The deterioration determination device of claim 1, wherein

the deterioration determination unit determines that the valve operating mechanism is deteriorated when at least one of conditions is met, the conditions including a condition that the differential pressure is larger than a differential pressure at the time when the inflow stroke is normally switched to the pumping stroke, and a condition that the differential pressure is smaller than a differential pressure at the time when the pumping stroke is normally switched to the inflow stroke.

3. A deterioration determination device for a liquid pumping apparatus comprising:

a casing that forms a reservoir space for storing liquid flowed thereto;

a feed valve that introduces working gas into the reservoir space;

an exhaust valve that releases the working gas from the reservoir space; and

a valve operating mechanism having a float arranged in the reservoir space, and performing a pumping stroke in which the liquid is pumped from the reservoir space under a pressure of the working gas by opening the feed valve and closing the exhaust valve when the float moves up to a predetermined high level, and an inflow stroke in which the liquid flows into the reservoir space and the working gas is released from the reservoir space by closing the feed valve and opening the exhaust valve when the float moves down to a predetermined low level, wherein

the deterioration determination device comprising:

a first pressure sensor arranged to communicate with a lower portion of the reservoir space to detect a pressure of a liquid layer in the reservoir space; and

5 a deterioration determination unit that determines a degree of deterioration of the valve operating mechanism based on a change in the pressure detected by the first pressure sensor, wherein

the deterioration determination unit determines that the valve operating mechanism is deteriorated when an amount of change in the pressure detected by the first pressure sensor in the entire inflow stroke or pumping stroke is larger than an
10 amount of change in the pressure in a normal state.

4. The deterioration determination device of any one of claims 1 to 3, further comprising:

a state determination unit which determines that the liquid pumping apparatus
15 is in an operating state of performing the pumping stroke from when a predetermined amount of pressure rise is detected to when a predetermined amount of pressure drop

is detected by the first or second pressure sensor, and that the liquid pumping apparatus is in an operating state of performing the inflow stroke from when a predetermined amount of pressure drop is detected to when a predetermined amount of pressure rise is detected by the first or second pressure sensor.

5

5. A liquid pumping apparatus, comprising:

a casing that forms a reservoir space for storing liquid flowed thereto;

a feed valve that introduces working gas into the reservoir space;

an exhaust valve that releases the working gas from the reservoir space;

10 a valve operating mechanism having a float arranged in the reservoir space, and performing a pumping stroke in which the liquid is pumped from the reservoir space under a pressure of the working gas by opening the feed valve and closing the exhaust valve when the float moves up to a predetermined high level, and an inflow stroke in which the liquid flows into the reservoir space and the working gas is released from
15 the reservoir space by closing the feed valve and opening the exhaust valve when the float moves down to a predetermined low level; and

the deterioration determination device of any one of claims 1 to 4.