

**FASTENER SYSTEM COMPRISING AN EXTERNALLY
THREADED BOLT AND AN INTERNALLY THREADED NUT
FOR THE AVOIDANCE OF CROSS-THREADING OF THE
MATING THREADS DURING ASSEMBLY**

5 **CROSS-REFERENCE TO RELATED APPLICATION**

This application claims benefit of U.S. Provisional Application No. 61/987,138, filed on May 1, 2015, the contents of which is hereby incorporated by reference herein.

BACKGROUND OF THE INVENTION

10 In general and with reference to Fig. 1 it is recognized that an assembly that requires a bolt thread 1, of standard proportions, to be inserted into a pre-threaded nut 2, of standard proportions, can often result in a condition where the crest of the bolt thread 10, 10a makes initial contact with the root of the nut thread. The counter rotation of the nut and bolt threads may then cause the threads to jam into each other 3, 3a and will further restrict the action of the mating threads from achieving relative axial movement of the nut anchor and the bolt. As is well known to those skilled in 15 the art, this action is termed "cross threading".

As will be appreciated by those skilled in the art, cross threading becomes more prevalent where the axes of the bolt thread 4 and the nut thread 5 are out of angular alignment at the initial point of assembly. It requires only a small 20 misalignment of axes 4 and 5 to create this adverse assembly condition.

Many attempts have been introduced to bolt lead entry threads and/or nut entry threads, to overcome this adverse assembly condition. Exemplary anti-cross threading devices are described in United States Patent Nos. 7,334,975, entitled FASTENER 25 ASSEMBLY, by Jungman, et al, 7,438,512, entitled U-BOLT ASSEMBLY, by Jakuszeski, et al. and 5,836,731, entitled ANTI-CROSS THREADED FASTENER, by Goodwin et al, the contents of each are hereby incorporated by reference.

An example of the systems in current use can be viewed in relation to Fig. 2. Conventional systems rely upon changes to the bolt lead entry point geometrical 30 configuration 14 that is aimed toward encouraging the lead threads of the bolt to slide

over the nut thread root diameter and to assist in the mating threads creating thread pitch engagement and minimize cross threading. The above noted prior art recognizes that the circular (or radius) cross section of the lead entry threads 14 may not achieve this aim and anticipate that an additional plain dog point of circular cross section or of a special form that diminishes in magnitude as the section approaches the bolt entry end may be a requirement toward resisting nut and bolt threads from cross threading.

In each of these cases, the axial pitch 12 of the bolt lead entry threads are maintained at the same numerical value as the standard pitch of the bolt and nut threads. Without the extended point feature and with a small amount of misalignment between the nut and bolt axes, it remains a possibility for the initial assembly conditions as outlined and discussed in relation to Fig. 1 to be present and, due to the influence of the constant thread pitch 12, cross threading will still occur.

SUMMARY OF THE INVENTION

The present inventions relates to a fastener system aimed toward avoiding the cross-threading of a threaded bolt and a pre-tapped nut at the point of assembly and, in particular, to an innovative bolt lead entry point to achieve resistance to cross-threading at the point of assembly. More specifically, the present invention is directed to the development of a screw or bolt lead entry thread that is aimed toward inducing axial alignment of the nut and bolt threads, in an assembly, while eliminating the potential for the crest of the bolt thread 10 and 10a to have interference contact at the root diameter of the nut thread 11. Further, at initial assembly, the novel design of the lead entry point allows accelerated relative axial movement between the bolt thread 1 and the nut thread 2 and avoids the cross threading (jamming) of the nut and bolt threads.

BRIEF DESCRIPTION OF THE DRAWINGS

The organization and method of the invention together with further objects and advantages thereof can best be understood with reference to the following descriptions and accompanying drawings in which like reference numerals identify identical or functionally identical elements and in which:

Fig. 1, previously described, is a schematic diagram illustrating the conditions that take place and can that lead to the adverse assembly condition of cross threading;

Fig. 2, previously described, is a schematic diagram illustrating a prior art method aimed toward overcoming cross threading;

Fig. 3 is a schematic illustration of a bolt in accordance with an illustrative embodiment of the present invention; and

5 Fig. 4 an illustration of the effect that the variable pitch lead threads have in developing axial alignment of the nut and bolt threads in accordance with an illustrative embodiment of the present invention.

DETAILED DESCRIPTION OF AN ILLUSTRATIVE EMBODIMENT

10

The present disclosure should be considered as an exemplification of the principles of illustrative embodiments of the present invention and that it is not intended to limit the invention to those embodiments illustrated and described herein. The system and principles may be susceptible to embodiments in differing forms from those that are described in detail.

15

Referring again to Fig.1, there is shown a schematic illustration of a fastener system comprising a bolt in accordance with the present invention and a pre-threaded nut into which the bolt is to be assembled. It should be noted that while the description is written in terms of a bolt, any externally threaded fastener may be utilized in accordance with alternative embodiments of the present invention. It should further be noted that the description term 'nut' can be related to any internally threaded fastener that may be utilized in accordance with alternative embodiments of the present invention. As such, the description of a bolt and a nut as being utilized should be viewed as exemplary only.

20

25 The bolt and nut are being operatively assembled and whereby the bolt thread crest 10 contacts the nut thread root 11 and creates a potential thread interference, in these contact zones, where the bolt is rotated in a clockwise direction, relative to the nut, when viewed from the bolt head end of the assembly (denoted by arrow X) and due to the thread helix angles of the bolt and nut threads generated from the axial pitch 12 and major diameter 30 of the chosen thread, the bolt wants to move axially forward relative to the nut. However, due to the helix angles of both the nut thread and the bolt thread being of the same magnitude, the crest of the bolt thread maintains

30

its initial contact position with the root of the nut thread and creates an increasing interference in the contact zones. This increasing interference will cause the relative bolt and nut threads to seize or otherwise jam.

Referring again to Fig. 2, there is illustrated a proprietary system that has been developed to overcome this initial adverse assembly condition. The system, as illustrated, relates to a number of different patents, described and previously incorporated by reference above. The system illustratively has a bolt thread entry point pitch 12 that is of the same magnitude as the nut and bolt pitches 12. However, a noted disadvantage of such a system is that should the initial thread contact be that of allowing the bolt thread crest 10 to contact the nut thread root 11, a similar adverse assembly condition, to that previously outlined, can develop, i.e., the bolt and the nut may become cross threaded.

Referring to Fig. 3 of the drawings there is shown a schematic illustration of the bolt in accordance with an illustrative embodiment of the present invention that comprises a head 20, a shank (or body) portion 21 and a lead entry point 22. The head 20 can be of any configuration that may be used for developing rotational movement to the bolt by means of a fastener drive system. The shank portion 21 may be round or may have a lobular cross sectional area as is known to those skilled in the art.

The shank 21 illustratively has a thread 25 formed thereon. The thread 25 is illustratively generated as a helical form around a core 26 in a manner that contains a thread height 27 as being of a constant magnitude for a specified size of bolt. The helical thread generated is illustratively in accordance with a known international/national standards specification or may be in accordance with a proprietary threaded fastener system that may deviate from international and/or national standards specifications. The thread on the shank 21 illustratively has an axial pitch 12 that develops the thread helix angle 28 in relationship to the axial pitch 12 and the bolt thread outside diameter 30. The bolt thread 25 may extend over the length of the bolt shank or may extend over only a portion thereof.

In accordance with an illustrative embodiment of the present invention, the bolt thread pitch 12 is the same as the pitch of the pre-threaded nut that has been chosen by the assembly fabricator.

The bolt lead entry threads are illustratively of an outside diameter 31 that nominally equates to the nut thread root diameter 36. The thread diameter 31 is

1 nominally parallel in illustrative embodiments of the present invention. It is
2 recognized that for practical purposes, the outside circumscribing circle of the lead
3 threads 31 will be reduced below the inner diameter of the nut threads 36 such that the
4 bolt lead entry threads 22 can enter the nut threads 2 without designed interference
5 being present.

6 The lead entry point threads have a thread pitch 39 that equates to
7 approximately 1.562 times the thread axial pitch 12 of the body threads of the bolt in
8 accordance with an illustrative embodiment of the present invention. More generally,
9 the lead entry point thread pitch 39 may be within the range of approximately 1.40 to
10 1.60 times the body thread axial pitch 12.

11 Referring to Fig. 4 it will be seen that the lead entry threads 22 of the bolt do
12 not engage the thread profile 2 of the nut. They do make contact with the root
13 diameter of the nut thread 36 and due to their higher pitch 39 and subsequent helix
14 angle 38, when related to the nut helix angle 28, will accelerate the bolt axial
15 movement relative to the nut thread than would be the case if all threads were of the
16 same pitch.

17 When the accelerated forward movement takes place there is created axial
18 alignment of the nut and bolt axes such that the main body threads 25 approach and
19 contact the nut thread cavities 2 in a way that will eliminate the high potential for
20 cross threading that has been encountered with previously designed (prior art)
21 systems.

22 The geometrical construction of the bolt angle of the lead entry threads and the
23 manner, in which the body threads and the lead entry threads are interrelated, work to
24 ensure that the thread helix angle 38 of the lead entry threads is greater than the thread
25 helix angle 28 of the body threads. As can be seen in Fig. 4, should the insertion of
26 the bolt be at an angle that does not line up with the axis of the nut thread and should
27 the crest of the lead angle threads contact the root of the nut thread, the higher helix
28 angle of the bolt thread lead will accelerate the bolt threads forward at a rate that is
29 faster than would normally be achieved should the helix angles match. This action
30 will tend toward pulling the axes of the related threaded parts into alignment.

31 It can be further seen that the action of increasing the forward movement of
32 the lead entry threads relative to the nut threads will eliminate the potential for the
33 bolt thread crest to produce interference with the nut thread root and eliminate the
34 potential for cross threading, in the manner prescribed in the references to Fig. 1.

The main body threads will, under these conditions, achieve initial mating thread contact in an acceptable and prescribed manner and will eliminate the cross threading that has been seen as cause for concern.

What is claimed is:

CLAIMS

1. A system comprising:

a shank of a bolt, having an external thread formed to engage a pre-threaded internal thread in a nut member, wherein the external thread of the shank and the internal thread of the nut member have a same thread pitch and a same thread helix angle;

a lead entry point on the bolt, having a threaded entry point, wherein the threaded entry point has an entry point thread pitch higher in magnitude than the thread pitch of the shank and wherein the threaded entry point has an entry point helix angle higher in magnitude than the thread helix angle of the shank of the bolt;

wherein an outside diameter of the lead entry point is approximately below an inner thread diameter of the nut member; and

wherein the entry point thread pitch equals approximately 1.562 times the thread pitch.

2. A system comprising:

a shank of a bolt, having an external thread formed to engage a pre-threaded internal thread in a nut member, wherein the external thread of the shank and the internal thread of the nut member have a same thread pitch and a same thread helix angle;

a lead entry point on the bolt, having a threaded entry point, wherein the threaded entry point has an entry point thread pitch higher in magnitude than the thread pitch of the shank and wherein the threaded entry point has an entry point helix angle higher in magnitude than the thread helix angle of the shank of the bolt;

wherein an outside diameter of the lead entry point is approximately below an inner thread diameter of the nut member; and

wherein the entry point thread have a pitch that lies within the range of 1.4 to 1.6 times greater than the pitch of the body of the bolt threads.