



159159

WO2006/105832

PCT/EP2006/001850

Plug-in connection

Description

5

The invention relates to a plug-in connection which comprises a connector and an associated connector holder and is fastened in a front panel, and to a securing element that is suitable for it.

10

Various types of connectors are known in telecommunications and data technology. Examples are optical waveguide connectors, copper cable connectors or coaxial connectors for which associated matching connector holders respectively exist.

15

Various locking mechanisms have already been disclosed in order to prevent the connector from inadvertently being removed. By way of example, coaxial connectors are thus secured using a bayonet fitting with a $\frac{1}{4}$ turn. Three different variants of standard optical waveguide connectors having a ferrule diameter of 2.5 mm are known: the FC, the ST and the SC connector. The FC connector is screwed onto the coupling using a screw thread, for example. The ST connector has a bayonet lock, and the SC connector has a push-pull lock. Various types of SFF (Small Form Factor) connectors are also known. Examples of the latter are LC connectors, MU connectors or LX.5 connectors. Variants such as mini-duplex connectors (MT-RJ), where the connector comprises two glass fibers, also exist. These also have different locks. The mini-duplex connector and the MU connector have a push-pull lock, for example. All of these locking mechanisms protect the connector, to a greater or lesser extent, against inadvertently being removed. However, it is always possible to deliberately remove the connector. This constitutes a problem, however, in environments in which access can be



G00002

- 2 -

controlled to only a limited extent.

Therefore, the invention is based on the technical problem of providing a plug-in connection and a
5 securing element that is suitable for it, which connection is used to more reliably prevent a connector from being removed and can be used to remove the connector in a manner that does not go unnoticed.

10 The technical problem is solved by the subject matters having the features of patent claims 1 and 6. Further advantageous refinements of the invention can be found in the subclaims.

15 In this respect, a securing element is used to secure the connector against being pulled out when inserted in the connector holder, with the securing element having at least one latching element and at least one cover
20 part, with the latching element being used to connect the securing element to the connector holder and/or to the front panel in a captive manner, and with the cover part of the securing element covering a grip region of the connector and/or clamping the cable behind the grip
25 region. As a result of the securing element being connected to the front panel and/or to the connector holder in a captive manner, the securing element has to be destroyed in order to be removed. This in turn makes it possible to visually check, in a rapid and simple
30 manner, whether someone has tampered with the connector in an unauthorized manner. Although authorized service personnel also have to destroy the securing element, they can then fit a new securing element again after handling. The basic principle of the securing element is that, if the grip region of most connectors is not
35 accessible, it cannot be pulled. This applies equally to push-pull, bayonet, screw and latching connections. Alternatively or in addition, the cable of the

- 3 -

connector can be clamped behind the grip region. This results in the connector being fixed, at the front, by the latching element of the securing element and, at the back, by the clamping. This variant is preferably
5 used in connectors which could otherwise also be removed from the connector holder by pulling on the cable. One advantage over conceivable key-operated locks is the simple and cost-effective implementation. Appropriate color markings also make it possible to
10 sell the same securing elements to different customers, with the different colors making it possible to restrict misuse as a result of unauthorized passing on to third parties.

In one preferred embodiment, the securing element has a
15 cutout, so that the securing element can be pushed onto the connector that has been inserted. Subsequent securing can thus be carried out without having to pull the connector.

In another preferred embodiment, the connector is in
20 the form of an optical waveguide connector and the connector holder is in the form of a coupling or adapter, with a coupling being formed for the purpose of accommodating identical connectors, and an adapter being formed for the purpose of accommodating two
25 connectors of different types. In this case, it should be noted, in addition, that, sometimes in usage, the coupling is also even referred to as an adapter and the adapters are referred to as hybrid adapters. The coupling or the adapter is fastened in the front panel
30 using a front clip. The front clip can be used to unlock the coupling or the adapter from the front side. To this end, the front clip is preferably in two parts. As regards one preferred refinement of the front clip, reference is made to WO 02/27373 A1, to whose
35 disclosure reference is hereby expressly made. The latching element for the securing element is then latched into an opening in the front clip, with an

- 4 -

additional blocking element for the securing element preventing the front clip from being removed.

5 In another preferred embodiment, the connector is in the form of an SC or MU connector having a push-pull lock.

10 In another preferred embodiment, the connector holder is in the form of a coupling or an adapter onto which a laser shutter (which can be retrofitted) is plugged, with the cover part completely covering the grip region of the connector in the longitudinal direction. In other words, the securing element is preferably dimensioned in such a manner that, even when the laser shutter is used, this ensures that the grip region is completely covered. Such a laser shutter (which can be retrofitted) is disclosed, for example, in DE 102 19 892 A1 to which reference is expressly made as regards the design of the laser shutter.

15 20 The invention will be explained in more detail below using one preferred exemplary embodiment. In the figures:

25 Figure 1 shows a plug-in connection of an SC connector having a coupling, and

Figure 2 shows a perspective illustration of a securing element.

30 Figure 1 shows a perspective illustration of a plug-in connection 1 having a coupling 2. On the upper and lower faces, the coupling 2 has a respective flange 3, 4, by means of which the coupling 2 strikes against a front panel (not illustrated). In order to fasten the coupling to, and remove it from, the front panel, the coupling 2 has a two-part front clip 5, 6. This front clip 5, 6 is designed in such a manner that it uses latching hooks 7 to hook in behind the front panel and

- 5 -

thus fasten the coupling. Pressing the areas 8 (which are on the upper and lower faces of the coupling 2) together unlocks the front clip 5, 6 and thus the associated coupling 2. Attachments 11 comprising a laser shutter are also latched onto the front sides 9, 10 of the coupling 2. The attachments 11 can thus be used to subsequently form a coupling 2 having a laser shutter in a simple manner. A first SC connector 12 is inserted from the rear side of the coupling 2. The SC connector 12 comprises a grip region 13, kink protection 14 and the glass fiber cable 15. In order to pull the SC connector 12, the connector must be held at the grip region 13, that is to say the SC connector 12 cannot be removed by merely pulling on the kink protection 14 or on the glass fiber cable 15. To this end, the SC connector 12 is usually gripped and pulled on the grooved upper face 16 and lower face. However, it is also possible to hold and pull the SC connector 12 on the side surfaces. When inserted, a guide web 17, which is arranged on each of the side surfaces, is located in the slots (which are open to the outside) in the coupling 2. An SC connector 12, which, however, is secured using a securing element 20 (which is illustrated on its own in Figure 2), is likewise inserted from the front face of the coupling 2.

The securing element 20 has a planar rectangular upper face 21 and lower face 22. A cuboidal blocking element 23, on which a latching element 24 is located, is arranged on the upper face 21. The upper and lower faces 21, 22 are connected to one another via a side wall 25, whereas the other side has a cutout. The end face 26 (which is opposite the latching element 24) of the securing element 20 also has thickened regions 27, so that a stop edge 28 is formed at the end of the thickened regions 27.

- 6 -

As can now be seen in Figure 1, the latching element 24 latches into an opening in the front clip 5, with the blocking element 23 preventing the area 8 from being pressed down. It can also be seen that the upper face 21 and lower face 22 of the securing element 20 completely cover the grooved upper face 16 and lower face. The side wall 25 also covers the protruding part of one side surface of the SC connector 12. As a result, the SC connector 12 can no longer be pulled without destroying the securing element 20. The latter must then be pulled with great force until the latching element 24 shears off at the front clip 5.

In this case, the securing element 20 (which is preferably integral) is preferably made of plastic. In the exemplary embodiment illustrated in Figures 1 and 2, the upper face 21, lower face 22 and side wall 25 form the cover part of the securing element 20.

List of reference symbols

1	Plug-in connection
2	Coupling
3	Flange
4	Flange
5	Front clip
6	Front clip
7	Latching hook
8	Areas
9	Front face
10	Front face
11	Attachments
12	SC connector
13	Grip region of the SC connector
14	Kink protection
15	Glass fiber cable
16	Grooved upper face
17	Guide web
20	Securing element
21	Planar rectangular upper face
22	Planar rectangular lower face
23	Cuboidal blocking element
24	Latching element
25	Side wall
26	End face
27	Thickened regions
28	Stop edge

Plug-in connection

Patent Claims

5

1. A plug-in connection which comprises a connector and an associated connector holder and is fastened in a front panel,
characterized in that
10 a securing element (20) is used to secure the connector against being pulled out when inserted in the connector holder, with the securing element (20) having at least one latching element (24) and at least one cover part, with the latching element
15 (24) being used to connect the securing element (20) to the connector holder and/or the front panel in a captive manner, and with the cover part of the securing element (20) covering a grip region (13) of the connector and/or clamping the
20 cable (15) behind the grip region (13).
2. The plug-in connection as claimed in claim 1, characterized in that the securing element (20) has a cutout, so that the securing element (20)
25 can be pushed onto the connector that has been inserted.
3. The plug-in connection as claimed in claim 1 or 2, characterized in that the connector is in the form
30 of an optical waveguide connector and the connector holder is in the form of a coupling (2) or adapter, with the coupling (2) or the adapter being fastened in the front panel using a front clip (5, 6), the latching element (24) of the
35 securing element (20) being latched into the front clip (5, 6), and a blocking element (23) of the securing element (20) preventing the front clip (5, 6) from being removed.

4. The plug-in connection as claimed in one of the preceding claims, characterized in that the connector is in the form of an SC connector (12) or MU connector.
- 5
5. The plug-in connection as claimed in one of the preceding claims, characterized in that the connector holder is in the form of a coupling (2) or an adapter onto which a laser shutter (which can be retrofitted) is plugged, with the cover part completely covering the grip region (13) of the connector in the longitudinal direction.
- 10
6. A securing element (20) for securing a connector in a connector holder, comprising a cover part and a latching element (24).
- 15
7. The securing element as claimed in claim 6, characterized in that a blocking element (23) is arranged on the cover part, with the latching element (24) being arranged on said blocking element.
- 20