



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : H01G 9/12, 2/16	A1	(11) International Publication Number: WO 97/16837 (43) International Publication Date: 9 May 1997 (09.05.97)
(21) International Application Number: PCT/JP96/03093 (22) International Filing Date: 24 October 1996 (24.10.96) (30) Priority Data: 7/281266 30 October 1995 (30.10.95) JP (71) Applicant (for all designated States except US): MAT-SUSHITA ELECTRIC INDUSTRIAL CO., LTD. (JP/JP); 1006, Oaza Kadoma, Kadoma-shi, Osaka 571 (JP). (72) Inventors; and (75) Inventors/Applicants (for US only): YAMADA, Morihiro (JP/JP); 26-3, Nagao Nishimachi 3-chome, Hirakata-shi, Osaka 573-01 (JP). KURIMOTO, Hiroshi (JP/JP); 3-13-105, Mitsuya-cho, Hirakata-shi, Osaka 573 (JP). MINAMI, Masaharu (JP/JP); 9-162, Kohata Minamiyama, Uji-shi, Kyoto 611 (JP). (74) Agents: AOYAMA, Tamotsu et al.; Aoyama & Partners, IMP Building, 3-7, Shiromi 1-chome, Chuo-ku, Osaka-shi, Osaka 540 (JP).		(81) Designated States: CN, KR, SG, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report. With amended claims.

(54) Title: ELECTROLYTIC CAPACITOR WITH OPEN CIRCUIT MODE MECHANISM

(57) Abstract

An electrolytic capacitor (K1-K3) with an open circuit mode mechanism comprises: a metallic casing (32; 52; 62) for accommodating a capacitor element (31; 51; 61); an upper lid (33; 53; 63) which is mounted on a mouth of the metallic casing; a pair of metallic rivets (35; 54; 55) which are secured to the upper lid; a pair of external connection terminals (39; 55; 70) each of which is connected to one end portion of each of the metallic rivets; and a fixing member (40; 56; 71) which is molded by resin and is formed with a pair of through-holes (41; 57; 72) each for passing the other end portion of each of the metallic rivets therethrough such that the other end of each of the metallic rivets projecting out the fixing member is connected, by metallic junction, to each of a pair of lead-out lead plates (42; 58; 73) drawn from the capacitor element. In case pressure in the metallic casing rises due to a malfunction of the electrolytic capacitor, the upper lid is deformed by this rise of the pressure, so that the metallic rivets are lifted in a direction away from the capacitor element upon this deformation of the upper lid and thus, the metallic junction between the other end of each of the metallic rivets and each of the lead-out lead plates is cut off, thereby resulting in break of an electric circuit of the electrolytic capacitor.

