

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
13 June 2002 (13.06.2002)

PCT

(10) International Publication Number
WO 02/46344 A1

(51) International Patent Classification⁷: **C11D 1/835**,
3/04, 7/04, 7/08, 7/26, B08B 3/04, C23G 5/036, H01L
21/00

(21) International Application Number: PCT/US01/43171

(22) International Filing Date: 3 December 2001 (03.12.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/732,414 7 December 2000 (07.12.2000) US

(71) Applicant: **ASHLAND INC.** [US/US]; P.O. Box 2291,
Columbus, OH 43216 (US).

(72) Inventors: **PETERS, Daryl, W.**; 111 Kennedy Mill Road,
Stewartsville, NJ 08886-2402 (US). **ROVITO, Roberto,**
J.; 1435 Beverly Drive, Quakertown, PA 18951 (US).

(74) Agents: **CONNAUGHTON, Martin**; Ashland Inc., P.O.
Box 2219, Columbus, OH 43216 et al. (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM,
HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK,
LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX,
MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL,
TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR,
GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent
(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR,
NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.



162162



G00002

(54) Title: METHOD FOR CLEANING ETCHER PARTS

(57) Abstract: The invention relates to a method useful in removing etch residue from etcher equipment parts. The compositions used are aqueous, acidic compositions containing fluoride and polar, organic solvents. The compositions are free of glycols and hydroxyl amine and have a low surface tension and viscosity.

WO 02/46344 A1