

PROCESS FOR STEAM CRACKING HYDROCARBONS

PRIORITY CLAIM

[0001] This application claims the benefit of Provisional Application No. 62/436,626, filed December 20, 2016 and European Application No. 17159130.8, filed March 3, 2017, the disclosures of which are incorporated herein by their reference.

FIELD OF THE INVENTION

[0002] The present invention relates to processes for steam cracking hydrocarbons. In particular, the present invention relates to processes for producing alkenes from steam cracking hydrocarbons in a steam cracking furnace.

BACKGROUND OF THE INVENTION

[0003] Steam cracking is the major commercial process for the production of light olefins, especially ethene and propene. In typical steam cracking, the hydrocarbon feed is first preheated and mixed with dilution steam in the convection section of the furnace. After preheating in the convection section, the vapor feed/dilution steam mixture is rapidly heated in the radiant section to achieve the desired thermal cracking. After the desired degree of thermal cracking has been achieved in the radiant section, the furnace effluent is rapidly quenched in either an indirect heat exchanger or by the direct injection of a quench oil stream.

[0004] An undesirable byproduct of the cracking process is often the deposition of carbon deposits, commonly referred to as "coke," on the inner surfaces of the radiant tubes of the furnace. Depending on the feedstock being cracked, coke may also be deposited in certain tubes in the convection section, or in the quench system of the furnace.

[0005] Steam cracking furnace performance is most frequently limited by the build of coke inside the radiant tubes. The coke acts as a thermal insulator resulting in increasing radiant tube metal temperatures (TMT's) as a run progresses. Once the TMT's approach or reach the design limit, the furnace needs to be decoked.

[0006] The coke inside the tubes also causes a hydraulic restriction and higher coil pressure drop. When the pressure drop becomes high enough, the resulting higher backpressure causes a loss-of-critical-flow at the critical flow nozzles located at the inlet of the radiant section. Once critical flow is lost for a particular tube, the flow rate through that tube will be reduced which results in a higher coking rate, which aggravates the hydraulic restriction further. This cycle continues rapidly and a decoke operation will be required.

[0007] It is desirable to reduce the radiant tube metal temperatures without a significant adverse impact on throughput and production.

[0008] One method for reducing the radiant TMT's is to raise the process duty of the furnace convection section so that the required radiant duty is lower for a given feed rate, S/HC, and conversion. Raising the duty of the convection section will of course raise the temperature of the process gas leaving the convection section. The temperature of the process gas leaving the convection section is referred to as the cross-over temperature ("XOT", not to be confused with the term used in industry to denote radiant coil outlet temperature "COT").

[0009] The perception in industry seems to be that the temperatures in the convection section need to be limited such that any significant thermal cracking does not occur therein. The concerns are likely based on the assumed drawbacks that thermal cracking in the convection section or cross-over is too unselective for ethene, and that it will cause coking inside the convection section tubes.

15 **SUMMARY OF THE INVENTION**

[0010] It was discovered that, surprisingly, raising the XOT such that a reasonable amount of thermal cracking happens in the convection section and cross-over piping has the benefit of reducing radiant section TMT's with minimal drawbacks of reduced ethene selectivity and coking propensity inside the convection section tubes. The impact on overall furnace ethene selectivity is small to manageable, and is often offset economically by the production of valuable co-products. In addition, it was discovered that, surprisingly, there is usually little or no measurable coking in the convection section when XOT's and associated convection section cracking are high. Thus, one can use a high XOT to increase the time interval (run-length) between decoking operations for a set of fixed conditions (e.g., feed rate, stream to hydrocarbon ratio, conversion) due to lower TMT's. Alternatively, the feed rate and/or conversion can be raised while maintaining a similar TMT and/or furnace run-length.

[0011] Accordingly, the present invention provides a process for steam cracking hydrocarbon in a steam cracking furnace including a tube comprising a convection section, a cross-over section downstream of the convection section, and a heated radiant section downstream of the cross-over section, comprising: (i) feeding the hydrocarbon material and steam into the convection section to obtain a feed mixture; (ii) heating the hydrocarbon material mixture in the convection section to obtain a first fluid stream at a temperature T1 at the end of the convection section; (iii) passing the first fluid stream through the cross-over section to obtain a second fluid stream at the end of the cross-over section at a temperature

T2; (iv) passing the second fluid stream through the radiant section to obtain a cracked fluid mixture at the end of the radiant section at a temperature T3, wherein: T3 is higher than T2 and T1; and T1 and T2 are selected such that significant cracking reaction occurs at least in a portion of the convection section and at least a portion of the cross-over section.

5 **BRIEF DESCRIPTION OF THE DRAWING**

[0012] The FIGURE is a schematic illustration of a steam cracking furnace in operation to convert hydrocarbons to produce lighter hydrocarbons such as ethene and propene.

DETAILED DESCRIPTION OF THE INVENTION

10 [0013] As used herein, the term “severity index” is defined as weight ratio of C₃H₆ to CH₄ in a cracked mixture. As used herein, a “C_m hydrocarbon” means a hydrocarbon having n carbon atoms in its molecular structure, where n is an integer; and “C_m to C_n hydrocarbons” means hydrocarbons having from m to n carbon atoms in the molecular structures thereof, where m and n are integers and m < n, and mixtures thereof.

15 [0014] The FIGURE schematically illustrates a typical steam cracking furnace 101 in operation. The furnace 101 includes a radiant fire box 103 in the lower portion thereof and a convection zone 105 in the upper portion thereof. A hydrocarbon feed stream 107 (comprising ethane, propane, butane, gas oil, or naphtha, and the like) is fed into the hydrocarbon inlet of an upstream portion 108a of convection section 108 of a steam cracking tube. A diluent steam stream 109 is fed into a downstream portion 108b of the convection section 108 at a location downstream of the hydrocarbon inlet to mix with the hydrocarbon feed stream. The combined hydrocarbon/steam stream travels downward along the convection section 108. Because of hot gas traveling upwards inside the firebox, the hydrocarbon/steam feed mixture inside the convection section is gradually heated up as it travels along the tube. When it reaches the end (location 111) of the convection section which is located immediately outside of the wall of furnace 101 as the first fluid stream, its temperature reaches T1°C. The end of the convection section is connected to the start of the cross-over section 113 of the steam cracking tube. The cross-over section is typically located outside of the wall of the furnace 101 to avoid heating the hydrocarbon and stream mixture to an exceedingly high temperature where substantial cracking can occur prematurely. At the end of the cross-over section, a second fluid stream at T2°C is obtained. The cross-over section is thermally insulated to prevent excessive heat loss with or without active heating. Where no active heating is applied, T2 is typically slightly lower than T1 as a result of heat loss and/or endothermal cracking reactions occurring if T1 is sufficiently high. The cross-over section ends with one or more critical flow nozzles (at the location of 115), which are

connected to a lower end of one or more vertical radiant tubes 117 (radiant section of the steam cracking tube) installed inside the walls of the radiant zone of the furnace 101. The steam cracking tubes 117 in the radiant section are typically heated externally by a series of flames generated by burners (not shown) installed on the floor of the fire box and/or the side walls of the fire box. Operating conditions can be chosen such that a majority of the heat supplied to the radiant tubes are by radiation instead of convection or conduction. The fluid stream inside the radiant tubes travel at a very high space velocity while being heated by the radiant heat from the flames. After a very short residence time in the vertical radiant tubes, at the end of the radiant tubes 119 which are located immediately outside of the furnace box 103, the fluid stream can reach a temperature of $T_3^{\circ}\text{C}$ significantly higher than T_2 and T_1 , where the cracking of large hydrocarbon molecules to form small hydrocarbon molecules such as ethene, propene, and the like, are favored. The cracked fluid mixture stream 119 exiting the radiant section at location 109 can be quenched and subsequently separated to obtain the desired product fractions, such as ethene, propene, butadiene, and the like. Typically, in a steam cracking process, saturated hydrocarbon materials such as alkanes are fed into the process, and a cracked fluid mixture comprising higher concentrations of alkenes, typically having fewer carbon atoms and/or smaller molecular weight in molecules thereof than those in the hydrocarbon materials than the hydrocarbon feed, is obtained.

[0015] In the past, the temperature of the hydrocarbon/steam feed mixture stream inside the convection section has been typically controlled at a low level such that significant cracking of hydrocarbon molecules does not occur. Thus, the concentration of olefins in the first fluid stream at the end of the convection section typically is not much higher than in the hydrocarbon/steam feed mixture at the location where the hydrocarbon feed and the steam stream is first admixed. Alternatively, the concentration of the saturated hydrocarbon material in the first fluid stream at the end of the convection section is typically not much lower than in the hydrocarbon/steam feed mixture at the location where the hydrocarbon feed and the steam stream is first admixed. As discussed above, such lower temperature operation in the convection section was chosen due to the assumed drawbacks of a higher-temperature operation in the convection section: (i) a higher coking propensity in the convection section and the cross-over section if substantial steam cracking is allowed to occur therein; and (ii) a subsequently lower temperature in the radiant section if a higher convection section temperature is used, which would be unfavorable to the conversion from ethane to ethene.

[0016] However, as indicated by the many examples given below, the present inventors have found, in a surprising manner, that even if the temperature in the convection section,

especially the downstream portion thereof close to the cross-over section, is sufficiently high to allow significant cracking to occur therein, coking in the convection section and cross-over section does not increase to an unacceptable level. In addition, the yield of ethene did not decrease to an unacceptable level in the overall process. Furthermore, surprisingly, at least in the case of ethane steam cracking, the yield of valuable fractions of other hydrocarbons such as C5 and C6 olefins can increase, which can compensate the slightly decreased yield of ethene. Moreover, a higher temperature T1 at the end of the convection section means a higher temperature T2 in the cross-over section, and a higher temperature of the second fluid stream entering into the radiant section of the tube, thus enabling a lower tube metal temperature (TMT) of the tube in the radiant section during normal operation, thereby extending the time interval (run-length) between adjacent decoking operations required.

The hydrocarbon material

[0017] The process of the present invention can be effectively and efficiently used for the conversion of various types of hydrocarbon feed materials rich in aliphatic hydrocarbons into lighter hydrocarbons rich in olefins. To that extent, the hydrocarbon material fed into the furnace can contain ethane as a major component. For example, the fresh hydrocarbon material can contain, by weight of the total fresh feed, from a1 % to a2 %, of ethane, where a1 and a2 can be, independently, 50, 55, 60, 65, 70, 75, 80, 85, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, as long as $a1 < a2$.

[0018] In an alternative process of the present invention, the hydrocarbon material fed into the furnace can contain butane as a major component. For example, the fresh hydrocarbon material can contain, by weight of the total fresh feed, from b1 % to b2 %, of butane, where b1 and b2 can be, independently, 50, 55, 60, 65, 70, 75, 80, 85, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, as long as $b1 < b2$.

[0019] In another alternative process of the present invention, the hydrocarbon material fed into the furnace can contain naphtha as a major component. As used herein, "naphtha" means a mixture of C5-C10 aliphatic hydrocarbons. For example, the fresh hydrocarbon material can contain, by weight of the total fresh feed, from c1 % to c2 %, of naphtha, where c1 and c2 can be, independently, 50, 55, 60, 65, 70, 75, 80, 85, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, as long as $c1 < c2$.

[0020] In another alternative process of the present invention, the hydrocarbon material fed into the furnace can contain gas oil as a major component. As used herein, "gas oil" means a mixture of C10-C20 hydrocarbons. A typical gas oil contains at least 50 wt% of C10-C20 alkanes. For example, the fresh hydrocarbon material can contain, by weight of the

total fresh feed, from d1% to d2%, of gas oil, where d1 and d2 can be, independently, 50, 55, 60, 65, 70, 75, 80, 85, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, as long as $d1 < d2$.

[0021] In practical manufacture operation, the reaction conditions are controlled such that a majority, but not 100% of conversion per pass of the feed hydrocarbon is achieved. Thus, the cracked fluid mixture at the exit of the radiant section typically contains a non-negligible amount of the hydrocarbon material fed into the cracking furnace. Upon separation from the useful product, the unreacted hydrocarbon may be recycled to the steam cracking furnace in order to increase the overall conversion of the process.

The steam cracking conditions

[0022] Typically, the heavier the hydrocarbon material fed into the steam cracking furnace, the lower the operation temperature, and the heavier the cracked fluid mixture tends to be. As indicated above, the process of the present invention can be used for steam cracking of various hydrocarbon materials as the fresh feed, to obtain different cracked products, particularly olefins with different molecular sizes.

[0023] In general, in the process of the present invention, temperature at the lower portion of the convection zone, particularly at the end thereof (T1), is controlled at sufficiently high, such that significant cracking reactions occur in the lower portion of the convection section and the cross-over section before the second fluid stream enters into the radiant section, where a great majority of the steam cracking take place. Thus, compared to the feed mixture including all fresh feed, recycled hydrocarbon, and steam assuming no chemical reactions having taken place, the first fluid mixture exiting the end of the convection section and entering the cross-over section tends to have an overall olefins concentration. Thus, assuming the feed comprises olefins at a total concentration of C0 mol% based on the total moles of the fluid species in the feed before any cracking reaction occurs; the first fluid stream comprises olefins at a total concentration of C1 mol% based on the total moles of the fluid species therein; then $g1 \% \leq C1 - C0 \leq g2 \%$, where g1 and g2 can be, independently, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, as long as $g1 < g2$.

[0024] As indicated above, typically $T2 < T1 < T3$. Where the cross-over section is not actively heated and merely thermally insulated outside of the furnace box, due to the endothermic nature of the cracking reactions, the temperature of the fluid stream inside the cross-over section decreases from the beginning to the end. Thus, the temperature differential $T1 - T2$ can be in the range from e1 to e2°F, where e1 and e2 can be, independently, 75, 70, 65, 60, 55, 50, 45, 40, 35, 30, 25, 20, 15, 10, or even 5, as long as $e1 < e2$. In the cross-over section of the reactor, additional cracking is allowed to continue

because of the relatively high temperature T_1 of the first fluid mixture entering the cross-over section, even if $T_2 < T_1$. Thus, assuming the feed comprises olefins at a total concentration of C_0 mol% based on the total moles of the fluid species in the feed before any cracking reaction occurs; the second fluid stream comprises olefins at a total concentration of C_2 mol % based on the total moles of the fluid species therein; then $h_1 \% \leq C_2 - C_0 \leq h_2 \%$, where h_1 and h_2 can be, independently, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, as long as $h_1 < h_2$.

[0025] The temperature differential $T_3 - T_2$ can be in the range from f_1 to $f_2^\circ\text{F}$, where f_1 and f_2 can be, independently, 100, 150, 200, 250, 300, 350, 400, 450, or 500, as long as $f_1 < f_2$. This significantly higher T_3 would lead to a majority of the cracking reactions in the radiant sections even though the residence time therein is typically very short, e.g., on the order of milliseconds to hundreds of milliseconds.

[0026] The cracking conditions, especially those in the radiant section, are chosen to favor the thermal pyrolysis of the aliphatic hydrocarbon molecules in the feed material to produce smaller, unsaturated hydrocarbon molecules and hydrogen in the cracked fluid mixture. The unsaturated hydrocarbons tend to have higher economic value than the aliphatic feed and used as industrial raw materials for making additional materials such as polymers.

[0027] At the end of the radiant section, the cracked fluid mixture is typically quenched immediately by a heat exchanger or by the injection of a quenching fluid stream. The quenched fluid stream is at a temperature where significant chemical reactions between and among the chemical species in the cracked fluid mixture is substantially stopped, preventing the formation of undesirable compounds that may form coke. The cracked fluid mixture can be separated in a downstream vessel by conventional methods such as condensation and evaporation to obtain various fractions: hydrogen, desirable unsaturated hydrocarbon fractions, and residual aliphatic hydrocarbons. The residual aliphatic hydrocarbons may be recycled into the steam cracking reactor, where it is further converted into desirable products, or alternatively, it may be combusted as a fuel for, e.g., producing the flames that heat the steam cracking furnace, particularly the radiant section.

[0028] A particularly undesirable byproduct in the steam cracking reactor is coke, a complex mixture of hydrocarbons having much higher boiling temperatures than the hydrocarbon feed material, which tend to deposit on the inner surface of the reactor tubes. Buildup of a coke layer over time can reduce heat transfer from the tube wall to the fluid stream inside, increase pressure differential from the inlet to the outlet of the tube coil, and lead to reactor wall corrosion by carbonization of the tube metal. To compensate the

reduction of heat transfer resulting from coke deposition, higher tube external wall temperature is necessary, which can further aggravate coke formation. A steam cracking furnace is designed to operate only under a maximal pressure drop and a maximal tube wall temperature. When either limit is reached, the reactor has to cease operation and a decoking operation is required. It is highly desirable to reduce coke formation and deposition in order to extend the run-lengths of normal operations and minimize decoking events to the extent possible.

[0029] Reducing radiant section external wall temperature during normal operation of the reactor favors the reduction of coke formation. However, it is also generally detrimental to the conversion of the aliphatic hydrocarbons in the radiant section because of the highly endothermal nature of the reactions, and the selectivity toward desired products especially olefins in the radiant section.

[0030] One method to compensate for the reduced conversion and selectivity in the radiant section is to increase the temperature of the fluid stream in at least a portion of the convection section and the cross-over section such that a significant level of thermal cracking reactions occur before the radiant section. Historically, it was perceived that doing so would lead to undesirable level of coke deposition in the convection section and the cross-over section, given the residence time in these sections and conditions (particularly, a medium temperature between the high temperature in the radiant section and the low temperature of the cracked fluid mixture after quenching). However, surprisingly, the present inventors found that, by increasing the convection section temperature and reducing the radiant section temperature, the disadvantages of coke deposition before the radiant section and the overall reduction of conversion and selectivity of the reactor are acceptable, while the advantage of reduced coking deposition in the radiant section is substantial.

[0031] By using the process of the present invention, the decoking interval (defined as the run-length of the operation of a furnace between two adjacent decoking sessions) of the furnace can be extended by at least 10% (or at least 50%, 80%, 100%, 150%, 200%, 300%, 400%, or even 500%), compared to a process where the convection section and the cross-over section are operated at a temperature at which essentially no cracking occurs of the major component in the hydrocarbon material fed into the reactor, all other process parameters being held equal.

Ethane steam cracking

[0032] For ethane cracking, preferred fresh feed to the steam cracking reactor comprises from 50 – 100 mol % (e.g., 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 96, 97, 98, 99, 100 mol%)

of ethane. As a minor component, propane may be present in the total hydrocarbon feed material as well, e.g., at a concentration from 5% to 50% by mole (e.g., 5, 10, 15, 20, 25, 30, 35, 40, 45, 50 mol %) of the total hydrocarbon feed. Under the cracking conditions, especially in the radiant section where the temperature is high, the cracking of ethane and propane are favored to produce methane, ethene, propene, hydrogen, acetylene, methylacetylene, which are smaller in molecular weight than ethane and/or propane. Larger molecules, such as C₄, C₅, and C₆ hydrocarbons, may be produced as well, but typically at low concentrations. Upon separation in down-stream processes, C₄, C₅, and C₆ olefins and aromatics can be obtained as valuable byproducts, and residual ethane and propane can be recycled to the steam cracking furnace as a portion of the overall feed.

[0033] T₁ can be in the range from T₁(ethane)₁ to T₁(ethane)₂°F, where T₁(ethane)₁ and T₁(ethane)₂ can be, independently, 1300, 1325, 1350, 1375, 1400, 1405, 1410, 1415, 1420, 1425, 1430, 1435, as long as T₁(ethane)₁ < T₁(ethane)₂;

T₂ can be in the range from T₂(ethane)₁ to T₂(ethane)₂°F, where T₂(ethane)₁ and T₂(ethane)₂ can be, independently, 1275, 1300, 1325, 1350, 1375, 1400, 1410, 1420, 1430, as long as T₂(ethane)₁ < T₂(ethane)₂; and

T₃ can be in the range from T₃(ethane)₁ to T₃(ethane)₂°F, where T₃(ethane)₁ and T₃(ethane)₂ can be, independently, 1500, 1525, 1550, 1575, 1600, 1625, 1650, 1675, 1700, 1725, 1750, 1775, 1800, as long as T₃(ethane)₁ < T₃(ethane)₂.

[0034] The conversion of ethane in the process of the present invention can be desirably high, generally higher than 50% and lower than 80%. At higher than 80%, the selectivity toward ethene can be low. Thus, the conversion of ethane can be from Con(1)% to Con(2)%, where Con(1) and Con(2) can be, independently, 60, 62, 64, 66, 68, 70, 72, 74, 76, 78, 80, as long as Con(1) < Con(2).

[0035] In the steam cracking process of the present invention for ethane, it is highly desirable that the total concentration of C₅ and C₆ olefins, dienes and benzene in the cracked fluid mixture is in a range from x₁ mol% to x₂ mol% based on the total moles of different species therein, where x₁ and x₂ can be, independently, 1.0, 1.5, 2.0, 2.5, 3.0, 3.5, 4.0, 4.5, 5.0, 5.5, 6.0, 6.5, 7.0, 7.5, and 8.0, as long as x₁ < x₂.

[0036] In the steam cracking process of the present invention for ethane, it is highly desirable that process has a total severity index (SI) in the cracked fluid mixture in a range from s₁ to s₂, where s₁ and s₂ can be, independently, 0.50, 0.55, 0.60, 0.65, 0.70, 0.75, 0.80, 0.85, 0.90, 0.95, 1.00, 1.05, 1.10, 1.15, 1.20, 1.25, as long as s₁ < s₂.

Propane steam cracking

[0037] For propane cracking, preferred fresh feed to the steam cracking reactor comprises from 50 – 100 mol% (e.g., 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 96, 97, 98, 99, or 100 mol%) of propane. As a minor component, ethane may be present in the total hydrocarbon feed material as well, e.g., at a concentration from 5% to 50% by mole (e.g., 5, 10, 15, 20, 25, 30, 35, 40, 45, 50 mol%) of the total hydrocarbon feed. As another minor component, butane may be present in the total hydrocarbon feed material as well, e.g., at a concentration from 0% to 10% by mol of the total hydrocarbon feed. Under the cracking conditions, especially in the radiant section where the temperature is high, the cracking of propane, butane and ethane are favored to produce methane, ethene, propene, hydrogen, acetylene, and methylacetylene, which are smaller in molecular weight than propane. Larger molecules, such as C₄, C₅, and C₆ hydrocarbons, may be produced as well, but typically at low concentrations. Upon separation in down-stream processes, C₄, C₅, and C₆ olefins and aromatics can be obtained as valuable byproducts, and residual propane, ethane and butane can be recycled to the steam cracking furnace as a portion of the overall feed.

[0038] T₁ can be in the range from T₁(propane)₁ to T₁(propane)₂°F, where T₁(propane)₁ and T₁(propane)₂ can be, independently, 1200, 1225, 1250, 1275, 1300, 1325, 1350, 1375, 1400, 1405, 1410, and 1415, as long as T₁(propane)₁ < T₁(propane)₂;

T₂ can be in the range from T₂(propane)₁ to T₂(propane)₂°F, where T₂(propane)₁ and T₂(propane)₂ can be, independently, 1175, 1200, 1225, 1250, 1275, 1300, 1325, 1350, 1375, 1400, and 1410, as long as T₂(propane)₁ < T₂(propane)₂; and

T₃ can be in the range from T₃(propane)₁ to T₃(propane)₂°F, where T₃(propane)₁ and T₃(propane)₂ can be, independently, 1525, 1550, 1575, 1600, 1625, 1650, 1675, 1700, 1725, 1750, 1775, and 1800, as long as T₃(propane)₁ < T₃(propane)₂.

[0039] The conversion of propane in the process of the present invention can be desirably high, generally higher than 70% (desirably higher than 80%) and lower than 99%. At higher than 96%, the total selectivity toward ethene and propene can be low. Thus, the conversion of propane can be from ConP(1)% to ConP(2)%, where ConP(1) and ConP(2) can be, independently, 70, 72, 74, 76, 78, 80, 82, 84, 85, 86, 88, 90, 92, 94, 96, 98, 99, and 100, as long as Con(1) < Con(2).

Butane steam cracking

[0040] For butane cracking, preferred fresh feed to the steam cracking reactor comprises from 50 – 100 mol% (e.g., 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 96, 97, 98, 99, or 100 mol%) of butane. As a minor component, propane may be present in the total hydrocarbon feed

material as well, e.g., at a concentration from 5% to 50% by mole (e.g., 5, 10, 15, 20, 25, 30, 35, 40, 45, 50 mol%) of the total hydrocarbon feed. As another minor component, C_5H_{10} may be present in the total hydrocarbon feed material, e.g., at a concentration from 0% to 10% by mol of the total hydrocarbon feed. Under the cracking conditions, especially in the radiant section where the temperature is high, the cracking of propane, butane, C_5H_{10} and ethane are favored to produce methane, ethene, propene, hydrogen, acetylene, and methylacetylene, which are smaller in molecular weight than propane. Larger molecules, such as C_4 , C_5 , and C_6 hydrocarbons, may be produced, but typically at low concentrations. Upon separation in down-stream processes, C_4 , C_5 , and C_6 olefins and aromatics can be obtained as valuable byproducts, and residual butane, ethane and propane can be recycled to the steam cracking furnace as a portion of the overall feed.

[0041] T_1 can be in the range from $T_1(\text{butane})_1$ to $T_1(\text{butane})_2^\circ\text{F}$, where $T_1(\text{butane})_1$ and $T_1(\text{butane})_2$ can be, independently, 1150, 1175, 1200, 1225, 1250, 1275, 1300, 1325, 1350, 1375, 1400, as long as $T_1(\text{butane})_1 < T_1(\text{butane})_2$;

T_2 can be in the range from $T_2(\text{butane})_1$ to $T_2(\text{butane})_2^\circ\text{F}$, where $T_2(\text{butane})_1$ and $T_2(\text{butane})_2$ can be, independently, about 25 to 150°F (14 to 83°C) lower than T_1 , as long as $T_2(\text{butane})_1 < T_2(\text{butane})_2$; and

T_3 can be in the range from $T_3(\text{butane})_1$ to $T_3(\text{butane})_2^\circ\text{F}$, where $T_3(\text{butane})_1$ and $T_3(\text{butane})_2$ can be, independently, 1500, 1525, 1550, 1575, 1600, 1625, 1650, 1675, 1700, 1725, 1750, 1775, 1800, as long as $T_3(\text{butane})_1 < T_3(\text{butane})_2$.

[0042] In the steam cracking process of the present invention for butane, it is highly desirable that the total concentration of C_5 and C_6 olefins, dienes and benzene in the cracked fluid mixture is in a range from x_3 mol% to x_4 mol% based on the total moles of different species therein, where x_3 and x_4 can be, independently, 1.0, 1.5, 2.0, 2.5, 3.0, 3.5, 4.0, 4.5, 5.0, 5.5, 6.0, 6.5, 7.0, 7.5, 8.0, 8.5, 9.0, 9.5, 10.0, as long as $x_3 < x_4$.

[0043] In the steam cracking process of the present invention for butane, it is highly desirable that process has a total severity index (SI) in the cracked fluid mixture in a range from s_3 to s_4 , where s_3 and s_4 can be, independently, 0.50, 0.55, 0.60, 0.65, 0.70, 0.75, 0.80, 0.85, 0.90, 0.95, 1.00, 1.05, 1.10, 1.15, 1.20, 1.25, 1.30, 1.35, 1.40, 1.45, 1.50, 1.55, 1.60, 1.65, as long as $s_3 < s_4$.

Naphtha steam cracking

[0044] For naphtha cracking:

T1 can be in the range from T1(naphtha)1 to T1(naphtha)2°F, where T1(naphtha)1 and T1(naphtha)2 can be, independently, 1150, 1175, 1200, 1225, 1250, as long as T1(naphtha)1 < T1(naphtha)2;

5 T2 can be in the range from T2(naphtha)1 to T2(naphtha)2°F, where T2(naphtha)1 and T2(naphtha)2 can be, independently, 1125, 1150, 1175, 1200, 1225, 1245, as long as T2(naphtha)1 < T2(naphtha)2; and

T3 can be in the range from T3(naphtha)1 to T3(naphtha)2°F, where T3(naphtha)1 and T3(naphtha)2 can be, independently, 1450, 1475, 1500, 1525, 1550, 1575, 1600, as long as T3(naphtha)1 < T3(naphtha)2.

10 **[0045]** In the steam cracking process of the present invention for naphtha, it is highly desirable that the total concentration of C5 and C6 olefins, dienes and benzene in the cracked fluid mixture is in a range from x5 mol% to x6 mol% based on the total moles of different species therein, where x5 and x6 can be, independently, 1.0, 1.5, 2.0, 2.5, 3.0, 3.5, 4.0, 4.5, 5.0, 5.5, 6.0, 6.5, 7.0, 7.5, 8.0, 8.5, 9.0, 9.5, 10.0, as long as x5 < x6.

15 **[0046]** In the steam cracking process of the present invention for naphtha, it is highly desirable that process has a total severity index (SI) in the cracked fluid mixture in a range from s5 to s6, where s5 and s6 can be, independently, 0.50, 0.55, 0.60, 0.65, 0.70, 0.75, 0.80, 0.85, 0.90, 0.95, 1.00, 1.05, 1.10, 1.15, 1.20, 1.25, as long as s5 < s6.

Gas oil steam cracking

20 **[0047]** For gas oil cracking:

T1 can be in the range from T1(GO)1 to T1(GO)2°F, where T1(GO)1 and T1(GO)2 can be, independently, 1060, 1075, 1100, 1125, 1150, 1160, as long as T1(GO)1 < T1(GO)2;

25 T2 can be in the range from T2(GO)1 to T2(GO)2°F, where T2(GO)1 and T2(GO)2 can be, independently, 1035, 1050, 1075, 1100, 1125, 1150, 1155, as long as T2(GO)1 < T2(GO)2; and

T3 can be in the range from T3(GO)1 to T3(GO)2°F, where T3(GO)1 and T3(GO)2 can be, independently, 1375, 1400, 1425, 1450, 1475, 1500, 1525, as long as T3(GO)1 < T3(GO)2.

30 **[0048]** In the steam cracking process of the present invention for gas oil, it is highly desirable that the total concentration of C5 and C6 olefins, dienes and benzene in the cracked fluid mixture is in a range from x7 mol % to x8 mol % based on the total moles of different species therein, where x7 and x8 can be, independently, 1.0, 1.5, 2.0, 2.5, 3.0, 3.5, 4.0, 4.5, 5.0, 5.5, 6.0, 6.5, 7.0, 7.5, 8.0, 8.5, 9.0, 9.5, 10.0, as long as x7 < x8.

[0049] In the steam cracking process of the present invention for gas oil, it is highly desirable that process has a total severity index (SI) in the cracked fluid mixture in a range from s7 to s8, where s7 and s8 can be, independently, 0.8, 1.0, 1.1, 1.2, 1.3, 1.4, 1.5, 1.7, 1.8, 1.9, 2.0, 2.1, 2.2, 2.4, as long as $s7 < s8$. Examples include an SI from 1.3 to 1.8.

5 [0050] The following non-limiting examples further illustrate the present invention.

EXAMPLES

[0051] The following examples of steam cracking processes were run in industrial reactors.

Example 1

10 [0052] An ethane feed having an average composition (wt%) as follows was used:

C5+ and heavier	0.02
Propane	0.47
Propene	0.25
1-Butene	0.03
15 2-Butene	0.01
Ethene	0.78
Ethane	97.53
Methane	0.91

[0053] The ethane feed was fed into a steam cracking furnace in five different runs with
20 the following conditions of temperature at the end of the convection section (T1, which is also the temperature at the beginning of the cross-over section), pressure at the end of the convection section (P1), temperature at the outlet of the radiant section (T3), pressure at the outlet of the radiant section (P3), and firing rate in the furnace identified in TABLE I below. Conversion of ethane was calculated from the measured composition of the cracked fluid
25 mixture and reported in TABLE I as well.

TABLE I

Run No.		<u>1</u>	<u>2</u>	<u>3</u>
T1	(°F)	1350	1356	1358
	(°C)	732.2	735.6	736.7
P1 (absolute)	(psi)	67.7	65.9	63.7
	(kPa)	6838	6656	6434
T3	(°F)	1597	1617	1631
	(°C)	869.4	880.6	888.3
P3 (absolute)	(psi)	33.7	33.7	33.85
	(kPa)	3404	3404	3419
Flow Rate	(Pounds/hour/furnace)	40,920	38,990	37,750
Ethane Conversion	(%)	70.5	76.1	80
Furnace Firing Rate	(MBtu/hour)	130	130	130

[0054] Compositions of the gas mixture sampled at the cross-over section were analyzed for each run described in TABLE I above, and reported in TABLE II below.

TABLE II

Run No.		<u>1</u>	<u>2</u>	<u>3</u>
C2 Conversion @ Cross-Over Section		18	20	21
Final C2 Conversion (%)		70	75	80
Severity		0.353	0.205	0.247
Ethene Selectivity (%)		11.165	11.222	10.313
T1 (°F)		1350	1356	1358
Composition (wt%)	Hydrogen	1.06	1.24	1.38
	Methane	1.44	1.58	1.81
	Acetylene	0.00	0.00	0.00
	Ethene	16.09	17.78	18.70
	Ethane	75.89	77.88	78.70
	Propene	0.51	0.49	0.45
	Propane	0.34	0.24	0.21
	C ₄ H ₆	0.09	0.11	0.12
	1-Butene	0.12	0.14	0.14
	2-Butene	0.03	0.04	0.04
	1-Butylene	0.00	0.00	0.00
	n-Butane	0.23	0.26	0.28
	Iso-Butane	0.00	0.00	0.00
	Total C4 hydrocarbons	0.48	0.54	0.57
	Cyclopentadiene	0.01	0.02	0.02
	Methylcyclopentadiene	0.00	0.00	0.00
	Isoprene	0.00	0.00	0.00
	Total C5 hydrocarbons	0.05	0.06	0.08
	Benzene	0.01	0.02	0.02
	Toluene	0.00	0.00	0.00
	Styrene	0.00	0.00	0.00
	Xylene	0.00	0.00	0.00
	Total C5+	0.13	0.16	0.16

Run No.		<u>1</u>	<u>2</u>	<u>3</u>
	Total SCN	0.12	0.16	0.15
	SOGO	0.02	0.00	0.01
	Tar	0.00	0.00	0.00

- [0055] Compositions of two samples of cracked fluid mixture collected at the end of the radiant section for each run of run Nos. 1 and 2 above were analyzed and provided in TABLE IIa below. The end of the radiant section is located out of but in close proximity to the cracking furnace. The samples analyzed are believed to represent the compositions of the cracked fluid mixture at the end of the radiant section because immediately before or after sample collection, the samples were quenched to stop further cracking and other reactions therein.

TABLE IIa

Case No. of Runs		<u>1A</u>	<u>1B</u>	<u>2A</u>	<u>2B</u>
C2 Conversion		70.4	70.5	76.5	75.7
Severity		0.231	0.229	0.199	0.204
Ethene Selectivity in Radiant Section (%)		8.089	8.056	6.845	6.960
T3	(°F)	1597	1597	1617	1617
	(°C)	869	869	880	880
Composition (wt%)	Hydrogen	4.20	4.26	4.58	4.53
	Methane	6.52	6.54	8.00	7.83
	Acetylene	0.57	0.57	0.78	0.76
	Ethene	52.76	52.70	54.79	54.50
	Ethane	28.88	28.75	22.97	23.66
	Methylacetylene and propadiene	0.07	0.08	0.10	0.10
	Propene	1.51	1.50	1.59	1.59
	Propane	0.18	0.18	0.15	0.16
	C ₄ H ₆	1.88	1.89	2.23	2.18
	1-Butene	0.14	0.14	0.15	0.15
	2-Butene	0.00	0.00	0.00	0.00
	1-Butylene	0.19	0.19	0.14	0.15
	n-Butane	0.00	0.00	0.00	0.00
	Isobutane	2.43	2.44	2.76	2.72
	Cyclopentadiene	0.52	0.50	0.68	0.65
	Methylcyclopentadiene	0.00	0.00	0.00	0.00
	Isoprene	0.04	0.04	0.04	0.04
	Total C5's	0.83	0.76	0.97	0.94
	Benzene	1.21	1.19	2.04	1.88
	Toluene	0.15	0.14	0.26	0.23
	Styrene	0.09	0.09	0.17	0.16
	Xylene	0.01	0.03	0.03	0.03
	Total C5+	2.71	2.73	4.02	3.87
	Total Steam-Cracked Naphtha	2.68	2.59	3.93	3.71
	Steam-Cracked Gas Oil	0.03	0.14	0.10	0.16
	Tar	0.00	0.00	0.00	0.00

[0056] As can be seen from the data in TABLE II, as T1 increased from about 1350 to 1373°F, the C2 conversion in the cross-over section increased from 18% to 27%, and the selectivity of ethene in the cross-over section only decreased slightly from 11.165% to about 9.582%.

- 5 [0057] As can be seen from the data in TABLE IIa, as T1 increased from 1350°F in run No. 1 to 1356°F in run No. 2, ethane conversion in the cross-over section increased from 18% to 20%, ethane final conversion at the end of the radiant section increased by about 5%, but the final selectivity at the end of the radiant section toward ethene was essentially unchanged: both at about 49%. It is believed that the increase of temperature in the lower portion of the
- 10 convection section and the cross-over section, therefore a higher conversion in the convection section and the cross-over section, would require a lower temperature in the radiant section in order to achieve the overall same level of selectivity toward ethene at the end of the radiant section. A lower temperature in the radiant section would require less thermal input from the flames inside the furnace. This would result in the less formation of coke on the internal wall
- 15 of the radiant section, thereby extending the run-length between required adjacent decoking sessions.

Example 2

[0058] A butane feed having an average composition (wt%) as follows was used:

	Hydrogen	0.02
20	Propane	0.11
	Propene	0.01
	Isobutane	1.47
	n-Butane	97.12
	Isobutene	0.29
25	t2-Butene	0.04
	Ethane	0.02
	Methane	0.03
	C5 & heavier	0.81

- [0059] The butane feed was fed into a steam cracking furnace in 16 runs (with the
- 30 following conditions of temperature at the end of the convection section (T1), pressure at the end of the convection section (P1), temperature at the outlet of the radiant section (T3), pressure at the outlet of the radiant section (P3), and firing rate in the furnace identified in TABLE IIIa and IIIb below. Conversion of butane was calculated from the measured composition of the cracked fluid mixture and reported in TABLE IIIa and IIIb as well. Note

- for Run Nos. 1A, 1B, 2A, 2B, 3A, 3B, 4A, 4B, 5A, 5B, 6A, 6B, 7A, and 7B, all conversion, severity and selectivity data are for the overall process including the convection section, the cross-over section and the radiant section, and composition data for Run Nos. 7A and 7B are for samples collected at the end of the radiant section. However, for Run Nos. 8A and 8B,
- 5 the conversion, severity, selectivity and composition data are for samples collected at the end of cross-over section before the radiant section. All these exemplary runs were conducted at cross-over temperatures (T1) where significant butane steam-cracking occurs.

TABLE IIIa

Run No.		1A	1B	2A	2B	3A	3B	4A	4B
Conversion	(wt%)	89.63	89.79	89.94	89.34	93.98	94.48	95.68	96.29
Severity		1.049	1.044	1.024	1.051	0.8	0.808	0.75	0.709
Selectivity		1.688	1.687	1.74	1.746	1.713	1.716	1.648	1.638
T3	(°F)	1536	1537	1538	1536	1563	1564	1570	1568
	(°C)	835.6	836.1	836.7	835.6	850.6	851.1	854.4	853.3
T1	(°F)	1286	1287	1290	1289	1291	1289	1300	1300
	(°C)	696.7	697.2	698.9	698.3	699.4	698.3	704.4	704.4
P3	(psig)	12	12	12	12	12	12	12	12
	(kPa, Gauge)	83	83	83	83	83	83	83	83
P1 (absolute)	(psi)					46		42.1	
	(kPa)					317		290	
Steam/Oil Ratio	(wt)	0.3	0.3	0.5	0.5	0.5	0.5	0.3	0.3
Feed Rate	(kilo-pounds per hour, Quad)	10.6	10.2	9.7	9.8	9	9.1	9.2	9.1
Firing Rate	(MBTU/Hour)	107	107	107	108	108	108	108	107

TABLE IIIb

Run No.		5A	5B	6A	6B	7A	7B	8A*	8B*
Conversion	(wt%)	97.72	97.84	99.06	99.02	98.92	99.04	24.81	24.54
Severity		0.594	0.583	0.448	0.453	0.47	0.458	2.434*	2.433*
Selectivity		1.545	1.54	1.555	1.555	1.613	1.616	1.312*	1.306*
T3	(°F)	1574	1574	1606	1608	1615	1615	1563	1563
	(°C)	856.7	856.7	874.4	875.6	879.4	879.4	850.6	850.6
T1	(°F)	1291	1291	1294	1292	1291	1289	1290	1290
	(°C)	699.4	699.4	701.1	700	699.4	698.3	698.9	698.9
P3	(psig)	18	18	12	12	12	12	12	12
	(kPa, Gauge)	124	124	83	83	83	83	83	83
P1 (absolute)	(psi)	45.9							
	(kPa)	316							
Steam/Oil Ratio	(wt)	0.3	0.3	0.3	0.3	0.5	0.5	0.5	0.5
Feed Rate	(kilo pounds per hour, Quad)	9.1	9	8.2	8.2	7.8	7.8	7.8	7.8
Firing Rate	(MBTU/Hour)	107	107	108	108	108	108	108	108

* Data are for samples collected at the end of the cross-over section before the radiant section.

TABLE IV

Component Name	Run No.			
	7A	7B	8A*	8B*
Hydrogen	1.183	1.191	0.149	0.147
Carbon Dioxide	0.000	0.000	0.000	0.000
Ethene	38.861	38.985	5.747	5.664
Ethane	4.113	4.067	2.174	2.149
Acetylene	0.971	1.008	0.024	0.027
Nitrogen	1.102	1.093	0.145	0.138
Methane	24.099	24.127	4.382	4.337
Carbon Monoxide	0.041	0.074	0.000	0.013
Propane	0.278	0.273	0.266	0.270
Propene	11.338	11.046	10.667	10.550
Isobutane	0.014	0.011	1.145	1.158
Cyclopropane	0.000	0.000	0.000	0.000
Propadiene	0.284	0.286	0.000	0.000
n-Butane	1.048	0.934	73.025	73.289
1-Butene	0.398	0.374	0.533	0.530
Isobutene	0.259	0.249	0.514	0.515
Methylacetylene	0.510	0.519	0.022	0.023
t-2-Butene	0.152	0.148	0.299	0.298
c-2-Butene	0.148	0.139	0.205	0.206
1,3-Butadiene	3.643	3.648	0.136	0.133
Ethylacetylene	0.000	0.000	0.000	0.000
Vinylacetylene	0.123	0.134	0.161	0.176
1,2-Butadiene	0.020	0.052	0.000	0.000
1-Butene	0.000	0.000	0.004	0.016
Pentane	0.000	0.000	0.143	0.154
1,4-pentadienes	0.039	0.040	0.000	0.000
Dimethylacetylene	0.024	0.040	0.000	0.000
1-Pentene	0.050	0.039	0.087	0.093
2-Methyl-1-Butene	0.000	0.000	0.012	0.012
n-Pentane	0.000	0.000	0.010	0.012
Isoprene	0.194	0.205	0.011	0.010
t2-Pentane	0.000	0.000	0.010	0.010
3-methyl-1,2-butadiene	0.000	0.000	0.000	0.000
c2-Pentene	0.000	0.000	0.010	0.013
2-Methyl-2-Butene	0.000	0.000	0.000	0.000
1-t3-Pentadiene	0.142	0.145	0.009	0.005
Cyclopentadiene	1.620	1.697	0.011	0.014
2,2-Dimethylbutane	0.000	0.000	0.000	0.000
1,c3-pentadienes	0.112	0.108	0.000	0.000
Cyclopentene	0.077	0.077	0.019	0.008
3T,4-methyl-1-pentene	0.000	0.000	0.008	0.013
Cyclopentane	0.000	0.000	0.000	0.000
2,3-Dimethylbutane	0.000	0.000	0.000	0.000
2,3-Dimethyl-1-butene	0.000	0.000	0.000	0.000
2-Methylpentane	0.000	0.000	0.000	0.000

<u>Component Name</u>	<u>Run No.</u>			
	<u>7A</u>	<u>7B</u>	<u>8A*</u>	<u>8B*</u>
4-Methyl-1,2-pentadiene	0.000	0.000	0.000	0.000
3-Methyl-1,4-pentadiene	0.000	0.000	0.008	0.008
3-Methylpentane	0.000	0.000	0.000	0.000
2-Methyl-1-pentene	0.000	0.000	0.016	0.000
T3-Hexene	0.000	0.000	0.005	0.000

*Data are for samples collected at the end of the cross-over section before the radiant section.

[0060] Data of Run Nos. 8A and 8B clearly show that at a cross-over temperature (T1) of 1290°F (698.9°C), conversion of butane in the cross-over section reached at a level of close to 25%. Run Nos. 3A, 3B, 5A, 5B, 7A, 7B, 8A, and 8B have very similar conditions before the fluid stream enters the radiant section. The temperatures at the end of the radiant section (T3) increases from Run Nos. 3A/3B and 8A/8B (about 1563°F) to Run Nos. 5A/5B (1574°F) to Run Nos. 7A/7B (1615°F). The conditions in Run Nos. 3A/3B/8A/8B are almost identical in terms of T1, P1, T3, and P3. Thus, it can be expected that in all Run Nos. in TABLES IIIa and IIIb, significant cracking occurs in the cross-over section and part of the convection section. Data in TABLES IIIa and IIIb clearly show that the overall conversion in Run Nos. 3A/3B (which presumably corresponds to those in Run Nos. 8A/8B) is only slightly smaller than in Run Nos. 7A/7B, and the selectivity in Run Nos. 3A/3B is slightly higher than in Run Nos. 7A/7B, and the severity in Run Nos. 3A/3B is significantly lower than in Run Nos. 7A/7B, even though the radiant section temperature T3 in Run Nos. 7A/7B (1615°F) is much higher than in Run Nos. 3A/3B/8A/8B (1563°F). These data show that where the cross-over section temperature (T1) is sufficiently high to allow for significant cracking in the cross-over sections before the fluid stream is fed into the radiant section, one can use a substantially lower radiant section temperature (T3) to achieve an overall high conversion, selectivity, and more favorable severity.

20 Example 3

[0061] A gas oil feed having an average composition (wt%) and properties in TABLE Va as follows was used:

TABLE Va

Hydrocarbon Components (wt%)	n-Paraffins	15.70
	Isoparaffins	14.15
	Naphthenes	38.09
	Aromatics	32.06
	Total	100.00
Elemental Analysis (wt%)	Hydrogen	13.25
	Carbon	86.75
	Sulfur	0.14
Naphthenes Ring Breakdown	One Ring	12.32
	Two Rings	12.59
	Three Rings	8.42
	Four Rings	4.76
	Total	38.09
Asphaltenes		0.0
Properties	Mean Average Boiling Point (°F)	551
	Molecular Weight	225
	Bureau of Mines Combustion Index	33.46
	Color	22
	API Gravity	34.5
	Specific Gravity	0.8524

[0062] The gas oil feed was fed into a steam cracking furnace (with the following conditions of temperature at the end of the convection section (T1), pressure at the end of the convection section (P1), temperature at the outlet of the radiant section (T3), pressure at the outlet of the radiant section (P3), and firing rate in the furnace identified in TABLE V below. Conditions at the end of the radiant section and at the end of the cross-over section, as well compositions of the cracked fluid mixtures at the end of the radiant section and the cross-over fluid stream were analyzed and provided in TABLE VI below.

TABLE V

Conditions		Radiant Section	Cross-Over Section
Severity	Measurement No. 1	1.541	2.059
	Measurement No. 2	1.503	1.5
Selectivity	Measurement No. 1	1.957	1.903
	Measurement No. 2	1.98	1.984
T3	(°F)	1487	1486
	(°C)	808.3	807.8
T1	(°F)	1162	1161
	(°C)	627.8	627.2
P3	(psi, gauge)	22.5	22.5
	(kPa, Gauge)	155	155
P1	(psi, gauge)	34	34
	(kPa, Gauge)	234	234

<u>Conditions</u>		<u>Radiant Section</u>	<u>Cross-Over Section</u>
Feed Rate	(kilo pounds per hour)	14.64	14.29
Firing Rate	(MBTU per hour)	265	264.9
Steam/Oil Ratio	(wt)	0.45	0.45

TABLE VI

<u>Component Name</u>	<u>Radiant Cracked Fluid Stream Composition (wt%)</u>	<u>Cross-Over Stream Composition (wt%)</u>
Hydrogen	0.403	0.053
Carbon dioxide	0.000	0.000
Ethene	16.473	3.225
Ethane	4.146	1.669
Acetylene	0.122	0.004
Nitrogen	0.166	0.015
Methane	8.412	1.695
Carbon monoxide	0.000	0.000
Propane	0.735	0.469
Propene	12.959	3.489
Isobutane	0.043	0.020
Cyclopropane	0.001	0.000
Propadiene	0.122	0.000
n-Butene	0.112	0.067
1-Butene	2.686	1.181
Isobutene	2.233	0.753
Methylacetylene	0.126	0.007
t2-Butene	0.718	0.260
c2-Butene	0.450	0.138
1,3-Butadiene	4.077	0.487
Ethylacetylene	0.002	0.000
Vinylacetylene	0.004	0.000
1, 2-Butadiene	0.036	0.003
3-Methyl-1-Butene	0.154	0.147
Isopentane	0.023	0.009
1,4-pentadiene	0.118	0.042
Dimethylacetylene	0.000	0.000
1-Pentene	0.481	0.948
2-Methyl-1-butene	0.442	0.309
n-Pentane	0.26	0.029
Isoprene	1.114	0.218
T2-Pentene	0.287	0.128
3-Methyl-1,2-butadiene	0.000	0.000
c2-Pentane	0.185	0.074
2-Methyl-2-butene	0.208	0.139
1-t3-pentadiene	0.541	0.192
Cyclopentadiene	1.525	0.173
2,2-Dimethylbutane	0.009	0.034
1,c3-Pentadiene	0.335	0.094

<u>Component Name</u>	<u>Radiant Cracked Fluid Stream Composition (wt%)</u>	<u>Cross-Over Stream Composition (wt%)</u>
Cyclopentene	0.219	0.205
3&4-Methyl-1-pentene	0.033	0.277
Cyclopentane	0.021	0.008
2,3-Dimethyl-butane	0.000	0.001
2,3-Dimethyl-1-butene	0.016	0.024
2-Methyl-pentane	0.010	0.009
4-Methyl-t2-pentene	0.053	0.030

[0063] As can be seen from the above TABLEs V and VI, significant cracking reactions occurred in the convention section and the cross-over section, leading to the presence of substantial amounts of cracked products (ethene, propene, and the like) in the composition of the cross-over fluid stream. This allowed for running the cracking reactions in the radiant section at a reduced temperature of 1486°F and a reduce severity of the conditions. In general, such milder cracking conditions in the radiant section lead to lower propensity of coke deposition on the inner walls of the radiant section, and hence a longer run-length between required de-coking sessions. In addition, the cracking conditions resulted in the production of ethene, propene, butene, butadiene, and cyclopentadiene at high concentrations, all of which can be valuable products upon separation from the cracked fluid mixture.

CLAIMSWhat is claimed is:

- 5 1. A process for steam cracking a hydrocarbon material in a steam cracking furnace including a tube comprising a convection section, a cross-over section downstream of the convection section, and a heated radiant section downstream of the cross-over section, comprising:
- 10 feeding the hydrocarbon material and steam into the convection section to obtain a feed mixture;
- heating the hydrocarbon material mixture in the convection section to obtain a first fluid stream at a temperature T1 at the end of the convection section;
- 15 passing the first fluid stream through the cross-over section to obtain a second fluid stream at the end of the cross-over section at a temperature T2;
- passing the second fluid stream through the radiant section to obtain a cracked fluid mixture at the end of the radiant section at a temperature T3, wherein:
- T3 is higher than T2 and T1; and
- T1 and T2 are selected such that significant cracking reaction occurs at least in a
- 20 portion of the convection section and at least a portion of the cross-over section.
2. The process of claim 1, wherein:
- the hydrocarbon material comprises olefins at a total concentration of C0 mol% based on the total moles of the fluid species in the hydrocarbon material;
- 25 the second fluid stream comprises olefins at a total concentration of C2 mol% based on the total moles of the fluid species therein; and
- $C2 - C0 \geq 5$.
3. The process of claim 2, wherein:
- 30 the first fluid stream comprise olefins at a total concentration of C1 mol% based on the total moles of the fluid species therein, and
- $C1 - C0 \geq 1$.
4. The process of claim 2, wherein:
- 35 $C2 - C1 \geq 1$.

5. The process of any of the preceding claims, wherein the hydrocarbon material comprises ethane at a concentration of at least 50 mol% based on the total moles of hydrocarbons in the hydrocarbon material, and T1 is in a range from 1300 to 1435°F (704.4 to 779.4°C).
- 5
6. The process of claim 5, wherein T2 is in a range from 1275 to 1430°F (690.6 to 776.6°C).
7. The process of claim 5 or claim 6, wherein T3 is in a range from 1500 to 1800°F (815.6 to 982.2°C).
- 10
8. The process of any of claims 5 to 7, wherein the total concentration of C5 and C6 olefins and benzene in the cracked fluid mixture is in a range from 1 to 8 mol%, based on the total moles of species therein.
- 15
9. The process of any of claims 5 to 8, wherein the overall conversion of ethane in the steam cracking furnace is in the range from 60% to 75%.
10. The process of any of claims 1 to 4, wherein the hydrocarbon material comprises propane at a concentration of at least 50 mol% based on the total moles of hydrocarbons in the hydrocarbon material, and T1 is in a range from 1200 to 1415°F (648.9 to 768.3°C).
- 20
11. The process of claim 10, wherein T2 is in a range from 1175 to 1410°F (635.0 to 765.6°C).
12. The process of claim 10 or claim 11, wherein T3 is in a range from 1525 to 1800°F (829.4 to 982.2°C).
- 25
13. The process of any of claims 10 to 12, wherein the overall conversion of propane in the steam cracking furnace is in the range from 80% to 96%.
- 30
14. The process of any of claims 1 to 4, wherein the hydrocarbon material comprises butane at a concentration of at least 50 mol% based on the total moles of hydrocarbons in the hydrocarbon material, and T1 is in a range from 1150 to 1400°F (670.9 to 809.8°C).

15. The process of claim 14, wherein T2 is from 25 to 150°F (14 to 83°C) lower than T1.

16. The process of claim 14 or claim 15, wherein T3 is in a range from 1475 to 1700°F (801.7 to 962.7°C).

5

17. The process of any of claims 14 to 16, having a severity index in a range from 0.50 to 1.65.

18. The process of any of claims 1 to 4, wherein the hydrocarbon material comprises naphtha
10 at a concentration of at least 50 mol% based on the total moles of the hydrocarbon material, and T1 is in a range from 1150 to 1250°F (621.1 to 676.6°C).

19. The process of claim 18, wherein T2 is in a range from 1125 to 1245°F (607.2 to 673.9°C).

15

20. The process of claim 18 or claim 19, wherein T3 is in a range from 1450 to 1600°F (787.8 to 871.1°C).

21. The process of any of claims 18 to 20, having a severity index in a range from 0.50 to
20 1.25.

22. The process of any of claims 1 to 4, wherein the hydrocarbon material comprises a gas oil at a concentration of at least 50 mol% based on the total moles of hydrocarbons in the hydrocarbon material, and T1 is in a range from 1060 to 1160°F (571.1 to 626.6°C).

25

23. The process of claim 22, wherein T2 is in a range from 1035 to 1155°F (557.2 to 623.9°C).

24. The process of claim 22 or claim 23, wherein T3 is in a range from 1375 to 1525°F
30 (746.1 to 849.4°C).

25. The process of any of claims 22 to 24, having a severity index in a range from 0.8 to 2.4.