

SURGICAL FASTENER AND CUTTER WITH SINGLE CABLE ACTUATOR

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] The present application is a continuation-in-part of U.S. Application No. 11/344,021 filed on January 31, 2006 and entitled "Electro-Mechanical Surgical Cutting And Fastening Instrument Having A Rotary Firing And Closure System With Parallel Closure And Anvil Alignment Components," which is hereby expressly incorporated by reference in its entirety.

FIELD OF THE INVENTION

[0002] The present invention relates broadly to methods and devices for controlling movement and actuation of an end effector on a surgical device.

BACKGROUND OF THE INVENTION

[0003] Endoscopic surgical instruments are often preferred over traditional open surgical devices since the use of a natural orifice tends to reduce the post-operative recovery time and complications. Consequently, significant development has gone into a range of endoscopic surgical instruments that are suitable for precise placement of a working end of a tool at a desired surgical site through a natural orifice. These tools can be used to engage and/or treat tissue in a number of ways to achieve a diagnostic or therapeutic effect.

[0004] One tool commonly used in endoscopic surgery is a surgical stapler and cutter, which typically includes an end effector that simultaneously makes a longitudinal incision in tissue and applies lines of staples on opposing sides of the incision. The end effector includes a pair of cooperating jaw members that are capable of passing through a cannula passageway. One of the jaw members receives a staple cartridge having at least two laterally spaced rows of staples. The other jaw member defines an anvil having staple-forming pockets aligned with the rows of staples in the cartridge. The instrument includes a plurality of reciprocating wedges which, when driven distally, pass through openings in the staple cartridge and engage drivers supporting the staples to effect the firing of the staples toward the anvil. The instrument also includes a knife that cuts the stapled tissue.

[0005] Surgical staplers/cutters continue to increase in complexity and function with each

generation due to the desire to introduce the devices endoscopically. However, endoscopic surgery requires that the shaft of the device be flexible while still allowing the end effector to be articulated and/or rotated to angularly orient the end effector relative to the tissue, and to be actuated to close the end effector and fire the staples. Integration of the controls for articulating, rotating, and/or actuating an end effector tend to be complicated by the use of a flexible shaft and by the size constraints of an endoscopic instrument. Generally, the control motions are all transferred through the shaft as longitudinal translations, which can interfere with the flexibility of the shaft.

[0006] There is also a desire to lower the force necessary to actuate the end effector to a level that all or a great majority of surgeons can handle. One known solution to lower the force-to-fire is to use electrical motors. However, surgeons typically prefer to experience feedback from the end-effector to assure proper operation of the end effector. The user-feedback effects are not suitably realizable in present motor-driven devices.

[0007] Accordingly, there remains a need for improved methods and devices for controlling movement and actuation of an end effector on an endoscopic surgical device.

SUMMARY OF THE INVENTION

[0008] The present invention generally provides methods and devices for controlling movement, i.e., rotation, and actuation, i.e., closing and firing, of an end effector on an endoscopic surgical device. In one exemplary embodiment, an endoscopic stapling device is provided and includes an elongate shaft having proximal and distal ends, an end effector coupled to a distal end of the elongate shaft for engaging tissue and delivering at least one fastener to the engaged tissue, a handle coupled to a proximal end of the elongate shaft, and an actuator operatively associated with the end effector and the handle. The actuator has a first position in which rotation of the actuator is effective to rotate the end effector, and a second position in which rotation of the actuator is effective to fire at least one fastener from the end effector. The actuator can also be adapted to translate along a longitudinal axis of the elongate shaft between the first and second positions. Translation of the actuator from the first position to the second position can be effective to close the end effector for engaging tissue.

[0009] The end effector can have a variety of configurations, but in one embodiment, the end effector can include opposed jaws for engaging tissue therebetween. The actuator can include a clutch on the distal end thereof, and, when the actuator is translated from the first position to the second position, the clutch can be adapted to abut against a cam surface formed on at least one of the jaws to close the jaws. The end effector can also include a cartridge removably disposed therein and containing a plurality of staples for stapling tissue and a blade for cutting stapled tissue.

[0010] The actuator can also have a variety of configurations, but in one embodiment it can be a rotatable and translatable drive shaft operatively associated with the handle and the end effector. The drive shaft can include a clutch on a distal end thereof. When the actuator is in the first position, the clutch can be adapted to engage a housing of the end effector such that rotation of the actuator and the clutch is effective to rotate the end effector. When the actuator is in the second position, the clutch can be adapted to engage and rotate a gear assembly that advances a driver disposed within the end effector to fire at least one fastener from the end effector. In other embodiments, at least a portion of the drive shaft can be formed from an electroactive polymer material, and wherein the handle is effective to deliver energy to the drive shaft to cause the electroactive polymer material to axially contract and radially expand and thereby translate the drive shaft.

[0011] The handle of the device can also have a variety of configurations, and in one embodiment the handle can include a translating member that is adapted to translate the actuator between the first and second positions, and a rotatable member that is adapted to rotate the actuator relative to the elongate shaft. The device can also include other features, such as an optical image gathering unit disposed on a distal end of the elongate shaft and configured to acquire images during endoscopic procedures. The optical image gathering unit can couple to an external image display screen, or an image display screen can be disposed on a proximal portion of the device for communicating with the optical image gathering unit to display the acquired images.

[0012] In another embodiment, an endoscopic stapling device is provided having an elongate shaft with an end effector coupled to a distal end thereof, a handle movably coupled to a

proximal end thereof, and a drive shaft operatively associated with the handle and the end effector and adapted to rotate the end effector relative to the elongate shaft, to close the end effector to engage tissue, and to fire at least one fastener from the end effector. The drive shaft can be movable between a first position, in which rotation of the drive shaft causes corresponding rotation of the end effector relative to the elongate shaft without closing and firing the end effector, and a second position, in which rotation of the drive shaft causes closing and firing of the end effector without rotating the end effector relative to the elongate shaft. The drive shaft can also be adapted to translate relative to a longitudinal axis of the elongate shaft to move between the first and second positions. Translation of the drive shaft from the first position to the second position can be adapted to close opposed jaws of the end effector. For example, a distal end of the drive shaft can engage a portion of the end effector to rotate the end effector when the drive shaft is in the first position, and a distal end of the drive shaft can engage a gear assembly to rotate the gear assembly when the drive shaft is in the second position. Rotation of the gear assembly can be effective to advance a driver disposed within the end effector to fire at least one fastener from the end effector.

[0013] Methods for fastening tissue are also provided, and in one exemplary embodiment the method includes inserting an elongate shaft into a body lumen to position an end effector coupled to a distal end of the elongate shaft adjacent to tissue to be fastened. A proximal end of the elongate shaft can include a handle assembly movably coupled thereto. The method can further include rotating a rotatable member in a first position on the handle assembly to rotate the end effector about a longitudinal axis of the elongate shaft, and rotating the rotatable member in a second position on the handle assembly to fire at least one fastener disposed within the end effector without rotating the end effector. The method can also include moving a translating member on the handle assembly to close opposed jaws of the end effector around tissue to be fastened. While the method can be used in various procedures, in certain exemplary embodiments the elongate shaft is flexible and is inserted transluminally.

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] The invention will be more fully understood from the following detailed description taken in conjunction with the accompanying drawings, in which:

[0015] FIG. 1A is a perspective view of one exemplary embodiment of a surgical stapling device in accordance with the present invention;

[0016] FIG. 1B is a perspective view of an end effector of the surgical stapling device of FIG. 1A;

[0017] FIG. 2 is a perspective, partially cut-away view of a portion of an elongate shaft of the surgical stapling device of FIG. 1A, showing a drive shaft extending through the elongate shaft;

[0018] FIG. 3 is a side cross-sectional view of the end effector of the surgical stapling device of FIG. 1A;

[0019] FIG. 4 is a top view of a portion of the end effector of the surgical stapling device of FIG. 1A, showing a clutch engaging the end effector to effect rotation thereof;

[0020] FIG. 5A is an enlarged side cross-sectional view of a portion of the end effector of FIG. 1A;

[0021] FIG. 5B is a side cross-sectional view of the end effector shown in FIG. 5A, showing the jaws moved to a closed position;

[0022] FIG. 6 is a side view of a portion of the end effector of FIG. 1A, showing a gear and driver assembly;

[0023] FIG. 7 is a perspective view of a portion of the end effector of FIG. 1A, showing a lead screw being driven through the end effector to fire staples from the cartridge;

[0024] FIG. 8A is a perspective view of a cartridge of the end effector of FIG. 1A;

[0025] FIG. 8B is a perspective view of a drive sled of the cartridge of FIG. 8A;

[0026] FIG. 9A is a perspective view of a handle of the device of FIG. 1A;

[0027] FIG. 9B is a perspective view of the handle of FIG. 9A, showing a knob in a second position; and

[0028] FIG. 10 is a perspective view of a portion of the elongate shaft of the device of FIG. 1A,

showing an optical image gathering unit.

DETAILED DESCRIPTION OF THE INVENTION

[0029] Certain exemplary embodiments will now be described to provide an overall understanding of the principles of the structure, function, manufacture, and use of the devices and methods disclosed herein. One or more examples of these embodiments are illustrated in the accompanying drawings. Those of ordinary skill in the art will understand that the devices and methods specifically described herein and illustrated in the accompanying drawings are non-limiting exemplary embodiments and that the scope of the present invention is defined solely by the claims. The features illustrated or described in connection with one exemplary embodiment may be combined with the features of other embodiments. Such modifications and variations are intended to be included within the scope of the present invention.

[0030] The present invention provides method and devices for controlling movement, i.e., rotation, and actuation, i.e., closing and/or firing, of an end effector on a surgical stapling device. In general, the surgical stapling device can include an elongate shaft having a distal end with an end effector extending therefrom for engaging tissue and delivering one or more fasteners to the engaged tissue, and a proximal end with a handle for controlling rotation of the end effector whereby the end effector swivels about the longitudinal axis of the elongate shaft, and actuation of the end effector whereby the end effector is closed and fired to deliver one or more fasteners and optionally cut tissue being fastened. In an exemplary embodiment, the device includes a single actuation mechanism that is configured to effect both rotation and actuation of the end effector. The actuation mechanism can be operatively associated with the handle and the end effector and it can have a first position in which the actuation mechanism is effective to rotate the end effector without actuating the end effector, and a second position in which the actuation mechanism it is effective to fire at least one fastener from the end effector without rotating the end effector. The actuation mechanism can also be configured such that movement from the first position to the second position is effective to close the end effector to engage tissue. Various other features are also provided to facilitate use of the device. A person skilled in the art will appreciate that the particular configuration of the end effector can vary and that the various control techniques described herein can be used on a variety of surgical instruments.

[0031] FIG. 1A illustrates one exemplary embodiment of an endoscopic surgical device that is in the form of a linear stapling and cutting device 10 for applying multiple linear rows of staples to tissue and for cutting the stapled tissue. As shown, the device 10 generally includes an elongate shaft 12 having a proximal end 12a with a handle 14 coupled thereto, and a distal, working end 12b having an end effector 16 coupled thereto or formed thereon. The elongate shaft 12 can have a variety of configurations. For example, it can be solid or hollow, and it can be formed from a single component or multiple segments. As shown in FIG. 1A, the elongate shaft 12 is hollow and is formed from multiple connecting segments to allow the elongate shaft 12 to flex. The flexibility of the shaft 12, as well as a relatively small diameter, allows the shaft 12 to be used in endoscopic procedures, whereby the device is introduced translumenally through a natural orifice. The end effector 16 can also have a variety of configurations, but in the illustrated embodiment, as shown in more detail in FIG. 1B, the end effector 16 includes opposed first and second jaws 18, 20 that are pivotally coupled to one another and that are adapted to receive tissue therebetween. The first jaw 18 is adapted to contain a staple cartridge having multiple staples disposed therein and configured to be driven into tissue, and the second jaw 20 forms an anvil for deforming the staples. The end effector 16 can be coupled to the distal end of the elongate shaft using various techniques, but in an exemplary embodiment the end effector 16 is rotatably coupled to the elongate shaft such that the end effector 16 can rotate about an axis of the elongate shaft. The end effector 16 can also be pivotally coupled to the distal end of the elongate shaft, or it can include a flexible neck 26 formed thereon for allowing angular movement of the end effector relative to the elongate shaft.

[0032] While not an essential feature of the present invention, FIG. 1A also illustrates a handle 14 that is operatively associated with the end effector 16 such that pivotal movement of the handle 14 is mimicked by the end effector 16, thereby allowing the handle 14 to be used to articulate the end effector 16 in multiple planes. The particular mechanism for achieving mimicking motion is described in more detail in the following U.S. Patent Applications filed on even date herewith: "Methods and Devices for Controlling Articulation," by Mark S. Ortiz, Frederick E. Shelton IV, and James Spivey (Atty. Docket No. 100873-32 (END5568USANP1)), "Articulating Endoscopic Accessory Channel," by James Spivey, Mark S. Ortiz, and Frederick E. Shelton IV (Atty. Docket No. 100873-105 (END5568USANP2)), and "Surgical Fastener and Cutter with Mimicking End Effector," by Mark S. Ortiz and Frederick E. Shelton IV (Atty.

Docket No. 100873-109 (END5568USANP3)), each of which is hereby incorporated by reference in its entirety.

[0033] The device 10 can also include an actuation mechanism for controlling movement and actuation of the end effector 16. Movement can include rotation of the end effector 16 about the longitudinal axis *A* of the elongate shaft 12, and actuation of the end effector, whereby the jaws 18, 20 are closed to engage tissue and the staples are fired from the end effector into the engaged tissue. Actuation can also include cutting the stapled tissue. In an exemplary embodiment, a single actuation mechanism is operatively associated with the handle and the end effector such that it can effect rotation and actuation of the end effector. While the actuation mechanism can have a variety of configurations, in the illustrated embodiment the actuation mechanism is in the form of a drive shaft 28, which is shown in FIG. 2 extending through a portion of the elongate shaft 12. The drive shaft 28 can be in the form of an elongate cable, multiple wound or braided cables, or a rod or shaft, and it is preferably flexible to allow flexion as the flexible shaft 12 of the device 10 is inserted translumenally through a tortuous pathway. The drive shaft 28 includes proximal and distal ends that are coupled to various portions of the handle 14 and the end effector 16, respectively, as will be discussed in more detail below. In use, the drive shaft 28 is configured to rotate and translate (slide) relative to the elongate shaft 12 to effect rotation and actuation of the end effector 16.

[0034] The distal end 28b of the drive shaft 28 and the end effector 16 are shown in more detail in FIG. 3, and as shown the distal end 28b of the drive shaft 28 extends distally from the elongate shaft 12 and extends into a proximal end of the end effector 16. The distal end 28b of the drive shaft 28 is preferably configured to rotate the end effector 16 when the drive shaft 28 is in a first position, and to fire the end effector 16 when the drive shaft 28 is in a second position. Movement of the drive shaft 28 from the first position to the second position can also be effective to close the jaws 18, 20 of the end effector 16. While various techniques can be used to allow the drive shaft 28 to effect rotation, closing, and firing of the end effector 16, in the illustrated embodiment the distal end 28b of the drive shaft 28 includes a clutch 30 formed thereon or fixedly mated thereto. The clutch 30 can have various shapes and sizes, but it is preferably asymmetrical to allow the clutch 30 to engage various mechanism within the end effector 16, as will be discussed below. In the illustrated embodiment, the clutch 30 has a

hexagonal shape. When the clutch 30 is in a first position, e.g., a distal position shown in FIG. 3, it can be engaged with the end effector 16 such that rotation of the drive shaft 28 and the clutch 30 is effective to rotate the end effector 16. In particular, as shown in FIG. 4, the opposed inner walls of first jaw 18 can include opposed protrusions (only one protrusion 18a is shown in FIG. 4) formed thereon that are configured to engage the clutch 30 therebetween. Thus, when the clutch 30 is positioned between the protrusions, rotation of the clutch 30 is effective to rotate the end effector 16 about its longitudinal axis and relative to the elongate shaft 12.

[0035] Once the end effector 16 is rotated to a desired position, the drive shaft 28 and clutch 30 can be moved axially relative to the elongate shaft 12 to remove the clutch 30 from between the protrusions in the first jaw 18. In an exemplary embodiment, the drive shaft 28 and clutch 30 are translated along the elongate shaft 12 in a proximal direction to position the drive shaft 28, and thus the clutch 30, in the second position. As the drive shaft 28 and clutch 30 are moved proximally, the drive shaft 28 and clutch 30 can be effective to close the jaws 18, 20 of the end effector 16. In particular, as shown in FIG. 5, the second jaw, i.e., the anvil 20, can include a proximal end 20a having a ramped surface 20r formed thereon and extending into a path of movement of the clutch 30. The ramped surface 20r on the anvil 20 is located proximal to a pivot point at which the anvil 20 is attached to the first jaw 18. As the clutch 30 moves proximally with the drive shaft 28, the clutch 30 can abut against the ramped surface 20r, pushing the surface upward away from the first jaw 18. As a result, the anvil 20 will pivot to a closed position, as shown in FIG. 5B, to engage tissue positioned between the jaws 18, 20. When the drive shaft 28 and clutch 30 are in the second proximal position, the second jaw or anvil 20 will remain closed as the clutch 30 will prevent the proximal end 20a of the second jaw or anvil 20 from returning to its initial position.

[0036] Once the drive shaft 28 and clutch 30 are in the second position, rotation of the drive shaft 28 and clutch 30 can be effective to fire at least one fastener from the jaws 18, 20. In particular, the clutch 30 can be configured to engage a gear assembly that is effective to advance a driver through the end effector 16. The gear assembly is shown in FIG. 6 and includes first (upper) and second (lower) drive gears 32, 34 that are in the form of cylindrical members having teeth formed therearound. The first drive gear 32 includes a socket 32a (shown in FIGS. 5A and 5B) formed therein that has a shape that complements a shape of a portion of the clutch 30 such

that the socket 32a can receive and engage the clutch 30 on the drive shaft 28. In particular, the clutch 30 can include a second hexagonal member 30a (FIG. 4) formed thereon and configured to be received in the socket 32a. The second drive gear 34 is positioned adjacent to and in engagement with the first drive gear 32. As a result, when the drive shaft 28 and clutch 30 are rotated, the first drive gear 32 will rotate to rotate the second drive gear 34. The second drive gear 34, in turn, includes a shaft or lead screw 36 extending distally therefrom and fixedly coupled thereto. The lead screw 36 has threads (not shown) formed on an external surface thereof, and a lead nut 38 is threadably disposed around the lead screw 36. As the second drive gear 34 and lead screw 36 are rotated, the lead screw 36 remains in a fixed axial position, i.e., it does not translate longitudinally, thereby causing the lead nut 38 to move distally through the end effector 16, as shown in FIG. 7. The lead nut 38, in turn, is coupled to or abuts against a proximal end of a drive sled 40 that is effective to drive one or more fasteners from a cartridge 42 disposed within the first jaw 18. Thus, as the drive shaft 28 and clutch 30 are rotated, the first drive gear 32 rotates to rotate the second drive gear 34 and the lead screw 36 attached thereto. As the lead screw 36 rotates, the lead nut 38 is moved distally within the end effector 16, thereby advancing the drive sled 40 distally within the end effector 16. The drive sled 40 will force one or more fasteners through one or more fastener receiving slots formed in the cartridge 42. The fasteners will extend through tissue engaged between the jaws 18, 20, and will deform against the anvil 20 to fasten the tissue. The drive sled 40 can also include a blade formed thereon and configured to cut tissue being fastened.

[0037] While the particular configuration of the drive sled 40 and the cartridge 42 can vary depending on the particular configuration of the end effector 16, in an exemplary embodiment, as shown in FIG. 8A, the cartridge 42 is configured to apply multiple linear rows of staples, and to form a cut extending between the rows of staples to separate the stapled tissue. In particular, the cartridge 42 is in the form of a generally elongate housing that can be removably disposed within a channel formed in the first jaw 18. The housing includes several, e.g., six, linear rows of staple-receiving slots 44 formed therein, and each slot contains a staple therein. Several driver members (not shown) are positioned underneath the staples for supporting the staples and advancing the staples through the staple-receiving slots 44. The drive sled 42 is shown in more detail in FIG. 8B and it includes several, e.g., four, upright members 41a, 41b, 41c, 41d formed thereon and having a wedge-shaped configuration. As the sled 40 is advanced distally through

the end cartridge 40, the upright members 41a-d will abut against the driver members, moving them upward toward the anvil 20, thereby driving the staples toward the anvil 20. The drive sled 40 also includes a central member that extends through the middle of the cartridge, and that has a blade 40b formed thereon for cutting the stapled tissue.

[0038] In use, the cartridge 42, with the drive sled 40 coupled thereto, can be disposed within the end effector 16 for a single use application. Once the staples are fired from the cartridge 42, a new cartridge having a new drive sled 40 can be placed in the jaw 18. Such a configuration is particularly advantageous as the blade 40b can be replaced with each use, rather than most stapling devices in which the drive sled and blade are disposed within the jaw of the end effector, rather than being removable with the cartridge. A person skilled in the art will appreciate that virtually any cartridge known in the art can be used with the various devices disclosed herein, and that the illustrated cartridge 42 is merely one exemplary embodiment of a cartridge.

[0039] As indicated above, the proximal end of the drive shaft 28 is coupled to various portions of the handle 14 that are effective to rotate the drive shaft 28 in the first position to thereby rotate the end effector 16, to translate the drive shaft 28 axially into a second position to thereby close the jaws 18, 20, and to rotate the drive shaft 28 in the second position to fire the staples from the cartridge 42 in the end effector 16. While various techniques known in the art can be used to effect rotation and translation of the drive shaft 28, in one exemplary embodiment the handle 14 can include a rotatable and translatable knob 50 for rotating and translating the drive shaft 28 relative to the elongate shaft 12 of the device 10. The knob 50 of the handle 14 is shown in more detail in FIG. 9A and 9B, and as shown the knob 50 is merely a cylindrical member disposed on the proximal-most end of the handle 14 and coupled to the proximal end of the drive shaft 28. FIG. 9A illustrates the knob 50 in a first position, in which rotation of the knob 50 will rotate the drive shaft 28 to thereby rotating the end effector 16. FIG. 9B illustrates the knob 50 moved proximally to a second position, i.e., retracted relative to the elongate shaft 12, to thereby close the jaws 18, 20. Movement of the knob 50 can be achieved by simply pulling on the knob 50, or alternatively the device 10 can include a separate translating member 55 formed on the handle 14 and coupled to the drive shaft 28 for moving the drive shaft 28, and consequently the knob 50) between the first and second positions. In an exemplary embodiment, as shown, the translatable member 55 is shaped to fit within a palm of a user's hand. A toggle link or over-center link

extends between the translatable member 55 and the handle 14 for controlling movement of the translatable member 55 relative to the handle. In use, the translatable member 55 can be squeezed to close the translatable member 55, thereby applying a proximally directed force to the drive shaft 28 to move the drive shaft 28 to the second position, shown in FIG. 9B. Rotation of the knob 50 in the second position will be effective to fire the staples from the cartridge 42, as previously explained, thereby stapling the tissue engaged between the jaws. The tissue can also be cut simultaneous with or subsequent to firing the staples. A person skilled in the art will appreciate that the particular location and configuration of the knob or other member used to effect rotation and translation of the drive shaft 28 can vary.

[0040] While FIGS. 9A-9B illustrate a rotatable and translatable knob, in other embodiments, the drive shaft 28 used to effect rotation and actuation of the end effector 16 can optionally be formed from an electroactive polymer material. Electroactive polymers (EAPs), also referred to as artificial muscles, are materials that exhibit piezoelectric, pyroelectric, or electrostrictive properties in response to electrical or mechanical fields. In particular, EAPs are a set of conductive doped polymers that change shape when an electrical voltage is applied. The conductive polymer can be paired to some form of ionic fluid or gel and electrodes, and the flow of ions from the fluid/gel into or out of the conductive polymer can induce a shape change of the polymer. Typically, a voltage potential in the range of about 1V to 4kV can be applied depending on the particular polymer and ionic fluid or gel used. It is important to note that EAPs do not change volume when energized, rather they merely expand in one direction and contract in a transverse direction. Thus, the drive shaft 28 previously disclosed herein can be replaced by an EAP actuator, and the handle 14 can be configured to activate an external or internal energy source to selectively deliver energy to the EAP cable to cause the EAP cable to axially contract and move the clutch 30 from the first position to the second position. The EAP cable can then be rotated, e.g., using a rotatable knob, to fire one or more staples from the end effector 16. When energy delivery is terminated, the EAP cable will axially expand to return the clutch 30 to the first position.

[0041] The various devices disclosed herein can also include a variety of other features to facilitate use thereof. For example, the device 10 can include an optical image gathering unit disposed on a distal end of the elongate shaft 12, or on the end effector 16, and configured to

acquire images during endoscopic procedures. While the location of the unit can vary, FIG. 10 illustrates a ramp-shaped housing 60 that protrudes from an outer surface of a coupling 63 on the elongate shaft 12, and that contains the optical image gathering unit therein. A viewing window 62 is formed on a distal-facing surface of the housing 60 to allow the unit to acquire images of the end effector 16 and surrounding surgical site. The images from the optical image gathering unit can be transferred to an external image display screen, or alternatively the device 10 can include image display screen disposed on or coupled to a proximal portion of the device. FIGS. 9A-9B illustrates one embodiment of an image display screen 70 protruding outward from the handle 14.

[0042] The present invention also provides exemplary methods for fastening and optionally cutting tissue. In one exemplary embodiment, the elongate shaft of a surgical stapling and cutting device, such as device 10 of FIG. 1A, can be inserted transluminally, i.e., trans-orally or trans-anally, into a body lumen to position the end effector 16 coupled to the distal end 12b of the elongate shaft 12 adjacent to tissue to be fastened. The end effector 16 can then be manipulated to position tissue to be fastened within the jaws 18, 20, and the knob 50 can be moved as previously described to rotate the end effector 16, close the jaws 18, 20, and fire the staples.

[0043] In another embodiment, the various devices disclosed herein, including portions thereof, can be designed to be disposed of after a single use, or they can be designed to be used multiple times. In either case, the device can be reconditioned for reuse after at least one use.

Reconditioning can include any combination of the steps of disassembly of the device, followed by cleaning or replacement of particular pieces, and subsequent reassembly. By way of example, the cartridge, including the drive sled, can be removed from the end effector and replaced with a new cartridge containing one or more fasteners therein. The cartridge can also preferably contain a blade formed on the drive sled for cutting fastened tissue. Various other portions of the device can also be removed and replaced. Upon cleaning and/or replacement of particular parts, the device can be reassembled for subsequent use either at a reconditioning facility, or by a surgical team immediately prior to a surgical procedure. Those skilled in the art will appreciate that reconditioning of a device can utilize a variety of techniques for disassembly, cleaning/replacement, and reassembly. Use of such techniques, and the resulting reconditioned

device, are all within the scope of the present application.

[0044] One skilled in the art will appreciate further features and advantages of the invention based on the above-described embodiments. Accordingly, the invention is not to be limited by what has been particularly shown and described, except as indicated by the appended claims. All publications and references cited herein are expressly incorporated herein by reference in their entirety.

CLAIMS:

1. An endoscopic stapling device, comprising:
 - an elongate shaft having proximal and distal ends;
 - an end effector coupled to a distal end of the elongate shaft for engaging tissue and delivering at least one fastener to the engaged tissue;
 - a handle coupled to a proximal end of the elongate shaft; and
 - an actuator operatively associated with the end effector and the handle, the actuator having a first position in which rotation of the actuator is effective to rotate the end effector, and a second position in which rotation of the actuator is effective to fire at least one fastener from the end effector.
2. The device of claim 1, wherein the actuator is adapted to translate along a longitudinal axis of the elongate shaft between the first and second positions, and wherein translation of the actuator from the first position to the second position is effective to close the end effector for engaging tissue.
3. The device of claim 2, wherein the end effector includes opposed jaws for engaging tissue therebetween and the actuator includes a clutch on the distal end thereof, and wherein, when the actuator is translated from the first position to the second position, the clutch is adapted to abut against a cam surface formed on at least one of the jaws to close the jaws.
4. The device of claim 1, wherein the actuator comprises a rotatable and translatable drive shaft operatively associated with the handle and the end effector.
5. The device of claim 4, wherein the drive shaft includes a clutch on a distal end thereof.
6. The device of claim 5, wherein, when the actuator is in the first position, the clutch is adapted to engage a housing of the end effector such that rotation of the actuator and the clutch is effective to rotate the end effector.
7. The device of claim 5, wherein, when the actuator is in the second position, the clutch is adapted to engage and rotate a gear assembly that advances a driver disposed within the end effector to fire at least one fastener from the end effector.

8. The device of claim 2, wherein the handle includes a translating member that is adapted to translate the actuator between the first and second positions, and a rotatable member that is adapted to rotate the actuator relative to the elongate shaft.
9. The device of claim 1, wherein the end effector includes a cartridge removably disposed therein, the cartridge containing a plurality of staples for stapling tissue and a blade for cutting stapled tissue.
10. The device of claim 4, wherein at least a portion of the drive shaft is formed from an electroactive polymer material, and wherein the handle is effective to deliver energy to the drive shaft to cause the electroactive polymer material to axially contract and radially expand and thereby translate the drive shaft.
11. The device of claim 1, further comprising an optical image gathering unit disposed on a distal end of the elongate shaft, the optical image gathering unit being adapted to acquire images during endoscopic procedures.
12. The device of claim 11, further comprising an image display screen disposed on a proximal portion of the device and adapted to communicate with the optical image gathering unit to display the acquired images.
13. A method of reconditioning the device of claim 1, comprising:
removing and replacing a cartridge removably disposed in the end effector to prepare the device for re-use, the cartridge containing a plurality of fasteners disposed therein.
14. The method of claim 13, wherein the cartridge includes a blade disposed therein for cutting fastened tissue.
15. An endoscopic stapling device, comprising:
an elongate shaft having an end effector coupled to a distal end thereof, a handle movably coupled to a proximal end thereof, and a drive shaft operatively associated with the handle and the end effector and adapted to rotate the end effector relative to the elongate shaft, to close the end effector to engage tissue, and to fire at least one fastener from the end effector.
16. The device of claim 15, wherein the drive shaft is movable between a first position, in

which rotation of the drive shaft causes corresponding rotation of the end effector relative to the elongate shaft without closing and firing the end effector, and a second position, in which rotation of the drive shaft causes closing and firing of the end effector without rotating the end effector relative to the elongate shaft.

17. The device of claim 16, wherein the drive shaft is adapted to translate relative to a longitudinal axis of the elongate shaft to move between the first and second positions, and wherein translation of the drive shaft from the first position to the second position is adapted to close opposed jaws of the end effector.

18. The device of claim 16, wherein a distal end of the drive shaft engages a portion of the end effector to rotate the end effector when the drive shaft is in the first position, and wherein a distal end of the drive shaft engages a gear assembly to rotate the gear assembly when the drive shaft is in the second position, rotation of the gear assembly being effective to advance a driver disposed within the end effector to fire at least one fastener from the end effector.

19. A method for fastening tissue, comprising:

inserting an elongate shaft into a body lumen to position an end effector coupled to a distal end of the elongate shaft adjacent to tissue to be fastened, a proximal end of the elongate shaft include a handle assembly movably coupled thereto;

rotating a rotatable member in a first position on the handle assembly to rotate the end effector about a longitudinal axis of the elongate shaft; and

rotating the rotatable member in a second position on the handle assembly to fire at least one fastener disposed within the end effector without rotating the end effector.

20. The method of claim 19, further comprising moving a translating member on the handle assembly to close opposed jaws of the end effector around tissue to be fastened.

21. The method of claim 19, wherein the elongate shaft is flexible and is inserted transluminally.