



- (51) **International Patent Classification:**
G11C 8/10 (2006.01) *G11C 8/14* (2006.01)
- (21) **International Application Number:**
PCT/US2014/068090
- (22) **International Filing Date:**
2 December 2014 (02.12.2014)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
14/139,493 23 December 2013 (23.12.2013) US
- (71) **Applicant:** MICRON TECHNOLOGY, INC. [US/US];
8000 South Federal Way, Mail Stop 1-525, Boise, Idaho
83716-9632 (US).
- (72) **Inventor:** TANG, Stephen H.; 44317 Arapaho Ave., Fremont,
California 94539 (US).
- (74) **Agents:** DORSEY & WHITNEY LLP et al.; 701 5TH
Ave, Suite 6100, Seattle, Washington 98104 (US).
- (81) **Designated States** (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG,
MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM,
PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC,
SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) **Designated States** (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ,
TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU,
TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,
DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

- (54) **Title:** APPARATUSES, MEMORIES, AND METHODS FOR ADDRESS DECODING AND SELECTING AN ACCESS LINE




FIG. 1

- (57) **Abstract:** Apparatuses, memories, and methods for decoding memory addresses for selecting access lines in a memory are disclosed. An example apparatus includes an address decoder circuit coupled to first and second select lines, a polarity line, and an access line. The first select line is configured to provide a first voltage, the second select line is configured to provide a second voltage, and the polarity line is configured to provide a polarity signal. The address decoder circuit is configured to receive address information and further configured to couple the access line to the first select line responsive to the address information having a combination of logic levels and the polarity signal having a first logic level and further configured to couple the access line to the second select line responsive to the address information having the combination of logic levels and the polarity signal having a second logic level.