

HEARING AID AND A METHOD OF PROCESSING A SOUND SIGNAL

FIELD OF THE INVENTION

The present invention relates to hearing aids and to methods of processing sound signals. The invention more specifically relates to a hearing aid with a compressor that is active at very low sound levels. The invention, still more specifically, relates to a hearing aid that alerts the user of the occurrence of a sudden sound in a stationary sound environment.

BACKGROUND OF THE INVENTION

As used in this context, a hearing aid is understood as generally comprising a device with an input transducer for transforming an acoustic input signal into a first electrical signal, a signal processor for generating a second electrical signal based on the first electrical signal, an output transducer for conversion of the second signal into sound, and a battery for supplying energy to the signal processor.

Typically, a hearing aid has a housing holding the input and the output transducer, the battery and the signal processor. The housing is adapted to be worn, i.e. behind the ear, in the ear, or in the ear canal, and the output of the output transducer is led to the eardrum in a way that is well-known in the art of hearing aids. The processor will generally be adapted for processing the electric signal in order that the resulting acoustic output signal compensates a hearing deficiency of a user.

US-A-4,777,474 provides an alarm system for the hearing impaired, comprising a base station radio transmitter adapted to transmit, upon detection of an alarm state, a signal to a portable unit. The portable unit includes all parts of an ordinary hearing aid together with a radio receiver to receive the signal transmitted by the base station.

WO 99/34642 discloses a hearing aid with an automatic gain control, effected by detecting an input sound level and/or an output sound level and adapting the output sound level supplied by the hearing aid in response to the detected sound level by controlling the gain of the hearing aid towards an actual desired value of the output sound level. The gain control is effected at increases and decreases, respectively, of the input sound level by adjusting the gain towards the actual desired value with an attack time and a release time, respectively, which are adjusted in response to the detected sound level to a relatively short duration providing fast gain adjustment at high input and/or output sound levels and to a relatively long duration providing slow gain adjustment at low input and/or output sound levels.

- It is well known in the art to provide a hearing aid having a compressor with a characteristic that has two linear segments that are interconnected at a knee-point. The knee-point is typically placed at 50 dB SPL input level, close to the level of normal speech in order to allow a high level of amplification of speech. Below the knee point, the linear segment has substantially no compression, i.e. the gain is a constant gain adapted for compensating the hearing loss at low input signal levels. Above the knee point, the segment has a compression ratio above 1, typically 2:1, for compensating for recruitment. Recruitment is a sensorineural hearing loss whereby loudness increases rapidly with increased sound pressure just above the hearing threshold and increases normally at high sound pressures.
- Many hearing aid users being situated in a stable sound environment desire to be able to hear a faint, sudden change in the sound environment, such as a sudden occurrence of a faint sound. For example, being at home, a hearing aid user may desire to be able to hear that a baby starts crying, or that water starts running, that somebody is present at the door, etc. The hearing aid user can increase the gain of the hearing aid to accomplish this but then the hearing aid user may be bothered by other sounds in the stationary sound environment, such as the sound of a ventilator, traffic noise, etc, that might then also be amplified to surpass the hearing threshold. The hearing threshold is the lowest sound level at which sound is perceptible.

SUMMARY OF THE INVENTION

- One embodiment of the present invention provides a hearing aid that makes it possible for the user to hear a faint, sudden sound occurring in a stationary sound environment without being bothered with stationary sounds.

- According to the present invention in a first aspect, the above-mentioned and other objects are fulfilled by the provision of a multichannel hearing aid with a microphone, an output transducer and a signal processor, wherein the signal processor has at least one frequency channel having a compressor, characterized in that the compressor is provided with a compression threshold at an output level below the hearing threshold, with a knee point situated below 25 dB SPL input level, and with an attack time above 0.5 seconds, whereby hearing of a sudden sound in a stationary sound environment is facilitated.

- With this compressor, the amplification of low signal levels may be increased compared to the prior art, as the compressor kicks in to generally suppress steady noises. In the hearing aid according to the present invention, the gain may generally be increased as high as feasible in view of the microphone baseline noise, which should preferably be kept below the hearing

threshold. Thus the user of the hearing aid according to the invention will generally have the option of a higher gain of low level sounds than generally feasible with prior art hearing aids.

According to the invention in a second aspect, the above-mentioned and other objects are fulfilled by the provision of a method of processing a sound signal in a hearing aid, comprising
5 the steps of converting an acoustic signal into an electric signal, processing the electric signal in a signal processor having in at least one frequency channel a compressor, and converting the processed signal into a sound signal, characterized in that the compressor has a compression threshold at an output level below the hearing threshold, a knee point situated below 25 dB SPL input level, and an attack time above 0.5 seconds.

- 10 The compressor is provided with a slow attack time, such as an attack time above 0.5 seconds, or, in some embodiments, above 1 second, for example 2 seconds or more. The slow attack time permits transient sounds to be amplified without distortion to be clearly perceptible to the user.

- 15 The compressor may have a long release time, e.g. 10 times the attack time, for recovering the gain upon the vanishing of high level sounds.

It is an important advantage of the present invention that the gain of the hearing aid is high at low signal levels while the microphone noise is still kept just below the hearing threshold.

- When a sudden sound occurs, the sound is amplified with the current large gain to provide an output signal above the hearing threshold so that it can be heard by the hearing aid user. If the
20 sudden sound persists for a longer time than the attack time of the compressor, the gain will decrease with time, gradually lowering the hearing aid output signal as far as permitted by the compression ratio, and possibly causing the faint sudden sound to be no longer amplified above the hearing threshold. Thus the sudden sound can be heard by the hearing aid user for substantially the attack time of the compressor which is a sufficient period for the user to be
25 alerted by the sound.

According to an advantageous embodiment, the hearing aid signal processor may have a plurality of channels, preferably more than 6 channels, more preferred more than 8 channels, most preferred more than 10 channels, e.g. 15 channels.

5 According to another advantageous embodiment, the knee point is situated at 10 dB SPL input level. Typically, the knee-point is situated below 20 dB SPL input level, for example below 15 dB SPL. This allows for a maximum of gain at sound levels close to lowest level audible to people with normal hearing. The maximum of gain selected for a particular user will depend on his particular hearing deficiency and the fitting rule. Generally a complete compensation of the hearing deficiency is not feasible for reasons such as user comfort. The amount of faint sounds
10 that may be amplified sufficiently to be audible to the user may vary according to the specific circumstances. However, sounds at 25 dB SPL input will generally not be amplified so much as to be audible to a hearing impaired person using a hearing aid tuned according to standard fitting rules.

Other advantageous embodiments of the invention appear from the dependent claims.

Still other objects of the present invention will become apparent to those skilled in the art from the following description wherein the invention will be explained in greater detail. By way of example, there is shown and described a preferred embodiment of the invention. As will be realized, the invention is capable of other different embodiments, and its several details are capable of modification in various, obvious aspects all without departing from the invention. Accordingly, the drawings and descriptions will be regarded as illustrative in nature and not as restrictive. In the drawing:

BRIEF DESCRIPTION OF THE DRAWING

- 10 Fig. 1 shows a prior art compressor characteristic,
- Fig. 2 shows a compressor characteristic according to the present invention,
- Fig. 3 illustrates amplification by a hearing aid according to the present invention of a sudden sound in a stationary sound environment,
- Fig. 4 shows a blocked diagram of a hearing aid according to the present invention, and
- 15 Fig. 5 is an enlarged view of a compressor characteristic according to the invention with illustration of the processing of a sound stimulus.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

- Fig. 1 shows a plot of a prior art compressor characteristic, i.e. a plot of the compressor output level as a function of the input level, both in SPL. This characteristic may be for a general compressor or it may be for one among a bank of narrow-band compressors in a hearing aid signal processor. The particular characteristic may depend on the fitting to a particular user. The example in the figure assumes the hearing aid has been tuned to compensate a particular hearing deficiency, as partially illustrated by the hearing threshold line at 70 dB. The fitting to other users may be suggested by those skilled in the art of hearing aid fitting.
- 20 The characteristic comprises two linear segments 5, 6, that are interconnected at a knee-point 10 (CT – Compression Threshold) typically positioned at 50 dB SPL input level. At sound levels below the knee point 10, as evidenced by the linear segment 5, there is substantially no compression, i.e. the gain is a constant gain, suitable for compensating the hearing loss at low input signal levels. In Fig. 1, this gain is 30 dB as illustrated at the line G_{15} at 15 dB input level

and identically 30 dB as illustrated at the line G_{50} at 50 dB input level. Normal speech is about 50 dB input level. Above the knee point 10, as evidenced by the segment 6, there is a compression ratio above 1, typically 2:1, lowering the gain at high input levels as appropriate for compensating for recruitment. The compression ratio of a segment is equal to the reciprocal value of the slope of the segment. Given a low end gain of 30 dB and a hearing threshold of 70 dB, input levels below 40 dB will not be audible to this hearing aid user.

In order to be able to hear a faint sudden change in the sound environment, such as a sudden occurrence of a faint sound, the hearing aid user can increase the gain of the hearing aid thereby displacing the characteristic shown in Fig. 1 upwardly in the direction of the y-axis. In that case, however, other faint sounds in the stationary sound environment, such as the sound of a ventilator, traffic noise, etc, will also be amplified, possibly to a level above the hearing threshold causing an annoyance or an uncomfortable disturbance of the user.

Fig. 2 shows a compressor characteristic of a compressor according to the present invention. In Fig. 2, the segments 5, 6 correspond to the segments 5, 6 shown in Fig. 1. Preferably, segment 6 has a compression ratio that is greater than 1.4, and, more preferred, a compression ratio substantially equal to 2. Other values of the compression ratio may be used if appropriate. It is the gist of the present invention that the output level 9 at the knee-point or compression threshold is lower than the hearing threshold 8. In Fig. 2, the knee-point is situated at about 15 dB input level, i.e. in the low end of the range audible to people with normal hearing. The gain at the knee-point and below is about 40 dB as illustrated by G_{15} , drawn at 15 dB input level. Above the knee-point the gain rolls off governed by the compressor, reaching about 30 dB at 50 dB input level as illustrated by G_{50} . Thus the gain at normal speech level is similar to that illustrated in Fig. 1. On the other hand the gain is substantially higher at low signal levels than for the prior art compressor.

The hearing aid according to the present invention may have a microphone that generates a low level of microphone noise. The hearing aid signal processor may have a plurality of channels, preferably more than 6 channels, more preferred more than 8 channels, most preferred more than 10 channels, e.g. 15 channels. Since noise in each channel is substantially proportional to channel bandwidth, an increase in the number of channels leads to a reduction of the noise in each channel. Thus, in spite of the increased gain, the noise in a channel is still maintained below the hearing threshold. In the present example, the knee point is situated at 15 dB SPL input level. The knee-level is always situated below 25 dB SPL input level, more often below 20 dB SPL input level, for example below 15 dB SPL.

Fig. 3 illustrates amplification by a hearing aid according to the present invention of a sudden sound in an otherwise steady sound background 11. The sudden sound is illustrated by a square wave pulse rising at 12 and disappearing at 13. The steady sound background is processed in the hearing aid to produce an output signal at the level A, below the hearing threshold. The compressor is provided with a slow attack time, such as 1 or 2 seconds. Transient signals are amplified linearly. When the sound pulse occurs at 12, the sound pulse is amplified with the current large gain in order to produce initially an output sound signal at level B. In the example, B exceeds the hearing threshold 14, signifying that the signal is indeed audible to the hearing aid user.

- 10 If the sound pulse persists for a longer time than the attack time 16 of the compressor, the compressor will kick in to decrease the gain over time 18 to gradually arrive at the output level C, below the threshold of hearing. Thus, depending on the magnitude of the signal, eventually the sudden sound may no longer be amplified above the hearing threshold 14. In the example, the sudden sound 13 can be heard by the hearing aid user for substantially the attack time 16 of the compressor which is a sufficient period for the user to be alerted by the sound.

15 Disappearance of the square wave sound pulse at 13 produces a downward step taking the output level to the point D. The compressor recovers from this new lower level only slowly. Gradually, according to the compressor release time, the gain grows to take the output level back to the initial level A.

- 20 Reference is also made to Fig. 5 for a plot of the points A, B, C and D in the input-output diagram. This plot illustrates the points A and C on the compressor curve, which represent steady state situations, whereas the points B and D, which represent transient states, are defined by a respective starting point and by a step height (up or down).

- 25 Generally, it is assumed that the human ear has a time constant for loudness perception in the order of 0.2 to 0.3 seconds. This is the minimum duration required by a human ear for a full perception of the loudness of the signal. Shorter signals may also be perceived, however the loudness of shorter signals tend to be underestimated.

- Fig. 4 shows a schematic block diagram of a hearing aid 20 according to the present invention. It will be obvious for the person skilled in the art that the circuits indicated in Fig. 6 may be implemented using digital or analogue circuitry or any combination hereof. In the present embodiment, digital signal processing is employed and thus, the processor 28 consists of digital signal processing circuits. In the present embodiment, all the digital circuitry of the hearing aid
- 30

20 may be provided on a single digital signal processing chip or, the circuitry may be distributed on a plurality of integrated circuit chips in another way.

In the hearing aid 20, a microphone 22 is provided for reception of a sound signal and conversion of the sound signal into a corresponding electrical signal representing the received sound signal. The hearing aid 20 may comprise a plurality of input transducers 22 with appropriate input stage processing for the purpose of added functionality, e.g. for providing a direction sensitive capability. The microphone 22 converts the sound signal into an analogue electric signal. The analogue electric signal is sampled and digitized by an A/D converter 24 into a digital signal 26 for digital signal processing in the hearing aid 20. The digital signal 26 is fed to a digital signal processor 28 for amplification of the microphone output signal 26 according to a desired frequency characteristic and compressor function to provide an output signal 30 suitable for compensating the hearing deficiency of the user. The output signal 30 is fed to a D/A converter 32 and further to an output transducer 34, i.e. a receiver 34, that converts the output signal 30 into an acoustic output signal.

The signal processor 28 comprises a first filter bank 36 with bandpass filters 36_i for dividing the electrical signal 26 into a set of bandpass filtered first electrical signal derivatives $26_1, 26_2, \dots, 26_i$. Further, the signal processor 28 comprises a set 38 of compressors and offset amplifiers $38_1, 38_2, \dots, 38_i$ each of which is connected to a different bandpass filter $36_1, 36_2, \dots, 36_i$ for individual compression of the corresponding bandpass filtered signal derivatives $26_1, 26_2, \dots, 26_i$. Fig. 4 illustrates the compressor and offset amplifiers $38_1, 38_2, \dots, 38_i$ in the respective frequency bands $36_1, 36_2, \dots, 36_i$ having compressor characteristics in accordance with the present invention.

The illustrated compressor characteristics 38_1 and 38_2 correspond to the characteristic shown in Fig. 2. In the present example, 36_1 and 36_2 are low frequency bandpass filters, e.g. with passbands below 500 Hz. 36_1 may have a passband below 300 Hz and 36_2 may have a passband between 300 Hz and 500 Hz. For simplicity, compressors are not illustrated in every frequency band. Compressors with characteristics in accordance with the present invention may be included in any appropriate frequency channel.

CLAIMS

1. A multichannel hearing aid with a microphone, an output transducer and a signal processor, wherein the signal processor has at least one frequency channel having a compressor, characterized in that the compressor is provided with a compression threshold at an output
5 level below the hearing threshold, with a knee point situated below 25 dB SPL input level, and with an attack time above 0.5 seconds, whereby hearing of a sudden sound in a stationary sound environment is facilitated.
2. The hearing aid according to claim 1, wherein the compressor has a knee point situated below 20 dB SPL input level, and more preferably below 15 dB SPL.
- 10 3. The hearing aid according to claim 1 or 2, wherein the compressor has an attack time above 1 second, and in particular 2 seconds or more.
4. The hearing aid according to claim 1, 2 or 3, wherein the compressor has a release time above 5 seconds, preferably above 10 seconds, and in particular 20 seconds or more.
5. The hearing aid according to any of the preceding claims, wherein the compressor has a
15 compression ration above 1.4, and preferably about 2.0.
6. The hearing aid according to any of the preceding claims, wherein the signal processor comprises a set of compressors and offset amplifiers, each of which is connected to a respective bandpass filter for individual compression of the corresponding bandpass filtered signal derivatives.
- 20 7. The hearing aid according to claim 6, wherein the signal processor comprises a plurality of channels, preferably more than 6 channels, more preferred more than 8 channels, most preferred more than 10 channels, and still more preferred 15 channels.
8. A method of processing a sound signal in a hearing aid, comprising the steps of
converting an acoustic signal into an electric signal,
25 processing the electric signal in a signal processor having in at least one frequency channel a compressor, and
converting the processed signal into a sound signal, characterized in that

the compressor has a compression threshold at an output level below the hearing threshold, a knee point situated below 25 dB SPL input level, and an attack time above 0.5 seconds.

9. The method according to claim 8, comprising compressing the signals above a knee point situated below 20 dB SPL input level, and more preferably below 15 dB SPL.
- 5 10. The method according to claim 8 or 9, comprising compressing the signals upon the expiry of an attack time above 1 second, and in particular 2 seconds or more.
11. The method according to claim 8, 9 or 10, comprising relinquishing compressing the signals upon the expiry of a release time above 5 seconds, preferably above 10 seconds, and in particular 20 seconds or more.
- 10 12. The method according to any of the claims 8 - 11, comprising compressing the signals to a compression ratio above 1.4, and preferably about 2.0.
13. The method according to any of the claims 8 - 12, comprising processing the electric signals in a signal processor having a set of compressors and offset amplifiers, each of which is connected to a respective bandpass filter for individual compression of the
- 15 corresponding bandpass filtered signal derivatives.
14. The method according to any of the claims 8 - 13, comprising processing the electric signals in a signal processor having a plurality of channels, preferably more than 6 channels, more preferred more than 8 channels, most preferred more than 10 channels, and still more preferred 15 channels.