

Lift system

The invention relates to a lift installation according to the preamble of claim 1.

Lift installations are usually installed in a shaft in a building and serve for the transport of persons or goods. The cage, which is movable in vertical direction in the shaft, is supported by support means in the form of, for example, cables or belts, wherein the support means are, for movement of the cage, connected with a drive. Depending on the respective design of the lift installation the cage and/or a counterweight connected with the cage by way of the support means is or are connected with the support means by way of one or more deflecting units. In the case of a 2:1 suspension, for example, one or two deflecting units are associated with the cage and one deflecting unit is associated with the counterweight.

Deflecting units comprise one or more deflecting rollers which are mounted to be freely rotatable with use of, for example, roller bearings. The axle is fastened to a support at which the cage or the counterweight is hung or suspended. This axle fastening can lead to problems with the deflecting units known for lift installations. In rare cases it can happen that, for example, if maintenance has been deficient or omitted the deflecting roller no longer can freely rotate with respect to the axle, as a result of which high levels of torque between deflecting roller and axle can arise. This can have a negative effect on the axle fastening. In extreme cases the axle could migrate out of the support, which could lead to accidents.

A deflecting unit with a deflecting roller freely rotatable about an axis of rotation and mounted by way of axle on a support has become known from WO 2010/103165 A1 and has - with respect to a centre plane running vertically relative to the axis of rotation of the deflecting roller - a mirror-symmetrical form of the axle. For axial securing, the axle, which is formed by a cylindrical body, has on two sides grooves in which the support engages directly or indirectly by way of a retaining part fastened to the support. The circumferential surface of the axle is interrupted by a planar section, which outwardly adjoins the respective groove and which is supported at a securing element screw-connected with the support and formed by a plate. The securing elements have the purpose of ensuring rotationally secure mounting of the axle. After failure of the rotational securing due to wear, according to a description in WO 2010/103165 the axle, which is firmly held by way

of the grooves in the support, shall allow rotation of the axle. However, depending on the respective construction the desired axial securing is not provided, is insufficient or is achievable only by constructional solutions which are costly.

It is accordingly an object of the present invention to avoid the disadvantages of the prior art and, in particular, to create a lift installation by which operational reliability can be increased. The deflecting unit for the lift installation shall, in addition, be of simple construction and able to be produced simply as well as characterised by a robust construction.

According to the invention this object is fulfilled by a lift installation with the features of claim 1. Due to the fact that retaining means for axial securing of the axle to the support are provided on both sides of the axle, between which retaining means the support is received preferably with slight play and which retaining means allow rotation of the axle with respect to the support, operational reliability and the service life of the lift installation can be increased or improved. Since due to the mentioned retaining means at least for special operational states (for example after the installation was improperly maintained or not maintained and accordingly the deflecting roller suddenly and unpredictably can no longer fully freely rotate) a rotation of the axle in the support is possible the risk of operational disturbances or accidents can be substantially reduced. It is ensured by this arrangement that unintended escape of the axle from the support, due to axial migration in the case of excessive mechanical loading, can be virtually excluded. With particular advantage, the axle arrangement and axle fastening according to the invention is employed in the deflecting unit associated with the counterweight. The retaining means is formed on one side by an axle head, which is formed on the axle, for formation of a shoulder-like abutment for the support. For axial securing of the axle in the support, another retaining means is used on the opposite side. The axle with the axle head is preferably of monolithic construction and consists of, for example, a metallic material. The axle can be a substantially rotationally symmetrical axle body of steel. The axle thus has a mushroom-shaped configuration, wherein the axle comprises the mentioned axle head ('mushroom cap') adjoined in axial direction by an axle shank. The axle head is, for example, of substantially cylindrical construction and has a larger diameter than the axle shank. A retaining means rigidly connected with the axle in that manner leads to a particularly high degree of stability of the axle fastening. The axle head can in simple manner be dimensioned in such a way that breaking-off or another form of destruction of

the axle head is virtually impossible even in the case of extraordinarily strong mechanical loads during operation of the lift. The axle arrangement with the mushroom-shaped axle body is, moreover, simple to handle and enables simple and quick assembly and disassembly.

In a first form of embodiment at least the axle head and/or the (arranged on the opposite side) retaining means can, for rotationally secure mounting of the axle in a first life cycle, be fixed by rotational securing means to be secure against rotation with respect to the support. With an arrangement of that kind the respective deflecting unit can operate in optimum manner at least in the first life cycle. For example, the deflecting roller can rotate with low output of noise and with little wear. However, depending on the respective field of use it can obviously also be sufficient if the axle, which is fitted in the bearing mounts of the support, is prevented - due to the significantly higher (by comparison with, for example, the roller-bearing arrangement) friction between axle and support - from rotating in normal operation during cage travel.

It can be advantageous if at least one deflecting unit is constructed so that in the case of exceeding a specific torque between deflecting roller and axle the rotational securing means releases the corresponding retaining means (or the retaining means associated with the rotational securing means) and the axle in a second life cycle is rotatably mounted in the support between the retaining means. The service life of the axial fastening of the deflecting unit is thus distinguished by two life cycles. In the first life cycle, which approximately corresponds with the normal state, the axle cannot rotate in the support. In the second life cycle following thereupon, which approximately corresponds with an emergency operational state, the axle can rotate in the support, wherein as before the axial securing of the axle in the support is ensured. Through division of the service life into two cycles better monitoring of the deflecting unit is possible. In the second life cycle it can happen that the axle due to wear frets to a certain degree in the support and a slot vertically extending to greater or lesser extent in the support arises. This phenomenon can be easily observed, whereby monitoring of the deflecting unit is simplified for maintenance personnel.

The rotational securing means could, for example, comprise an operating mechanism which can be triggered in the case of exceeding the afore-mentioned excess torque and thus release the retaining means. However, it can be particularly advantageous if the

rotational securing means is executed as a frangible element. A rotational securing means of that kind can, for example, comprise a comparatively tightly dimensioned screw which breaks under the action of high shear forces if the predetermined torque between deflecting roller and axle is exceeded. However, other frangible elements would obviously be conceivable.

For rotationally secure mounting of the axle this can be achieved if the axle head has a rotational securing section which is preferably predefined by a planar surface and which is supported at a securing element fastened to the support. The rotational securing section can be arranged in the circumferential region of the axle head. If, for example, the axle head has a cylindrical external form the rotational securing section can be formed by milling the cylindrical circumferential surface in simple mode and manner. Instead of a rotational securing section created by milling, the axle head can also have a rotational securing section which protrudes in radial direction and which is fastened to the support by means of, for example, a screw connection.

The securing element can be a body which is preferably formed by a plate and which is fastened to the support by way of at least one screw. This screw can be constructed as a frangible element which can break under the action of excessive shear forces and thus cancel the rotational securing of the axle.

It can be advantageous if the securing element is secured to the support by a single screw. With the single-screw arrangement the desired target breaking value at which the rotational securing is to be cancelled can be set in particularly simple manner.

The screw can be oriented axially parallelly to the axle in such a manner that, at least for a first life cycle - in which the axle is arranged in the support to be rotationally fast - screw and axle lie on a surface normal of the rotational securing section.

Moreover, it can be advantageous if the retaining means on at least one side is formed by a separate component. Simple assembly and disassembly of the deflecting unit is ensured in this way.

The retaining means can be formed on at least one side by a retaining part surrounding the axle in radial direction. The retaining part surrounding the axle can be mounted on the

axle and removed again in simple manner. It can be particularly advantageous if the retaining part is formed to be horseshoe-shaped or annular.

For rotationally secure retention of the retaining part on the axle the horseshoe-shaped retaining part can have planar flanks and the axle can have mechanically positive coupling sections which are executed to be complementary to the flanks and which are preferably created by milling. The horseshoe-shaped retaining part can be mounted in simple manner in radial direction on the axle from outside.

The axle can have a groove for receiving the horseshoe-shaped retaining part. The groove ensures precise positioning of the retaining part on the axle.

For securing the retaining part, a securing part surrounding the axle in radial direction can be provided and is connected with the retaining part preferably by means of screws. The securing part can in that case be of annular form.

Further individual features and advantages of the invention are evident from the following description of an embodiment and from the drawings, in which:

Figure 1 shows a simplified illustration of a lift installation in a side view,

Figure 2 shows a detail of a cross-section through a deflecting unit of the lift installation according to Figure 1,

Figure 3 shows a perspective view of one side of the deflecting unit of Figure 2 in a partly exploded illustration,

Figure 4 shows the other side of the deflecting unit of Figure 2 and

Figure 5 shows a perspective exploded illustration of the axle arrangement for the deflecting unit according to Figure 2.

Figure 1 shows a lift installation, which is denoted overall by 1, in a substantially simplified and schematic illustration. The lift comprises a cage 2, which is vertically movable up and down, for the transport of persons or goods. Support means 5 for supporting the cage and

a counterweight 4 can be a cable or several cables. Obviously, however, other support means, for example in the form of belts, are also conceivable. The cage 2 and the counterweight 4 are respectively connected by way of deflecting units 7, 8, 9 with the support means. For moving the cage 2 and the counterweight 4 use is made of a drive 6, for example a drive-pulley drive, which, for example, is arranged in a separate engine room in the region of the shaft head. The specific deflecting units described in more detail in the following would obviously also be suitable for other lifts and, in particular, also for so-called engine-room-less lifts. The lift installation 1 illustrated in Figure 1 is constructed in a 2:1 suspension configuration. However, other suspension variants (for example 1:1, 4:1, etc.) would obviously also be conceivable. Moreover, a deflecting unit could also be arranged in the region of the cage roof instead of the under-looping of the cage 2 shown in Figure 1.

Technical details with respect to the construction of a deflecting unit are apparent from Figure 2. Figure 2 shows the region of the rotational axle of the deflecting unit 9, which is associated with the counterweight and at which the counterweight (not illustrated here) is suspended by way of the support 13. The deflecting unit illustrated here could, however, also be associated with the cage (7, 8; cf. Fig. 1) or even be arranged at another location in the lift installation. The deflecting unit 9 comprises a deflecting roller 11, at the circumference of which the support means (not illustrated here) is guided and deflected. The deflecting roller 11 is connected with an axle 10 by way of a bearing 12 and mounted on the axle 10 to be freely rotatable. The bearing 12 can, for example, contain one or more roller bearings depending on the respective requirements. The axle 10 is fastened to a support 13. The support 13 is connected with the counterweight (not illustrated). The support 13 has two mutually opposite walls 25 and 26, which are each provided with a respective bearing receptacle, through which the axle 10 is guided. The axle 10 is secured in axial direction on both sides. On one side, the retaining means for axial securing of the axle at the support is formed by an axle head 15, which is integral with the axle 10 and predefines a shoulder-like abutment. On the opposite side, the axial securing is achieved by a retaining part 14 mounted on the axle. The securing part denoted by 20 serves for securing the retaining part 14 in the illustrated position.

The axle 10 is connected with the support 13 to be secure against rotation, wherein the rotational securing acts merely on one side of the axle. This rotational securing secures the securing element which is denoted by 16 and which is screw-connected with the

support 13. The axle head 15 has a rotational securing section 21, which is predefined by a planar surface and which is supported at a securing element 16. The securing element 16 is fastened to the support 13 by way of a screw connection.

It is evident from Figure 3 that, inter alia, the retaining part 14 is of horseshoe-shaped design. The horseshoe-shaped retaining part 14 has mutually opposite parallel flanks 18, which co-operate with complementary mechanically positive coupling sections 19 and thus ensure rotationally fast fixing of the retaining part 14 in the finally assembled position. In inserted position, the retaining part 14 surrounds the axle 19 with respect to the radial direction predefined by the axle. The securing part 20 is of annular form and includes four passage holes 28, which correspond with the threaded bores 27 and through which the screws 23 are insertable. The retaining part 14 is provided with receptacles, which are formed as threaded bores, for fastening screws 23. As an alternative to the variant shown here, the retaining part could be designed to be annular and the securing part to be horseshoe-shaped.

As Figure 4 shows, the securing element 16 is formed by a plate-like body. Instead of the rectangular plate illustrated in plan view, other forms could also be selected for the component 16. It is to be noted that the securing element 16 has an edge or section which co-operates with the rotational securing section 21 of the axle 10 and rests thereon. The securing element 16 has a hole 30 through which the screw 17 is introducible and can then be screwed into the threaded bore in the wall 26 of the support 13. The axle head of substantially cylindrical construction has a rotational securing section 21 created by a chamfering.

The screw 17 represents a frangible element which under the action of excessive shear forces, for example when the deflecting roller suddenly and unpredictably can no longer rotate and a specific torque between deflecting roller and axle is exceeded, breaks and thereby the rotational securing of the axle 10 is cancelled. The mentioned torque can be set in simple manner by the selection and dimensioning of the screw 17. Thanks to the two lateral retaining means, i.e. the axle head 15 on one side and the retaining means 14 on the other side, the axle is, as before, secured against undesired movement in axial direction. If maintenance personnel discover the axle rotating in the support, they can institute repair or reconditioning measures. After release of the rotational securing the axle 10 is thus, in a second life cycle of the deflecting unit, received in the support to be

rotatable. Tests have shown that the rotating axle can after some time fret to a certain degree in the support 13 due to wear and a slot extending vertically to greater or lesser extent in the support 13 can arise. Thanks to the special axle arrangement, however, axle securing is guaranteed at all times so that the axle cannot fall or migrate out of the support. The slot which in a given case might arise also allows simple monitoring of the deflecting unit.

Instead of the rotational securing section created by chamfering shown in Figure 4, the axle head could also comprise a rotational securing section protruding in radial direction or a special shaping in circumferential direction. For example, the plate body denoted in Figure 4 by 16 could be welded to the axle head. This rotational securing means integrated with or in the axle head would - analogously to the embodiment according to Figure 4 - have to be fastened to the support merely by a screw.

For specific applications the special securing means shown by way of example in Figure 4 are not necessary, because it can be sufficient if the axle fitted in bearing mounts of the support is prevented, due to the significantly higher level of friction between axle and support, from rotating in normal operation during cage travel. The axle head of the embodiment according to Figure 4 could in this case have a cylindrical external form without chamfering and the bearing unit would not have to have a securing element. After a bearing defect, the friction in the roller bearing or bearings would be greater than that between axle and support, whereupon the axle could rotate in the support. Screw 17 and axle 24 lie on a surface normal of the rotational securing section.

Figure 5 shows the individual components of the axle arrangement containing the axle 10 with the axle head 15 formed at the axle, the securing element 16 designed as a plate, the retaining part 14 and the securing part 20. The axle 10 is, as apparent, formed to be mushroom-shaped, wherein the axle head 15 forms the 'mushroom cap'. The axle shank 24 adjoining the axle head in axial direction has a smaller diameter D_1 by comparison with the diameter D_2 of the axle head 15. The axle shank 24 can be fitted into corresponding bearing receptacles of the support. A mushroom-shaped axle of that kind can be produced economically. The axle can be made in simple manner from a metallic material (for example steel) by a material-removing process (turning, milling, etc.).

Patent claims

1. Lift installation having a cage, a counterweight and a support means for supporting the cage and the counterweight, wherein the cage and/or the counterweight is or are, respectively, connected with the support means by way of at least one deflecting unit, wherein the at least one deflecting unit comprises at least one deflecting roller and an axle which is fastened to a support and on which the at least one deflecting roller is mounted to be freely rotatable, wherein the axle is of mushroom-shaped form, having an axle shank and an axle head which is formed at the axle shank to provide an abutment, and wherein a retaining means is provided on the side of the axle opposite the axle head, wherein the support is received between the axle head and the retaining means in a manner which allows rotation of the axle with respect to the support but limits its axial displacement relative to the support.
2. Lift installation according to claim 1, characterised by further including means for preventing rotation of at least the axle head and/or the retaining means with respect to the support and thus fix the axle in a first life cycle against rotation.
3. Lift installation according to claim 2, characterised in that the at least one deflecting unit is so constructed that upon a specific torque between deflecting roller and axle being exceeded, the means for preventing rotation releases the associated retaining means and the axle is free to rotate at the support during a second life cycle. .
4. Lift installation according to claim 2 or 3, characterised in that the rotational securing means for preventing rotation is constructed as a frangible element.
5. Lift installation according to claim 4, characterised in that the axle head has, as a part of the means for preventing rotation, a rotational securing section which is preferably predefined by a planar surface and which is supported on a securing element fastened to the support.
6. Lift installation according to claim 5, characterised in that the securing element is a body which is preferably formed by a plate and which is fastened to the support by way of at least one screw .

7. Lift installation according to claim 6, characterised in that the securing element is secured to the support by a single screw.
8. Lift installation according to claim 5, 6 and 7, characterised in that the screw is so aligned to be axially parallel to the axle, and in that the screw and axle lie on a surface normal of the rotational securing section.
9. Lift installation according to any one of claims 1 to 8, characterised in that the retaining means is formed by a separate component.
10. Lift installation according to any one of claims 1 to 9, characterised in that the retaining means is formed by a retaining part surrounding the axle.
11. Lift installation according to claim 10, characterised in that the retaining means is formed to be horseshoe-shaped or annular.
12. Lift installation according to claim 11, characterised in that for rotationally secure retention of the retaining part at the axle, the horseshoe-shaped retaining part has planar flanks and the axle has mechanically positive coupling sections formed to be complementary with the flanks.
13. Lift installation according to claim 11 or 12, characterised in that the axle has a groove for receiving the horseshoe-shaped retaining part.
14. Lift installation according to any one of claims 10 to 13, characterised in that for securing the retaining part there is provided a securing part, which surrounds the axle in radial direction and is connected with the retaining part preferably by means of screws.
15. Lift installation according to claim 14, characterised in that the securing part is formed to be annular.