

HARNESS FOR STRETCHING THE PENIS

TECHNICAL FIELD

The present invention relates to harnesses for stretching of human tissue, and in particular the penis. The present invention utilizes originally constructed harness to accomplish stretching of the penis.

BACKGROUND ART

Numerous attempts have been made in order to solve the problem of phallus elongating and enlarging. The following art defines present state of this field : Jorn (EP0814733), Jakob (WO9728764), Heinz-Guenther (DE19915407 and DE19620719), Daniel (US5599275), Didier (EP0370932) etc, all describe mechanical devices for stretching the penis by using mechanical and/or gravitational forces, while Roland (US5836864) uses the same forces adding a vacuum in his invention for obtaining the same purpose.

All aforesaid devices have one big drawback: they are not designed for whole-day use. Mechanical parts this devices are made of are: rigid, sensitive to human body movement, uncomfortable for use, due to their's bulky size they are very well noticeable under the clothing, or they do not effectively solve the problem of fast and easy stretching force adjustment. All these shortcomings reduce the use of these apparatuses only on for home use i.e. for conditions of privacy use, and consequently cause their's low efficiency. With respect to a fact that for elongation and enlargement of the penis a man need to wear these devices constantly and for a long period of time (e.g. 1 year, 6-8 hours each day for 2-3cm gain approximately), the most important thing, one has to concern about while constructing such device, is to make it comfortable and practical for use in any occasion (walking, sitting on work, car driving, bus riding, physical work, physical activities and sports etc.). According to our scope into the world's patent databases, we can say that this demand still has not been answered adequately well.

DISCLOSURE OF THE INVENTION

Accordingly, the primary object of the present invention is to provide a harness for stretching a human penis that is comfortable and practical for a long time and whole-day use.

Another object of the present invention is to provide a harness for stretching a human penis of any size, with the possibility of attaining strong tractive forces, and with the possibility of fast and easy regulation of said forces.

To meet the aforesaid needs, according to the invention a harness for stretching the penis comprises a belt, adapted to be worn around one's waist, connected at the rear side via small rotating snap-hooks with two inextensible cinching straps, said straps each having a pair of

half-rings for length adjustment. One said strap on lower end carrying adjustable rope loop to be placed around penis base. Second said strap on lower end is connected via L-shaped connecting member with flexible adjustable loop being encircled and tightened around penis next to the penis head. Tightening of the said straps provides permanent penis stretching force, which force in a sufficiently long time, by the process of tissue mass increasing (which process was, and still is very well known to many primitive tribes), provides penis elongation and enlargement. The provided harness is accomplished from flexible, human-body-friendly materials, do not contain bulky rigid parts and is therefore easy to wear and to bear. The harness is not noticeable not only under the trousers, but also under the shorts, boxers etc. While using it one can freely walk, do everyday activities, work, drive a car, even run, swim and do many other activities. Furthermore, using adequate fingers' moves over the clothing or true the pockets (even while walking, without stopping), a man can easily and quickly adjust stretching force on straps. By this harness is possible to provide heavy traction on penis, due to its construction and due to a fact it is made of strong inextensible band at the rear side of the belt, of inextensible cinching straps and of very low elastic rope loop (the only needed-to-be flexible part is silicone i.e. rubber loop), providing this way the harness can be used for stretching the penis of any (even big) size. Minimal size (the same minimal size for all sizes of the penises), weight and single-part feature of L-shaped connecting member facilitate a harness to be "imperceptible" while in use, while U-shaped aperture on said member provides a wide range of angles and positions penis can be stretched in. Comfortability of the harness is further provided with possibility of easy changing of the sides of the cinching straps (i.e. change of penis placement and stretching side). Comfortability is also conducted with fast-release function of both rope and elastic loops in order to prevent any kind of pain arising and side-effects. This harness is very easy to disassemble and to wash. Regarding to durable materials harness is made of, it can be used for years.

This and other features and advantages of the present invention will become apparent from the following more detailed description taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings illustrate the present invention. In such drawings:

FIG. 1 is a view in front elevation of the present invention

FIG. 2 is a view in front elevation of present invention disassembled on its 3 subsystems

FIG. 3 is a view in front elevation of the present invention as worn by a user

FIG. 4 is a view in rear elevation of the present invention as worn by a user

FIG. 5 illustrate a rope regulator means

FIG. 6 illustrate a L-shaped connecting member

BEST MODE FOR CARRYING OUT THE INVENTION

Referring now to FIGS. 1 - 4, the illustrated harness for stretching the penis includes stretchable belt **1**, manufactured from mixture of cotton and synthetic fibres or like, having adjusting means **2** for securing around one's waist. Adjusting means **2** can have a wide variety of embodiments. In this preferred embodiment it comprises a simple plastic light-weight buckle. Referring to FIG. 4, unstretchable strong thin string **3** and, over said string, unstretchable strong band with holes **4**, both made from synthetic fibres, are attached to the rear outer side of the belt **1**, along with the upper edge thereof. String **3** is attached to the belt **1** at three points : at the both left and right ends and at the middle, and said string is pulled out twice ie. through the two of holes of the band **4** (through which two holes depends on a user's waist size – see FIG. 4) such forming two loops **5** and **6**. In loops **5** and **6** are plugged subsystems **A** and **B** (see FIG. 2) using small metal rotating snap-hooks **7** and **14** respectively. In accordance with the provided functionality of the present invention and for the sake of easier description three functional parts of the present invention are further signed as belt means subsystem, subsystem **A** and subsystem **B**. Subsystem **B** provides tractive forces to the penis and to the belt **1** in certain directions, while subsystem **A** provides tractive forces in opposite direction relating to subsystem **B** to the penis, but also to the belt **1**, in order to prevent belt **1** rotation around wearer's waist and consequently loose and total absence of stretching forces. A further object of subsystem **A** is to provide means for disabling testicles pulling-up under the influence of tractive force, leaving them freely hanging, such preventing any pain arousal and side effects emersion.

Subsystem **A** consist of (see FIG. 2) unstretchable cotton cinching strap **8** having two metal half-rings **9** for strap length adjustment, which said strap upper part is inserted through loop on snap-hook **7** and lower part is inserted around part of the rope **11** which part is threaded through holes **24a** and **24b** on rope regulator means **10** (see FIG. 5). Subsystem **A** further includes said rope regulator means **10** and said rope **11** with protective pad **12**, which rope **11** is threaded thorough holes **24a** and **24b** on rope regulator means **10**, thus rope **11** forming in use adjustable loop **13** for penis base abutment.

Subsystem **B** consist of (see FIG. 2) unstretchable cotton cinching strap **15** having two metal half-rings **16** for strap length adjustment, which said strap upper part is inserted through loop on snap-hook **14** and lower part is inserted through U-shaped aperture **20** on L-shaped generally planar connecting member **17** (see FIG. 6). Subsystem **B** further includes said member **17** having two holes **21**, through which holes elastic cord-like member **18** is inserted,

thus said cord-like member **18** forming in use adjustable loop **19** for enabling stretching force appliance on the edge of the head of the penis.

Rope **11** is of 9 - 10 mm diameter and is preferably made of synthetic fibres. Rope regulator means **10** and connecting member **17** are manufactured of heavy-duty unflexible material, under this exemplary embodiment from transparent plastic, but may be also manufactured of metal, woods etc, and both may be partialy coated with some thin, soft and skin-cosy material. L-shaped connecting member **17** is, in this preferred embodiment, preferably of the smallest size it can be emodied respective to all of the including constitutive elements and functionality (see FIG. 6). Elastic cord-like member **18** is of 5 - 6 mm diameter, preferably formed of silicone, but may be manufactured of soft rubber too, and is preferably hose-like (hollow inside), but may be cord-like (full profile).

Referring now to FIG. 2, harness for stretching the penis according to the present invention is shown disassembled on it's subsystems, while in use, first, belt **1** is loosely secured (it is not needed a belt **1** to be frimly tightened since all the forces are applied at it's rear portion to the band **4**) around a male's waist using buckle **2**, thus that buckle **2** is not placed on the middle of the wearer's body, in order not to interact with eventually present trouser's buckle. Then, the head of the penis (optionally being previously wrapped with 1 or 2 layers of the protective gauze) is inserted through elastic loop **19** formed of elastic cord-like member **18** in conjunction with connecting member **17**, whereby cinching strap **15** with snap-hook **14** and half-rings **16** are freely hanging down. Said cord-like member **18** is then cinched around penis next to the penis head, and said cord-like member **18** is finally being fixed using channels **22a** and **22b** on said connecting member **17**, thus providing fulcrum for stretching force application. After that, in use, subsystem **A** is being connected by the snap-hook **7** to the belt **1** via loop **5**, and penis and subsystem **B** (being already connected with) together are inserted through rope loop **13**, formed of rope regulator means **10**, rope **11** and protective pad **12**, having said pad **12** placed on the top (dorsal) side of the base of the penis. Further, snap-hook **14** is connected to loop **6** on belt **1** providing the harness for stretching the penis to be ready for use. Finally, cinching straps **8** and **15** are gradually and alternately tightened, until desired tractive force is attained.

Desired angle of torsion of the penis while stretching is provided by strap's **15** lower part gliding along the aperture **20** (in a direction of the arrows **e** or **f**, see FIG. 3) which adjustment of the torsion angle is possible due to a U-shape and at the same time L-shape design of aperture **20** (see FIG. 6).

Respecting that the cinching straps **8** and **15** freely glide on it's upper parts through loops of the snap-hooks **7** and **14** respectively, and said straps freely glide on it's lower parts through

part of the rope **11** and through aperture **20** on connecting member **17** respectively, it is very easy to place pairs of half-rings **9** and **16** respectively (by in-one-point traction of said strap's side next to the wearer's body or that strap's second side carrying half rings, where traction is realised either in a direction of the arrow **c** or in a direction of the arrow **d**, see FIG. 3) in a place on one's body where said half-rings are easiest to manage and hence to adjust stretching forces, even over the clothing, and even while walking.

Fast and easy unplugging of snap-hooks **7** and **14**, which hold on subsystems **A** and **B** to the belt **1**, from loops **5** and **6**, and replacement of the positions of said snap-hooks and consequently said subsystems provides fast and easy alternation of one's body side where penis is settled, meaning that the penis is stretched while settled in left or in right groin groove, all of this towards better comfortability of the harness and towards side-effects preventing.

While preferred embodiment of the present invention have been shown and described, various modifications may be made without departing from the scope of the present invention, and all such equivalents and modifications are intended to be covered.

CLAIMS

What is claimed is :

1. A harness for stretching the penis **characterized by** that harness for stretching the penis comprising

a belt (1) for encircling the waist of the user with the fastening means (2) and at rear side including two string loops (5,6) with adjustable position for connecting two cinching straps (8,15) with the said belt,

a means (A) for application of tractive forces at the base of the penis and at the said belt and for preventing testicles from unpleasant pulling-up caused by the stretching force, and

a means (B) for application of tractive forces at the edge of the head of the penis and at the said belt.

2. Harness for stretching the penis according to claim 1 **characterized by** that loops (5,6) for connecting two cinching straps (8,15) are constructed of string (4) which is pulled out twice through two of the holes in a holed-band (3), and both said string and said holed-band are attached at the upper part of the outer side of the rear portion of the said belt (1), whereby having said holed band attached over said string.

3. Harness for stretching the penis according to claim 1 **characterized by** that means (A) for applying tractive force at the base of the penis and at the belt (1) and for preventing testicles from unpleasant pulling-up caused by the stretching force comprises cinching strap (8), the strap (8) further includes rotating snap-hook (7) for connecting cinching strap (8) to the belt (1), two half-rings (9) for said strap length adjustment, rope (11) with protective pad (12) and rope regulator means (10) for forming an adjustable loop (13) for penis base abutment.

4. Harness for stretching the penis according to claim 1 **characterized by** that means (B) for applying tractive force at the edge of the head of the penis and at the belt (1) comprises cinching strap (15), the strap (15) further includes rotating snap-hook (14) for connecting strap (15) to the belt (1), two half-rings (16) for strap (15) length adjustment, flexible and slightly extensible cord-like member (18) and L-shaped connecting member (17) for connecting the penis with the cinching strap (15) and for forming an adjustable loop (19) for encircling around the penis next to the edge of the penis head and hence for enabling tractive force appliance thereto.

5. Harness for stretching the penis according to claim 2 **characterized by** that rope regulator means (10), for forming an adjustable loop for penis base abutment, is single U-shaped rigid member having a pair of slightly overlapping holes (23a with 24a, 23b with 24b) on

each of the two U-branches, said holes (23a,24a,23b,24b) for rope (11) leading and securing, said holes having diameter equal to diameter of said rope.

6. Harness for stretching the penis according to claim 3 **characterized by** that L-shaped connecting member (17), for connecting the penis with the cinching strap (15) and for forming an adjustable loop (19) for encircling around the penis next to the edge of the penis head and hence for enabling tractive force appliance thereto, is single rigid planar L-shaped member, having U-shaped aperture (20) on L-shape's shorter portion for cinching strap (15) passing through, having a pair of channels (22a,22b) on each of the sides of L-shape's longer portion for cord-like member (18) adjusting, securing and fast releasing, said channels dimensioned for tight cord-like member (18) passing through, and said connecting member (17) having two adjacent holes (21) in the middle of the lower end of said L-shape's longer portion for said cord-like member (18) passing through, which said cord-like member such forms an adjustable loop (19) for encircling the penis next to the penis head, said holes (21) having diameter greater than diameter of the said cord-like member.