said plurality of switches are connected in series within said circuit.

5. The system of claim 1, wherein:

said plurality of switches are connected in parallel within said circuit.

6. The system of claim 1, wherein:

said plurality of switches are individually addressable and uniquely identifiable.

7. The system of claim 1, wherein:

a first of said plurality of latch couplings is arranged to prevent axial translation but allow rotation of said tubing string with respect to the first pipe;

a first of said plurality of latch keys corresponds to said first latch coupling and is operatively coupled to a first of said plurality of switches;

a second of said plurality of latch couplings is arranged to prevent rotation of said tubing string with respect to the first pipe; and

a second of said plurality of latch keys corresponds to said second latch coupling and is operatively coupled to a second of said plurality of switches.

8. The system of claim 7, wherein:

said first latch coupling is disposed at an elevation spaced apart from said second latch coupling.

9. A method for orienting a tubing string with respect to a casing string in a wellbore, the casing string having a latch coupling and a casing string window associated with a lateral wellbore, the method comprising:

providing a tubing string having a tubing string window and a latch key;

disposing the tubing string into the wellbore to a position at which at least part of the tubing string window is adjacent to at least part of the casing string window and at which the latch coupling is configured to receive the latch key to prevent at least one of the group consisting of rotation and axial translation of the tubing string with respect to the casing string;