

**PRETREATMENT, PRE-COOLING, AND CONDENSATE RECOVERY OF
NATURAL GAS BY HIGH PRESSURE COMPRESSION AND EXPANSION**

CROSS REFERENCE TO RELATED APPLICATIONS

- 5 **[0001]** This application claims the priority benefit of United States Provisional Patent Application No. 62/902455, filed September 19, 2019, entitled PRETREATMENT, PRE-COOLING, AND CONDENSATE RECOVERY OF NATURAL GAS BY HIGH PRESSURE COMPRESSION AND EXPANSION.

FIELD OF THE INVENTION

- 10 **[0002]** The invention relates to the liquefaction of natural gas to form liquefied natural gas (LNG), and more specifically, to the production of LNG in remote or sensitive areas where the construction and/or maintenance of capital facilities, and/or the environmental impact of a conventional LNG plant may be detrimental.

BACKGROUND

- 15 **[0003]** LNG production is a rapidly growing means to supply natural gas from locations with an abundant supply of natural gas to distant locations with a strong demand for natural gas. The conventional LNG production cycle includes: a) initial treatments of the natural gas resource to remove contaminants such as water, sulfur compounds and carbon dioxide; b) the separation of some heavier hydrocarbon gases, such as propane, butane, pentane, etc. by a variety of possible
20 methods including self-refrigeration, external refrigeration, lean oil, etc.; c) refrigeration of the natural gas substantially by external refrigeration to form liquefied natural gas at near atmospheric pressure and about -160 °C; d) transport of the LNG product in ships or tankers designed for this purpose to a market location; e) re-pressurization and regasification of the LNG at a regasification plant to a pressurized natural gas that may be distributed to natural gas consumers.
25 Step (c) of the conventional LNG cycle usually requires the use of large refrigeration compressors often powered by large gas turbine drivers that emit substantial carbon and other emissions. Large capital investment in the billions of US dollars and extensive infrastructure are required as part of the liquefaction plant. Step (e) of the conventional LNG cycle generally includes re-pressurizing the LNG to the required pressure using cryogenic pumps and then re-
30 gasifying the LNG to pressurized natural gas by exchanging heat through an intermediate fluid but ultimately with seawater or by combusting a portion of the natural gas to heat and vaporize

the LNG.

[0004] Although LNG production in general is well known, technology improvements may still provide an LNG producer with significant opportunities as it seeks to maintain its leading position in the LNG industry. For example, floating LNG (FLNG) is a relatively new technology option for producing LNG. The technology involves the construction of the gas treating and liquefaction facility on a floating structure such as barge or a ship. FLNG is a technology solution for monetizing offshore stranded gas where it is not economically viable to construct a gas pipeline to shore. FLNG is also increasingly being considered for onshore and near-shore gas fields located in remote, environmentally sensitive and/or politically challenging regions. The technology has certain advantages over conventional onshore LNG in that it has a reduced environmental footprint at the production site. The technology may also deliver projects faster and at a lower cost since the bulk of the LNG facility is constructed in shipyards with lower labor rates and reduced execution risk.

[0005] Although FLNG has several advantageous over conventional onshore LNG, significant technical challenges remain in the application of the technology. For example, the FLNG structure must provide the same level of gas treating and liquefaction in an area or space that is often less than one quarter of what would be available for an onshore LNG plant. For this reason, there is a need to develop technology that reduces the footprint of the liquefaction facility while maintaining its capacity to thereby reduce overall project cost. Several liquefaction technologies have been proposed for use on an FLNG project. The leading technologies include a single mixed refrigerant (SMR) process, a dual mixed refrigerant (DMR) process, and expander-based (or expansion) process.

[0006] In contrast to the DMR process, the SMR process has the advantage of allowing all the equipment and bulks associated with the complete liquefaction process to fit within a single FLNG module. The SMR liquefaction module is placed on the topside of the FLNG structure as a complete SMR train. This “LNG-in-a-Box” concept is favorable for FLNG project execution because it allows for the testing and commissioning of the SMR train at a different location from where the FLNG structure is constructed. It may also allow for the reduction in labor cost since it reduces labor hours at ship yards where labor rates tend to be higher than labor rates at conventional fabrication yards. The SMR process has the added advantage of being a relatively efficient, simple, and compact refrigerant process when compared to other mixed refrigerant processes. Furthermore, the SMR liquefaction process is typically 15% to 20% more efficient than expander-based liquefaction processes.

[0007] The choice of the SMR process for LNG liquefaction in an FLNG project has its advantages; however, there are several disadvantages to the SMR process. For example, the required use and storage of combustible refrigerants such as propane significantly increases loss prevention issues on the FLNG. The SMR process is also limited in capacity, which increases the number of trains needed to reach the desired LNG production. Also, to remove heavy hydrocarbons and recover the necessary natural gas liquids for refrigerant makeup, a scrub column is often used. **Figure 1** illustrates a typical LNG liquefaction system **100** integrating a simple SMR process with a scrub column **104**. A SMR refrigerant loop **106** cools and liquefies a feed gas stream **102** in one or more heat exchangers **108a**, **108b**, **108c**. Specifically, the SMR refrigerant loop **106** cools the feed gas stream **102** before it is sent to the scrub column **104**. Heavy hydrocarbons are removed from a bottom stream **110** of the scrub column **104**, and a cooled vapor stream **112** is removed from the top of the scrub column **104**. The cooled vapor stream **112** is then cooled and partially condensed in heat exchanger **108b** through heat exchange with the SMR refrigerant loop **106**. The cooled vapor stream is sent to a separating vessel **114**, where the condensed portion of the cooled vapor stream is returned to the scrub column as a liquid reflux stream **116**, and the vapor portion **118** of the cooled vapor stream is liquefied through heat exchange with the SMR refrigerant loop **106** in the heat exchanger **108c**. An LNG stream **120** exits the LNG liquefaction system **100** for storage and/or transport.

[0008] The integrated scrub column design, such as the one depicted in **Figure 1** and described above, is usually the lowest cost option for heavy hydrocarbon removal. However, this design has the disadvantage of reducing train capacity because some of the refrigeration of the SMR train is used in heat exchanger **108b** to produce the column reflux. It also has the disadvantage of increasing the equipment count of an SMR train, which may limit the ability to place the SMR train within a single FLNG module. Furthermore, for FLNG applications of greater than 1.5 MTA, multiple SMR trains are required, with each train having its own integrated scrub column. For these reasons and others, a significant amount of topside space and weight is required for the SMR trains. Since topside space and weight are significant drivers for FLNG project cost, there remains a need to improve the SMR liquefaction process to further reduce topside space, weight and complexity to thereby improve project economics. There remains an additional need to develop a heavy hydrocarbon removal process capable of increasing train capacity while also reducing overall equipment count for high production FLNG applications.

[0009] The expander-based process has several advantages that make it well suited for

FLNG projects. The most significant advantage is that the technology offers liquefaction without the need for external hydrocarbon refrigerants. Removing liquid hydrocarbon refrigerant inventory, such as propane storage, significantly reduces safety concerns on FLNG projects. An additional advantage of the expander-based process compared to a mixed refrigerant process is that the expander-based process is less sensitive to offshore motions since the main refrigerant mostly remains in the gas phase. However, application of the expander-based process to an FLNG project with LNG production of greater than 2 million tons per year (MTA) has proven to be less appealing than the use of the mixed refrigerant process. The capacity of an expander-based process train is typically less than 1.5 MTA. In contrast, a mixed refrigerant process train, such as that of known dual mixed refrigerant processes, can have a train capacity of greater than 5 MTA. The size of the expander-based process train is limited since its refrigerant mostly remains in the vapor state throughout the entire process and the refrigerant absorbs energy through its sensible heat. For these reasons, the refrigerant volumetric flow rate is large throughout the process, and the size of the heat exchangers and piping are proportionately greater than those of a mixed refrigerant process. Furthermore, the limitations in compressor horsepower size results in parallel rotating machinery as the capacity of the expander-based process train increases. The production rate of an FLNG project using an expander-based process can be made to be greater than 2 MTA if multiple expander-based trains are allowed. For example, for a 6 MTA FLNG project, six or more parallel expander-based process trains may be sufficient to achieve the required production. However, the equipment count, complexity and cost all increase with multiple expander trains. Additionally, the assumed process simplicity of the expander-based process compared to a mixed refrigerant process begins to be questioned if multiple trains are required for the expander-based process while the mixed refrigerant process can obtain the required production rate with one or two trains. An integrated scrub column design may also be used to remove heavy hydrocarbons for an expander-based liquefaction process. The advantages and disadvantages of its use is similar to that of an SMR process. The use of an integrated scrub column design limits the liquefaction pressure to a value below the cricondenbar of the feed gas. This fact is a particular disadvantage for expander-based processes since its process efficiency is more negatively impacted by lower liquefaction pressures than mixed refrigerant processes. For these reasons, there is a need to develop a high LNG production capacity FLNG liquefaction process with the advantages of an expander-based process. There is a further need to develop an FLNG technology solution that is better able to handle the challenges that vessel motion has on gas processing. There remains a further need to develop a heavy hydrocarbon removal process better suited for expander based process by eliminating the efficiency and production loss

associated with conventional technologies.

[0010] United States Patent No. 6,412,302 describes a feed gas expander-based process where two independent closed refrigeration loops are used to cool the feed gas to form LNG. In an embodiment, the first closed refrigeration loop uses the feed gas or components of the feed gas as the refrigerant. Nitrogen gas is used as the refrigerant for the second closed refrigeration loop. This technology requires smaller equipment and topside space than a dual loop nitrogen expander-based process. For example, the volumetric flow rate of the refrigerant into the low pressure compressor can be 20 to 50% smaller for this technology compared to a dual loop nitrogen expander-based process. The technology, however, is still limited to a capacity of less than 1.5 MTA.

[0011] United States Patent No. 8,616,012 describes a feed gas expander-based process where feed gas is used as the refrigerant in a closed refrigeration loop. Within this closed refrigeration loop, the refrigerant is compressed to a pressure greater than or equal to 1,500 psia (10,340 kPa), or more preferably greater than 2,500 psia (17,240 kPa). The refrigerant is then cooled and expanded to achieve cryogenic temperatures. This cooled refrigerant is used in a heat exchanger to cool the feed gas from warm temperatures to cryogenic temperatures. A subcooling refrigeration loop is then employed to further cool the feed gas to form LNG. In one embodiment, the subcooling refrigeration loop is a closed loop with flash gas used as the refrigerant. This feed gas expander-based process has the advantage of not being limited to a train capacity range of less than 1 MTA. A train size of approximately 6 MTA has been considered. However, the technology has the disadvantage of an increased equipment count and increased complexity due to its requirement for two independent refrigeration loops and the compression of the feed gas.

[0012] GB 2,486,036 describes a feed gas expander-based process that is an open loop refrigeration cycle including a pre-cooling expander loop and a liquefying expander loop, where the gas phase after expansion is used to liquefy the natural gas. According to this document, including a liquefying expander in the process significantly reduces the recycle gas rate and the overall required refrigeration power. This technology has the advantage of being simpler than other technologies since only one type of refrigerant is used with a single compression string. However, the technology is still limited to capacity of less than 1.5 MTA and it requires the use of liquefying expander, which is not standard equipment for LNG production. The technology has also been shown to be less efficient than other technologies for the liquefaction of lean natural gas.

[0013] United States Patent No. 7,386,996 describes an expander-based process with a pre-cooling refrigeration process preceding the main expander-based cooling circuit. The pre-cooling refrigeration process includes a carbon dioxide refrigeration circuit in a cascade arrangement. The carbon dioxide refrigeration circuit may cool the feed gas and the refrigerant gases of the main expander-based cooling circuit at three pressure levels: a high pressure level to provide the warm-end cooling; a medium pressure level to provide the intermediate temperature cooling; and a low pressure level to provide cold-end cooling for the carbon dioxide refrigeration circuit. This technology is more efficient and has a higher production capacity than expander-based processes lacking a pre-cooling step. The technology has the additional advantage for FLNG applications since the pre-cooling refrigeration cycle uses carbon dioxide as the refrigerant instead of hydrocarbon refrigerants. The carbon dioxide refrigeration circuit, however, comes at the cost of added complexity to the liquefaction process since an additional refrigerant and a substantial amount of extra equipment is introduced. In an FLNG application, the carbon dioxide refrigeration circuit may be in its own module and sized to provide the pre-cooling for multiple expander-based processes. This arrangement has the disadvantage of requiring a significant amount of pipe connections between the pre-cooling module and the main expander-based process modules. The “LNG-in-a-Box” advantages discussed above are no longer realized.

[0014] Thus, there remains a need to develop a pre-cooling process that does not require additional refrigerant and does not introduce a significant amount of extra equipment to the LNG liquefaction process. There is an additional need to develop a pre-cooling process that can be placed in the same module as the liquefaction module. Furthermore, there is an additional need to develop a pre-cooling process that can easily integrate with a heavy hydrocarbon removal process and provide auxiliary cooling upstream of liquefaction. Such a pre-cooling process combined with an SMR process or an expander-based process would be particularly suitable for FLNG applications where topside space and weight significantly impacts the project economics. There remains a specific need to develop an LNG production process with the advantages of an expander-based process and which, in addition, has a high LNG production capacity without significantly increasing facility footprint. There is a further need to develop an LNG technology solution that is better able to handle the challenges that vessel motion has on gas processing. Such a high capacity expander-based liquefaction process would be particularly suitable for FLNG applications where the inherent safety and simplicity of expander-based liquefaction process are greatly valued.

[0015] In the production of LNG, feed gas is required to be conditioned to remove heavy hydrocarbons, such as long-chain alkanes and aromatics, which would freeze under the cryogenic conditions of natural gas liquefaction. For mixed refrigerant (MR) based liquefaction processes, such as propane pre-cooled mixed refrigerant processes or dual MR processes, when mixed refrigerant components such as ethane, propane, and butane must be produced from the feed gas to replace mixed refrigerant lost in the respective refrigerant loop, pre-liquefaction conditioning of the feed gas may involve deep natural gas liquids (NGL) recovery. Such NGL recovery not only removes freezing heavy hydrocarbons but also extracts ethane and liquefied petroleum gas (LPG) to generate mixed refrigerant make-up via a downstream deethanizer, a depropanizer, and/or a debutanizer. However, when mixed refrigerant components can be obtained from other sources, such as existing ethane/propane/butane streams in brownfield expansion projects or external sources where either the logistics are convenient for importation (e.g. gulf coast project) or there is a need to simplify downstream processing (e.g. using FLNG), it would be desirable to minimize slip to a scrub column bottom stream of non-freezing components such as ethane/methane/propane, while targeting the removal of heavy hydrocarbons from the feed stream via said slip to the scrub column bottom stream.

[0016] Figure 10 discloses a known gas pretreatment apparatus 1000 in which a slip of ethane/methane/butane is minimized while targeting heavy hydrocarbons for removal from a natural gas stream 1002. The natural gas stream 1002 is expanded and cooled using a first expansion device 1004, and then flows into a heat exchanger 1006 to be partially condensed. The partially condensed natural gas stream is directed to a scrub column 1008 to be separated into a column overhead stream 1010 and a column bottom stream 1012. The column overhead stream 1010 flows through the heat exchanger 1006 to be partially condensed and forming a two-phase stream 1014. The two-phase stream 1014 flows into a separator 1016 and is separated into a cold pretreated gas stream 1018 and a liquid stream 1020 rich in heavy hydrocarbons and non-freezing components such as ethane/propane/butane. The cold pretreated gas stream 1018 flows through a second expansion device, such as a Joule-Thompson (J-T) valve 1022, and then flows through the heat exchanger 1006 to provide an auxiliary cooling stream therein. The cold pretreated gas stream 1018 is warmed by indirectly exchanging heat with the column overhead stream 1010 to form a pretreated natural gas stream 1024. The liquid stream 1020 may be pressurized using a pump 1026 and then directed to the scrub column 1006 as a column reflux stream. A stripping gas stream 1028 for the scrub column operation may be sourced from the natural gas stream 1002; alternatively, a reboiler (not shown) may be used to provide the

stripping gas for the scrub column. Pretreated natural gas stream **1024** is input into a high pressure compression and expansion (HPCE) process module **1050**. HPCE process module compresses, cools, and expands the pretreated natural gas stream **1024** to produce a chilled pretreated gas stream **1078**. The chilled pretreated gas stream **1078** may then be liquefied in a liquefaction process **1080** to produce an LNG stream **1082**.

[0017] The configuration depicted in **Figure 10** minimizes slip of non-freezing components, as the warmer and richer column overhead stream **1010** of the scrub column **1008** is used to generate the reflux stream **1014**. However, this approach also limits recovery of heavy hydrocarbons in the liquid stream **1020** and consequently reduces condensate production, which is generated through further processing of liquid stream **1020**. Typically, a natural gas liquids (NGL) recovery process is required to increase condensate production, and such processes are complicated and energy intensive. Therefore, there is a need to optimize natural gas conditioning in a manner that balances the requirements of heavy hydrocarbon removal, condensate recovery, and pre-cooling prior to liquefaction.

15

SUMMARY OF THE INVENTION

[0018] According to disclosed aspects, a method is provided for producing liquefied natural gas (LNG) from a natural gas stream. Heavy hydrocarbons are removed from the natural gas stream in a first separator to thereby generate a separated natural gas stream and a separator bottom stream. The separated natural gas stream is used as a coolant in a heat exchanger to thereby generate a pretreated natural gas stream. The pretreated natural gas stream is compressed and cooled to form a chilled pretreated natural gas stream. A portion of the chilled pretreated gas stream forms a recycle stream to exchange heat with the separated natural gas stream in the heat exchanger, thereby generating a cooled recycle stream. A temperature and a pressure of the cooled recycle stream are reduced. The cooled recycle stream is separated into a gaseous separator overhead stream and a reflux stream. The reflux stream is directed to a top portion of the first separator. The chilled pretreated gas stream is liquefied to form LNG.

[0019] An apparatus for the liquefaction of a natural gas stream is also provided. A first heat exchanger cools at least a portion of the natural gas stream to generate a cooled natural gas stream. The portion of the natural gas stream is combined with the natural gas stream. A first separation device removes heavy hydrocarbons from the natural gas stream to thereby generate a separated natural gas stream and a separator bottom stream. The separated natural gas stream is directed to the first heat exchanger to act as a coolant therein, thereby generating a pretreated

natural gas stream. A compression and cooling unit compresses and cools the pretreated natural gas stream to form a chilled pretreated stream. A portion of the chilled pretreated gas stream is recycled to the first heat exchanger as a recycle stream to exchange heat with one or more process streams comprising at least one of the portion of the natural gas stream and the separated natural gas stream, thereby generating a cooled recycle stream. A temperature and pressure reducing device reduces the temperature and pressure of the cooled recycle stream. A fourth separation device separates the cooled recycle stream into a gaseous separator overhead stream and a reflux stream. The reflux stream is directed to a top portion of the first separator. At least one liquefaction unit liquefies the chilled pretreated gas stream.

10

BRIEF DESCRIPTION OF THE FIGURES

[0020] **Figure 1** is a schematic diagram of a SMR process with an integrated scrub column for heavy hydrocarbon removal according to known principles.

[0021] **Figure 2** is a schematic diagram of a high pressure compression and expansion (HPCE) module with heavy hydrocarbon removal according to disclosed aspects.

15 [0022] **Figure 3** is a schematic diagram showing an arrangement of single-mixed refrigerant (SMR) liquefaction modules according to known principles.

[0023] **Figure 4** is a schematic diagram showing an arrangement of SMR liquefaction modules according to disclosed aspects.

20 [0024] **Figure 5** is a graph showing a heating and cooling curve for an expander-based refrigeration process.

[0025] **Figure 6** is a schematic diagram of an HPCE module with heavy hydrocarbon removal according to disclosed aspects.

[0026] **Figure 7** is a schematic diagram of an HPCE module with heavy hydrocarbon removal and a feed gas expander-based liquefaction module according to disclosed aspects.

25 [0027] **Figure 8** is a flowchart of a method of liquefying natural gas to form LNG according to disclosed aspects.

[0028] **Figure 9** is a flowchart of a method of liquefying natural gas to form LNG according to disclosed aspects.

30 [0029] **Figure 10** is a schematic diagram of a natural gas pretreatment apparatus according to known principles.

[0030] **Figure 11** is a schematic diagram of a natural gas pretreatment apparatus according to disclosed aspects.

[0031] **Figure 12** is a schematic diagram of a natural gas pretreatment apparatus according to disclosed aspects.

5 [0032] **Figure 13** is a flowchart depicting a method of producing liquefied natural gas according to disclosed aspects.

DETAILED DESCRIPTION

[0033] Various specific aspects, embodiments, and versions will now be described, including definitions adopted herein. Those skilled in the art will appreciate that such aspects, 10 embodiments, and versions are exemplary only, and that the invention can be practiced in other ways. Any reference to the "invention" may refer to one or more, but not necessarily all, of the embodiments defined by the claims. The use of headings is for purposes of convenience only and does not limit the scope of the present invention. For purposes of clarity and brevity, similar reference numbers in the several Figures represent similar items, steps, or structures and may 15 not be described in detail in every Figure.

[0034] All numerical values within the detailed description and the claims herein are modified by "about" or "approximately" the indicated value, and take into account experimental error and variations that would be expected by a person having ordinary skill in the art.

[0035] As used herein, the term "compressor" means a machine that increases the pressure 20 of a gas by the application of work. A "compressor" or "refrigerant compressor" includes any unit, device, or apparatus able to increase the pressure of a gas stream. This includes compressors having a single compression process or step, or compressors having multi-stage compressions or steps, or more particularly multi-stage compressors within a single casing or shell. Reference herein to more than one compressor includes more than one single-stage compressor, one or 25 more multi-stage compressors, and any combination thereof. Evaporated streams to be compressed can be provided to a compressor at different pressures. Some stages or steps of a cooling process may involve two or more compressors in parallel, series, or both. The present invention is not limited by the type or arrangement or layout of the compressor or compressors, particularly in any refrigerant circuit.

30 [0036] As used herein, "cooling" broadly refers to lowering and/or dropping a temperature and/or internal energy of a substance by any suitable, desired, or required amount. Cooling may include a temperature drop of at least about 1 °C, at least about 5 °C, at least about 10 °C, at least

about 15 °C, at least about 25 °C, at least about 35 °C, or least about 50 °C, or at least about 75 °C, or at least about 85 °C, or at least about 95 °C, or at least about 100 °C. The cooling may use any suitable heat sink, such as steam generation, hot water heating, cooling water, air, refrigerant, other process streams (integration), and combinations thereof. One or more sources of cooling
5 may be combined and/or cascaded to reach a desired outlet temperature. The cooling step may use a cooling unit with any suitable device and/or equipment. According to some embodiments, cooling may include indirect heat exchange, such as with one or more heat exchangers. In the alternative, the cooling may use evaporative (heat of vaporization) cooling and/or direct heat exchange, such as a liquid sprayed directly into a process stream.

10 **[0037]** As used herein, the term "environment" refers to ambient local conditions, e.g., temperatures and pressures, in the vicinity of a process.

[0038] As used herein, the term "expansion device" refers to one or more devices suitable for reducing the pressure of a fluid in a line (for example, a liquid stream, a vapor stream, or a multiphase stream containing both liquid and vapor). Unless a particular type of expansion
15 device is specifically stated, the expansion device may be (1) at least partially by isenthalpic means, or (2) may be at least partially by isentropic means, or (3) may be a combination of both isentropic means and isenthalpic means. Suitable devices for isenthalpic expansion of natural gas are known in the art and generally include, but are not limited to, manually or automatically, actuated throttling devices such as, for example, valves, control valves, Joule-Thomson (J-T)
20 valves, or venturi devices. Suitable devices for isentropic expansion of natural gas are known in the art and generally include equipment such as expanders or turbo expanders that extract or derive work from such expansion. Suitable devices for isentropic expansion of liquid streams are known in the art and generally include equipment such as expanders, hydraulic expanders, liquid turbines, or turbo expanders that extract or derive work from such expansion. An example
25 of a combination of both isentropic means and isenthalpic means may be a Joule-Thomson valve and a turbo expander in parallel, which provides the capability of using either alone or using both the J-T valve and the turbo expander simultaneously. Isenthalpic or isentropic expansion can be conducted in the all-liquid phase, all-vapor phase, or mixed phases, and can be conducted to facilitate a phase change from a vapor stream or liquid stream to a multiphase stream (a stream
30 having both vapor and liquid phases) or to a single-phase stream different from its initial phase. In the description of the drawings herein, the reference to more than one expansion device in any drawing does not necessarily mean that each expansion device is the same type or size.

[0039] The term "gas" is used interchangeably herein with "vapor," and is defined as a

substance or mixture of substances in the gaseous state as distinguished from the liquid or solid state. Likewise, the term "liquid" means a substance or mixture of substances in the liquid state as distinguished from the gas or solid state.

[0040] A "heat exchanger" broadly means any device capable of transferring heat energy or cold energy from one medium to another medium, such as between at least two distinct fluids. Heat exchangers include "direct heat exchangers" and "indirect heat exchangers." Thus, a heat exchanger may be of any suitable design, such as a co-current or counter-current heat exchanger, an indirect heat exchanger (e.g. a spiral wound heat exchanger or a plate-fin heat exchanger such as a brazed aluminum plate fin type), direct contact heat exchanger, shell-and-tube heat exchanger, spiral, hairpin, core, core-and-kettle, printed-circuit, double-pipe or any other type of known heat exchanger. "Heat exchanger" may also refer to any column, tower, unit or other arrangement adapted to allow the passage of one or more streams therethrough, and to affect direct or indirect heat exchange between one or more lines of refrigerant, and one or more feed streams.

[0041] As used herein, the term "heavy hydrocarbons" refers to hydrocarbons having more than four carbon atoms. Principal examples include pentane, hexane and heptane. Other examples include benzene, aromatics, or diamondoids.

[0042] As used herein, the term "indirect heat exchange" means the bringing of two fluids into heat exchange relation without any physical contact or intermixing of the fluids with each other. Core-in-kettle heat exchangers and brazed aluminum plate-fin heat exchangers are examples of equipment that facilitate indirect heat exchange.

[0043] As used herein, the term "natural gas" refers to a multi-component gas obtained from a crude oil well (associated gas) or from a subterranean gas-bearing formation (non-associated gas). The composition and pressure of natural gas can vary significantly. A typical natural gas stream contains methane (C_1) as a significant component. The natural gas stream may also contain ethane (C_2), higher molecular weight hydrocarbons, and one or more acid gases. The natural gas may also contain minor amounts of contaminants such as water, nitrogen, iron sulfide, wax, and crude oil.

[0044] As used herein, the term "separation device" or "separator" refers to any vessel configured to receive a fluid having at least two constituent elements and configured to produce a gaseous stream out of a top portion and a liquid (or bottoms) stream out of the bottom of the vessel. The separation device/separator may include internal contact-enhancing structures (e.g.

packing elements, strippers, weir plates, chimneys, etc.), may include one, two, or more sections (e.g. a stripping section and a reboiler section), and/or may include additional inlets and outlets. Exemplary separation devices/separators include bulk fractionators, stripping columns, phase separators, scrub columns, and others.

5 **[0045]** As used herein, the term “scrub column” refers to a separation device used for the removal of heavy hydrocarbons from a natural gas stream.

[0046] Certain embodiments and features have been described using a set of numerical upper limits and a set of numerical lower limits. It should be appreciated that ranges from any lower limit to any upper limit are contemplated unless otherwise indicated. All numerical values are
10 “about” or “approximately” the indicated value, and take into account experimental error and variations that would be expected by a person having ordinary skill in the art.

[0047] All patents, test procedures, and other documents cited in this application are fully incorporated by reference to the extent such disclosure is not inconsistent with this application and for all jurisdictions in which such incorporation is permitted.

15 **[0048]** Aspects disclosed herein describe a process for pretreating and pre-cooling natural gas to a liquefaction process for the production of LNG by the addition of a high pressure compression and high pressure expansion process prior to liquefying the natural gas. A portion of the compressed and expanded gas is used to cool one or more process streams associated with pretreating the feed gas. More specifically, the invention describes a process where heavy
20 hydrocarbons are removed from a natural gas stream to form a pretreated natural gas stream. The pretreated natural gas is compressed to pressure greater than 1,500 psia (10,340 kPa), or more preferably greater than 3,000 psia (20,680 kPa). The hot compressed gas is cooled by exchanging heat with the environment to form a compressed pretreated gas. The compressed pretreated gas is near-isentropically expanded to a pressure less than 3,000 psia (20,680 kPa), or more
25 preferably to a pressure less than 2,000 psia (13,790 kPa) to form a first chilled pretreated gas, where the pressure of the first chilled pretreated gas is less than the pressure of the compressed pretreated gas. The first chilled pretreated gas is separated into at least one refrigerant stream and a non-refrigerant stream. The at least one refrigerant stream is directed to at least one heat exchanger where it acts to cool a process stream and form a warmed refrigerant stream. The
30 warmed refrigerant stream is mixed with the non-refrigerant stream to form a second chilled pretreated gas. The second chilled pretreated gas may be directed to one or more SMR liquefaction trains, or the second chilled pretreated gas may be directed to one or more expander-

based liquefaction trains where the gas is further cooled to form LNG.

[0049] **Figure 2** is an illustration of a pretreatment apparatus **200** for pretreating and pre-cooling a natural gas stream **201**, followed by a high pressure compression and expansion (HPCE) process module **212**. A natural gas stream **201** may flow into a separation device, such as a scrub column **202**, where the natural gas stream **201** is separated into a column overhead stream **203** and a column bottom stream **204**. The column overhead stream **203** may flow through a first heat exchanger **205**, known as a ‘cold box’, where the column overhead stream **203** is partially condensed to form a two-phase stream **206**. The two-phase stream **206** may flow into another separation device, such as a separator **207**, to form cold pretreated gas stream **208** and a liquid stream **209**. The cold pretreated gas stream **208** may flow through the first heat exchanger **205** where the cold pretreated gas stream **208** is warmed by indirectly exchanging heat with the column overhead stream **203**, thereby forming a pretreated natural gas stream **210**. The liquid stream **209** may be pressurized within a pump **211** and then directed to the scrub column **202** as a column reflux stream.

[0050] The HPCE process module **212** may comprise a first compressor **213** which compresses the pretreated natural gas stream **210** to form an intermediate pressure gas stream **214**. The intermediate pressure gas stream **214** may flow through a second heat exchanger **215** where the intermediate pressure gas stream **214** is cooled by indirectly exchanging heat with the environment to form a cooled intermediate pressure gas stream **216**. The second heat exchanger **215** may be an air cooled heat exchanger or a water cooled heat exchanger. The cooled intermediate pressure gas stream **216** may then be compressed within a second compressor **217** to form a high pressure gas stream **218**. The pressure of the high pressure gas stream **218** may be greater than 1,500 psia (10,340 kPa), or more preferably greater than 3,000 psia (20,680 kPa). The high pressure gas stream **218** may flow through a third heat exchanger **219** where the high pressure gas stream **218** is cooled by indirectly exchanging heat with the environment to form a cooled high pressure gas stream **220**. The third heat exchanger **219** may be an air cooled heat exchanger or a water cooled heat exchanger. The cooled high pressure gas stream **220** may then be expanded within an expander **221** to form a first chilled pretreated gas stream **222**. The pressure of the first chilled pretreated gas stream **222** may be less than 3,000 psia (20,680 kPa), or more preferably less than 2,000 psia (13,790 kPa), and the pressure of the first chilled pretreated gas stream **222** is less than the pressure of the cooled high pressure gas stream **220**. In a preferred aspect, the second compressor **217** may be driven solely by the shaft power produced by the expander **221**, as indicated by the dashed line **223**. The first chilled pretreated

gas stream **222** may be separated into a refrigerant stream **224** and a non-refrigerant stream **225**. The refrigerant stream **224** may flow through the first heat exchanger **205** where the refrigerant stream **224** is partially warmed by indirectly exchanging heat with the column overhead stream **203**, thereby forming a warmed refrigerant stream **226**. The warmed refrigerant stream **226** may mix with the non-refrigerant stream **225** to form a second chilled pretreated gas stream **227**. The second chilled pretreated gas stream **227** may then be liquefied in, for example, an SMR liquefaction train **240** through indirect heat exchange with an SMR refrigerant loop **228** in a fourth heat exchanger **229**. The resultant LNG stream **230** may then be stored and/or transported as needed.

[0051] It should be noted that the refrigerant stream **224** may be used to cool or chill any of the process streams associated with the pretreatment apparatus **200**. For example, one or more of the column overhead stream **203**, the two-phase stream **206**, the cold pretreated gas stream **208**, the liquid stream **209**, and the pretreated natural gas stream **210** may be configured to exchange heat with the refrigerant stream **224**. Furthermore, other process streams not associated with the pretreatment apparatus **200** may be cooled through heat exchange with the refrigerant stream **224**. The refrigerant stream **224** may be split into two or more sub-streams that are used to cool various process streams.

[0052] In an aspect, the SMR liquefaction process may be enhanced by the addition of the HPCE process upstream of the SMR liquefaction process. More specifically, in this aspect, pretreated natural gas may be compressed to a pressure greater than 1,500 psia (10,340 kPa), or more preferably greater than 3,000 psia (20,680 kPa). The hot compressed gas is then cooled by exchanging heat with the environment to form a compressed pretreated gas. The compressed pretreated gas is then near-isentropically expanded to pressure less than 3,000 psia (20,680 kPa), or more preferably to a pressure less than 2,000 psia (13,790 kPa) to form a first chilled pretreated gas, where the pressure of the first chilled pretreated gas is less than the pressure of the compressed pretreated gas. The first chilled pretreated gas stream is separated into a refrigerant stream and a non-refrigerant stream. The refrigerant stream is warmed by exchanging heat with a column overhead stream in order to help partially condense the column overhead stream and produce a warmed refrigerant stream. The warmed refrigerant stream is mixed with the non-refrigerant stream to produce a second chilled pretreated gas. The second chilled pretreated gas may then be directed to multiple SMR liquefaction trains, arranged in parallel, where the chilled pretreated gas is further cooled therein to form LNG.

[0053] The combination of the HPCE process with pretreatment of the natural gas and

liquefaction within multiple SMR liquefaction trains has several advantages over the conventional SMR process where natural gas is sent directly to the SMR liquefaction trains for both heavy hydrocarbon removal (final pretreatment step) and liquefaction. For example, the pre-cooling of the natural gas using the HPCE process allows for an increase in LNG production rate within the SMR liquefaction trains for a given horsepower within the SMR liquefaction trains. **Figures 3 and 4** demonstrate how the disclosed aspects provide such an LNG production increase. **Figure 3** is an illustration of an arrangement of liquefaction modules or trains, such as SMR liquefaction trains, on an LNG production facility such as an FLNG unit **300** according to known principles. A natural gas stream **302** that is pretreated to remove sour gases and water to make the natural gas suitable for cryogenic treatment may be distributed between five identical or nearly identical SMR liquefaction trains **304, 306, 308, 310, 312** arranged in parallel. As an example, each SMR liquefaction train may receive approximately 50 megawatts (MW) of compression power from either a gas turbine or an electric motor (not shown) to drive the compressors of the respective SMR liquefaction train. Each SMR liquefaction module comprises an integrated scrub column to remove heavy hydrocarbons from the natural gas stream and to recover a sufficient amount of natural gas liquids to provide refrigerant make-up. Each SMR liquefaction module may produce approximately 1.5 million tons per year (MTA) of LNG for a total stream production of approximately 7.5 MTA for the entire FLNG unit **300**.

[0054] In contrast, **Figure 4** schematically depicts an LNG liquefaction facility such as an FLNG unit **400** according to disclosed aspects. FLNG unit **400** includes four SMR liquefaction trains **406, 408, 410, 412** arranged in parallel. Unlike the SMR liquefaction trains shown in Figure 3, none of the SMR liquefaction trains **406, 408, 410, 412** include a scrub column. Instead, a natural gas stream **402**, which is pretreated to remove sour gases and water to make the gas suitable for cryogenic treatment, may be directed to a HPCE module **404** to produce a chilled pretreated gas stream **405**. As previously explained, the HPCE module is integrated with a heavy hydrocarbon removal process therein (including a scrub column or similar separator) to remove any hydrocarbons that may form solids during the liquefaction of the natural gas stream **402**. The HPCE module **404** may receive approximately 55 MW of compression power, for example, from either a gas turbine or an electric motor (not shown) to drive one or more compressors within the HPCE module **404**. The chilled pretreated gas stream **405** may be distributed between the SMR liquefaction modules **406, 408, 410, 412**. Each SMR liquefaction module may receive approximately 50 MW of compression power from either a gas turbine or an electric motor (not shown) to drive the compressors of the respective SMR liquefaction modules. Each SMR

liquefaction module may produce approximately 1.9 MTA of LNG for a total production of approximately 7.6 MTA of LNG for the FLNG unit **400**. If the FLNG unit **400** uses the disclosed HPCE process module integrated with a single scrub column and cold box (referred to collectively as the HPCE process module **404**), only a single scrub column is required to remove heavy hydrocarbons from the natural gas stream **402**. The replacement of one SMR liquefaction train with the disclosed HPCE module **404** is advantageous since the HPCE module is expected to be smaller, of less weight, and having significantly lower cost than the replaced SMR liquefaction train. Like the replaced SMR liquefaction train, the HPCE module **404** may have an equivalent size gas turbine to provide compression power, and it will also have an equivalent amount of air or water coolers. Unlike the replaced SMR liquefaction train, however, the HPCE module **404** does not have an expensive main cryogenic heat exchanger. The vessels and pipes associated with the refrigerant flow within an SMR module are eliminated in the replaced HPCE liquefaction train. Furthermore, the amount of expensive cryogenic pipes in the HPCE module **404** is significantly reduced.

[0055] The disclosed HPCE module comprises a single scrub column used to remove the heavy hydrocarbons from the natural gas that is then fed to all the liquefaction trains. This design increases the required power of the HPCE module by 10 to 15% compared to a design where heavy hydrocarbon removal is not included. However, integrating the heavy hydrocarbon removal within the HPCE module instead of within each SMR liquefaction train reduces the weight of each SMR liquefaction train and may result in a total reduction in equipment count and overall topside weight of an FLNG system. Another advantage is that the liquefaction pressure can be greater than the cricondenbar of the feed gas, which results in increased liquefaction efficiency. Furthermore, the proposed design is more flexible to feed gas changes than the integrated scrub column design.

[0056] Another advantage of the disclosed HPCE module is that the required storage of refrigerant is reduced since the number of SMR liquefaction trains has been reduced by one. Also, since a large fraction of the warm temperature cooling of the gas occurs in the HPCE module, the heavier hydrocarbon components of the mixed refrigerant can be reduced. For example, the propane component of the mixed refrigerant may be eliminated without any significant reduction in efficiency of the SMR liquefaction process.

[0057] Another advantage is that for a SMR liquefaction process which receives chilled pretreated gas from the disclosed HPCE module, the volumetric flow rate of the vaporized refrigerant of the SMR liquefaction process can be more than 25% less than that of a

conventional SMR liquefaction process receiving warm pretreated gas. The lower volumetric flow of refrigerant may reduce the size of the main cryogenic heat exchanger and the size of the low pressure mixed refrigerant compressor. The lower volumetric flow rate of the refrigerant is due to its higher vaporizing pressure compared to that of a conventional SMR liquefaction process.

[0058] Known propane-precooled mixed refrigeration processes and dual mixed refrigeration (DMR) processes may be viewed as versions of an SMR liquefaction process combined with a pre-cooling refrigeration circuit, but there are significant differences between such processes and aspects of the present disclosure. For example, the known processes use a cascading propane refrigeration circuit or a warm-end mixed refrigerant to pre-cool the gas. Both these known processes have the advantage of providing 5% to 15% higher efficiency than the SMR liquefaction process. Furthermore, the capacity of a single liquefaction train using these known processes can be significantly greater than that of a single SMR liquefaction train. The pre-cooling refrigeration circuit of these technologies, however, comes at the cost of added complexity to the liquefaction process since additional refrigerants and a substantial amount of extra equipment is introduced. For example, the DMR liquefaction process's disadvantage of higher complexity and weight may outweigh its advantages of higher efficiency and capacity when deciding between a DMR liquefaction process and an SMR liquefaction process for an FLNG application. The known processes have considered the addition of a pre-cooling process upstream of the SMR liquefaction process as being driven principally by the need for higher thermal efficiencies and higher LNG production capacity for a single liquefaction train. The disclosed HPCE process combined with the SMR liquefaction process has not been realized previously because it does not provide the higher thermal efficiencies that the refrigerant-based pre-cooling process provides. As described herein, the thermal efficiency of the HPCE process with the SMR liquefaction is about the same as a standalone SMR liquefaction process. The disclosed aspects are believed to be novel based at least in part on its description of a pre-cooling process that aims to reduce the weight and complexity of the liquefaction process rather than increase thermal efficiency, which in the past has been the biggest driver for the addition of a pre-cooling process for onshore LNG applications. As an additional point, the integrated scrub column design is traditionally seen as the lowest cost option for heavy hydrocarbon removal of natural gas to liquefaction. However, the integration of heavy hydrocarbon removal with a HPCE process, as disclosed herein, provides a previously unrealized advantage of potentially reducing total equipment count and weight when multiple liquefaction trains is the preferred design

methodology. For the newer applications of FLNG and remote onshore application, footprint, weight, and complexity of the liquefaction process may be a bigger driver of project cost. Therefore the disclosed aspects are of particular value.

[0059] In an aspect, an expander-based liquefaction process may be enhanced by the addition of an HPCE process upstream of the expander-based process. More specifically, in this aspect, a pretreated natural gas stream may be compressed to pressure greater than 1,500 psia (10,340 kPa), or more preferably greater than 3,000 psia (20,680 kPa). The hot compressed gas may then be cooled by exchanging heat with the environment to form a compressed pretreated gas. The compressed pretreated gas may be near-isentropically expanded to a pressure less than 3,000 psia (20,680 kPa), or more preferably to a pressure less than 2,000 psia (13,790 kPa) to form a first chilled pretreated gas, where the pressure of the first chilled pretreated gas is less than the pressure of the compressed pretreated gas. The first chilled pretreated gas stream is separated into refrigerant stream and a non-refrigerant stream. The refrigerant stream is warmed by exchanging heat with a column overhead stream in order to help partially condense the column overhead stream and produce a warmed refrigerant stream. The warmed refrigerant stream is mixed with the non-refrigerant stream to produce a second chilled pretreated gas. The second chilled pretreated gas is directed to an expander-based process where the gas is further cooled to form LNG. In a preferred aspect, the second chilled pretreated gas may be directed to a feed gas expander-based process.

[0060] **Figure 5** shows a typical temperature cooling curve **500** for an expander-based liquefaction process. The higher temperature curve **502** is the temperature curve for the natural gas stream. The lower temperature curve **504** is the composite temperature curve of a cold cooling stream and a warm cooling stream. The natural gas is liquefied at pressure above its cricondenbar which allows for the close matching of the natural gas cooling curve (shown at **502**) with the composite temperature curve of the cold and warm cooling streams (shown at **504**) to maximize thermal efficiency. As illustrated, the cooling curve is marked by three temperature pinch-points **506**, **508**, and **510**. Each pinch point is a location within the heat exchanger where the combined heat capacity of the cooling streams is less than that of the natural gas stream. This imbalance in heat capacity between the streams results in a reduction of the temperature difference between the cooling stream to the minimally acceptable temperature difference which provides effective heat transfer rate. The lowest temperature pinch-point **506** occurs where the colder of the two cooling streams, typically the cold cooling stream, enters the heat exchanger. The intermediate temperature pinch-point **508** occurs where the second cooling stream, typically

the warm cooling stream, enters the heat exchanger. The warm temperature pinch-point **510** occurs where the cold and warm cooling streams exit the heat exchanger. The warm temperature pinch-point **510** causes a need for a high mass flow rate for the warmer cooling stream, which subsequently increases the power demand of the expander-based process.

5 **[0061]** One proposed method to eliminate the warm temperature pinch-point **510** is to pre-cool the feed gas with an external refrigeration system such as a propane cooling system or a carbon dioxide cooling system. For example, United States Patent No. 7,386,996 eliminates the warm temperature pinch-point by using a pre-cooling refrigeration process comprising a carbon dioxide refrigeration circuit in a cascade arrangement. This external pre-cooling refrigeration
10 system has the disadvantage of significantly increasing the complexity of the liquefaction process since an additional refrigerant system with all its associated equipment is introduced. Aspects disclosed herein reduce the impact of the warm temperature pinch-point **510** by pre-cooling the feed gas stream by compressing the feed gas to a pressure greater than 1,500 psia (10,340 kPa), cooling the compressed feed gas stream, and expanding the compressed gas stream
15 to a pressure less than 2,000 psia (20,690 kPa), where the expanded pressure of the feed gas stream is less than the compressed pressure of the feed gas stream. This process of cooling the feed gas stream results in a significant reduction in the in the required mass flow rate of the expander-based process cooling streams. It also improves the thermodynamic efficiency of the expander-based process without significantly increasing the equipment count and without the
20 addition of an external refrigerant. This process may also be integrated with heavy hydrocarbon removal in order to remove the heavy hydrocarbon upstream of the liquefaction process. Since the gas is now free of heavy hydrocarbons that would form solids, the pretreated gas can be liquefied at a pressure above its cricondenbar in order to improve liquefaction efficiency.

[0062] In a preferred aspect, the expander-based process may be a feed gas expander-based
25 process. This feed gas expander process comprises a first closed expander-based refrigeration loop and a second closed expander-based refrigeration loop. The first expander-based refrigeration loop may be principally charged with methane from a feed gas stream. The first expander-based refrigeration loop liquefies the feed gas stream. The second expander-based refrigeration loop may be charged with nitrogen as the refrigerant. The second expander-based
30 refrigeration loop sub-cools the LNG streams. Specifically, a produced natural gas stream may be treated to remove impurities, if present, such as water, and sour gases, to make the natural gas suitable for cryogenic treatment. The treated natural gas stream may be directed to a scrub column where the treated natural gas stream is separated into a column overhead stream and a

column bottom stream. The column overhead stream may be partially condensed within a first heat exchanger by indirectly exchanging heat with a cold pretreated gas stream and a refrigerant stream to thereby form a two phase stream. The two phase stream may be directed to a separator where the two phase stream is separated into the cold pretreated gas stream and a liquid stream.

5 The cold pretreated gas stream may be warmed within the first heat exchanger by exchanging heat with the column overhead stream to form a pretreated natural gas stream. The liquid stream may be pressurized within a pump and then directed to the scrub column to provide reflux to the scrub column. The pretreated natural gas stream may be directed to an HPCE process as disclosed herein, where it is compressed to a pressure greater than 1,500 psia (10,340 kPa), or

10 more preferably greater than 3,000 psia (20,680 kPa). The hot compressed gas stream may then be cooled by exchanging heat with the environment to form a compressed treated natural gas stream. The compressed treated natural gas stream may be near-isentropically expanded to a pressure less than 3,000 psia (20,680 kPa), or more preferably to a pressure less than 2,000 psia (12,790 kPa) to form a first chilled treated natural gas stream, where the pressure of the first

15 chilled treated natural gas stream is less than the pressure of the compressed treated natural gas stream. The first chilled natural gas stream may be separated into the refrigerant stream and a non-refrigerant stream. The refrigerant stream may be partially warmed within the first heat exchanger by exchanging heat with the column overhead stream to form a warmed refrigerant stream. The warmed refrigerant stream may mix with the non-refrigerant stream to form a second

20 chilled natural gas stream. The second chilled treated natural gas may be directed to the feed gas expander process where the first expander-based refrigeration loop acts to liquefy the second chilled treated natural gas to form a pressurized LNG stream. The second expander refrigeration loop then acts to subcool the pressurized LNG stream. The subcooled pressurized LNG stream may then be expanded to a lower pressure in order to form an LNG stream.

25 **[0063]** The combination of the HPCE process with pretreatment of the natural gas and liquefaction of the pretreated gas within an expander-based process has several advantages over a conventional expander-based process. Including the HPCE process therewith may increase the efficiency of the expander-based process by 5 to 25% depending of the type of expander-based process employed. The feed gas expander process described herein may have a liquefaction

30 efficiency similar to that of an SMR process while still providing the advantages of no external refrigerant use, ease of operation, and reduced equipment count. Furthermore, the refrigerant flow rates and the size of the recycle compressors are expected to be significantly lower for the expander-base process combined with the HPCE process. For these reasons, the production

capacity of a single liquefaction train according to disclosed aspects may be greater than 30 to 50% above the production capacity of a similarly sized conventional expander-based liquefaction process. The combination of HPCE process with heavy hydrocarbon removal upstream of an expander-based liquefaction process has the additional benefit of providing the option to liquefy the gas at pressures above its cricondenbar to improve liquefaction efficiency. Expander-based liquefaction processes are particularly sensitive to liquefaction pressures. Therefore, the HPCE process described herein is well suited for removing heavy hydrocarbons while also increasing the liquefaction efficiency and production capacity of expander-based liquefaction processes.

10 **[0064]** Figure 6 is an illustration of an aspect of an HPCE module **600** with an integrated scrub column according to another aspect of the disclosure. A natural gas stream **601**, which has been pretreated to remove sour gases and water to make the gas suitable for cryogenic treatment, is fed into a separation device, such as a scrub column **602**, where the natural gas stream **601** is separated into a column overhead stream **603** and a column bottom stream **604**. The column overhead stream **603** may flow through a first heat exchanger **605** where the column overhead stream **603** is partially condensed to form a two-phase stream **606**. The two-phase stream **606** may be directed to another separation device, such as a separator **607**, to form a cold pretreated gas stream **608** and a liquid stream **609**. The cold pretreated gas stream **608** may flow through the first heat exchanger **605** where the cold pretreated gas stream **608** is warmed by indirect heat exchange with the column overhead stream **603** to form a pretreated natural gas stream **610** therefrom. The liquid stream may be pressurized within a pump **611** and then directed to the scrub column **602** as a column reflux stream. The pretreated natural gas stream **610** is directed to a first compressor **612** and compressed therein to form a first intermediate pressure gas stream **613**. The first intermediate pressure gas stream **613** may flow through a second heat exchanger **614** where the first intermediate pressure gas stream **613** is cooled by indirect heat exchange with the environment to form a cooled first intermediate pressure gas stream **615**. The second heat exchanger **614** may be an air cooled heat exchanger or a water cooled heat exchanger. The cooled first intermediate pressure gas stream **615** may then be compressed within a second compressor **616** to form a second intermediate pressure gas stream **617**. The second intermediate pressure gas stream **617** may flow through a third heat exchanger **618** where the second intermediate pressure gas stream **617** is cooled by indirect heat exchange with the environment to form a cooled second intermediate pressure gas stream **619**. The third heat exchanger **618** may be an air cooled heat exchanger or a water cooled heat exchanger. The cooled second

intermediate pressure gas stream **619** may then be compressed within a third compressor **620** to form a high pressure gas stream **621**. The pressure of the high pressure gas stream **621** may be greater than 1,500 psia (10,340 kPa), or more preferably greater than 3,000 psia (20,680 kPa). The high pressure gas stream **621** may flow through a fourth heat exchanger **622** where the high pressure gas stream **621** is cooled by indirectly exchanging heat with the environment to form a cooled high pressure gas stream **623**. The fourth heat exchanger **622** may be an air cooled heat exchanger or a water cooled heat exchanger. The cooled high pressure gas stream **623** may then be expanded within an expander **624** to form a first chilled pretreated gas stream **625**. The pressure of the first chilled pretreated gas stream **625** may be less than 3,000 psia (20,680 kPa), or more preferably less than 2,000 psia (13,790 kPa), and the pressure of the first chilled pretreated gas stream **625** may be less than the pressure of the cooled high pressure gas stream **623**. In an aspect, the third compressor **620** may be driven solely by the shaft power produced by the expander **624**, as illustrated by line **624a**. The first chilled pretreated gas stream **625** may be separated into a refrigerant stream **626** and a non-refrigerant stream **627**. The refrigerant stream **626** may flow through the first heat exchanger **605** where the refrigerant stream **626** is partially warmed by indirectly exchanging heat with the column overhead stream **603** to form a warmed refrigerant stream **628** therefrom. The warmed refrigerant stream **628** may mix with the non-refrigerant stream **627** to form a second chilled pretreated gas stream **629**, which may then be liquefied by an SMR liquefaction process as previously explained. As with pretreatment apparatus **200**, the refrigerant stream **626** may be used to cool any process stream associated or not associated with the HPCE module **600**.

[0065] **Figure 7** is an illustration of an HPCE module **700** with an integrated scrub column and combined with a feed gas expander-based LNG liquefaction process according to disclosed aspects. A natural gas stream **701**, which has been pretreated to remove sour gases and water to make the gas suitable for cryogenic treatment, is fed into a separation device, such as a scrub column **702**, where the treated natural gas stream **701** is separated into a column overhead stream **703** and a column bottom stream **704**. The column overhead stream **703** may flow through a first heat exchanger **705** where the column overhead stream **703** is partially condensed to form a two-phase stream **706**. The two-phase stream **706** may be directed to another separation device, such as a separator **707**, to form a cold pretreated gas stream **708** and a liquid stream **709**. The cold pretreated gas stream **708** may flow through the first heat exchanger **705** where the cold pretreated gas stream **708** is warmed by indirect heat exchange with the column overhead stream **703** to form a pretreated natural gas stream **710** therefrom. The liquid stream **709** may be

pressurized within a pump **711** and then directed to the scrub column **702** as a column reflux. The pretreated natural gas stream **710** is directed to a first compressor **713** and compressed therein to form an intermediate pressure gas stream **714**. The intermediate pressure gas stream **714** may flow through a second heat exchanger **715** where the intermediate pressure gas stream **714** is cooled by indirect heat exchange with the environment to form a cooled intermediate pressure gas stream **716**. The second heat exchanger **715** may be an air cooled heat exchanger or a water cooled heat exchanger. The cooled intermediate pressure gas stream **716** may then be compressed within a second compressor **717** to form a high pressure gas stream **718**. The pressure of the high pressure gas stream **718** may be greater than 1,500 psia (10,340 kPa), or more preferably greater than 3,000 psia (20,680 kPa). The high pressure gas stream **718** may flow through a third heat exchanger **719** where the high pressure gas stream **718** is cooled by indirect heat exchange with the environment to form a cooled high pressure gas stream **720**. The third heat exchanger **719** may be an air cooled heat exchanger or a water cooled heat exchanger. The cooled high pressure gas stream **720** may then be expanded within an expander **721** to form a first chilled pretreated gas stream **722**. The pressure of the first chilled pretreated gas stream **722** is less than 3,000 psia (20,680 kPa), or more preferably less than 2,000 psia (13,790 kPa), and where the pressure of the first chilled pretreated gas stream **722** is less than the pressure of the cooled high pressure gas stream **720**. In an aspect, the second compressor **717** may be driven solely by the shaft power produced by the expander **721**, as represented by the dashed line **723**. The first chilled pretreated gas stream **722** may be separated into a refrigerant stream **724** and a non-refrigerant stream **725**. The refrigerant stream **724** may flow through the first heat exchanger **705** where the refrigerant stream **724** is partially warmed by indirect heat exchange with the column overhead stream **703** to form a warmed refrigerant stream **726** therefrom. The warmed refrigerant stream **726** may mix with the non-refrigerant stream **725** to form a second chilled pretreated gas stream **727**. As with pretreatment apparatus **200** and HPCE module **600**, the refrigerant stream **724** may be used to cool any process stream associated or not associated with the HPCE module **700**.

[0066] As illustrated in **Figure 7**, the second chilled pretreated gas stream **727** is directed to a feed gas expander-based LNG liquefaction process **730**. The feed gas expander-based process **730** includes a primary cooling loop **732**, which is a closed expander-based refrigeration loop that may be charged with components from the feed gas stream. The liquefaction system also includes a subcooling loop **734**, which is also a closed expander-based refrigeration loop preferably charged with nitrogen as the sub-cooling refrigerant. Within the primary cooling loop

732, an expanded, cooled refrigerant stream 736 is directed to a first heat exchanger zone 738 where it exchanges heat with the second chilled pretreated gas stream 727 to form a first warm refrigerant stream 740. The first warm refrigerant 740 is directed to a second heat exchanger zone 742 where it exchanges heat with a compressed, cooled refrigerant stream 744 to additionally cool the compressed, cooled refrigerant stream 744 and form a second warm refrigerant stream 746 and a compressed, additionally cooled refrigerant stream 748. The second heat exchanger zone 742 may comprise one or more heat exchangers where the one or more heat exchangers may be of a printed circuit heat exchanger type, a shell and tube heat exchanger type, or a combination thereof. The heat exchanger types within the second heat exchanger zone 742 may have a design pressure of greater than 1,500 psia, or more preferably, a design pressure of greater than 2,000 psia, or more preferably, a design pressure of greater than 3,000 psia.

[0067] The second warm refrigerant stream 746 is compressed in one or more compression units 750, 752 to a pressure greater than 1,500 psia, or more preferably, to a pressure of approximately 3,000 psia, to thereby form a compressed refrigerant stream 754. The compressed refrigerant stream 754 is then cooled against an ambient cooling medium (air or water) in a cooler 756 to produce the compressed, cooled refrigerant stream 744. The compressed, additionally cooled refrigerant stream 748 is near isentropically expanded in an expander 758 to produce the expanded, cooled refrigerant stream 736. The expander 758 may be a work expansion device, such as a gas expander, which produces work that may be extracted and used for compression.

[0068] The first heat exchanger zone 738 may include a plurality of heat exchanger devices, and in the aspects shown in Figure 7, the first heat exchanger zone includes a main heat exchanger 760 and a sub-cooling heat exchanger 762. These heat exchangers may be of a brazed aluminum heat exchanger type, a plate fin heat exchanger type, a spiral wound heat exchanger type, or a combination thereof.

[0069] Within the sub-cooling loop 734, an expanded sub-cooling refrigerant stream 764 (preferably comprising nitrogen) is discharged from an expander 766 and drawn through the sub-cooling heat exchanger 762 and the main heat exchanger 760. The expanded sub-cooling refrigerant stream 764 is then sent to a compression unit 768 where it is re-compressed to a higher pressure and warmed. After exiting compression unit 768, the resulting recompressed sub-cooling refrigerant stream 770 is cooled in a cooler 772. After cooling, the recompressed sub-cooling refrigerant stream 770 is passed through the main heat exchanger 760 where it is further cooled by indirect heat exchange with the expanded, cooled refrigerant stream 736 and

the expanded sub-cooling refrigerant stream **764**. After exiting the first heat exchanger area **738**, the re-compressed and cooled sub-cooling refrigerant stream is expanded through the expander **766** to provide the expanded sub-cooling refrigerant stream **764** that is re-cycled through the first heat exchanger zone as described herein. In this manner, the second chilled pretreated gas stream **727** is further cooled, liquefied and sub-cooled in the first heat exchanger zone **738** to produce a sub-cooled gas stream **774**. The sub-cooled gas stream **774** may be expanded to a lower pressure to produce the LNG stream (not shown).

[0070] **Figure 8** illustrates a method **800** of producing LNG according to disclosed aspects. At block **802** heavy hydrocarbons are removed from the natural gas stream to thereby generate a separated natural gas stream. At block **804** the separated natural gas stream is partially condensed in a first heat exchanger to thereby generate a partially condensed natural gas stream. At block **806** liquids are separated from the partially condensed natural gas stream to thereby generate a pretreated natural gas stream. At block **808** the pretreated natural gas stream is compressed in at least two serially arranged compressors to a pressure of at least 1,500 psia to form a compressed natural gas stream. At block **810** the compressed natural gas stream is cooled to form a cooled compressed natural gas stream. At block **812** the cooled natural gas stream is expanded to a pressure that is less than 2,000 psia and no greater than the pressure to which the at least two serially arranged compressors compress the pretreated natural gas stream, to thereby form a chilled natural gas stream. At block **814** the chilled natural gas stream is separated into a refrigerant stream and a non-refrigerant stream. At block **816** the refrigerant stream is warmed through heat exchange with one or more process streams comprising the natural gas stream, the separated natural gas stream, the partially condensed natural gas stream, and the pretreated natural gas stream, thereby generating a warmed refrigerant stream. At block **818** the warmed refrigerant stream and the non-refrigerant stream are liquefied.

[0071] **Figure 9** illustrates a method **900** of producing LNG according to disclosed aspects. At block **902** the natural gas stream is pretreated to generate a pretreated natural gas stream. At block **904** the pretreated natural gas stream is compressed in at least two serially arranged compressors to a pressure of at least 1,500 psia. At block **906** the compressed natural gas stream is cooled. At block **908** the cooled compressed natural gas stream is expanded in at least one work producing natural gas expander to a pressure that is less than 2,000 psia and no greater than the pressure to which the at least two serially arranged compressors compress the pretreated natural gas stream, to thereby form a chilled natural gas stream. At block **910** the chilled natural gas stream is separated into a refrigerant stream and a non-refrigerant stream. At block **912** the

refrigerant stream is warmed in a heat exchanger through heat exchange with one or more process streams associated with pretreating the natural gas stream, thereby generating a warmed refrigerant stream. At block **914** the warmed refrigerant stream and the non-refrigerant stream are liquefied.

5 **[0072]** **Figure 11** depicts a pretreatment apparatus **1100** for pretreating and pre-cooling a natural gas stream **1102**, followed by a high pressure compression and expansion (HPCE) process module **1150**, according to another aspect of the disclosure. A side stream **1104** of the natural gas stream **1102** may be directed to a first heat exchanger **1106** to be cooled therein and form a cooled natural gas stream **1108**. The cooled natural gas stream **1108** is combined with the
10 natural gas stream **1102** to produce a combined natural gas stream **1110**. The side stream may comprise 1% to 100%, or 10% to 90%, or 25% to 75%, or 40% to 60% of the natural gas stream **1102**, depending on the temperature of the natural gas stream **1102** and the desired input temperature of the combined natural gas stream **1110** into a scrub column **1112**, into which the combined natural gas stream is directed. Inside the scrub column **1112**, the combined natural gas
15 stream **1110** is separated into a column overhead stream **1114** (which may be called a separated natural gas stream) and a column bottom stream **1116**. The column bottom stream **1116** is directed to a stabilizer **1118**. The stabilizer **1118** removes light hydrocarbons from the column bottom stream **1116**, and is thereby separated into a stabilizer overhead stream **1120** and a stabilized hydrocarbons liquid stream **1122**. The stabilized hydrocarbons liquid stream **1122** is
20 stable at normal storage conditions and is salable as stabilized condensate. The stabilizer overhead stream **1120** is cooled in a reflux cooler **1124** and directed to a reflux separator **1126**, where it is separated into a reflux liquid stream **1128** and a gas product stream **1130**. The gas product stream **1130** may be used as a fuel gas or liquefied using an end flash gas (not shown) in a liquefaction unit. Alternatively, part or all of the gas product stream **1130** may be compressed
25 and then combined, using line **1131**, with a pretreated natural gas stream **1140**, which is further described herein. The reflux liquid stream **1128** may be pumped by pump **1132** to be returned to the stabilizer **1118**, where it functions to wash down any heavy hydrocarbons from upflowing gas in the stabilizer. A stripping gas stream **1134** for the scrub column may be sourced from the natural gas stream **1102**; alternatively, a reboiler (not shown) may be used to provide the
30 stripping gas for the scrub column.

[0073] The column overhead stream **1114** flows through first heat exchanger **1106**, thereby forming a pretreated natural gas stream **1140**. Prior to flowing through the first heat exchanger **1106**, the pressure and temperature of the column overhead stream **1114** may be reduced using

a pressure-reducing device such as a Joule-Thomson valve **1142**. The pretreated natural gas stream **1140** is sent to a compression and cooling unit, which in an aspect may comprise a high pressure compression and expansion (HPCE) process module **1150**. The HPCE process module **1150** may comprise a first compressor **1152** which compresses the pretreated natural gas stream **1140** to form an intermediate pressure gas stream **1154**. The intermediate pressure gas stream **1154** may flow through a second heat exchanger (not shown) where the intermediate pressure gas stream **1154** is cooled by indirectly exchanging heat with an ambient environment. The second heat exchanger may be an air cooled heat exchanger or a water cooled heat exchanger. The intermediate pressure gas stream **1154** may then be compressed within a second compressor **1156** to form a high pressure gas stream **1158**. The pressure of the high pressure gas stream **1158** may be greater than 1,500 psia (10,340 kPa), or more preferably greater than 3,000 psia (20,680 kPa). The high pressure gas stream **1158** may flow through a third heat exchanger **1160** where the high pressure gas stream **1158** is cooled by indirectly exchanging heat with an ambient environment, thereby forming a cooled high pressure gas stream **1162**. The third heat exchanger **1160** may be an air cooled heat exchanger or a water cooled heat exchanger. The cooled high pressure gas stream **1162** may then be expanded within an expander **1164** to form a chilled pretreated gas stream **1166**. Chilled pretreated gas stream **1166** may also be referred to herein as a cooled pretreated gas stream. The pressure of the chilled pretreated gas stream **1166** may be less than 3,000 psia (20,680 kPa), or more preferably less than 2,000 psia (13,790 kPa), and the pressure of the chilled pretreated gas stream **1166** is less than the pressure of the cooled high pressure gas stream **1162**. In a preferred aspect, the second compressor **1156** may be driven solely by shaft power produced by the expander **1164**. In other disclosed aspects, including those aspects in which the HPCE process module **1150** includes only one compressor, the expander **1164** may be connected to a generator (not shown) to generate power.

[0074] A portion of the chilled pretreated gas stream is directed to the first heat exchanger **1106** as a recycle stream **1168**, where it and side stream **1104** are cooled by column overhead stream **1114** and/or a gaseous separator drum overhead stream **1176** as described below. The resulting cooled recycle stream **1170** passes through a pressure and temperature reducing device, such as a Joule-Thomson valve **1172**, and is directed into a separator drum **1174**. The separator drum separates the cooled recycle stream **1170** into the gaseous separator drum overhead stream **1176** and a scrub column reflux stream **1178**. Gaseous separator drum overhead stream **1176** may be combined with the column overhead stream **1114** (i.e., upstream of the first heat exchanger). Alternatively, the gaseous separator drum overhead stream **1176** may be combined

with the pretreated natural gas stream **1140** (i.e., downstream of the first heat exchanger), such that the gaseous separator drum overhead stream passes through the first heat exchanger as a separate stream from the column overhead stream. This alternative scenario may provide more flexibility in matching cooling curves within the first heat exchanger, while passing the combined two streams through the first heat exchanger reduces complexity of the system. The scrub column reflux stream **1178** is directed to a top portion of the scrub column **1112**, where it provides sufficient cooling to liquefy and separate heavy hydrocarbons within the scrub column. The remainder of the chilled pretreated gas stream **1166** is directed to further processing, which in a preferred aspect is a natural gas liquefaction module **1180**. The liquefaction module **1180** may employ any type of liquefaction technology, such as single mixed refrigerant (SMR), dual mixed refrigerant (DMR), expander-based technologies using nitrogen and/or methane, or other liquefaction techniques. Such liquefaction techniques are considered to be within the scope of the disclosed aspects.

[0075] **Figure 12** depicts a pretreatment apparatus **1200** for pretreating and pre-cooling a natural gas stream **1202** according to another aspect of the disclosure. A valve **1203** (or another pressure-reducing device such as an expander) reduces the temperature and pressure of the natural gas stream, which is directed to a first heat exchanger **1206** to be cooled therein, thereby forming a cooled natural gas stream **1208**. The cooled natural gas stream **1208** is directed into a scrub column **1212**. Inside the scrub column **1212**, the cooled natural gas stream **1208** is separated into a column overhead stream **1214** (which may be called a separated natural gas stream) and a column bottom stream **1216**. The column bottom stream **1216** is directed to a stabilizer **1218**, which removes light hydrocarbons from the column bottom stream **1216**, and is thereby separated into a stabilizer overhead stream **1220** and a stabilized hydrocarbons liquid stream **1222**. The stabilized hydrocarbons liquid stream **1222** is stable at normal storage conditions and is salable as stabilized condensate. The stabilizer overhead stream **1220** is cooled in a reflux cooler **1224** and directed to a reflux separator **1226**, where it is separated into a reflux liquid stream **1228** and a gas product stream **1230**. The gas product stream **1230** may be used as a fuel gas or liquefied using an end flash gas (not shown) in a liquefaction unit. Alternatively, part or all of the gas product stream **1230** may be compressed in a gas product compressor **1231a** and then combined, using line **1231**, with a pretreated natural gas stream **1240**, which is further described herein. The reflux liquid stream **1228** may be pumped by pump **1232** to be returned to the stabilizer **1218**, where it functions to wash down any heavy hydrocarbons from upflowing gas in the stabilizer. A stripping gas stream **1234** for the scrub column may be sourced from the

natural gas stream **1202**; alternatively, a reboiler (not shown) may be used to provide the stripping gas for the scrub column.

[0076] The column overhead stream **1214** flows through first heat exchanger **1206**, thereby forming a pretreated natural gas stream **1240**. The pretreated natural gas stream **1240** is sent to a feed compressor **1252** which compresses the pretreated natural gas stream **1240** to form an intermediate pressure gas stream **1254**. The intermediate pressure gas stream **1254** may flow through a second heat exchanger **1255** where the intermediate pressure gas stream **1254** is cooled by indirectly exchanging heat with an ambient environment, thereby forming a chilled or cooled pretreated gas stream **1266**. The second heat exchanger may be an air cooled heat exchanger or a water cooled heat exchanger. The pressure of the cooled pretreated gas stream **1266** may be less than 3,000 psia (20,680 kPa), or more preferably less than 2,000 psia (13,790 kPa).

[0077] A portion of the cooled pretreated gas stream **1266** is directed to the first heat exchanger **1206** as a recycle stream **1268**, where it and the natural gas stream are cooled by the column overhead stream **1214** and/or a gaseous separator drum overhead stream **1276** as described below. The resulting cooled recycle stream **1270** passes through a pressure and temperature reducing device, such as a Joule-Thomson valve **1272**, and is directed into a separator drum **1274**. The separator drum separates the cooled recycle stream **1270** into the gaseous separator drum overhead stream **1276** and a scrub column reflux stream **1278**. Gaseous separator drum overhead stream **1276** may be combined with the column overhead stream **1214** (i.e., upstream of the first heat exchanger). Alternatively, as depicted in **Figure 12**, the gaseous separator drum overhead stream **1276** may be combined with the pretreated natural gas stream **1240** downstream of the first heat exchanger such that the gaseous separator drum overhead stream passes through the first heat exchanger as a separate stream from the column overhead stream. This alternative scenario may provide more flexibility in matching cooling curves within the first heat exchanger, while passing the combined two streams through the first heat exchanger reduces complexity of the system. The scrub column reflux stream **1278** is directed to a top portion of the scrub column **1212**, where it provides sufficient cooling to liquefy and separate heavy hydrocarbons within the scrub column. The remainder of the cooled pretreated gas stream **1266** is directed to further processing, which in a preferred aspect is a natural gas liquefaction module **1280**. The liquefaction module **1280** may employ any type of liquefaction technology, such as single mixed refrigerant (SMR), dual mixed refrigerant (DMR), expander-based technologies using nitrogen and/or methane, or other liquefaction techniques. Such liquefaction techniques are considered to be within the scope of the disclosed aspects.

[0078] The aspects disclosed in **Figures 11-12** provide several advantages over known gas pretreating or conditioning processes. For example, the gaseous separator drum overhead stream **1176/1276** and the column overhead stream **1114/1214** have acceptably low levels of heavy hydrocarbons, and the scrub column reflux stream **1178/1278** provides sufficient cooling for heavy hydrocarbon separation in the scrub column **1112/1212**. As a result, enhanced recovery of heavy hydrocarbons is achieved when compared with known gas pretreatment technologies. Additionally, the energy required for gas pretreatment is reduced, as is the overall cost of gas pretreatment.

[0079] An advantage of the gas pretreatment process of the disclosed aspects is that it is more applicable to a wide range of feed gas compositions.

[0080] Another advantage is that because of the enhanced heavy hydrocarbons recovery from the stabilizer **1118/1218**, the condensate stream at **1122/1222** is greater. This enables a processor to take advantage of favorable price or demand conditions for condensate sale. Therefore, the disclosed aspects provide a flexible approach to gas processing to be responsive to changes in commodity price and demand.

[0081] Additionally, the aspects disclosed herein can be used in any LNG liquefaction location, they have especial utility in circumstances where space is at a premium for LNG liquefaction, such as offshore liquefaction, onshore remote facilities, and the like.

[0082] **Figure 13** is a flowchart showing a method **1300** of producing liquefied natural gas (LNG) from a natural gas stream according to disclosed aspects. At block **1302** heavy hydrocarbons are removed from the natural gas stream in a first separator to thereby generate a separated natural gas stream and a separator bottom stream. At block **1304** the separated natural gas stream is used as a coolant in a heat exchanger to thereby generate a pretreated natural gas stream. At block **1306** the pretreated natural gas stream is compressed and cooled to form a chilled pretreated natural gas stream. At block **1308** a portion of the chilled pretreated gas stream forms a recycle stream to exchange heat with the separated natural gas stream in the heat exchanger, thereby generating a cooled recycle stream. At block **1310** a temperature and a pressure of the cooled recycle stream are reduced. At block **1312** the cooled recycle stream is separated into a gaseous separator overhead stream and a reflux stream. At block **1314** the reflux stream is directed to a top portion of the first separator. At block **1316** the chilled pretreated gas stream is liquefied to form LNG.

[0083] While the foregoing is directed to aspects of the present disclosure, other and further

aspects of the disclosure may be devised without departing from the basic scope thereof, and the scope thereof is determined by the claims that follow.