(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
11 March 2004 (11.03.2004)

PCT

(10) International Publication Number
WO 2004/020785 A1

(51) International Patent Classification[7]: E21B 34/04, 33/035, H02K 7/06, F16K 31/04

(21) International Application Number:
PCT/EP2003/009696

(22) International Filing Date:
1 September 2003 (01.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
202 13 364.8 30 August 2002 (30.08.2002) DE

(71) Applicant *(for all designated States except US)*: **COOPER CAMERON CORPORATION** [US/US]; 1333 West Loop South, Suite 1700, Houston, TX 77027-9109 (US).

(72) Inventor; and

(75) Inventor/Applicant *(for US only)*: **BIESTER, Klaus** [DE/DE]; Am Maschsee 2, 29342 Wienhausen (DE).

(74) Agent: **HILGERS, Hans**; Grünecker, Kinkeldey, Stockmair & Schwanhäusser, Anwaltssozietät, Maximilianstrasse 58, 80538 München (DE).


(81) Designated States *(national)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States *(regional)*: ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— *with international search report*
— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

[Continued on next page]

(54) Title: DRIVE DEVICE



(57) Abstract: A drive device (1) serves for adjusting an operating element (2) for a valve, a throttle, a blow-out preventor or the like, in particular in the field of gas and oil production, the operating element (2) being actively connected to at least one driving motor (4) via a drive train (3), and at least one transmission changing unit (5) being arranged in the drive train (3) for converting a revolution of the driving motor (4) into a revolution of the operating element (2) and/or a revolution/linear motion converter being arranged for converting the revolution of the driving motor (4) into a linear motion of the operating element (2). In order to also have a very compact design in case of a high possible performance and to simultaneously permit a good thermal distribution within the drive device, so that separate cooling devices for carrying off the generated lost heat are superfluous, the drive train (3) comprises at least one essentially disk- or wheel-shaped revolution introducing device which is actively connected with at least two drive shafts driven by separate driving motors.

WO 2004/020785 A1

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.