

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
29 January 2009 (29.01.2009)

PCT

(10) International Publication Number
WO 2009/015362 A1

(51) International Patent Classification:
H04Q 7/38 (2006.01)

(21) International Application Number:
PCT/US2008/071244

(22) International Filing Date: 25 July 2008 (25.07.2008)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
11/828,333 25 July 2007 (25.07.2007) US

(71) Applicant (for all designated States except US): **QUALCOMM INCORPORATED** [US/US]; ATTN: International IP Administration, 5775 Morehouse Drive, San Diego, California 92121-1714 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **LI, Linbo** [CN/US]; 5775 Morehouse Drive, San Diego, California 92121-1714 (US). **MANTRAVADI, Ashok** [IN/US]; 5775 Morehouse Drive, San Diego, California 92121-1714 (US). **LING,**

Fuyun [US/US]; 5775 Morehouse Drive, San Diego, California 92121-1714 (US). **KRISHNAMOORTHY, Raghuraman** [IN/US]; 5775 Morehouse Drive, San Diego, California 92121-1714 (US).

(74) Agent: **BRADEN, Stanton C.**; Attn: International Ip Administration, 5775 Morehouse Drive, San Diego, California 92121-1714 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: CHANNEL HANDOFF METHODS IN WIRELESS BROADCAST SYSTEMS




FIG. 7

(57) Abstract: Systems and methodologies are described that facilitate monitoring RF channels in a wireless communication environment to determine whether one or more channels comprise a forward-link-only (FLO) signal. A receiver can receive a first RF channel with a FLO signal and can monitor other RF channels for FLO signals. Upon a determination that a monitored RF channel comprises a FLO signal, the receiver can switch between the first RF channel and the monitored RF channel, employing information on current MLC decoding status, to facilitate providing seamless reception of the FLO signal, which can be superframe synchronized between RF channels. FLO signal detection can be performed using one or more of a wide-area identification channel energy detection protocol and a wide-area overhead information symbol decoding error detection protocol.



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))*

Published:

— *with international search report*

Declarations under Rule 4.17:

— *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*