APPLICATION FOR PATENT

Title: Downhole Barrier Valve

Inventor: Clifford H. Beall; Michael J. May; James T. Sloan; Andrew Haynes and Thad D. Andrews

RELATED APPLICATIONS

[0001] This application is a continuation in part of US Application Serial No. 11/595,596 filed on November 9, 2006 and having the title Downhole Lubricator Valve.

FIELD OF THE INVENTION

[0002] The field of the invention relates to downhole barrier valves such as, among other applications, a valve for forming a downhole lubricator that allow a string to be made up in a live well by isolation of a lower portion of it and more particularly to features regarding such valves relating to locking them, assembling them and component fabrication techniques.

BACKGROUND OF THE INVENTION

[0003] Lubricator valves are valves used downhole to allow long assemblies to be put together in the well above the closed lubricator valve with well pressure further below the closed lubricator valve. These valves are frequently used in tandem with sub-surface safety valves to have redundancy of closures against well pressures below. Valves are also used downhole for other isolation purposes.

[0004] Lubricator assemblies are used at the surface of a well and comprise a compartment above the wellhead through which a bottom hole assembly is put together with the bottom valve closing off well pressure. These surface lubricators have limited lengths determined by the scale of the available rig equipment. Downhole lubricators simply get around length limitations of surface lubricators by using a lubricator valve downhole to allow as much as thousands of feet of length in the wellbore to assemble a bottom hole assembly.

[0005] In the past ball valves have been used as lubricator valves. They generally featured a pair of control lines to opposed sides of a piston whose movement back and forth registered with a ball to rotate it 90 between an open and a closed position. Collets could be used to hold the ball in both positions and would release in response to control pressure in one of the control lines. An example of such a design can be seen in USP 4,368,871; 4,197,879 and 4,130,166. In these patents, the ball turns on its own axis on trunnions. Other designs translate the ball while rotating it 90 degrees between and open and a closed position. One example of this is the 15K Enhanced Landing String Assembly offered by the Expro Group that includes such a lubricator valve. Other designs combine rotation and translation of the ball with a separate locking sleeve that is hydraulically driven to lock the ball turning and shifting sleeve in a ball closed position as shown in USP 4,522,370. Some valves are of a tubing retrievable style such as Halliburton's PES® LV4 Lubricator Valve. Lock open sleeves that go through a ball have been proposed in USP 4,449,587. Other designs, such as USP 6,109,352 used in subsea trees have a rack and pinion drive for a ball and use a remotely operated vehicle (ROV) to power the valve between open and closed positions claiming that either end positioned is a locked position but going on to state that the same ROV simply reverses direction and the valve can reverse direction.

[0006] What is lacking and addressed by the present invention is a more elegant solution to a downhole ball type lubricator valve. One of the features is the ability to translate the ball for the purpose of locking open a ball that normally rotates between open and closed on its own axis. Another feature is a method of manufacturing parts that must be longitudinally split so that they retain the original bore dimension despite the wall removal occasioned by longitudinally splitting the part. Yet another feature is the ability to assemble components to a given overall dimension so as to accurately set preload on biased seats that engage the ball.

[0007] In one embodiment, the annular piston that actuates the valve is replaced with at least one rod piston and the space made available with this change allows the addition of a seal to prevent leakage under high differential pressure conditions from the uphole to the downhole direction.

[0008] These and other features of the present invention will be more readily apparent to those skilled in the art from a review of the preferred embodiment and associated drawings that are described below while recognizing that the full scope of the invention is determined by the claims.

SUMMARY OF THE INVENTION

[0009] A ball type downhole barrier valve capable of bidirectional sealing features a ball rotating on its axis to open or close with control line pressure to an actuating rod piston assembly. The ball is also shiftable to a locked open position. A cage surrounds the ball and retains opposed seats to it. The cage is made from one piece and tangential holes are drilled and tapped before the piece is longitudinally split with a wire EDM cutting technique. Fasteners to rejoin the cut halves properly space them to the original one piece internal dimension. Auxiliary tools allow determination of spacing of internal components so that a desired spring preload on the seats against the ball can be achieved. Seals on the sleeves that form ball seats help prevent leakage due to ball distortion at high differential pressures when the valve is closed.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] FIG. 1 is a section view of the entire lubricator valve;

[0011] FIG. 2 is a larger view of the top end of the valve of FIG. 1;

[0012] FIG. 3 is a larger view of the middle of the valve from FIG. 1showing the ball open;

[0013] FIG. 4 is an alternate view to FIG. 3 showing the ball closed;

[0014] FIG. 5 is a larger view of the lower end of the valve of FIG. 1;

[0015] FIG. 6 is a perspective view of the section views shown in FIGS. 4 and 5;

[0016] FIG. 7 shows the top end of the valve in FIG. 1 during assembly to get proper spacing of internal components;

[0017] FIG. 8 shows the lower end of the valve in FIG. 1 during assembly to get proper spacing of internal components;

[0018] FIG. 9 is a perspective of the cage that surrounds the ball and is longitudinally split.

[0019] FIG. 10 is a section view of the embodiment showing the use of rod pistons and an additional lower seal to deal with issues of ball distortion under high differential pressures;

[0020] FIG. 11 is an enlarged view of an upper seal around a sleeve that support the upper ball seat;

[0021] FIG. 12 is a force diagram of the FIG. 1 design showing a condition of a differential force in an uphole direction;

[0022] FIG. 13 is the view of FIG. 12 with a differential force in a downhole direction and leakage from ball distortion under high differential pressures;

[0023] FIG. 14 shows a differential in the uphole direction using a seal on the sleeve above the ball;

[0024] FIG. 15 is the view of FIG. 14 with a differential in a downhole direction showing how leakage is reduced or eliminated under high differentials in a downhole direction and showing an additional seal on the OD of the lower sleeve to assist with sealing.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0025] FIG. 1 illustrates the layout of the main components to show their position relative to each other with the ball **10** in the center and in the closed position. Sleeve **12** is above ball **10** and sleeve **14** is below ball **10**. These sleeves respectively form seats **16** and **18** that are held against ball **10** by a cage **20**. Cage **20** is shown in perspective in FIG. 9. A slide **22** extends through cage **20** and registers with ball **10** to rotate it between the open and closed position on trunnions **24**. A piston **26** is responsive to control line

pressure to reciprocate the slide **22** to operate ball **10**. A lock open assembly **28** is disposed near the top of the tool while the preload adjustment mechanism **30** is located near the opposite end. Using this basic locating of the major components of the valve, the other FIGS. will now be used to bring out additional details and explain the basic operation.

[0026] FIG. 6 can be used to appreciate how the ball **10** is rotated 90 degrees between the closed position shown in FIG. 6 and the open position shown in section in FIG. 3. Piston **26** operates like many pistons known in the art and used in downhole valves. A pair of control lines (not shown) are run from the surface to opposing piston face areas on piston **26** to urge it to move in opposed directions. The piston **26** is secured to the slide **22** for tandem movement. Slide **22** has an upper ring **32** and a lower ring **34** connected by arms **36**, one of which is visible in FIG. 6. Looking at FIG. 9 it can be seen that the cage has longitudinal slots **38** and **40** that accept the arms **36** of slide **22**. Referring to FIGS. 1 and 6 it can be seen that slide **22** is at the end of its uphole stroke as it has contacted the mandrel **42**. Ball **10** has opposed angled exterior slots **44** one of which is partially in view in FIG. 6. The slots **44** are parallel to each other on opposed flats **46** better seen in FIG. 1. Flats **46** on ball **10** abut arms **48** and **50** of cage **20** as best seen in FIGS. 6 and 9. Holes **52** and **54** accept trunnions **24** that extend into ball **10** to allow it to rotate on its own axis. Cage **22** does not move but when slide **22** is moved by piston **26** the result is rotation of ball **10** on its own axis. This happens because arms **36** have inwardly facing pins (not shown) that register with slots **44** in ball **10** off center from trunnions **24** to induce rotation of ball **10**.

[0027] To better see this movement, FIGS. 3 and 4 need to be compared. FIG. 4 shows the ball **10** in a closed position and upper ring **32** close to mandrel **42** but not in contact. This is because, optionally, a snap ring **56** registers with slot **58** on sleeve **12** to hold the ball **10** in a closed position until enough pressure is exerted on piston **26** to pop the snap ring **56** out of groove **58** until it registers with groove **60** to define the open position of FIG. 3. Again, in FIG. 4 during normal opening and closing of the ball **10**, the only moving part except ball **10** shown in that FIG. is slide **22** with ring **56**. FIG. 3 shows the fully open position of ball **10** with ring **56** registering with groove **60**. Slide **22** may

optionally contact cage **20** at this time. FIG. 3 also shows piston **26** attached to slide **22** with an anti-rotation pin **62**. One of the control line connections **65** to operate piston **26** is also shown in FIG. 3. FIG 3 also shows that sleeves **12** and **14** respectively form flanges **64** and **66** and how the cage **20** retains those flanges together against ball **10**. Seals **16** and **18** respectively are disposed in flanges **64** and **66** for circumferential sealing contact with ball **10** as it rotates between the open and the closed positions of FIGS. 3 and 4.

[0028] Looking now at FIG. 5, the lower end of the sleeve **14** can be seen as well as another control line connection **68** that is used to urge piston **26** in an opposite direction from pressure applied to connection **65** shown in FIG. 3. A bottom sub **70** has a shoulder **72** on which a spring **74** is supported. Spring **74** pushes on ring **76** that is attached to sleeve **14** with a thread **78**. A screw **80** locks the position of ring **76** after that position is initially determined in a procedure that will be explained below. In essence, spring **74** is a preload spring on an assembly that begins with ring **76** and extends to the upper end of the valve shown in FIG. 2.

[0029] Referring to FIG. 2 a spring **114** is used to push on ring **86** and through the other parts described before downwardly on sleeve **12** to insure engagement of seat 16 with respect to the ball when pressure above the ball 10 is applied. Conversely, sleeve 14 is biased uphole by spring **74** to ensure a similar engagement of the ball and seat when pressure below the ball is applied. As those skilled in the art will appreciate the assembly of parts from shoulder **84** at the upper end to shoulder **118** at the lower end each have their own tolerance and the adjustment available for the position of ring **76** on thread **78** is fairly minimal. As a result, the total dimension of the parts between shoulders **84** and **118** can be determined and the position of ring **76** necessary to give the right preload to the assembled parts also determined before final assembly of top sub **82** and bottom sub **70**. FIGS. 7 and 8 show this technique.

[0030] Instead of assembling top sub **82** and spring **114** to mandrel **42** an upper gauge **122** is assembled to mandrel **42**. When fully threaded on, a shoulder **124** hits ring **86** in nearly the exact spot that shoulder **84** from top sub **82** would normally engage it. At the same time at the lower end in FIG. 8 instead of putting on bottom sub **70**, spring **74** or

screw **80**, a lower gauge **124** is threaded on to mandrel **42**. Lower gauge **124** has a pair of arms **126** and **128** that respectively have shoulders **130** and **132** that wind up exactly where shoulder **118** would be when bottom sub **70** is screwed on. Because of the open gaps between arms **126** and **128** there is access to adjustment ring **76** and it can be moved up or down on thread **78** as long as screw **80** is not assembled. Ring **76** is turned to bottom on shoulders **130** and **132** and then the rotation is reversed to allow installation of screw 80 in recess **136** (see FIG. 5) so that ring **76** has its position fixed as close as possible to shoulder **118** when the bottom sub **70** is assembled with spring **74**. Similarly, the upper gauge **122** (FIG. 7) is first removed and replaced with top sub **82** and spring **114** (FIG. 2). When the bottom sub **70** and spring **74** get screwed on, spring **74** will have the needed preload since despite the accumulation of tolerances of all the assembled parts the actual surface of ring 76 is determined as it related to spring **74** for the desired preload.

[0031] Referring now to FIG. 9 the cage **20** is illustrated as fully assembled. Since it needs to straddle ball **10** and flanges **64** and **66** (FIG. 3) it needs to be made into two pieces. The technique for making this piece or, for that matter, other pieces that need to be made in two pieces to be assembled over yet other pieces, is to make a longitudinal cut **140**. Before doing that, all the machining shown in FIG 9 is done including bores **142** and **144** on one side and similar bores on the other side (not visible) that go though where longitudinal cut **140** will be made. Again, before the cut is made, the bores **142** and **144** are tapped. Thereafter the cut **140** is made by a wire EDM technique. This known technique removes a part of the wall away where the cut is made. Thus, after the cut halves are pushed together, their inside diameter **146** will be smaller than it was before the cut. However, the pitch of the tapped thread and the matching thread on the studs **148** and **150** when screwed in to bridge the cut **140** will, because of the thread pitch separate the halves at cut **140** just enough to compensate for the amount of wall removed during the cut so that when fully assembled the original one piece diameter **146** that was there before the cut is again present. While the wire EDM removes only a few thousandths of an inch out of the wall to make the longitudinal cut the result is still a change in the internal bore dimension. This technique of drilling and tapping before a longitudinal cut

with wire EDM allows the original bore dimension to be regained while holding the cut halves together.

[0032] Referring to FIG. 2 the lock open feature will be described. Sleeve **12** is ultimately selectively retained by top sub **82**. Shoulder **84** contains fixed ratchet ring **86** to prevent upward movement of the ratchet ring **86**. Ring **86** has an undercut **88** defining taper **90**. Ring **92** initially sits in undercut **88**. It has ratchet teeth **94** that, in the position of FIG. 2 are offset from ratchet teeth **96** on ring **86**. Ring **92** bears on retainer ring **98** which, in turn, captures split ring **100** in groove **102** of sleeve **12**. Due to urging of spring **114**, sleeve **12** is held down against ball **10** and against the uphole force on sleeve **14** from spring **74** (see FIG. 5). Locking collar **104** has one or more internal grooves **106** for engagement with a tool (not shown) that will ultimately pull the collar **104** uphole. A shear screw **108** initially secures the collar **104** to the sleeve **12**. Sleeve **12** has a groove **110** that eventually registers with tangential pins **112** extending from collar **104**. Collar **104** initially retains ring **92** in undercut **88**. In operation, the collar **104** is pulled up with a tool (not shown) to break the shear screw **108**. As the collar then moves up, tangential pins **112** ride in groove **110** until hitting the top of it at which time the collar **104** moves in tandem with sleeve **12**. In the meantime, collar **104** moves uphole from ring **92** allowing it to collapse inwardly to clear taper **90**. When pins **112** register with the top of groove **110** and the sleeve **12** is moving with collar **104**, ring **100** in groove **102** of sleeve **12** takes with it ring **98** which, in turn now can push ring **92** beyond taper **90** so that ratchet teeth **94** move into engagement with ratchet teeth **96** on ratchet ring **86**. The uphole movement described above continues until sleeve **12** hits a travel stop. This happens in two ways depending on the position of ball **10** when sleeve **12** is being pulled up. If the ball **10** is open, as shown in FIG. 3, flange **64** pulls up cage **20** as well as slide **22** which was registered with sleeve **12** at groove **60**. The ball **10** comes up with cage **20** because they are connected at trunnions **24**. The ball **10** does not rotate because there is no relative movement between the slide **22** and the cage **20**. Motion of sleeve **12** stops when ring **32** hits mandrel **42** and that position is held locked by the ratchet teeth engagement of teeth **94** and **96**. On the other hand, if ball **10** is in the closed position of FIG. 4, the sleeve **12** will bring up the cage **20** and move it relatively to slide **22**. This happens because at the onset of movement of sleeve **12** the upper ring **32** of slide **22** is

already close to mandrel **42** and fairly quickly hits it as the sleeve **12** comes up. Further uphole movement of sleeve **12** pulls the cage **20** relative to the slide **22** which causes the pins in slide **22** to rotate ball **10** to open as they register with slots **44** in ball **10**. When the cage **20** comes against already stopped ring **32** of the slide **22** uphole motion stops and the position is again locked in by engaging teeth **94** and **96**.

[0033] Those skilled in the art will recognize that the ball type lubricator valve can be normally operated with control line pressure that moves piston **26** in opposed directions to rotate ball **10** on its own axis for 90 degrees to the open and closed positions. An optional indexing feature holds the open and closed positions when they are attained. The valve can be locked open from either the open position or the closed position by freeing the upper sleeve **12** to move and lifting it until it ratchet locks with the ball **10** in the open position while maintaining a full bore through the valve. While a ratchet lock is illustrated other locking devices such as dog through windows, collets or other equivalent devices are also contemplated. It should be noted that translation of ball **10** is only employed when attempting to lock it open. It should be noted that parts can be reconfigured to alternatively allow the ball **10** to be locked closed as an alternative.

[0034] Yet another feature of the barrier valve is the preloading of the internal components and the ability to gauge the dimension of the internal components before mounting the top and bottom subs with the spring or springs that provide the preload so the proper amount of preload can be applied. Yet another feature is a way of making longitudinally split parts so that they retain their original internal dimension despite removal of a part of the wall for a cutting operation using the drill and tap technique before longitudinal cutting by wire EDM and then regaining near the original spacing in the joined halves relying on the pitch of the tapped thread and the fastener inserted in the bore and spanning the longitudinal cut. In this particular tool the cage **20** and slide **22** can be made with this technique. The technique has many other applications for longitudinally split parts with internal bores that must be maintained despite wall removal from a cutting process like wire EDM.

[0035] FIGS. 12 and 13 illustrate what happens under high differential loading conditions in the uphole and downhole directions respectively in the design discussed above and illustrated in FIGS. 1 and 4. In FIG. 12 the ball **10** is in the closed position and holding pressure from below. Upper ball seal **16** is on sleeve **12** and there is an external seal **200** to isolate the annular space **202** which is not sealed from the interior passage **204** of the ball **10** because the pivots **24** are not sealed. Pressure from downhole can come to the ball **10** through the annular space **204** as well as tube **14** since there is no outer seal on tube **14** to isolate the annular space **202**. Lower seal **18** that is below the ball **10** is mainly a dust seal as seal **16** is the seal that is intended to hold pressure differential in either direction. When the pressure differential is in an uphole direction as illustrated in FIG. 12 the pressure reaches annular space **202** because there is no exterior seal on tube **14**. The uphole directed differential pressure is stopped at seal **200** and seal **16**. The downhole pressure enters the passage **204** in the ball to uniformly load the ball **10** from its interior as illustrated by arrows **208**. This uniform loading from within the ball **10** helps the ball **10** maintain its shape and contact continues all along the seat **16** for a seal against uphole differential pressure against high differentials of over 10,000 PSI.

[0036] In a high downhole oriented differential pressure situation as shown in FIG. 13, something different happens. Here seal **200** isolates such pressure from uphole from getting to the annular space **202** so that the entire differential loading on the ball **10** is from within passage **210** as long as seal **16** is holding. However, at this time the pressure inside the ball **10** at **204** is substantially less so that the pressure in passage **210** represented by arrows **212** can distort ball **10** to an oblong shape as illustrated schematically by dashed line **214**. When that happens the seal between the ball **10** and its seat **16** no longer holds and pressure get beyond the ball **10** into the annular space **202** and beyond seat **18** that is meant only to serve as a dust seal as well as down the outside of sleeve **14** because in this embodiment it has no external seal. While the assembly in FIG. 13 has been shown to be perfectly serviceable at lower pressure differentials, testing has indicated the potential for leakage in the manner described above at differentials in the downhole direction in excess of 10, 00 PSI.

[0037] In FIG. 14 an additional seal **216** has been added. It blocks pressure from downhole from getting around tube **14** and into annular space **202**. Seal **200** is still there on the outside of tube **12**. Arrows **218** reflect the initial loading on ball **10** that until a predetermined differential pressure exists can hold the pressure in passage **206** at seal **18**. After the differential gets higher the pressure will get by seal **18** by either distorting ball **10** or displacing sleeve **14** away from ball **10**. At that time the downhole pressure will get into the annular space **202** as well as within ball **10** at **204**. This effect is demonstrated schematically by arrows **220**. At this point seal **16** holds the high uphole oriented pressure differential in the manner described before for FIG. 12. Again, even if temporary distortion of ball **10** occurs to let pressure into annular space **202** the deformation is elastic rather than plastic and the ultimate job of sealing against uphole oriented differential pressures falls to seal **16**. Once the internal space **204** of the ball **10** is equalized with the pressure from downhole, regardless of the mechanism by which that occurs, the ball **10** is uniformly loaded against seat **16** and as a result even with high uphole differential pressures, there is no leakage uphole past seal **16**.

[0038] FIG. 15 is now contrasted with the same situation as shown in FIG. 13. Only this time there is a seal **216** outside of tube **14** and seal **200** is still there above ball **10** and outside sleeve **12** although it is not shown in FIG. 15. A buildup of downhole oriented differential pressure is shown by arrows **220**. This differential pressure force at a predetermined level gets past seal **16** temporarily and into annular space **202** and into the ball **10** in space **204**. Now the annular space is sealed with seal **216** so pressure in space **204** represented by arrows **222** equalizes with the pressure on ball **10** represented by arrows **220** so that ball **10** is uniformly loaded on seat **18** and seat **18** holds the downhole oriented differential pressure from getting in passage **206**. In essence the performance of the assembly under a differential pressure from downhole in FIG. 14 is the same as when the differential is in the opposite direction as shown in FIG. 15. The only difference is which seal holds the differential. In both cases the ball **10** elastically deforms to equalize ball pressure through the annular space **202** and the ball goes right back to its spherical shape once equalization of pressure takes place. This is to be contrasted with the downhole oriented pressure differential situation of FIG. 13 where leakage continued as

equalization did not happen and the ball **10** distorted under the differential as indicated by lines **214** and leakage continued as long as the differential pressure on ball **10** existed.

[0039] In another aspect of the present invention, it was noticed that in very deep settings of the valve assembly shown in FIGS. 1-9 the annular piston **26** was subject to such high differential forces that its shape distorted in the annular passage that surrounded it and what resulted were wear locations on the surrounding wall that defeated the seals that surrounded annular piston **26** or in extreme cases could distort the piston shape to a sufficient extent to cause it to seize in its bore and become immovable. To counteract this effect noticed when the valve assembly depicted is in very deep applications that involve very high hydrostatic pressures on an annular piston **26**, the design was changed to use rod pistons **224** which is in pieces and is exposed to connections **68** and **64** to which a control line (not shown) is connected. Preferably the rod pistons are arrayed symmetrically about the central axis of the valve assembly so that any moment that one such rod piston created can be canceled by another rod piston disposed 180 degrees from it. Any number of rod pistons can be used although an even pairing for symmetry is preferred. The use of rod pistons eliminates the distortion issues at high differential pressures such as existed with annular piston **26**. It also makes room to add the seal **216** whose purpose was discussed above. It marks a first for downhole ball valves that are actuated with a rod piston assembly and makes the design useful for very high differential pressure installations where annular pistons can fail under differentials that can exist at differentials above 10,000 PSI. Of course the rod piston design can also be used at lower differentials instead of the annular design with good results.

[0040] While the preferred embodiment has been set forth above, those skilled in art will appreciate that the scope of the invention is significantly broader and as outlined in the claims which appear below.

We claim:

1. A downhole valve, comprising:

a housing having a passage therethrough:

a ball having a bore therethrough rotatably mounted to rotate, without translation, on its axis to align and misalign said bore with said passage; and

at least one rod piston in said housing operably connected to said ball for said rotation of it in opposed directions responsive to the direction of delivery of a differential pressure to said rod piston.

2. The valve of claim **1**, wherein:

said at least one rod piston comprises an even number of rod pistons.

3. The valve of claim **1**, wherein:

said pistons are symmetrically arrayed around said passage.

4. The valve of claim **1**, wherein:

said ball is disposed in said housing defining a surrounding annular space further defined by an upper sleeve and a lower sleeve in sealing contact with said ball;

said annular space is sealed against at least one of said sleeves.

5. The valve of claim **4**, wherein:

said annular space is sealed with a first seal against said upper sleeve.

6. The valve of claim **5**, wherein:

said upper sleeve comprises, adjacent a lower end, a seat with an upper resilient seal that engages said ball.

7. The valve of claim **6**, wherein:

said bore in said ball equalizes with pressure from downhole against said ball when said ball closes said passage as said first seal and said upper resilient seal contain pressure from downhole.

8. The valve of claim **4**, wherein:

said annular space is sealed against both sleeves.

9. The valve of claim **8**, wherein:

said annular space is sealed with a second seal against said lower sleeve.

10. The valve of claim **9**, wherein:

said lower sleeve comprises, adjacent an upper end, a seat with a lower resilient seal that engages said ball.

11. The valve of claim **10**, wherein:

said bore in said ball equalizes with pressure from uphole against said ball when said ball closes said passage as said second seal and said lower resilient seal contain pressure from uphole.

12. The valve of claim **7**, wherein:

said annular space is sealed against both sleeves.

13. The valve of claim **12**, wherein:

said annular space is sealed with a second seal against said lower sleeve.

14. The valve of claim **13**, wherein:

said lower sleeve comprises, adjacent an upper end, a seat with a lower resilient seal that engages said ball.

15. The valve of claim **14**, wherein:

said bore in said ball equalizes with pressure from uphole against said ball when said ball closes said passage as said second seal and said lower resilient seal contain pressure from uphole.