

(51) International Patent Classification:
H05B 33/10 (2006.01)(21) International Application Number:
PCT/IB2013/050037(22) International Filing Date:
3 January 2013 (03.01.2013)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

61/582,581	3 January 2012 (03.01.2012)	US
13/624,910	22 September 2012 (22.09.2012)	US
13/677,864	5 November 2012 (15.11.2012)	US

(72) Inventors: and

(71) Applicants : **ZSINKO, Andrew** [US/US]; 530 Wadsworth Road, Medina, Ohio 44256 (US). **MASTRICAN, Shawn J.** [US/US]; 15305 Sunningdale Street, Austin, Texas 78717 (US).

(74) Agent: **FORHAN, Michael A.**; 7870 Olentangy River Road, Suite 311, Columbus, OH 43235 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,


BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(54) Title: ELECTROLUMINESCENT DEVICES AND THEIR MANUFACTURE

**Fig. 1**

(57) Abstract: A process for producing a conformal electroluminescent system. An electrically conductive base backplane film layer (16) is applied upon a substrate (12). A dielectric film layer (18) is applied upon the backplane film layer (16), then a phosphor film layer (20) is applied upon the dielectric film layer (18). An electrode film layer (22) is applied upon the phosphor film layer (20) using a substantially transparent, electrically conductive material. An electrically conductive bus bar (24) may be applied upon the electrode film layer (22). Preferably, the backplane film layer (16), dielectric film layer (18), phosphor film layer (20), electrode film layer (22) and bus bar (24) are aqueous-based and are applied by spray conformal coating.