

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: H03D	A2	(11) International Publication Number: WO 95/28033 (43) International Publication Date: 19 October 1995 (19.10.95)
(21) International Application Number: PCT/IB95/00187 (22) International Filing Date: 20 March 1995 (20.03.95) (30) Priority Data: 94200986.1 12 April 1994 (12.04.94) EP (34) Countries for which the regional or international application was filed: NL et al. (71) Applicant: PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL). (71) Applicant (for SE only): PHILIPS NORDEN AB [SE/SE]; Kottbygatan 5, Kista, S-164 85 Stockholm (SE). (72) Inventors: SEMPEL, Adrianus; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL). VAN NIEUWENBURG, Johannes; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL). (74) Agent: SCHOONHEIJM, Harry, Barend; Internationaal Octrooibureau B.V., P.O. Box 220, NL-5600 AE Eindhoven (NL).		(81) Designated States: JP, KR, SG, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>Without international search report and to be republished upon receipt of that report.</i> SL 9611662-9 RTMP/copy +A3
(54) Title: RECEIVER COMPRISING A PULSE COUNT FM DEMODULATOR, AND PULSE COUNT FM DEMODULATOR		
(57) Abstract A receiver comprising, arranged in this order, an input section, an FM demodulator, to which a frequency-modulated input signal is applied, and an LF section, which FM demodulator comprises a pulse shaper and a low-pass filter, the pulse shaper comprising a series arrangement of at least a load and a capacitance, the base-emitter junction of a transistor being arranged across said capacitance, and further comprising a switching device for charging and discharging the capacitance. The pulse shaper generates a low-noise pulse in that charging of a capacitance is started upon an edge of the input signal. The capacitance voltage is measured by a single transistor and when the transistor is turned on the charging current of the capacitance is diverted via the transistor, so that the capacitance voltage is limited. The capacitance is discharged upon a second edge, after which the cycle is repeated. The output signal of the pulse shaper is a signal which varies with the current through the capacitance.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

9611662-9