

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
21 November 2002 (21.11.2002)

PCT

(10) International Publication Number
WO 02/093787 A1

(51) International Patent Classification⁷: **H04B 7/212**,
7/216, H04J 13/00

(21) International Application Number: PCT/US02/14955

(22) International Filing Date: 13 May 2002 (13.05.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/290,717 14 May 2001 (14.05.2001) US
10/029,651 21 December 2001 (21.12.2001) US

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant: **INTERDIGITAL TECHNOLOGY CORPORATION** [US/US]; 300 Delaware Avenue, Suite 527, Wilmington, DE 19801 (US).

(72) Inventors: **TERRY, Stephen, E.**; 15 Summit Avenue, Northport, NY 11768 (US). **DICK, Stephen, G.**; 61 Bobann Drive, Nesconset, NY 11767 (US). **MILLER, James, M.**; 18 Louisburg Square, Verona, NJ 07044 (US). **ZEIRA, Eldad**; 239 West Neck Road, Huntington, NY 11743 (US). **ZEIRA, Ariela**; 239 West Neck Road, Huntington, NY 11743 (US).

(74) Agents: **VOLPE, Anthony, S. et al.**; Volpe and Koenig, P.C., Suite 400, One Penn Center, 1617 John F. Kennedy Boulevard, Philadelphia, PA 19103 (US).


Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **PHYSICAL CHANNEL CONFIGURATION SIGNALING PROCEDURES**

53



(57) Abstract: A method for signaling code and time slot assignments to support a communication of a user in a wireless hybris TDMA/CDMA communication system supporting wireless RF communications, comprising: at the transmitter: 1) selecting at least one time slot; 2) selecting at least one code, and if more than one code is selected, selecting consecutive codes from the predetermined sequence (54, 56); and 3) signaling an identifier of the at least one time slot and a first and last code of the consecutive codes (58).

WO 02/093787 A1

[0001] METHOD AND APPARATUS FOR MINIMIZING THE AMOUNT OF
DATA NECESSARY TO SIGNAL CODE AND
TIMESLOT ASSIGNMENTS

[0002] BACKGROUND

[0003] The invention is generally related to wireless hybrid time division multiple access (TDMA)/code division multiple access (CDMA) communication systems. In particular, the invention relates to configuring physical channels in such systems.

[0004] Wireless communication systems are evolving from carrying primarily voice and paging information to carrying voice, paging and other data information, such as wireless Internet data. The bandwidth required for all these types of information varies greatly. Some of this data requires far more bandwidth than traditional voice and paging information.

[0005] In CDMA communication systems, multiple communications are sent in a shared spectrum. These communications are distinguished by their channelization codes. To more efficiently use the shared spectrum, hybrid TDMA/CDMA communication systems time divide the shared bandwidth into repeating frames having a specified number of timeslots. A communication is sent in such a system using one or multiple timeslots and one or multiple codes. One such system is the universal mobile telecommunication systems (UMTS) time division duplex (TDD) communication system using CDMA, which uses fifteen (15) timeslots. In TDD, a particular cell's timeslot is used only for either uplink or downlink communications.

[0006] To deal with the variety of bandwidths required for various communications, adaptive modulation and coding (AM & C) is used. In AM & C, the modulation and coding scheme for transmitting data is varied to more efficiently use the radio resources. To illustrate, the modulation used for data may be varied, such as using binary phase shift keying (BPSK), quadrature phase shift keying (QPSK), or M-ary quadrature amplitude modulation. Furthermore, the data maybe assigned a single code in a timeslot, multiple codes in a timeslot, a single code in multiple timeslots or multiple codes in multiple timeslots.

[0007] Since data transmitted to or from particular user equipment (UE) may be sent with a variety of modulation, timeslot and coding schemes, this modulation/timeslot/coding information must be conveyed to the UE. This type of information is typically signaled or broadcast to a UE and is typically performed using a low speed control channel. Signaling this information uses valuable overhead and air resources. Since AM&C is typically not applied to control channels, any information sent over a control channel uses much more air resources than would be required if the information was sent over a channel to which AM & C is applied. However, reducing signaling overhead is desirable regardless of whether or not AM&C is used.

[0008] Accordingly, it is desirable to transmit as much of the modulation/timeslot/coding information as possible over channels to which AM&C is applied. Additionally, it is desirable to reduce timeslot and code assignment signaling.

[0009] SUMMARY

[0010] A sequence of codes are provided for potential assignment to a user in a wireless hybrid TDMA/CDMA communication system. At least one (1) timeslot is selected to support the communication. For each selected timeslot, at least one (1) code is selected. If more than one code is selected, the codes are selected consecutively. For at least one (1) of the selected timeslots, an identifier of a first and last code of the selected consecutive codes is signaled. The user receives the signaled identifier and uses the selected consecutive codes, as identified, to support the communication.

In accordance with a first aspect of the present invention, there is provided a method for minimizing the amount of data necessary to signal code and timeslot assignments to support a communication of a user in a wireless hybrid time division multiple access (TDMA)/code division multiple access (CDMA) communication system comprising at least one transmitter and at least one receiver, whereby the system supports wireless radio frequency (RF) communications utilizing at least one timeslot from a predetermined sequence of timeslots and a predetermined sequence of codes, the method comprising: at the transmitter: selecting at least one timeslot from the predetermined sequence of timeslots; for said at least one selected timeslot, selecting consecutive codes from said predetermined sequence of codes; and signaling an identifier of said at least one selected timeslot and a first and last code of said selected

consecutive codes without signaling the codes therebetween; and at the receiver: receiving the signaled identifier; and using said at least one selected timeslot and said selected consecutive codes to support the communication.

In accordance with a second aspect of the present invention, there is provided a method for minimizing the amount of data necessary to signal code/timeslot assignments to support a communication of a user in a wireless hybrid time division multiple access (TDMA)/code division multiple access (CDMA) communication system, the method comprising: selecting at least one timeslot to support the communication; for said at least one selected timeslot, selecting consecutive codes of the selected timeslot to support the communication; signaling an identifier of said at least one selected timeslot and a first and last code of the selected consecutive codes without signaling the codes therebetween; and using said at least one selected timeslot and the selected consecutive codes to support the communication.

In accordance with a third aspect of the present invention, there is provided a method for minimizing the amount of data necessary to signal code and timeslot assignments to support a communication of a user in a wireless hybrid time division multiple access (TDMA)/code division multiple access (CDMA) communication system comprising at least one transmitter and at least one receiver, whereby the system supports wireless radio frequency (RF) communications utilizing at least one timeslot from a plurality of timeslots and a plurality of codes, the method comprising: at the transmitter: selecting at least one timeslot from the plurality of timeslots; for said at least one selected timeslot, selecting consecutive codes from said plurality of codes; signaling a first identifier of said at least one selected timeslot; and signaling a second identifier of a first and last code of the selected consecutive codes without signaling the codes therebetween; and at the receiver: receiving the signaled identifiers; and using said at least one selected timeslot and said selected consecutive codes associated with said first and second identifier to support the communication.

In accordance with a fourth aspect of the present invention, there is provided a method for minimizing the amount of data necessary to signal code/timeslot assignments to support a communication of a user in a wireless hybrid time division multiple access (TDMA)/code division multiple access (CDMA) communication system using a plurality of timeslots, each timeslot having a plurality of codes, the method

comprising: consecutively numbering the codes of the plurality of timeslots; selecting consecutive codes from said plurality of codes to support the communication; signaling an identifier of a first and last code of the selected consecutive codes without signaling the codes therebetween; and receiving the signaled identifier and using the timeslots and selected consecutive codes associated with said identifier to support the communication.

In accordance with a fifth aspect of the present invention, there is provided a method for minimizing the amount of data necessary to signal code and timeslot assignments to support a communication of a user in a wireless hybrid time division multiple access (TDMA)/code division multiple access (CDMA) communication system comprising at least one transmitter and at least one receiver, whereby the system supports wireless radio frequency (RF) communications utilizing at least one timeslot from a predetermined sequence of timeslots and from a predetermined sequence of codes, the method comprising: at the transmitter: selecting at least one timeslot from the predetermined sequence of timeslots; selecting consecutive codes from said predetermined sequence of codes for said at least one selected timeslot; signaling an identifier of said at least one selected timeslot and a first and last code of the selected consecutive codes without signaling the codes therebetween; and at the receiver: receiving said signaled identifier; and using said at least one selected timeslot and the selected consecutive codes to support the communication.

In accordance with a sixth aspect of the present invention, there is provided a wireless hybrid time division multiple access (TDMA)/code division multiple access (CDMA) communication network for minimizing the amount of data necessary to signal code and timeslot assignments to support a communication of a user, the network comprising at least one transmitter and at least one receiver, whereby the network supports wireless radio frequency (RF) communications utilizing at least one timeslot from a predetermined sequence of timeslots and a predetermined sequence of codes, the system comprising: at the transmitter: means for selecting at least one timeslot from the predetermined sequence of timeslots; means for selecting consecutive codes from said predetermined sequence of codes for said at least one selected timeslot; means for signaling an identifier of said at least one selected timeslot and a first and last code of the selected consecutive codes without signaling the codes therebetween; and at the receiver: means for receiving said signaled identifier; and means for using said at least one selected timeslot and the selected consecutive codes to support the communication.

In accordance with a seventh aspect of the present invention, there is provided a wireless hybrid time division multiple access (TDMA)/code division multiple access (CDMA) transmitter for signaling code and timeslot assignments to support an RF communication utilizing at least one timeslot from a predetermined sequence of timeslots and at least one code from a predetermined sequence of codes, comprising: a selector for selecting at least one timeslot, and for said at least one selected timeslot, selecting at least one code, and if more than one code is selected, selecting consecutive codes from said predetermined sequence; a signaler for signaling an identifier of said at least one timeslot and a first and last code of said consecutive codes; whereby the transmitter uses said at least one timeslot and said at least one selected code to support the RF communication.

In accordance with an eighth aspect of the present invention, there is provided a wireless transmitter for signaling code/timeslot assignments to support a communication comprising: a selector selecting at least one timeslot to support the communication, and for each selected timeslot, selecting all codes of the selected timeslot to support the communication; and a signaler for signaling an identifier of said one timeslot; whereby said transmitter uses the signaled identifier and said at least one timeslot to support the communication.

In accordance with a ninth aspect of the present invention, there is provided a transmitter for signaling code and timeslot assignments to support an RF communication of a user in a wireless hybrid time division multiple access (TDMA)/code division multiple access (CDMA) format, utilizing at least one timeslot from a plurality of timeslots and a plurality of codes, comprising: a selector for selecting at least one timeslot, and for said at least one selected timeslot, selecting at least one code; and a signaling means for first and second identifiers of said at least one timeslot, said first identifier representing a first of said plurality of codes and said second identifier representing a last of said plurality of codes.

In accordance with a tenth aspect of the present invention, there is provided a transmitter for signaling code/timeslot assignments to support a communication of a user in a wireless hybrid time division multiple access (TDMA)/code division multiple access (CDMA) format using a plurality of timeslots, each timeslot having a plurality of codes, whereby the codes from all timeslots are consecutively numbered, the

transmitter comprising: a selector for selecting the desired codes to support the communication; and a signaler for signaling an identifier of the desired codes; whereby the time slots and codes associated with said identifier are used to support the communication.

[0011] BRIEF DESCRIPTION OF THE DRAWING (S)

[0012] Fig. 1 is a simplified illustration of wireless physical channel configuration signaling system for the downlink.

[0013] Fig. 2 is a simplified illustration of such a system for the uplink.

[0014] Fig. 3 is a flow diagram for signaling using consecutive codes.

- [0015] Fig. 4 is a table illustrating assigning using consecutive codes.
- [0016] Fig. 5 is a flow diagram for signaling using common consecutive codes.
- [0017] Fig. 6 is a table illustrating assigning using common consecutive codes.
- [0018] Fig. 7 is a flow diagram for signaling using common consecutive codes in consecutive timeslots.
- [0019] Fig. 8 is a table illustrating assigning using common consecutive codes in consecutive timeslots.
- [0020] Fig. 9 is a flow diagram for signaling using entire timeslot assignments.
- [0021] Fig. 10 is a table illustrating entire timeslot assignments.
- [0022] Fig. 11 is a flow diagram for signaling using consecutive entire timeslots.
- [0023] Fig. 12 is a table illustrating consecutive entire timeslot assignments.
- [0024] Fig. 13 is a table summarizing the bits required to signal the code/timeslot assignments for a sixteen code and twelve available timeslot system.
- [0025] Fig. 14 is a flow diagram for the method of numbering all codes consecutively in all timeslots.
- [0026] Fig. 15 is a table illustrating consecutive code assignment.

[0027] DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT(S)

[0028] The present invention will be described with reference to the drawing figures wherein like numerals represent like elements throughout.

[0029] One method 53 for assigning codes to timeslots in accordance with the present invention uses consecutive codes and will be described with reference to the flow diagram of Fig. 3, and a simplified illustration of such code assignments for UE A, UE B and UE C is shown in Fig. 4. In Fig. 4, twelve (12) potential timeslots and sixteen (16) potential codes are shown, although the present invention is not limited to a specific number of timeslots and/or codes.

[0030] Each timeslot is potentially assigned a predetermined number of codes, such as sixteen codes. The predetermined number of codes are assigned an order or sequence, such as from 0 to 15, (step 54). For a particular UE, only consecutive codes

are assigned to that UE in a given timeslot, (step 56). To illustrate, referring to Fig. 4 for UE A in timeslot 2, codes 4-8 are assigned. An assignment of codes 1, 3 and 4 to UE A is not permitted, unless code 2 is also assigned to UE A. Likewise, UE A in timeslot 6 has been assigned codes 6-9; UE B in timeslot 2 has been assigned codes 9-12 and in timeslot 9 has been assigned codes 0-13; and UE C in timeslot 11 has been assigned codes 1-5.

[0031] Referring back to Fig. 3, to signal this assignment scheme to a UE, for each assigned timeslot, an indication of the first code and the last code of the consecutive codes is required, (step 58). For a sixteen (16) potential code sequence, eight (8) bits are required. Four (4) bits indicate the start code, (code 0 to 15), and four (4) bits indicate the last code or the number of consecutive codes, (code 0 to 15) or the number (1 to 16) of consecutive codes. For a twelve (12) timeslot system, 96 bits are needed, (eight (8) bits per timeslot by twelve (12) timeslots).

[0032] One approach to reduce the number of bits signaled for downlink transmissions in the control channels is to signal only a small portion of the assignment information over a control channel, (hereinafter referred to as "prior signaled information"), and signal the remaining portion of the assignment information with the downlink data, (hereinafter referred to as "post signaled information"). The post signaled information sent with the downlink data will undergo the same AM&C processing as the data, thereby significantly reducing the amount of air resources required to transmit the assignment information over the control channel.

[0033] In a typical system, it takes two (2) timeslots to recover the data, since the control information must be received and then processed in order to be ready to receive the actual data. The prior signaled information must therefore only relay the assignment information for the first two (2) timeslots used to transmit downlink data which comprises a four (4) bit indicator for the first used timeslot; a four (4) bit indicator for the next timeslot; and indicators, (two (2) bits each), for the first and last codes for each of the used timeslots. Accordingly, only a maximum of sixteen (16)

bits are signaled as prior signaled information. The remaining assignment information is signaled as post signaled information with the downlink data. As a result, for a sixteen (16) code and a twelve (12) timeslot system, only sixteen (16) bits are prior signaled information, with the remaining post signaled information signaled with the downlink data.

[0034] One advantage to this approach is that it allows the use of any number of codes in any timeslot. However, this approach requires signaling for typically at least two timeslot assignments, and possibly all timeslot assignments. Although this limits the code choice to consecutive codes, with the use of code reassignment, this restriction is not significant. If an optimal reassignment requires non-consecutive codes, the timeslot UE code usage can be repacked to allow the assignment of only consecutive codes to all UEs.

[0035] A second method 80 to assign codes and timeslots uses common consecutive codes and is described with reference to the flow diagram of Fig. 5 and the simplified illustration of such code assignments for UE A, UE B and UE C in Fig. 6. Each timeslot is potentially assigned a predetermined number of codes, such as sixteen (16) codes. The predetermined number of codes are assigned an order or sequence, such as from 0 to 15, (step 82). The same set of consecutive codes assigned to one timeslot must be assigned to all timeslots used for a particular UE, (step 84). To illustrate using Fig. 6, UE A is assigned timeslots 2, 3 and 11 and is assigned codes 2-4 in each timeslot. However, since UE A was assigned codes 2-4 in timeslot 2, it could not be assigned only code 2 or codes 2-5 in another timeslot. Likewise, UE B is assigned codes 0-13 in timeslots 8 and 9; and UE C is assigned code 11 in timeslots 11 and 12.

[0036] To signal this assignment scheme to a UE, an indication of the first and last code of the consecutive set is required as well as an indicator of the used timeslots (step 86). For the system of Fig. 6, eight (8) bits are required for the consecutive codes, (four (4) bits for the first code and four (4) bits for the last code or number of codes), and twelve (12) bits to identify the used timeslot(s). Each bit corresponds to a

timeslot. In one (1) implementation, a one (1) bit value indicates that the timeslot is used and a zero (0) bit value indicates that it is not used. Thus, a total of twenty (20) bits are required.

[0037] The use of prior signaled information and post signaled information with this method 80 reduces the number of prior signaled bits. The prior signaled information must indicate the first used timeslot and the following timeslot, and the first and last codes of the common sequence. For the system of Fig. 6, eight (8) bits indicating the first two (2) timeslots of the twelve (12) timeslots, (four (4) bits to indicate each timeslot) and eight (8) bits for the start and end codes or number of codes. Thus, a total of sixteen (16) bits of prior signaled information is required.

[0038] To further reduce the bits of the prior signaled information, five (5) bits may be used for the first two (2) timeslots. Four (4) bits indicates the first used timeslot and the fifth bit represents whether the following timeslot is used. As a result, either sixteen (16) or thirteen (13) bits are prior signaled information, with at most ten (10) bits of post signaled information.

[0039] One advantage to the second method is that it reduces the amount of prior signaled information. One drawback is that it reduces flexibility in code and timeslot assignments, since each timeslot used by a particular UE must be assigned the same codes.

[0040] A third method 90 for code and timeslot assignment uses common consecutive codes in consecutive timeslots and is described with reference to the flow diagram of Fig. 7 and the simplified illustration of such code assignments for UE A, UE B and UE C in Fig. 8. Each timeslot is potentially assigned a predetermined number of codes, such as sixteen (16) codes. The predetermined number of codes are assigned an order or sequence, such as from 0 to 15, (step 92). In this approach, not only are the same codes assigned for each used timeslot, but also only consecutive timeslots may be assigned, (step 94). To illustrate using Fig. 8, UE A is assigned codes 2-4 in timeslots 5-7. However, UE A could not be assigned codes 2-4 in timeslots 5, 6 and 8, unless timeslot 7 was also assigned. Likewise, UE B is assigned

WO 02/093787

PCT/US02/14955

codes 0-13 in timeslots 8 and 9. UE B could not be assigned a lesser or greater number of codes in any other timeslots, nor could it be assigned codes 0-13 in timeslot 11 or 12, unless timeslot 10 was also assigned. UE C is assigned code 11 in timeslot 11.

[0041] To signal this assignment scheme to a UE, an indication of the first and last (or number of) assigned codes in each assigned timeslot and an indication of the first and last (or number of) assigned timeslots, (step 96). For the system of Fig. 8, eight (8) bits are required for the code assignments and eight (8) bits for the timeslot assignments, (four (4) for the first timeslot and four (4) for the last, or number of, timeslots), totaling sixteen (16) bits.

[0042] The use of prior signaled information and post signaled information with this method 90 reduces the number of prior signaled bits. In this method 90, thirteen (13) bits must be signaled prior to the data, (eight (8) for the codes used in the timeslots, four (4) for the first used timeslot and one (1) bit to indicate whether another timeslot is used). If another timeslot is used, four (4) bits indicating the last, or number of, timeslots are signaled as post signaled information with the data.

[0043] This third method limits the amount of signaling, but at the expense of code/timeslot assignment flexibility.

[0044] A fourth method 100 to assign codes and timeslots assigns UEs all the codes in a timeslot and is described with reference to the flow diagram of Fig. 9 and the simplified illustration of such code assignments for UE A, UE B and UE C in Fig. 10. In this approach, the UEs are assigned all of the codes in a timeslot (step 102). To illustrate using Fig. 10, UE A is assigned all the codes of timeslots 2 and 5, UE B is assigned all of the codes of slots 8 and 9, and UE C is assigned all of the codes of timeslot 11.

[0045] To signal this assignment scheme to a UE, an indicator of the assigned timeslots is needed, (step 104). For the system of Fig. 10, the indicator is a twelve (12) bit field, with each bit representing whether a particular timeslot is used. Typically, the maximum number of codes in a timeslot is known by the UE. However,

if the maximum number of codes is not known, an indicator of the number of codes is sent, (also a part of step 104), such as four (4) bits indicating a maximum number of codes ranging from 0 to 16.

[0046] The use of prior signaled information and post signaled information with this method 100 reduces the number of prior signaled bits. In this method 100, an indicator of the first two used timeslots is signaled. For the system of Fig. 10, this two timeslot indicator is eight (8) bits. The indicator of the remaining assigned timeslots is signaled as post signaled information with the data in the first timeslot. Alternately, to further reduce the number of signaled bits, five (5) bits of prior signaled information may be used. Four (4) bits indicate the first timeslot and the fifth bit indicates whether the following timeslot is used.

[0047] A fifth method 110 for code and timeslot assignment uses entire consecutive timeslots and is described with reference to the flow chart of Fig. 11 and the simplified illustration of such assignments for UE A, UE B and UE C in Fig. 12. In this approach, a UE is assigned all of the codes in consecutive timeslots (step 112). To illustrate using Fig. 12, UE A is assigned all the codes of timeslots 2-4. UE A could not be assigned all the codes of timeslots 2, 3 and 5 without also assigning UE A timeslot 4. Likewise, UE B is assigned all of the codes of timeslots 8 and 9; and UE C all of the codes of timeslot 11.

[0048] To signal this assignment scheme to a UE, an indicator of the first and last timeslots (or number of) used timeslots is signaled, (step 114). For the system of Fig. 11, eight (8) bits are required, (four (4) for the first used timeslot and four (4) for the last or number of timeslots).

[0049] The use of prior signaled information and post signaled information with this method 110 reduces the number of prior signaled bits. In this method 61, only five (5) bits are sent as prior signaled information. Four (4) bits indicate the first used code and the fifth bit indicates whether the following timeslot is used, (step 74). If the following timeslot is used, four (4) bits are signaled as post signaled information with the transmitted downlink data to indicate the last timeslot or number of timeslots.

[0050] A sixth method 120 numbers all codes consecutively in all timeslots and is described with reference to the flow diagram of Fig. 14 in the simplified illustration of such codes assignments for UEA, UEB and UEC in Fig. 15. In this method 120, all of the codes are numbered consecutively in all timeslots (step 122). The UE is then assigned a desired number of codes (step 124). To illustrate using Fig. 15, UEA is assigned codes 69-99, UEB is assigned codes 129-142 and UEC is assigned codes 162-181.

[0051] To signal this assignment scheme to a UE, an indicator of the first and last code is needed (step 126). For the system of Fig. 15, the indicator is sixteen (16) bits, (eight (8) bits for the first codes and eight (8) bits for the last code). Alternatively, the indicator of the first code may be signaled along with the number of codes; particularly when the number of codes is small.

[0052] The use of prior signaled information and post signaled information with this method 120 reduces the number of prior signaled bits. In this method 120, thirteen (13) bits must be signaled as prior signaled information, (eight (8) for the first code and five (5) bits for the number of codes in the first two (2) timeslots). If more codes are used, the code count can be superseded in the post signaled information.

[0053] The table of Fig. 13 summarizes the bits required to signal the code/timeslot assignment for the six (6) schemes for a sixteen (16) code and twelve (12) available timeslot system.

[0054] Although the present invention may be implemented by many physical systems, one such system for implementing the invention will be described with reference to Fig. 1. Fig. 1 illustrates a simplified wireless hybrid TDMA/CDMA communication system for use in physical channel configuration signaling. A preferred implementation is for downlink transmitted data, such as for a high speed downlink channel, although physical channel configuration signaling may also be used in other implementations, such as the uplink.

[0055] Downlink data to be communicated to a particular UE 24 is assigned at least one code and at least one timeslot by a resource management device 28. The resource

management device 28 may be in a radio network controller (RNC) or Node-B 20. The resource management device 28 assigns codes and timeslots as will be described in detail hereinafter. The assigned code and timeslot are sent to a signaling transmitter 30 and an AM&C controller 32 in the base station 22. The signaling transmitter 30 formats for transmission the code and timeslot information as will also be described in detail hereinafter.

[0056] A data modulation and spreading device 34 modulates, spreads and time multiplexes the downlink data in the timeslots and with the codes assigned by the resource management device 28. The modulated data and signaled information is radiated by an antenna 36 or antenna array through a wireless radio channel 26.

[0057] At the particular UE 24, the transmitted downlink data and signaled information is received by an antenna 38. A signaling receiver 40 recovers the signaled information and relays it to an AM&C controller 42. The AM&C controller 42 determines the modulation to be used and indicates the code and timeslot used for the downlink data to the data detection device 44. One potential data detection device 44 is a joint detection device using a channel estimation device, although other data detection devices may be used. The data detection device 44 recovers the downlink data using the timeslot and code information from the AM&C controller 42.

[0058] Fig. 2 illustrates a simplified system for use in uplink physical channel configuration signaling. The resource management device 28 assigns the code/timeslot to be used for the particular UE's uplink data. The assigned code/timeslot are sent to a signaling transmitter 30 in the base station 22. The signaling transmitter 30 formats for transmission the code and timeslot information as will be described in detail hereinafter. The signaled information is passed through a switch 48 or isolator and radiated by an antenna 36 or antenna array through a wireless radio channel 26.

[0059] The particular UE 24 receives the signaled information. The received information is passed thorough a switch 50 or isolator to a signaling receiver 40. The signaled information is recovered by the signaling receiver 40 and relayed to an

AM&C controller 42. The AM&C controller 42 relays the uplink code and timeslot assignment to the data modulation and spreading device 52. The data modulation and spreading device 52 modulates, spreads and time multiplexes the uplink data as directed by the AM&C controller 42 in the timeslots and with codes signaled by the base station 22. The modulated data is passed through a switch 50 or isolator and radiated by the UE antenna 38 through the wireless radio channel 26.

[0060] The transmitted data is received by the base station antenna 36 or antenna array. The received data is passed through a switch 48 or isolator to a data detection device 46. One possible data detection device 34 is a joint detection device using a channel estimation device, although other data detection devices may be used. A base station AM&C controller 32 receives the code and timeslot assignment from the resource management device 28. The data detection device 46 recovers the uplink data from the received uplink signal using the assigned code and timeslot as directed by the AM&C controller 32.

[0061] While the present invention has been described in terms of the preferred embodiment, other variations which are within the scope of the invention as outlined in the claims below will be apparent to those skilled in the art.

* * *

CLAIMS

What is claimed is:

1. A method for minimizing the amount of data necessary to signal code and timeslot assignments to support a communication of a user in a wireless hybrid time division multiple access (TDMA)/code division multiple access (CDMA) communication system comprising at least one transmitter and at least one receiver, whereby the system supports wireless radio frequency (RF) communications utilizing at least one timeslot from a predetermined sequence of timeslots and a predetermined sequence of codes, the method comprising:

at the transmitter:

selecting at least one timeslot from the predetermined sequence of timeslots;

for said at least one selected timeslot, selecting consecutive codes from said predetermined sequence of codes; and

signaling an identifier of said at least one selected timeslot and a first and last code of said selected consecutive codes without signaling the codes therebetween; and

at the receiver:

receiving the signaled identifier; and

using said at least one selected timeslot and said selected consecutive codes to support the communication.

2. The method of claim 1 wherein the last code is identified by the number of consecutive codes.

3. The method of claim 1 wherein each selected timeslot is potentially assigned a different set of consecutive codes and the signaled identifier comprises an identifier of a first and last code of each selected timeslot.

4. The method of claim 1 further comprising selecting a plurality of timeslots wherein each selected timeslot is assigned the same consecutive codes.

5. The method of claim 4 further comprising signaling a timeslot identifier for each selected timeslot.

6. The method of claim 5 wherein said timeslot identifier is a set of bits, each bit associated with one timeslot.

7. The method of claim 1 further comprising selecting a plurality of timeslots; whereby said plurality of selected timeslots are consecutive and the same codes are assigned to each selected timeslot; and
signaling an identifier of a first and last code of each selected timeslot.

8. The method of claim 1 wherein the communication is a downlink communication.

9. The method of claim 1 wherein the hybrid TDMA/CDMA communication system is a hybrid time division duplex communication system using CDMA.

10. A method for minimizing the amount of data necessary to signal code/timeslot assignments to support a communication of a user in a wireless hybrid time division multiple access (TDMA)/code division multiple access (CDMA) communication system, the method comprising:

selecting at least one timeslot to support the communication;

for said at least one selected timeslot, selecting consecutive codes of the selected timeslot to support the communication;

signaling an identifier of said at least one selected timeslot and a first and last code of the selected consecutive codes without signaling the codes therebetween; and

using said at least one selected timeslot and the selected consecutive codes to support the communication.

11. The method of claim 10 wherein said identifier is one bit for each timeslot.

12. The method of claim 10 further comprising:

providing a predetermined sequence of timeslots; whereby said selected timeslots are consecutive and the at least one selected timeslot identifier comprises an indicator of a first and last timeslot of the consecutive timeslots.

13. The method of claim 12 wherein the last timeslot identifier is an identifier associated with the last timeslot.

14. The method of claim 12 wherein the last timeslot identifier is an identifier associated with a number of timeslots of the consecutive timeslots.

15. A method for minimizing the amount of data necessary to signal code and timeslot assignments to support a communication of a user in a wireless hybrid time division multiple access (TDMA)/code division multiple access (CDMA) communication system comprising at least one transmitter and at least one receiver, whereby the system supports wireless radio frequency (RF) communications utilizing at least one timeslot from a plurality of timeslots and a plurality of codes, the method comprising:

at the transmitter:

selecting at least one timeslot from the plurality of timeslots;

for said at least one selected timeslot, selecting consecutive codes from said plurality of codes;

signaling a first identifier of said at least one selected timeslot; and

signaling a second identifier of a first and last code of the selected consecutive codes without signaling the codes therebetween; and

at the receiver:

receiving the signaled identifiers; and

using said at least one selected timeslot and said selected consecutive codes associated with said first and second identifier to support the communication.

16. The method of claim 15 wherein said first and second identifiers are combined into a single identifier.

17. A method for minimizing the amount of data necessary to signal code/timeslot assignments to support a communication of a user in a wireless hybrid time division multiple access (TDMA)/code division multiple access (CDMA) communication system using a plurality of timeslots, each timeslot having a plurality of codes, the method comprising:

consecutively numbering the codes of the plurality of timeslots;

selecting consecutive codes from said plurality of codes to support the communication;

signaling an identifier of a first and last code of the selected consecutive codes without signaling the codes therebetween; and

receiving the signaled identifier and using the timeslots and selected consecutive codes associated with said identifier to support the communication.

18. A method for minimizing the amount of data necessary to signal code and timeslot assignments to support a communication of a user in a wireless hybrid time division multiple access (TDMA)/code division multiple access (CDMA) communication system comprising at least one transmitter and at least one receiver, whereby the system supports wireless radio frequency (RF) communications utilizing at least one timeslot from a predetermined sequence of timeslots and from a predetermined sequence of codes, the method comprising:

at the transmitter:

selecting at least one timeslot from the predetermined sequence of timeslots;

selecting consecutive codes from said predetermined sequence of codes for said at least one selected timeslot;

signaling an identifier of said at least one selected timeslot and a first and last code of the selected consecutive codes without signaling the codes therebetween; and

at the receiver:

receiving said signaled identifier; and

using said at least one selected timeslot and the selected consecutive codes to support the communication.

19. The method of claim 18 further comprising signaling the number of codes to be used for each selected timeslot.

20. A wireless hybrid time division multiple access (TDMA)/code division multiple access (CDMA) communication network for minimizing the amount of data necessary to signal code and timeslot assignments to support a communication of a user, the network comprising at least one transmitter and at least one receiver, whereby the

network supports wireless radio frequency (RF) communications utilizing at least one timeslot from a predetermined sequence of timeslots and a predetermined sequence of codes, the system comprising:

at the transmitter:

means for selecting at least one timeslot from the predetermined sequence of timeslots;

means for selecting consecutive codes from said predetermined sequence of codes for said at least one selected timeslot;

means for signaling an identifier of said at least one selected timeslot and a first and last code of the selected consecutive codes without signaling the codes therebetween; and

at the receiver:

means for receiving said signaled identifier; and

means for using said at least one selected timeslot and the selected consecutive codes to support the communication.

21. A wireless hybrid time division multiple access (TDMA)/code division multiple access (CDMA) transmitter for signaling code and timeslot assignments to support an RF communication utilizing at least one timeslot from a predetermined sequence of timeslots and at least one code from a predetermined sequence of codes, comprising:

a selector for selecting at least one timeslot, and for said at least one selected timeslot, selecting at least one code, and if more than one code is selected, selecting consecutive codes from said predetermined sequence;

a signaler for signaling an identifier of said at least one timeslot and a first and last code of said consecutive codes; whereby the transmitter uses said at least one timeslot and said at least one selected code to support the RF communication.

22. The transmitter of claim 21 wherein the last code is identified by an identifier associated with the last code.

23. The transmitter of claim 21 wherein the last code is identified by the number of consecutive codes.

24. The transmitter of claim 21 wherein each selected timeslot is potentially assigned a different set of consecutive codes and the signaled identifier comprises an identifier of a first and last code of each selected timeslot.

25. The transmitter of claim 21 wherein said selector selects a plurality of timeslots and each selected timeslot is assigned the same consecutive codes.

26. The transmitter of claim 25 wherein said signaler signals a timeslot identifier for each selected timeslot.

27. The transmitter of claim 21 wherein said timeslot identifier is a set of bits, each bit associated with one timeslot.

28. The transmitter of claim 21 wherein said selector further selects a plurality of timeslots, whereby said plurality of selected timeslots are consecutive and the same codes are assigned to each selected timeslot, and said signaler signals an identifier of a first and last code of each selected timeslot.

29. The transmitter of claim 21 wherein the communication is a downlink communication.

30. A wireless transmitter for signaling code/timeslot assignments to support a communication comprising:

a selector selecting at least one timeslot to support the communication, and for each selected timeslot, selecting all codes of the selected timeslot to support the communication; and

a signaler for signaling an identifier of said one timeslot; whereby said transmitter uses the signaled identifier and said at least one timeslot to support the communication.

31. The transmitter of claim 30 wherein said identifier is one bit for each timeslot.

32. The transmitter of claim 30 whereby said selected timeslots are consecutive and the at least one selected timeslot identifier comprises an indicator of a first and last timeslot of the consecutive timeslots.

33. The transmitter of claim 30 wherein the last timeslot identifier is an identifier associated with the last timeslot.

34. The transmitter of claim 30 wherein the last timeslot identifier is an identifier associated with a number of timeslots of the consecutive timeslots.

35. A transmitter for signaling code and timeslot assignments to support an RF communication of a user in a wireless hybrid time division multiple access (TDMA)/code division multiple access (CDMA) format, utilizing at least one timeslot from a plurality of timeslots and a plurality of codes, comprising:

a selector for selecting at least one timeslot, and for said at least one selected timeslot, selecting at least one code; and

a signaling means for first and second identifiers of said at least one timeslot, said first identifier representing a first of said plurality of codes and said second identifier representing a last of said plurality of codes.

36. The transmitter of claim 35 wherein said first and second identifiers are combined into a single identifier.

37. A transmitter for signaling code/timeslot assignments to support a communication of a user in a wireless hybrid time division multiple access (TDMA)/code division multiple access (CDMA) format using a plurality of timeslots, each timeslot having a plurality of codes, whereby the codes from all timeslots are consecutively numbered, the transmitter comprising:

a selector for selecting the desired codes to support the communication; and

a signaler for signaling an identifier of the desired codes; whereby the time slots and codes associated with said identifier are used to support the communication.