

Credit card ejector addressing slip stick.

The invention relates to a card holder provided with a device (further also called "ejector") to eject or dispense
5 the cards, e.g. credit cards or bank cards, or different flat or plate like objects, from the holder and wherein the card or cards tightly fit within the holder, for which the holder has a cavity similar to the shape and slightly bigger than the card or cards stack. The ejected cards are preferably presented
10 as a staggered stack.

For the so called credit card format the main dimensions suffice ISO 7810 and the thickness and roundings suffice ISO 7813. This format is applied for many cards with a diversity of applications: bank cards, driving licenses, ID-cards,
15 membership cards, entry tickets, reduction cards, savings cards, etc.

The cards preferably have a solid, not foldable shape and a smooth, slippery, low friction surface. The holder preferably has a rigid flat box or sleeve shape.

20 The prior art discloses in EP-A 0 287 532, CH702919 B1, WO2010137975 (VILT) and WO2014098580 (FLEXARM) a pivoting ejector arm provided with a stepped or relief profile along its length such that each card engages with a different edge at the ejector arm, the cards are simultaneously dispensed to
25 present a staggered stack of cards, partly projecting out the card holder. Different card holders are disclosed in US2002/074246, US4887739, US5718329 and JP S60-179484 U.

The above cited prior art provides background knowledge for the present invention. The disclosure of this prior art
30 is enclosed herein by reference.

The object of the invention is versatile. In one aspect the object is a further improvement of the card holder, in particular of the feature to eject the stack of cards from the holder. By way of example, an object is a more elegant finger
35 or thumb operation of the eject button during cards eject. Additional possible aspects are a comfortable, simple and accurate operation of the holder with long life. In yet another aspect the object is error free handling, low production costs, attractive appearance.

Thus the invention is directed to a card holder and to a card holder eject arm according to the claims. Other aspects can be learned from the specification, drawings or claims. Two or more aspects can be combined.

5 The inventor discovered that one of the effects of the invention is that the finger or thumb operating the eject button requires substantially less effort to eject the cards stack. This was found out by surprise during laboratory experiments, wherein one of the experimental eject arms showed unexpected
10 low manual load requirements during cards ejecting. Subsequent thorough investigation pointed towards a unique spontaneous permanent deformation of the eject arm, possibly due to temporary malfunctioning of the laboratory injecting molding machine. This teaching was further elaborated and provided the
15 basis for the present invention.

Without to be bound to the following explanation, a possible effect of the invention is as follows. With the prior art, the eject arm engages with a substantial length part, e.g. its complete length part provided with all the steps for
20 ejecting a staggered cards stack, the entire cards stack. Thus, the cards are urged outward by a long lever arm. With the invention, initially the eject arm engages with a substantially smaller length part, e.g. only the length part closest to the pivot carrying one or two or only a minor number of steps, the
25 entire cards stack or only a part of the cards stack. Thus, initially, the lever arm is short which keeps the required effort to start the outward movement of the cards low, although the rather high static friction needs be overcome. As soon as the cards move, the kinetic friction, substantially lower than
30 the static friction, needs be overcome, such that the lever arm may lengthen (since steps further away from the pivot start engaging the cards) without negatively influencing the ergonomics experienced during finger or thumb operation of the eject button. Most elegant seems obtainable if during pivoting
35 the eject arm towards the extended position, steps start engaging the cards one by one, preferably wherein each subsequent step is located at a longer lever arm.

In a preferred embodiment, the holder is provided with an eject arm designed such that during ejecting the cards by moving the eject arm to its extended position, first the eject arm engages and pushes outward the cards stack at a first eject arm longitudinal location close to its pivot while simultaneously the longitudinal part of the eject arm beyond said first location, seen from the pivot, does not engage and/or push the cards stack; and subsequently after the eject arm has covered an angle or distance while pushing the cards stack outward, the eject arm starts engaging and pushing outward the cards stack at a second eject arm longitudinal location further away from its pivot, preferably longitudinally spaced from the first location, while the eject arm continues pivoting toward its extended position. Preferably, the eject arm is designed such that there is a plurality, e.g. at least four or five or six, such locations along the eject arm length, preferably mutually longitudinally spaced, e.g. as many as there are contact faces for engagement with the individual cards of the stack for simultaneously ejecting a staggered stack, which locations are provided such that while the eject arm pivots toward its extended position and pushed the cards stack outward, said locations start pushing the cards stack the one after the other. Preferably a or all locations already pushing the cards stack continue pushing the cards stack when a next location starts pushing the cards stack; and/or each next location is further away from the eject arm pivot point. Preferably these locations are provided by the location of the contact faces.

In an embodiment the first location engages the complete cards stack and each next location engages a smaller part of the cards stack, preferably such that the location furthest away from the pivot engages merely a single card from the stack. Alternatively, preferably, the eject arm is designed such that from the time all locations engage and push the cards stack, each location engages a single card from the stack, e.g. such that the cards stack becomes or remains staggered.

Preferably, the part of the eject arm beyond the first location, viewed longitudinally from the pivot, equals in

length or comprises at least 50% or 75% of the arm length provided with the contact faces. Preferably, the first location is provided at at least 25% or 30% or 40% and/or at the most 60% or 75% of the eject arm length, measured from the pivot.

5 Preferably, the locations are provided on a curved line, preferably with a single radius, e.g. circle, preferably of at least 100 or 150 or 200 millimeter. Alternatively, the locations are provided on a straight or stepped line. This line is e.g. provided by part of the leading edge of the eject arm,
10 which is the edge that engages and pushes outward the cards stack. This line is one or more of: a virtual line; extends in longitudinal direction of the eject arm; nears toward the trailing edge of the eject arm viewed longitudinally from the pivot.

15 Preferably, viewed in the direction of pivoting of the arm from the retracted to the extended position, each next location or a group of locations or all locations is set back at least 0.05 or 0.075 millimeter relative to the adjacent location; or a location, e.g. the last (e.g. at the free end
20 tip) location starting engaging and pushing the cards during pivoting of the eject arm, is set back at least 0.5 or 0.75, e.g. approximately 0.9, millimeter relative to the first (e.g. closest to the pivot) location starting engaging and pushing the cards.

25 This starting process of ejecting cards preferably is completed within a minor part, e.g. the first 25%, preferably 15% or 10%, of the movement or pivoting stroke of the eject arm from its retracted to its fully extended state and/or the outward movement stroke of the cards stack from completely
30 within to maximally ejected by the eject arm. By way of example, it is e.g. completed within the first 10 or 20 degrees pivoting and/or the cards project outside the holder less than 5 or 10 or 15 millimeter. Preferably, completion requires at least 5% of said stroke, e.g. at least 5 degrees pivoting and/or at least
35 5 millimeter projection.

Preferably one or more of the following applies to the holder: a rectangular shape, preferably elongated; fixed shape,

robust, of light weight material, e.g. metal or polymer material, polyester, PP; box or sleeve shaped; the card storage space receives a cards stack with tight fit; fixed length, width and depth; an ejector mechanism of the cards, preferably at the longitudinal end of the card holder opposite the card access opening to the housing space in which the cards are stored.

Preferably the invention is directed to a card holder provided with an ejector mechanism dispensing the complete stack of cards, thus all cards of the stack are dispensed simultaneously, e.g. since the ejector mechanism simultaneously engages the complete cards stack at the time of ejecting the cards. Preferably the cards are urged from the housing in such a manner that a staggered stack of cards, partly projecting out the card holder, is presented. This is preferably provided by the design of the ejector device. More preferably the design of the card holder or the ejector device is such that when the cards stack is completely contained within the card holder, the cards are mutually in register (in other words the cards are not staggered), and preferably is partly projected from the card holder, wherein the cards are presented in a staggered fashion. By presenting the cards in staggered fashion, they can be easily individually identified and individually taken from the stack by two fingers of the hand of the user. The card holder is preferably rigid in relation to the typical loads to which the card holder is exposed during normal daily use.

In particular the holder is designed to receive and dispense credit cards (and different items with dimensions comparable to credit cards, further mentioned as "cards"), preferably wherein a stack of, e.g. at least three, four or five, cards can be housed in the holder, more preferably wherein the cards in the stack are immediately mutually superposed or adjacent, in other words no further object, e.g. spacer, is or needs be present between adjacent cards. The holder preferably has two pairs of substantially or completely closed and fixed opposite sides, one pair with length and width almost equal to the same card dimensions (also called the "main sides")

and this pair spaced by the other (also called the "minor sides") pair (delimiting the stack thickness) such that the card stack tightly fits between these four sides. Preferably these sides are thin walled and/or provide a rigid, sleeve like casing.

5 Of the remaining pair of two opposite sides (typically located at the longitudinal ends of the sleeve) preferably one (also called the "bottom") is permanently substantially or completely closed and the other (also called the "top") is open but could be temporary closed, e.g. by a lid, such that the holder
10 preferably has merely a single open side through which the cards can enter and exit the holder. Thus the holder provides a rigid sleeve with closed bottom. Typically the cards enter and exit the holder by moving parallel to their main sides.

To avoid that the cards can spontaneously leave the card
15 holder, the device is preferably provided with card retaining means, e.g. a (preferably pivoting) removable lid associated with the access opening to open and close it, or clamping or friction means designed to engage e.g. a main side (a side defining a card face) or a minor side (a side defining the card
20 thickness, i.e. the thin side) of the card. E.g. WO2010137975 (above cited) addresses releasably retaining the cards within the housing by friction means and the relevant disclosures are incorporated in here by reference. Retaining means to keep the cards within the holder without closing the top side with a
25 lid, are preferred.

The ejector comprises an ejector element (further also called "arm") moving between a first and second (preferably a retracted and an extended, respectively) position inside the holder and engaging the cards stack, preferably engaging an
30 edge of the cards, to push the cards stack out of the holder while the cards move in a plane parallel to their main faces, preferably such that the cards (with the ejector element in its extended position) partly project from the holder in a stepped or staggered manner. For the purpose of presenting or
35 dispensing the cards in a stepped manner, the ejector arm is preferably provided with a relief profile, preferably having some relation with the thickness of the cards, such that the

element has a plurality of spaced features, preferably located along a straight or curved line, e.g. lengthwise of the arm, each such feature designed to engage a single card from the stack, preferably such that by movement of the element within 5 the holder, the one card is moving with the element for a further distance outward compared to another card from the same stack within the holder. In an embodiment such features are projections at the arm each providing an engagement edge (also called "face" or "contact face"), wherein preferably the 10 projections project a different distance from the element such that each engagement face is present at a different level. Preferably the arm is designed such that, in its retracted position, the cards fit within the holder such that the cards are mutually in register, in other words, present a neat stack.

15 Preferably the height (meaning the dimension normal to the housing main sides and parallel to the thickness direction of the cards or cards stack loaded into the housing) of the ejector arm stepwise increases longitudinally from the free end (in other words the distal end or the end remote from the 20 pivot point or the end opposite the end to which the drive means engage or are mounted). This stepwise increase of height provides step shaped features or contact faces for ejecting the cards stack in a staggered fashion.

The number of steps preferably at least equals the number 25 of cards within the stack and/or is at least 4 or 5 or 6 or 7. The steps preferably have approximately equal longitudinal spacing and/or height.

In its extended position, the ejector arm preferably extends diagonally within the holder or makes an angle between 30 20 and 90 degrees (90 degrees equals a right angle), preferably at least 45 or 55 or 60 degrees and/or less than 85 degrees, compared to its retracted position. In its retracted position, the ejector arm preferably extends parallel to an external side(also called "bottom") or edge of the holder, preferably 35 opposite the side from which the cards are dispensed from within the holder. Preferably the ejector arm rotates or swivels or turns or hinges or pivots between its first and second position,

for which it is preferably provided with a hinge or pivot feature, such as a pin or hole, with which it is mounted to the holder, for which the holder can be provided with a hole or pin, respectively. In the alternative a translating movement is
5 feasible.

To provide the movement of the ejector arm, the ejector comprises a drive means associated with the ejector arm. This could be a motoric means however a manually operated drive means, e.g. a finger operated button, is preferred, preferably
10 projecting or located outside the housing. Preferably the ejector arm and the drive means are connected in a rigid manner such that the movement of the drive means is directly transferred to the ejector arm and both these members move as one, e.g. since both these members are integrated in a single,
15 preferably rigid piece. The ejector arm and/or drive means could be injection moulded parts, e.g. of polymeric or plastic or equivalent material.

Preferably the ejector arm provides or is part of, a base or bottom of the holder, or part of it, preventing exit of the
20 cards from the associated side of the holder.

The card ejector feature gives the user the opportunity to partly slide the card stack from the housing. This is a preferred operation before the user can select a card and remove it from the housing.

25 By the time the eject arm is in its extended position, the cards are partly slid from the housing as a staggered or stepped stack such that each card presents an outside the housing projecting, exposed narrow strip of its upper main side and by viewing these strips the user can see at a blink which
30 cards are present in the holder. Also the user can easy and quick select within the cards stack the desired card and remove it by manually sliding the cards mutually in a direction equal to or opposite the direction in which the cards are slid from the housing from their stored position completely within the
35 housing.

An embodiment of the card ejector feature of the invention comprises, among others, a step like element, which by the user

relative to the housing, e.g. by means of rotation or translation, can be moved against the cards stack, wherein the individual steps of the step like element exert at the individual cards in the stack in the direction of the card opening a force, resulting that the card stack slides outward in stepped shape. The steps have a height which is measured parallel to the arm height and the card thickness and a spacing which is measured perpendicular to the height and which determines the degree wherein the cards slide mutually if they slide in stepped shape from the housing. Further preferred details of the step like element are provided by above cited WO2010137975 (VILT) and WO2014098580 (FLEXARM), the contents of which is inserted in here by reference.

An embodiment of the ejector, or part of it, e.g. the arm, as card remove feature of the card holder of the invention, is provided with or associated, e.g. coupled, with a reset means, e.g. a spring, with the effect that the ejector or the relevant part after operation will always immediately and automatically return to the initial position, e.g. move from the extended to the retracted position. Such by the reset means provided return offers the advantage such that without obstruction the user can slide cards back into the housing during making a selection from the partly exposed cards.

An embodiment of the card holder of the invention has a housing made of a galvanic material. The geometry of the housing of this invention lends itself for fabrication by means of metal extrusion, with which a proper Faraday cage is made.

The invention will now be further explained by way of the drawing, showing presently preferred embodiments. The drawing shows in:

- Fig. 1 - 2 a card holder, in perspective view;
- Fig. 3 a sectional view of the fig. 1 card holder;
- Fig. 4 in perspective view a pivoted ejector arm engaging a staggered cards stack;
- Fig. 5 an end view of the fig. 1 card holder;
- Fig. 6 - 7 in perspective view an ejector arm during different stages of its operation;

Fig. 8 a top view of the inventive ejector arm;

Fig. 9 a detail of fig. 8;

Fig. 10 a diagram to better understand fig. 9.

Fig. 1-5 provide technical background.

5 Fig. 1 - 3 show a perspective view of the housing of the card holder which tightly fits around the shown stack of at least three cards (four are shown), wherein one of the two longitudinal ends of the housing is referred to as a card opening because it is opened to receive and remove cards. The tightly
10 fit around the card stack implicates a main shape based on a right angled brick, but it can of course, for reasons of design or ergonomics, differ, e.g. by providing chamfers, roundings, ribs, etc.

Fig. 1 shows the holder 1 and a neat stack 2 of four mutually
15 registered cards, ready to be loaded into the holder through the cards opening 3. If completely located in the holder, the lower side of each card is in register with a relevant engagement or contact face of the ejector arm in its first (retracted) position. Starting from this position of the ejector arm and
20 moving (pivoting) it to its second position, the cards will be forced by the associated engagement face such that the cards stack is partly ejected. Since each engagement face has a different distance to the pivot point of the ejector arm, each card will travel a different distance such that a staggered
25 ejected stack 2 is obtained (shown in fig. 2 in which the ejector arm (not shown) is in its second, extended, position), each card presenting an exposed narrow strip of a main side as shown.

Fig. 3 shows in sectional view a holder (without cards) with a card eject feature (in the first (retracted) position)
30 provided by the stepped element 16 which can pivot around an axis 17 if the user exerts in the pivot direction (according to the arrow B) a force through the actuator 18 outside the housing, which actuator 18 is rigidly connected to element 16, meaning a direct coupling. The stepped element 16, which is
35 viewed from its top, is made from steps providing card contact faces 19 designed to exert force against the minor side of the cards to be ejected. The card contact faces 19 can be regarded

as the bridges between two subsequent steps in the stepped shape and the height of these faces is equal to or smaller than the nominal card thickness (approx. 0.8 mm), whereby each face 19 contacts a different card. A reset spring 20 ensures that the
5 ejector arm 16 after releasing the button 18 returns immediately and automatically to the initial (first) position shown. Friction elements 4, e.g. pads of rough fibre like material, e.g. felt, are located mutually opposite within the housing at the housing minor sides to engage each individual minor card
10 side to retain the cards against gravity force.

Fig. 3 shows the connection between the button 18 and the ejector arm 16 extending through a passage in the bottom edge, meaning the edge opposite the opening 3. Alternatively such passage could be present in a side edge or even in a main side
15 31. The button 18 is shown adjacent the bottom edge, however could be located adjacent a side edge or even a main side 31. The bottom edge or side edge is a minor side, bridging the main sides 31. These locations of the passage and button 18 are known from the prior art.

20 Fig. 3 also indicates the leading edge 6 of the arm 16. The leading edge 6 is facing in the direction of movement from the retracted towards the extended state (direction of arrow B), and is designed to push the cards stack outside the holder.

In fig. 4, illustrating the bottom end of the holder 1,
25 the housing is removed such that the eject elements within the housing are visible. The eject arm 16, which is viewed from its bottom, is pivoted to its second (extended) position, engaging the staggered cards stack 2 (only partly shown). Arm 16 is, by pivot 17, pivotably mounted to a fixture 10 which
30 is fixedly located in the housing opening opposite the card opening 3, thus providing the bottom edge as a closure of the housing.

Fig. 5 is the view when looking into the holder 1 from the entrance 3 and illustrates in side view the eject arm 16
35 located between the main sides 31. The height of the eject arm 16 stepwise increases from the free end 5 towards the pivot 17 by the steps that provide the contact faces 19. In the fig.

embodiment ten contact faces 19 are provided. The leading edge 6 faces towards the viewer of fig. 5. The mutual spacing of the components shown in fig. 7 is exaggerated for clarity.

As is clear from all fig. 1-5, the height of the ejector arm 16 stepwise decreases from the proximal (close to the pivot point 17) to the distal (free or remote) end 5. The maximum ejector arm 16 height equals the height of the housing determined by the clearance between the two main sides 31 of the housing which equals the maximum thickness of a cards stack tightly fitting in the housing. The maximum ejector arm 16 height could be slightly smaller to allow movement of the arm 16 within the housing without undue friction with the inner faces of the opposite housing main sides 31 along which the top and bottom side, respectively, of the arm 16 slide.

The opposite main side walls 31 have smooth, level and flat inner faces, extending mutually parallel.

Fig. 6 and 7 illustrate the eject arm 16 in its retracted (fig. 6) and extended (fig. 7) state, also illustrating the reset spring 20, the location 9 at which the spring 20 is mounted to the arm 16, and a by the fixture 10 provided upright wall 30 provided with a pivot feature 17 for hingedly mounting of the arm 16 to the fixture 10. The arm 16 is provided with twelve contact faces 19. Fig. 6 shows the leading edge 6, fig. 7 the opposite trailing edge 7.

Fig. 8 shows a top view of arm 16 of fig. 4 - 7. The present invention is embodied in the area A of fig. 8. This area A is detailed in fig. 9 and 10. The leading edge 6 tapers toward the trailing edge 7 in the arm longitudinal direction from the pivot 17 towards the free end 5.

Fig. 10 shows merely the outline of the in fig. 9 illustrated part of arm 16 and the adjacent edge of the stack of cards in the mutual relation just prior to starting ejecting the cards (arm 16 in the retracted position, cards stacked in mutual register completely inside the housing). As shown, the width of the arm 16 starts at C+D (left hand side of the drawing) and, longitudinally along the arm toward the free end 5, continuously decreases to D, since the leading edge 6 follows

a circular curved shape having radius R . The value of C is approximately 0.9 millimeter. This provides that, in the retracted state as fig. 10 shows, the part of the leading edge 6 near free end 5 is more remote from the facing edge of the card 2 within the housing 1, compared to the part of the leading edge 6 further away from the free end 5. Thus, at the start of the pivoting movement of arm 16 towards the extended state, engagement of contact faces 19 adjacent free end 5 is delayed such that loading of arm 16 gradually increases while the arm 16 rotates to eject the cards, adding to a comfortable operation of the holder while ejecting the cards. Arm 16 starts pushing outward cards 2 in area X and, due to progressive pivoting of arm 16 toward its extended state, this area increases progressively in direction Y, such that after arm 16 is pivoted approximately 15% of the stroke toward its extended state, area X has arrived at the free end 5 tip. This means, if arm 16 starts pushing cards 2, merely contact face 19 most to the left in fig. 9 pushes cards 2, and from then, due to progressive rotation of arm 16, each next contact face to the right in the drawing of fig. 9 is engaged in the process of pushing outward the cards 2 and finally the free end 5 tip is engaged, after which arm 16 rotates further toward its extended state while each card 2 is engaged and pushed by a private contact face 19.

At the pivoting start of arm 16, the first contact face 19 (most to the left in fig. 9) pushes all cards 2 of the stack simultaneously. Subsequently, as soon as the next face 19 to the right becomes engaged, the first contact face 19 merely pushes a single card (i.e. the first face 19 becomes the private face for this single card) and the next face 19 pushes the rest of the cards stack. Each time a next face 19 becomes engaged, this process of the previous face 19 becoming a private face 19 and the next face 19 pushing the remaining stack is repeated, until the remaining stack contains a single card.

It is appreciated that it is possible that a next face 19 is skipped or jumped by a card, e.g. depending on card thickness. Typically, the arm 16 is provided with more, e.g. at least two more, faces 19 compared to the maximum number of

cards for which the holder is designed (typically six or seven cards), to take account of skipping of jumping a face 19 by a card.

The present invention can also be applied to a different arm. The number of contact faces 19 can be more or less than the number shown in the drawing. In an alternative embodiment an indirect coupling is applied between the arm 16 and the button 18, e.g. by a rod hingedly coupled to the arm 16 and/or the button 18. Many other alternatives are also feasible.

10 The drawing, the specification and claims contain many features in combination. The skilled person will consider these also individually and combine them to further embodiments. Also different embodiments belong to the invention. Features of different in here disclosed embodiments can in different
15 manners be combined and different aspects of some features are regarded mutually exchangeable. All described or in the drawing disclosed features provide as such or in arbitrary combination the subject matter of the invention, also independent from their arrangement in the claims or their referral.

CLAIMS

1. A holder for cards, comprising a housing (1) which preferably tightly fits around a stack of at least three cards (2) and has at least one card opening (3) for locating and removing cards, while within the housing, preferably opposite the card opening (3), a card eject feature is provided such that the cards through the card opening (3) can be partly slid from the housing, which card eject feature comprises an ejector arm which is preferably designed to rotate within the housing between a retracted and an extended position and during said movement ejects the cards by engaging and forcing the cards simultaneously to partly exit the housing, and the holder comprises an external actuating feature, e.g. finger button, to provide the force to eject the cards by the card eject feature, which actuating feature is drivingly connected to the ejector arm through coupling means, wherein, viewed in the direction of pivoting of the arm from the retracted to the extended position, each next location or a group of locations or all locations is set back at least 0.05 or 0.075 millimeter relative to the adjacent location.
2. Holder according to claim 1, the ejector arm comprises several distal parts spaced along its length and each keeping a different initial distance, which initial distance is larger for a distal part closer to the free longitudinal end of the ejector arm.
3. Holder according to claim 1 or 2, wherein a or the initial distance measures at least 0.25 or 0.5 millimeter.

4. Holder according to any of claims 1-3, the leading edge (6) tapers towards the trailing edge (7) preferably according to a circular shape.

5. Holder according to any of claims 1-4, the arm (16) is designed such that at the start of ejecting the cards stack, cards are pushed and engaged by a shared contact face (19) of the arm and, after some movement of the arm (16) said cards (2) are pushed further outward by a relevant private contact face (19), possibly after an intermediate period of arm eject movement during which the cards one by one become engaged and pushed by a relevant private contact face (19).

6. Holder according to any of claims 1-5, wherein at the inner side of the housing a friction element is located which exerts a friction force to the side edge of each individual card within the housing, which friction element is of sufficient width/dimension to simultaneously engage all cards in the stack and/or is not rigid.

7. Holder according to any of claims 1-6, having one or more of the following features:

- the card eject feature comprises a stepped element (19), which can by the user be moved relative to the housing against the side of the within the housing present card stack, resulting that this stack in a stepped format partly moves outside the housing;
- the cards receiving space is sleeve or shaft like;
- the receiving space is designed such that the cards through the card opening parallel to their top face must be slid from this space;
- in the receiving space a stack of at least three right angled cards, mutually registered, with substantially

identical dimensions and each with a first side and an opposite second side, and the friction element in retaining engagement, in the direction of sliding out the card opening, with the to the friction element facing side of each card and the card sideways preloading such that the second side of each card is pressed against and retained by the side of the receiving space, while the distance between the first and second side of the one card is unequal to the same distance of a different card in the stack;

- a reset means, e.g. spring, biases the eject arm towards its retracted position.

8. Holder according to any of claims 1-7, wherein the part of the eject arm beyond the first location, viewed longitudinally along the eject arm from the pivot, comprises at least 50% of the eject arm length provided with the contact faces (19).

9. Holder according to any of claims 1-8, wherein the first location is provided at at least 25% of the eject arm length, measured from the pivot.

10. Holder according to any of claims 1-9, wherein the locations are provided on a curved line with a single radius, i.e. circle, of at least 150 millimeter, which line is provided by part of the leading edge of the eject arm, which is the edge that engages and pushes outward the cards stack, extends in longitudinal direction of the eject arm and nears toward the trailing edge of the eject arm viewed longitudinally from the pivot.

11. Holder according to any of claims 1-10, wherein the location (19) at the free end tip (5) is set back approximately

18

0.9 millimeter relative to the location (19) closest to the
pivot (17).