



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : C07C 2/64, 2/52, 2/66, 2/68, 5/22, 4/12, C10G 11/02, 35/06, B01J 29/06, 21/00, 21/02	A1	(11) International Publication Number: WO 00/12450 (43) International Publication Date: 9 March 2000 (09.03.00)
(21) International Application Number: PCT/US99/18472 (22) International Filing Date: 12 August 1999 (12.08.99) (30) Priority Data: 09/144,940 1 September 1998 (01.09.98) US (63) Related by Continuation (CON) or Continuation-in-Part (CIP) to Earlier Application US 09/144,940 (CON) Filed on 1 September 1998 (01.09.98) (71) Applicant (for all designated States except US): PHILLIPS PETROLEUM COMPANY [US/US]; 4th and Keeler, Bartlesville, OK 74004 (US). (72) Inventors; and (75) Inventors/Applicants (for US only): DRAKE, Charles, A. [US/US]; Route 1, Box 206, Nowata, OK 74048 (US). WU, An-hsiang [US/US]; 2609 Roanoke Ridge, Bartlesville, OK 74006 (US). YAO, Jianhua [CA/US]; Apartment 824, 1555 S.E. Kings Drive, Bartlesville, OK 74006 (US). LOVE, Scott, D. [US/US]; 1305 SW Westcliff Drive, Bartlesville, OK 74003 (US).		(74) Agents: RICHARDS, John; Ladas & Parry, 26 West 61st Street, New York, NY 10023 (US) et al. (81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>With amended claims.</i>
(54) Title: A COMPOSITION FOR USE IN CONVERTING HYDROCARBONS, ITS PREPARATION AND USE		
(57) Abstract A novel zeolite catalyst composition comprising a mixture of a zeolite, a binder, and a zinc borate compound wherein such mixture is calcined or treated with steam. Preferably, the zeolite has not been treated with an acid. Also provided is a process of making such composition, a product by such process, and the use thereof in the conversion of a hydrocarbon-containing fluid such as a gasoline-boiling range fluid or coker naphtha. Use of such zeolite in the conversion of a hydrocarbon-containing fluid also includes pre-treating such hydrocarbon-containing fluid with a nitrogen removal medium such as ion-exchange resin.		