

Description:

Spectacle lens and method for producing same

- 5 The invention relates to spectacle lenses according to the preamble of patent claims 3 to 7, and a method for producing a spectacle lens according to the preamble of patent claim 1.

Spectacle lenses are known in many variations from the prior art. There are spectacle lenses without nominal dioptric power and correction spectacle lenses, that is to say spectacle lenses
10 having dioptric power. Dioptric power is the collective term for the focusing and the prismatic power of a spectacle lens.

In the case of correction spectacle lenses, a distinction is drawn between single-vision spectacle lenses and multifocal spectacle lenses. A single-vision spectacle lens is a spectacle lens in which
15 only one dioptric power is present in respect of the design. A multifocal spectacle lens is a spectacle lens in which two or more visibly different parts having different focusing powers are present in respect of the design. Importance is attached in particular to bifocal spectacle lenses, namely multifocal spectacle lenses comprising two parts, usually for distance vision and near vision, and to varifocal spectacle lenses, namely spectacle lenses comprising at least one
20 progressive surface and an increasing (positive) power when the wearer of the spectacles looks down. Degressive spectacle lenses are uncommon, i.e., spectacle lenses comprising at least one progressive surface and a decreasing power (i.e. an attenuation of the power) when the wearer of the spectacles looks down.

25 What form must be obtained by the spectacle lens in order to obtain the desired optical correction is decisively determined by the material thereof. Here, the most important parameter is the refractive index of the material. While spectacle lenses were predominantly produced from mineral glasses in the past, in particular crown glasses (Abbe number >55) and flint glasses (Abbe number <50), spectacle lenses from a multiplicity of organic materials have become
30 available in the meantime. Such base materials for organic spectacle lenses are offered, inter alia, under the trade names CR 39, MR 8, MR 7, CR 330 and MR 174. A selection of such base materials is also found in the published specification EP 2692941 A1. Other materials are continuously being tested and developed in respect of the suitability thereof for organic spectacle

lenses. Table 1, below, elucidates characteristic variables and reference variables of a selection of known base materials:

Table 1: Base materials for the production of spectacle lenses

Trade name	Base material	Average refractive index n_e	Abbe number v_e
CR 39 CR 330 CR 607 CR 630	Poly allyl diglycol carbonate	1.500	56
Trivex	Polyurea / Polyurethane	1.530	45
PC	Polycarbonate	1.590	29
MR 6	Polythiourethane	1.598	
MR 8	Polythiourethane	1.598	41
MR 7	Polythiourethane	1.664	32
MR 10	Polythiourethane	1.666	32
MR 174	Polyepisulfide	1.738	32
	Mineral 1.5	1.525	58
	Mineral 1.6	1.604	44

5

Currently, a large number of organic spectacle lens semifinished products or spectacle lens finished products with spherical, rotationally symmetric aspherical or progressive front surfaces are cast in mass production in prototypes with front and back surface form shells, which are spaced apart from one another by means of a sealing ring, forming a cavity in the process, as described in e.g. the documents DE 30 07 572 C2, US 6,103,148 A or JP 2008 191186 A. This applies to base materials with the trade names MR 7, MR 8, MR 10 and CR 39, CR 607, CR 630, et al. The base materials with the trade names MR 7, MR 8, and MR 10 are polythiourethanes marketed by Mitsui Chemicals. The abbreviation “MR” here stands for Mitsui Resin. CR 39 or Columbia Resin 39 is the brand name selected by Pittsburgh Plate Glass Industries (PPG Industries) under which the material poly diethylene glycol bis allyl carbonate or poly allyl diglycol carbonate (abbreviation: PADC) is marketed. This is a thermosetting polymer material. CR 607 and CR 630 are also produced by PPG.

10

Semifinished products or finished products for spectacle lenses made out of polycarbonate are generally produced in metal forms by means of an injection molding technique. This production method is described in e.g. EP 0955147 A1. A semifinished product is understood to be a spectacle lens blank with surface whose treatment has finished and whose form is no longer modified in further production steps. As a rule, the opposite surface of a semifinished product

20

obtains its final form by means of a material-ablating method. A finished product is a spectacle lens blank in which both surfaces already have obtained their final form.

Mineral spectacle lenses are generally produced by machine-based mechanically abrasive
5 machining of a blank.

The semifinished products or finished products described above are often subjected to one or more finishing processes. In particular, functional layers are applied to one or both sides. Such functional layers are layers which equip the spectacle lenses with predetermined properties,
10 which are advantageous to the spectacle wearer and which the spectacle lenses would not have purely on the basis of the properties of the base or carrier material, onto which the functional layers are applied where necessary, and the forming. In addition to optical properties, such as an antireflection coating, silvering, light polarization, coloring, self-tinting etc., such advantageous properties also include mechanical properties, such as hardening, reduction of the adherence of
15 dirt or reduction in steaming up, etc., and/or electrical properties such as shielding from electromagnetic radiation, conduction of electrical current, etc., and/or other physical or chemical properties. Examples of functional coatings are gathered e.g. from the documents WO 10/109154 A1, WO 01/55752 A1 and DE 10 2008 041 869 A1.

Order-specific prescription spectacle lenses, i.e., in particular, individualized single vision and multi-focal lenses, the optical properties of which are not standardized in a preselectable manner, at least in part, but rather are individually calculated and manufactured in a manner adapted to the user in relation to the dimensions and/or the arrangement thereof on the spectacle lens, and, in particular, varifocal or progressive lenses are brought into their final form by mechanical, in
25 particular deforming and/or abrasive, methods. Here, the outer forms may have a round, oval or arbitrary embodiment, describing so-called free-forms in the latter case.

These days, high-quality spectacle lenses with individually adapted dioptric power are produced in a prescription manufacturing site that is designed to this end, a so-called Rx lab (Rx is the
30 abbreviation for recipe), by means of subtractive manufacturing methods from semifinished products (abbreviated HF in German). The finished product is defined by two optical surfaces that have varying distances from one another depending on strength or dioptric power, material and regulations. The two optical surfaces are continuous as a consequence of the generally used free-form manufacturing methods. The exceptions to this rule, the embedded near-region areas in

the case of bifocal and trifocal lenses, must already be introduced in the front side during the casting process in the case of polymer lenses. There are also corresponding spectacle lenses with near-region areas formed in protruding fashion on the back side.

- 5 The near region and far region are spatially separated from one another in current spectacle lenses with a plurality of strengths or optical powers, namely in the case of bifocal lenses, trifocal lenses and multifocal lenses, in particular varifocal lenses. In particular, this is always bothersome if the spectacle wearer wishes to see in the near region but high in front of the head or in the far region through the lower part of the spectacles.

10 In terms of design freedom, the current market for spectacle frames is very dependent on the forms and sizes of spectacle lenses that can be supplied by their producers. The diameter and the thickness of the semifinished products which decide whether a spectacle lens can still be manufactured because it fits in the semifinished product – or not, as the case may be – are particularly decisive. Here, the limits of conventional mass production can be significantly expanded because casting of the semifinished products in predetermined shell molds is dispensed with.

20 In the case of the spectacle lenses currently produced in mass production, the refractive index is uniform and constant independently of location, and so the thickness of the spectacle lens significantly increases toward the edge (in the case of myopic or near-sighted patients) or toward the center (in the case of hyperopic or far-sighted patients) in the case of significant corrections. This is unattractive from a cosmetic point of view, particularly in the first case because the large edge thickness is conspicuous.

25 The following inherent properties of mass-produced spectacle lenses, which are even present in the case of high-quality products, are perceived as bothersome:

1. The macroscopic spatial separation of near region and far region
- 30 2. The unavoidably occurring astigmatic distortions toward the edge in the case of a smooth transition from the far region into the near region in varifocal lenses according to Minkwitz's theorem.
3. The discontinuous or discontinuously differentiable optical surfaces that are only realizable with significant outlay.

4. The cosmetically unattractive edge, as it is visible, between main lens and segment in the case of non-progressive multifocal lenses, such as in the case of bifocal or trifocal lenses, for example.

5. The unaesthetic large edge thickness, as it is visible, in the case of spectacle lenses with a strong dioptric power; high prism values, in particular, lead to a thick edge of the spectacle lens in the case of myopic humans.

6. The restrictions relating to the producibility of corrective spectacles in the case of form prescriptions for the spectacle lens front surface and/or the spectacle frame that are considered aesthetic; current spectacle lenses are very significantly restricted in view of the outer form as a result of the production method and the shape of the frames and a correspondingly small freedom of design follows therefrom. Within the scope of currently existing restrictions, products such as the Nike Vaporwing Elite are practically not producible with optical power but only as 0 dpt sunglasses.

The prior art has disclosed different approaches for improving spectacle lenses in view of the aforementioned properties that are perceived as bothersome. Particularly in this context, it is known that so-called digital fabricators, in particular, offer manufacturing options for virtually any structure, said structures not being realizable or only being realizable with difficulty using conventional abrasive methods. Within the digital fabricator machine class, 3D printers represent the most important subclass of additive, i.e., accumulating, building fabricators. The most important techniques of 3D printing are selective laser melting (SLM) and electron-beam melting for metals and selective laser sintering (SLS) for polymers, ceramics and metals, stereolithography (SLA) and digital light processing for liquid artificial resins and multijet or polyjet modeling (e.g., inkjet printers) and fused deposition modeling (FDM) for plastics and, in part, artificial resins. A few approaches with which transmission optical units are produced with the aid of additive methods are sketched out below.

DE 10 2009 008 997 A1 proposes light-guiding structures that consist of a multiplicity of miniaturized elements, proceeding from a reference to spectacle lenses in which portions have different light-refractive power. Each element consists of a multiplicity of droplets made of a light-transmissive or transparent material, said droplets being deposited on a substrate with a plane delimiting surface and the approximately hemispherical arching of said droplets projecting from the substrate. The droplets have different diameters such that each element with the multiplicity of droplets forms a miniaturized partial prism or partial lens or any other particular

optical unit. Further, a method for producing light-guiding structures on a light-transmissive or transparent substrate can be gathered from the document. Transparent or translucent printing ink is applied onto the substrate in droplet form by means of inkjet printing. Here, droplets of the same and different size are applied for the purposes of producing miniaturized light-guiding elements, with a plurality of such elements that together form the light-guiding structure such as a prism or a lens being applied next to one another.

WO 2010/091888 A1 also describes an optical element, in which light-guiding structures and, in particular, an optical prism are applied to a transparent substrate with the aid of a 3D printing method, namely using a “drop on demand” inkjet printer (DOD inkjet printer) in particular, and a method for the production thereof. It also states that DE 10 2005 039 113 A1 has already described the application of cylindrical microlenses on a substrate with the aid of a microjet printing method. By way of example, silicone, a mixture of silicone and acrylic, an epoxy-modified cationic UV curable silicone are proposed as printing material for producing optical elements in WO 2014/108364 A1

Proceeding from a single vision spectacle lens finished product, EP 2 878 989 A1 proposes the production of a progressive spectacle lens with the aid of a 3D printing method.

WO 2015/014381 A1 describes the use of additive manufacturing processes, such as, e.g., stereolithography (SLA), inkjet printing, selective laser sintering (SLS), selective laser melting (SLM) or fused deposition modeling (FDM) for producing transparent ophthalmic lenses. The document describes the production of such lenses by stringing together volume elements (voxels) with an extent of between 0.1 μm and 500 μm , which form a three-dimensional grid, in a direction in a predetermined arrangement which, for example, can be defined in a CAD (computer aided design) file. Each volume element (voxel) consists of a composition with at least one polymer or pre-polymer or monomer. A connectivity between the volume elements (voxels) is established in each case by forming a chemical or mechanical bond. As suitable polymers, the document specifies polyolefinics such as cyclo olefin polymers, polyacrylates such as polymethyl(meth)acrylate, poly(meth)acrylate, polyethyl(meth)acrylate, polybutyl(meth)acrylate, polyisobutyl(meth)acrylate, polyesters, polyamides, polysiloxanes, polyimides, polyurethanes, polythiourethanes, polycarbonates, polyallylics, polysulfides, polyvinyls, polyarylenes, polyoxides, and polysulfones, and blends thereof. As suitable monomers or pre-polymers, the document specifies olefinics, acrylics, epoxides, organic acids,

carboxylic acids, styrenes, isocyanates, alcohols, norbornenes, thiols, amines, amides, anhydrides, allylics, silicones, vinyl esters, vinyl ethers, vinyl halides, and episulfides. The monomers or pre-polymers can be thermally curable or curable in radiation-induced fashion. Photoinitiators and, optional, co-photoinitiators can be used for radiation-induced curing.

5

H.-J. Trost et al., Proc. 2001 Ann. Mtg. ASPE, 10-15 Nov. 2001 (ASPE, Raleigh, NC 2001) pp. 533-536 propose, for example, the production of spectacle lenses with refractive index gradients, so-called GRIN (gradient index of refraction) spectacle lenses with the aid of drop-on-demand (DOD) technology. This technology is an inkjet printing method, in which ink droplets are applied in metered fashion through a nozzle. The desired variation in the refractive index is achieved by using different optical ink materials. After printing, the applied optical ink material is cured thermally or by UV light. The document shows the option of producing lenses with a radial and/or axial refractive index gradient.

10

15 WO 2015/102938 A1, too, describes the production of lenses from volume elements (voxels) with the aid of a 3D printing method. Layers with different dielectric materials are stacked and GRIN optical units are produced in this fashion.

20

Furthermore, WO 2014/179780 A1 describes the production of GRIN optical units by means of 3D printing for the purposes of producing optical GRIN structures with little dispersion. The gradient of the refractive index is produced by way of varying the nanoparticle concentration in the organic matrix. As possible materials for these nanoparticles, ZnS, ZrO₂, ZnO, BeO, AlN, TiO₂, SiO₂ are. According to the specification in the document, the organic matrix can consist of, e.g., di(ethylene glycol) diacrylate, neopentyl glycol diacrylate, hexanediol diacrylate, bisphenol A novolak epoxy resin (SU8), 2-hydroxyethylmethacrylate (HEMA), polyacrylate, polymethacrylate, polymethyl methacrylate (PMMA), styrene, and poly[(2,3,4,4,5,5-hexafluorotetrahydrofuran-2,3-diyl)(1,1,2,2-tetrafluoroethylene)] (CYTOP).

25

30 Although spectacle lenses that meet the needs of the aesthetical perception of many people can be produced using various methods, there is a need for further improvement.

JP 2004 157487 A describes a bifocal lens that is assembled from a plurality of sets of microlenses. Each of the sets of microlenses has a fixed focus or a fixed refractive index. It is possible to switch between the sets of microlenses with the aid of a liquid crystal arrangement.

- 5 JP 2003 029216 A describes reading spectacles. The back surfaces of the spectacle lenses of these reading spectacles have local changes of curvature in the near part and, optionally, in an intermediate region situated between the near part and far apart. There are groups of similarly curved hexagonal back surface segments that are arranged nested in one another. Each of the groups provides a different focal length.

10

JP H05 313 107 A describes a contact lens that is manufactured from a rod that consists of a bundle of fibers. There are a number of groups of fibers. All fibers in one group have the same refractive index. The fibers of different groups differ in terms of their refractive index. A microlens in the finished contact lens emerges from each fiber. On account of the production
15 process, the contact lens consists of a plurality of groups of microlenses that are arranged nested within one another. Each microlens group provides a focal plane on account of the uniform refractive index within the group, said focal plane differing from the focal plane of every other group.

- 20 The object of the invention consists of providing a method for producing a spectacle lens, in which there is an improvement in at least one of the aforementioned factors of conventional spectacle lenses that are perceived as bothersome.

The object of the invention consists further of providing a spectacle lens, in which there is an
25 improvement in at least one of the aforementioned factors of conventional spectacle lenses that are perceived as bothersome.

The method-related object is achieved by a method having the features of patent claim 1 for producing a spectacle lens. The product-related object is achieved by a spectacle lens which
30 selectively has the features of any one of patent claims 3 to 7. Advantageous embodiments and developments of the invention are the subject matter of the dependent claims.

What is common to all variants according to the invention is that the respective spectacle lens comprises at least two volume element groups, namely a first volume element group which

comprises a plurality of first volume elements, wherein the plurality of first volume elements are arranged in the style of grid points of a geometric grid so as to form a first partial grid and wherein the first volume elements together form a first part of the spectacle lens, said first part of the spectacle lens having the dioptric power for vision at a first object distance. Further, the
 5 spectacle lens comprises a second volume element group, which correspondingly comprises a plurality of second volume elements, wherein the plurality of second volume elements are arranged in the style of grid points of a geometric grid so as to form a second partial grid and wherein the second volume elements together form a second part of the spectacle lens, said
 10 second part of the spectacle lens having the dioptric power for vision at a second object distance that differs from the first object distance. In all variants of the spectacle lens according to the invention, the first partial grid and the second partial grid are arranged within one another (e.g., displaced or offset), penetrating one another in each case.

In geometry, a grid is a complete and overlap-free partition of a region of the space by a set of
 15 grid cells. The grid cells are defined by a set of (fictitious or imaginary) grid points which are interconnected by a set of (fictitious or imaginary) grid lines.

The first and the second partial grid penetrating one another means that the first partial grid and the second partial grid together have a space in common without coinciding in their entirety.
 20 Within the scope of the present invention, displaced within one another in penetrative fashion means an arrangement in the style of a zinc blend structure, for example, which can be described as a combination of two cubic face-centered partial lattices placed within one another, which are arranged displaced by $1/4$ of the space diagonal in relation to one another. Additionally, (single-
 25 ply) layer lattices, which are displaced in relation to one another by a certain dimension of a vector lying in the layer surface, should also be comprised. The two first and second partial grids need not have identical form either. Rather, what is decisive is that the two first and second partial grids provide no macroscopic spatial separation of the dioptric power for vision at different object distances.

30 The first part of the spectacle lens, which provides the dioptric power for vision at a first object distance, can correspond to the near region, for example, and the second part of the spectacle lens, which provides the dioptric power for vision at a second object distance, can correspond to the far region of a conventional spectacle lens, for example. Accordingly, the arrangement according to the invention of the first and second partial grids provides a three-dimensional

structure, in which the far and near regions, as it were, are present virtually nested within one another. Naturally, the first object distance can also be the usual eye-screen distance and the second object distance can be the customary reading distance. Such spectacle lenses are suitable for office work or the like.

5

Accordingly, the first part and the second part of the spectacle lens represent coinciding surface regions of the spectacle lens, through which the spectacle wearer looks in the case of intended use. Typical surface dimensions of these regions lie between 0.3 cm² and 7 cm², preferably between 0.5 cm² and 6 cm², further preferably between 0.8 cm² and 5 cm² and, finally, even more preferably between 1 cm² and 4 cm².

10

In the case of an appropriate embodiment, the spectacle lens can be distinguished in that

- no visible bifocal or trifocal regions are present,
- there is no need for a progression channel of varifocal spectacles and consequently all individualization parameters connected therewith become obsolete (progression channel length, inset, frame shape, varifocal profile, balance of the image aberration distribution that is unavoidable in the case of conventional varifocal lenses),
- the addition (the difference between the two foci) remains untouched, wherein the number of foci is only restricted by the number of different, individually set voxels (first, second and optional further volume element groups),
- the following parameters, inter alia, can remain untouched: vertex distance (abbreviated HSA in German), pantoscopic tilt and face form angle, provided this is desired.

15

20

25

Untouched means that these parameters such as addition, vertex distance, pantoscopic tilt and face form angle are taken into account when designing the spectacle lenses according to the invention in exactly the same way as in the case of conventional spectacle lenses according to the prior art.

30

In addition to these obvious applications in the field of varifocal and multifocal lenses, the described embodiment offers approaches for reducing the cosmetic problems of single vision lenses. To this end, it is possible to introduce the optical correction no longer exclusively by way of the relative position of the optical surfaces with a constant refractive index being taken into

account, as is the case in conventional spectacle lenses of the above-described type in the prior art.

The volume element groups according to the invention are produced with the aid of an additive manufacturing method. Specifically, the method according to the invention for producing a spectacle lens comprises the following steps:

- additive manufacturing of a first volume element group, wherein the first volume element group comprises a plurality of first volume elements, wherein the plurality of first volume elements are arranged in the style of grid points of a geometric grid so as to form a first partial grid, wherein the first volume elements together form a first part of the spectacle lens, said first part of the spectacle lens having the dioptric power for vision at a first object distance,

- additive manufacturing of a second volume element group, wherein the second volume element group comprises a plurality of second volume elements, wherein the plurality of second volume elements are arranged in the style of grid points of a geometric grid so as to form a second partial grid, wherein the second volume elements together form a second part of the spectacle lens, said second part of the spectacle lens having the dioptric power for vision at a second object distance that differs from the first object distance.

According to the invention, the method is characterized in that the first partial grid and the second partial grid are arranged within one another (e.g., displaced or offset), penetrating one another in each case, during the additive manufacturing.

The method steps of additive manufacturing of the first volume element group and additive manufacturing of the second volume element group should not necessitate the first volume element group being completed first and the second volume element group being completed thereafter. Rather, one or more volume elements of the first volume element group can be initially produced additively, followed in turn by one or more volume elements of the second volume element group, then by one or more volume elements of the first volume element group again, etc., until the two volume element groups are completed in the arrangement according to the invention in a manner corresponding to two partial grids displaced within one another in penetrative fashion.

Additive manufacturing (AM), or additive manufacturing methods, is a comprehensive label for the methods, previously often referred to as rapid prototyping, for fast and cost-effective manufacture of models, patterns, prototypes, tools and end products. This manufacture is implemented directly on the basis of computer-internal data models from formless (e.g., liquids, powder and the like) or form-neutral (band-shaped, wire-shaped) material by means of chemical and/or physical processes. Although these are primary forming methods, no special tools that have stored the respective geometry of the workpiece (e.g., molds) are required for a specific product. The current prior art is conveyed by the VDI Statusreport AM 2014. An overview of current 3D printing methods is provided by <https://3druck.com/grundkurs-3d-drucker/teil-2-uebersicht-der-aktuellen-3d-druckverfahren-462146/>, retrieved on July 13, 2016.

The method of multijet modeling or polyjet printing was found to be particularly suitable. This method is described, for example, at the URL https://de.wikipedia.org/wiki/Multi_Jet_Modeling, the URL <http://www.materialise.de/3d-druck/polyjet> or the URL <http://www.stratasys.com/de/3d-drucker/technologies/polyjet-technology>, respectively retrieved on July 13, 2016. Polyjet is a powerful 3D printing technology, by means of which smooth, precise components, prototypes and production aids can be produced. Thanks to microscopic layer resolution and an accuracy of up to 0.1 mm, thin walls and complex geometries can be produced thereby from the most comprehensive spectrum of materials available for each technology. The polyjet 3D printer has a similar operation to that of an inkjet printer. However, instead of spraying ink droplets onto paper, polyjet 3D printers spray layers made of a crosslinkable, liquid photopolymer onto a construction platform. The method is comparatively simple: In a first preparation step, the preparation software automatically calculates the placement of the photopolymer and of the support material (i.e., a material that only serves during the 3D printing for positioning and supporting the photopolymer until the latter is cured) on the basis of a 3D CAD file. During the actual production, the 3D printer sprays tiny droplets of liquid photopolymer and immediately crosslinks these by means of UV light. Thus, fine layers accumulate on the building platform, one or more precise 3D models or 3D parts arising therefrom. If overhanging or complex forms have to be supported, the 3D printer sprays a removable support material. The user can easily remove the support material by hand, with water or in a solvent bath. The models and components can preferably be processed and used directly from the 3D printer, without having to post-harden.

The Stratasys (Objet) Eden 260 V 3D printer, in particular, is suitable for the application according to the invention. The materials referred to above in the introductory part of the description and, in particular, specified in documents WO 2014/179780 A1 and WO 2015/014381 A1 are suitable for use in the method according to the invention. By way of

5 example, suitable polymers for the first and second volume elements are polyolefinics such as cyclo olefin polymers, polyacrylates such as polymethyl(meth)acrylate, poly(meth)acrylate, polyethyl(meth)acrylate, polybutyl(meth)acrylate, polyisobutyl(meth)acrylate, polyesters, polyamides, polysiloxanes, polyimides, polyurethanes, polythiourethanes, polycarbonates, polyallylics, polysulfides, polyvinyls, polyarylenes, polyoxides, and polysulfones, and blends

10 thereof. Olefinics, acrylics, epoxides, organic acids, carboxylic acids, styrenes, isocyanates, alcohols, norbornenes, thiols, amines, amides, anhydrides, allylics, silicones, vinyl esters, vinyl ethers, vinyl halides, and episulfides can be considered to be monomers or pre-polymers that are suitable as printed material for producing the first and second volume elements. The monomers or pre-polymers can be thermally curable or curable in radiation-induced fashion. Photoinitiators

15 and, optional, co-photoinitiators can be used for radiation-induced curing.

As described above, the first and second volume elements can also consist of an organic matrix to which nanoparticles have been added. The organic matrix can consist of, e.g., di(ethylene glycol) diacrylate, neopentyl glycol diacrylate, hexanediol diacrylate, bisphenol A novolak

20 epoxy resin (SU8), 2-hydroxyethylmethacrylate (HEMA), polyacrylate, polymethacrylates, polymethyl methacrylate (PMMA), styrene, and poly[(2,3,4,4,5,5-hexafluorotetrahydrofuran-2,3-diyl)(1,1,2,2-tetrafluoroethylene)] (CYTOP).

Possible materials for the nanoparticles are ZnS, ZrO₂, ZnO, BeO, AlN, TiO₂ und SiO₂, for

25 example.

The method-specific problem presented at the outset is solved in its entirety by such a method according to the invention for producing a spectacle lens.

30 With these words, reference is made to the fact that the invention is not restricted to only a penetrative arrangement of two partial grids. Rather, it is also possible to realize more than two partial grids for corresponding different object distances. However, it was found to be advantageous to restrict the number of different partial grids to no more than 5, preferably no

more than four or else no more than 3 because the human brain otherwise does not allow focused perception, or only allows this with difficulties.

5 The product-related problem specified above can be solved by one of the variants specified below: the starting product is always a spectacle lens having the features specified below:

10 The spectacle lens according to the invention comprises a first volume element group which comprises a plurality of first volume elements, wherein the plurality of first volume elements are arranged in the style of grid points of a geometric grid so as to form a first partial grid and wherein the first volume elements together form a first part of the spectacle lens, said first part of the spectacle lens having the dioptric power for vision at a first object distance. Further, the spectacle lens comprises a second volume element group, which correspondingly comprises a plurality of second volume elements, wherein the plurality of second volume elements are arranged in the style of grid points of a geometric grid so as to form a second partial grid and
15 wherein the second volume elements together form a second part of the spectacle lens, said second part of the spectacle lens having the dioptric power for vision at a second object distance that differs from the first object distance. The first partial grid and the second partial grid are arranged within one another (e.g., displaced or offset), penetrating one another in each case.

20 The first variant of the invention consists of the first partial grid having a three-dimensional embodiment and/or the second partial grid having a three-dimensional embodiment. There is an interaction that increases with the number of layers between the first and second parts as a result of the three-dimensional design of one or both partial grids, said interaction intending to be designed for in-focus vision at different object distances. Details are explained below in
25 conjunction with the description relating to figure 4. However, what is achieved in principle is that light on its passage through the spectacle lens is not only refracted twice, at the front surface and back surface, but refracted repeatedly at each interface between the partial grids, albeit by smaller angle in each case. Consequently, it is possible to optimize the light path through the spectacle lens individually, tailored to the user. Here, the light path can be influenced at the local
30 level and relatively large light beams, which remain tightly connected in conventional systems, can be split and controlled more precisely in smaller beams.

The second variant of the invention assumes that the first volume elements each have a first surface element and the second volume elements each have a second surface element. Here, a

surface element should be understood to mean an optical surface through which light beams emanating from an object have to pass in order to reach the eye. All surface elements that together form the front or back surface of the spectacle lens are special cases. This front or back surface and, accordingly, also the surface elements forming these may optionally also be coated.

- 5 The surface elements can also form internal interfaces to a carrier or to surface elements of other volume elements.

This second variant of the invention is characterized in that respectively one of the first surface elements of the first volume elements of the first volume element group and respectively one of
10 the second surface elements of the second volume elements of the second volume element group, which adjoin one another, are arranged at an angle to one another or arranged so as to form a step. Details are explained below in conjunction with the description relating to figure 5. However, what is achieved in principle is that two volume element groups with different focal spots are realized within a physically contiguous spectacle lens and that no bifocal lenses with
15 their clearly visible edge in the visual field are required. Moreover, it is possible to dispense with the progression channel of the varifocal lenses which, with its continuous change of the optical power, necessarily has astigmatic distortions at the edge of the spectacle lens as a consequence. As a consequence, small edges arise between the surfaces of the volume element groups, said edges being significantly less conspicuous to the observer than known solutions.

20

The third variant of the invention proceeds from the two following configurations, which may also be present cumulatively:

- (i) the first volume elements each have a first surface element of the above-described type and the second volume elements accordingly each have a second surface
25 element and
- (ii) the first volume elements consist of a first material and the second volume elements consist of a second material that differs from the first material.

According to the invention, provision is made for a transition between one of the first volume
30 elements and an adjoining one of the second volume elements to be implemented by gradual change in the material and/or by gradual change of an orientation of the respectively adjoining first and second surface elements of the adjoining first and second volume elements. While there is a jump from one focus to the next in the second variant of the invention, this change is implemented gradually, as a rule, in the third variant of the invention. Further details are

summarized in the last four portions of the description. However, what is achieved in principle is that the remaining edges in the optically effective surface, as can be observed in the third variant, can be reduced further in this embodiment and hence further improvements are obtained in the cosmetic properties. Additionally, gradual changes between the volume element groups lead to a reduced formation of stray light at the various interfaces between the volume element groups. Calculating the individual volume element groups and setting the respective refractive indices is significantly more complicated than in the second variant, and so more computational power must be available for the design.

The fourth variant consists of a smoothing hard coat being arranged on the first volume element group and the second volume element group. A smoothing hard coat is understood to mean a layer that reduces the surface roughness and surface structures of the spectacle lens substrate.

With this smoothing hard coat, the spectacle lens preferably has a surface roughness Ra of <10 nm. Further preferably, the surface roughness Ra of the spectacle lens over all optical surfaces in each case lies in a range of 1.0 nm to 8.0 nm, particularly preferably in a range of 3.0 nm to 7.0 nm and very particular preferably in a range of 4.0 nm to 6.0 nm. The aforementioned values for the surface roughness Ra in each case related to the front surface and back surface of the spectacle lens. The surface roughness Ra in relation to the completed spectacle lens is preferably determined by means of white-light interferometry, preferably using the NewView 7100 (Zygo Corporation) appliance.

The composition of the smoothing hard coat can contain at least one silane derivative $(R^4O)Si(OR^1)(OR^2)(OR^3)$, wherein R^1, R^2, R^3, R^4 can be the same or different from one another, substituted or unsubstituted and R^1, R^2, R^3, R^4 can be selected from the group consisting of alkyl, acyl, alkyleneacyl, cycloalkyl, aryl and alkylenearyl. Alternatively or additionally, the composition of the smoothing hard coat can contain at least one silane derivative $R^6R^7_{3-n}Si(OR^5)_n$, wherein R^5 can be selected from the group consisting of alkyl, acyl, alkyleneacyl, cycloalkyl, aryl and alkylenearyl, R^5 can be substituted or unsubstituted, R^6 is an organic radical, which comprises an epoxide group, R^7 can be selected from the group consisting of alkyl, cycloalkyl, aryl and alkenylaryl, R^7 can be substituted or unsubstituted. Further examples of such smoothing hard coats can be found in EP 2 578 649 A1, DE 10 2005 059 485 A1 and EP 2 385 086 A1. In principle, this renders the structure consisting of different volume elements to be inconspicuous or less conspicuous to the observer from the outside while the

spectacle lens is provided with scratch resistance. The cosmetic smoothing properties of this variant are particularly important if the optical system is based on the parameters with sharp edges and jump-like changes described in variant number two. A further advantage lies in the improved cleanability of the coated surface since fewer trenches, in which dirt can accumulate, are present. Compared to the uncoated variant, further advantages arise within the scope of applying a stamp figure (centering cross, measurement circles, etc.), which, optionally, can further be printed onto the spectacle lens surface by pad printing or inkjet printing methods.

The fifth variant of the invention is characterized in that the first volume element group and the second volume element group are arranged on a surface of a carrier that has a (spatial) refractive index gradient. As described in the introductory part of the description, a refraction gradient offers the possibility of producing a desired dioptric power of a body that has little dependence on the geometric form thereof. This allows the spectacle lens to have a thinner embodiment overall than if use were made of a carrier with a spatially constant refractive index. In a region in which the first volume element group and the second volume element are arranged, the thickness of the carrier is preferably between 0.1 and 5 mm, further preferably between 0.5 and 3 mm, most preferably between 1 and 2 mm.

The product-related problem posed at the outset is solved in its entirety by each of the above-described five variants.

The variants of the invention described below also can be combined in any way, as illustrated in detail below in an exemplary fashion.

In principle, it is possible for the first and second volume elements to consist of the same material. The provision of different dioptric powers for sharp vision at different object distances is then determined or set by the respective surface geometry of the individual first and second volume elements and/or the relative position and alignment of the individual first and second volume elements in relation to one another and/or the external geometry of the grid comprising the two first and second partial grids. Firstly, the term surface geometry comprises both surface area and surface form, in particular also the local curvature of the surface of the respective volume element.

According to the explanations made above, it is alternatively possible for the first volume elements to consist of a first material and for the second volume elements to consist of a second material that differs from the first material. The provision of different dioptric powers for sharp vision at different object distances then can be determined or set not only by the respective surface geometry of the individual first and second volume elements and/or the relative position and alignment of the individual first and second volume elements in relation to one another and/or the external geometry of the grid comprising the two first and second partial grids but also by the different light-refractive properties of the respective first and second volume elements. Particularly when the first material has a first refractive index and the second material has a second refractive index that differs from the first refractive index, it is not only the orientation of the optically effective surfaces of the volume elements that play a role, but also the refractive powers thereof. The restriction of the forming in respect of an aesthetic perception is largely removed or at least significantly reduced in comparison with conventional spectacle lenses. The use of an additive manufacturing method, in particular the use of the multijet or polyjet printing/modeling allows the realization of discontinuous and/or discontinuously differentiable optical surfaces with little outlay. The macroscopic spatial separation of, for example, near and far region (in general: a first object distance range and a second object distance range) is dispensed with and, connected therewith, the astigmatic distortions occurring toward the edge in the case of varifocal lenses of the conventional type are dispensed with.

If use is made of materials with different refractive indices for realizing the first and second volume elements, it is possible to produce the dioptric powers for the different object distances by arranging the first and second volume elements so that these together yield a smooth, optionally even plane surface which, when the spectacle lenses or the spectacles with the spectacle lens according to the invention are used as intended, is aligned either in the direction of the object (i.e., optionally provided with a coat, forming the front surface of the spectacle lens) and/or in the direction of the eye (i.e., optionally, provided with a coat, forming the back surface of the spectacle lens). By contrast, if use is made of materials with the same refractive indices or if use is even made of identical materials for the purposes of realizing the first and second volume elements, the surfaces of the first and second volume elements will have different orientations in relation to one another at the locations at which two different volume elements adjoin one another in order to obtain the property according to the invention of providing a macroscopic spatial unification of the regions for different object distances. In particular, in this case, the invention can be characterized in that the first volume elements each have a first surface

element and in that the second volume elements each have a second surface element and in that respectively one of the first surface elements and respectively one of the second surface elements, which adjoin one another, are arranged at an angle to one another.

5 To summarize, the transition between a first volume element and a second volume element can be implemented in discontinuous fashion by way of a jump-like change in the material and/or jump-like change in the orientation of the respective surface elements, adjoining one another, of neighboring volume elements.

10 As an alternative, the transition between a first volume element and a second neighboring volume element can also be implemented in a gradual or smooth fashion, with similar properties to the progression channel in conventional varifocal lenses. This can be implemented accordingly by a gradual change in the material and/or a gradual change in the orientation of the respective optical surface of the neighboring volume elements.

15 The first partial grid can have a two-dimensional embodiment. As an alternative or in addition thereto, the second partial grid can have a two-dimensional embodiment. Within the scope of the present application, a two-dimensional embodiment of a (partial) grid should be understood to mean a single-ply layer grid. Expressed differently, all volume elements forming the (partial)
 20 grid should lie in a plane. In the case where both partial grids have a two-dimensional embodiment, it is possible that a grid comprising the first partial grid and the second partial grid once again forms a two-dimensional grid, namely if the two partial grids are displaced in relation to one another in the above-described plane. By way of example, the two partial grids can be present in the style of a checkerboard-like structure, in which the light squares of the
 25 checkerboard are imagined to correspond to the first volume elements of the first partial grid and the dark squares of the checkerboard are imagined to correspond to the second volume elements.

Even if both the first partial grid and the second partial grid have a two-dimensional embodiment, these need not necessarily be displaced in relation to one another in the plane in
 30 which the volume elements are arranged. A displacement of the two partial grids in relation to one another both in a direction aligned exclusively perpendicular to this plane and in any spatial direction are possible.

The first partial grid can also have a three-dimensional embodiment. As an alternative or in addition thereto, the second partial grid can also have a three-dimensional embodiment. Once again, the two partial grids can be displaced in any spatial direction in relation to one another. Particularly in the case of a three-dimensional embodiment, the foci for the two different object distances will influence one another with each layer. Expressed differently, there will be an interaction that increases with the number of layers between the first and second parts in the case of the three-dimensional design of the partial grids, said interaction intending to be designed for in-focus vision at different object distances. Details are explained below in conjunction with the description relating to figure 4.

The first object distance can differ from the second object distance by more than 5 cm or by more than 10 cm or by more than 15 cm or by more than 20 cm or by more than 30 cm or even by more than 50 cm, for example. Expressed differently, the focal planes for which the parts comprising the first and second volume elements are designed in each case are spaced apart from one another by the values specified above. The spectacle wearer is able to see objects arranged in these focal planes in focus along the same viewing direction. A change of view, as required in conventional multifocal lenses, is not required with the aid of a spectacle lens of the type according to the invention.

In principle, it is possible that the spectacle lens only consists of, or is only formed by, the first and second volume element groups. It is also possible that one or more further volume element groups of the type corresponding to the first and second volume element groups are present and that the spectacle lens only consists of these volume element groups of different types, which each form parts of the spectacle lens that provide the dioptric power for vision for the same or different object distances. A particularly advantageous embodiment variant of the spectacle lens according to the invention is characterized in that the first volume element group and the second volume element group are arranged on a surface of a carrier. By way of example, the carrier could have been produced with the aid of a method such as casting or an abrasive method from a blank. However, the invention also provides for the method according to the invention optionally to be characterized by the method step of

- additive manufacturing of a carrier with a surface, on which the first volume element group and the second volume element group are arranged.

By way of example, the carrier can have an object-side spherical or toric or free-form surface and the surface on which the first volume element group and the second volume element group are arranged can be the eye-side surface of the carrier. Alternatively, the carrier can also have an eye-side spherical or toric or free-form surface and the surface on which the first volume element group and the second volume element group are arranged can be the object-side surface of the carrier. In both of the above-described variants, the overall effect of the spectacle lens is composed of the refractive power of the spherical or toric or rotationally symmetrical aspherical or free-form surface and the light-refractive properties of the volume elements of the first and the second volume element groups.

Finally, it is also possible that the surface on which the first volume element group and the second volume element group are arranged is/are the eye-side and/or the object-side surface of the carrier. Then, the overall effect of the spectacle lenses is substantially composed of the light-refractive properties of the volume elements of the first and the second volume element groups.

Further, it is possible for the carrier to have a refractive index gradient. As described in the introductory part of the description, a refraction gradient offers the possibility of producing a desired dioptric power of a body that has little dependence on the geometric form thereof.

Additionally, a coat can be arranged on the first volume element group and the second volume group. In particular, all functional layer structures mentioned in the introductory part of the description come into question as coats. In particular, mention should be given to those that influence or change optical properties, such as an antireflection coating, silvering, light polarization, coloring, self-tinting etc., and mechanical properties, such as hardening, reduction of the adherence of dirt or reduction in steaming up, etc., and/or electrical properties such as shielding from electromagnetic radiation, conduction of electrical current, etc., and/or other physical or chemical properties of the spectacle lens.

Finally, it is also possible that the first volume element group and the second volume element group are embodied as buried structures. On the one hand, this substantially simplifies a subsequent hard or antireflection coating (e.g., conventional smoothing hard coat systems can be used) and on the other hand discontinuities or bends or jumps in the surfaces of the volume elements adjoining one another do not form cavities for the subsequent collection of dirt on the

surface of the completed spectacle lens. Buried structures are understood to mean embedding in a substrate material.

The above-described dioptric power of the spectacle lens according to the invention can be obtained with first volume elements that each have a volume of between $1000\ \mu\text{m}^3$ and $1\ \text{mm}^3$ and/or with second volume elements that each have a volume of between $1000\ \mu\text{m}^3$ and $1\ \text{mm}^3$. The smallest possible volume of the volume element is predetermined by the production method, for example by the droplet size in the case of the multijet or polyjet modeling and, for example, by the focus dimension of the laser in the SLA method.

By way of example, the first volume elements could each have an object-side surface of between $100\ \mu\text{m}^2$ and $1\ \text{mm}^2$ and/or the second volume elements could each have an object-side surface of between $100\ \mu\text{m}^2$ and $1\ \text{mm}^2$. As an alternative or in addition thereto, it is possible for the first volume elements to each have an eye-side surface of between $100\ \mu\text{m}^2$ and $1\ \text{mm}^2$ and/or for the second volume elements to each have an eye-side surface of between $100\ \mu\text{m}^2$ and $1\ \text{mm}^2$.

The number of first volume elements, which form the first part, preferably lies between 50 and 10^9 , further preferably between 100 and 10^8 , finally further preferably between 200 and 10^7 and finally even more preferably between 500 and 10^6 .

The number of second volume elements, which form the second part, preferably lies between 50 and 10^9 , further preferably between 100 and 10^8 , finally further preferably between 200 and 10^7 and finally even more preferably between 500 and 10^6 .

Preferably, the number of first volume elements and number of second volume elements are of the same order of magnitude. This means that the number of the first volume elements and the number of the second volume elements do not deviate from one another by more than a factor of 10, preferably by no more than a factor of 8, further preferably by no more than a factor of 5 and finally further preferably by no more than a factor of 2.

The technological solution according to the invention has the following advantages, particularly when taking account of the by the above-presented advantageous embodiments and developments of the inventive concept:

In addition to the above-described applications in the field of varifocal and multifocal lenses and the likewise above-described approaches of reducing the cosmetic problems, particularly in the case a single vision lenses, it is moreover possible to select no systems purely based on a gradient optics (see the aforementioned publications WO 2015/102938 A1 and WO 2014/179780

5 A1), in which plane lenses or even physically plane plates are generated as a spectacle lens. A very good result emerges from an expedient combination of optically active surfaces with a refractive index gradient in the substrate material. If the refractive index increases towards the edge of the spectacle lens, it is possible to reduce the edge thickness of the spectacle lens when correcting myopic eye defects. If plastics are used, the maximum refractive index lift is from
10 1.48 to 1.80, wherein the realizability is difficult as a result of the necessary change of the underlying chemistry. Mineral glass offers further possibilities of increase.

Various restrictions of current technology are lifted in view of the design of the spectacle lens. Lifting of the restriction to spherical or aspherical rotationally symmetric front surfaces with a
15 restricted delivery range in view of the curvature is particularly advantageous. When the technologies described here are used, it is possible to realize any curvature and changes in curvature with or without consequence for the optical power of the lens. If necessary, the change in curvature can be compensated by a change in the refractive index.

20 A further advantageous property is the lifting of the size restriction of the spectacle lens as a result of the restriction to the diameter of the available semifinished products. Unlike in the case of the semifinished products which, for reasons of production, are restricted to a diameter of approximately 80 to 90 mm, the maximum size of the construction space of the 3D printer, which already lies significantly thereabove and may advantageously be more than 200 x 200 x
25 200 mm, represents the production limit. If this volume is exploited, it would be possible to print whole spectacles, shields, etc. in one piece.

The invention is described in greater detail below with reference to the drawing. In the figures:

30 Figure 1 shows a first exemplary embodiment for the arrangement of two partial grids formed by volume elements of the first and second volume element groups, displaced within one another in penetrative fashion.

- Figure 2 shows an exemplary embodiment for the arrangement of four partial grids formed by volume elements of the first, second, third and fourth volume element groups, displaced within one another in penetrative fashion.
- 5 Figure 3 shows a second exemplary embodiment for the arrangement of two partial grids formed by volume elements of the first and second volume element groups, displaced within one another in penetrative fashion.
- 10 Figure 4 shows a third exemplary embodiment for the arrangement of two partial grids formed by volume elements of the first and second volume element groups, displaced within one another in penetrative fashion.
- 15 Figure 5 shows a fourth exemplary embodiment for the arrangement of two partial grids formed by volume elements of the first and second volume element groups, displaced within one another in penetrative fashion
- a) arrangement of the volume elements
 - b) magnified illustration of in each case one of the first and second volume elements.
- 20 Figure 6 shows a first exemplary embodiment of a spectacle lens according to the invention in a plan view from the object side (schematic sketch).
- 25 Figure 7 shows a second exemplary embodiment of a spectacle lens according to the invention in cross section (schematic sketch).
- Figure 8 shows a third exemplary embodiment of a spectacle lens according to the invention in cross section (schematic sketch).
- 30 Figure 9 shows a fourth exemplary embodiment of a spectacle lens according to the invention in cross section (schematic sketch).
- Figure 10 shows a fifth exemplary embodiment of a spectacle lens according to the invention in cross section (schematic sketch).

Figure 11 shows an exemplary embodiment of spectacles with a spectacle lens according to the invention.

Explanations were given above that the spectacle lens according to the invention comprises at least two volume element groups. The two volume element groups, referred to as first and second volume element groups below, each comprise a plurality of corresponding volume elements. The volume elements of the first volume element group are referred to as first volume elements below; the volume elements of the second volume element group are referred to as second volume elements below.

The first volume elements are arranged in the style of grid points of a geometric grid and form a first partial grid. Together, the volume elements of the first volume element group form a first part of the spectacle lens. Together, they define a region of the spectacle lens through which the spectacle wearer gazes in the case of intended use, said region having the dioptric power for vision at a first object distance.

The second volume elements are likewise arranged in the style of grid points of a geometric grid and together form a second partial grid in their own right. Together, the volume elements of the second volume element group form a second part of the spectacle lens. Together, they define a region of the spectacle lens through which the spectacle wearer gazes in the case of intended use, said region having the dioptric power for vision at a second object distance, the second object distance deviating from the aforementioned first object distance that is set by the first partial grid formed by the volume elements of the first volume element group.

The first partial grid and the second partial grid are arranged displaced within one another in penetrative fashion in each case. As a result, the regions of the spectacle lens that are defined by the two partial grids respectively formed from different volume elements and that are designed for different object distances geometrically coincide on a macroscopic level. This should be elucidated once again below on the basis of the figures.

Figure 1 shows a first exemplary embodiment for the arrangement of two partial grids formed by volume elements of the first and second volume element groups, displaced within one another in penetrative fashion. In the present exemplary embodiment, the first partial grid consists of cuboid volume elements 1a, 1b, 1c ... 1t, 1u, which are arranged like the white fields of a

checkerboard. In the present exemplary embodiment, the second partial grid consists of cuboid volume elements 2a, 2b, 2c ... 2t, 2u, which are arranged like the black fields of a checkerboard. Each cuboid volume element 1a, 1b, 1c ... 1t, 1u, 2a, 2b, 2c ... 2t, 2u takes up the same amount of space, with edge lengths a_1, a_2, a_3 . The edge lengths a_1, a_2, a_3 regularly lie in the range

5 between 10 μm and 1 mm. The volumes of the cuboid volume elements 1a, 1b, 1c ... 1t, 1u, 2a, 2b, 2c ... 2t, 2u are then in the range between 1000 μm^3 and 1 mm^3 .

In the present exemplary embodiment, the first partial grid that is based on the cuboid volume elements 1a, 1b, 1c ... 1t, 1u and the second partial grid that is based on the cuboid volume
 10 elements 2a, 2b, 2c ... 2t, 2u have an identical embodiment. From the geometric point of view, the two partial grids are offset in relation to one another by the edge length a_1 in the direction of a sheet row. Alternatively, it is also possible to say that the two partial grids are offset in relation to one another by the edge length a_2 in a direction perpendicular to the direction of a sheet row. In this exemplary embodiment, both partial grids lie in one plane. In the present case, let the
 15 surface 3 visible in figure 1 be the surface facing the object in the case of an intended use of the spectacle lens, which is based on the structure shown in figure 1. Accordingly, the surface 4 that is not visible in figure 1 in that case is the surface facing the eye of the spectacle wearer in the case of an intended use of the spectacle lens. The object-side surface of a single volume element 1a, 1b, 1c ... 1t, 1u, 2a, 2b, 2c ... 2t, 2u, which in each case represents a plane surface in the
 20 present exemplary embodiment, lies between 100 μm^2 and 1 mm^2 , taking account of the aforementioned size specifications.

The part of the spectacle lens defined by the first partial grid is determined by the totality of the volumes of the cuboid volume elements 1a, 1b, 1c ... 1t, 1u in the present exemplary
 25 embodiment. Expressed differently, the region of the spectacle lens defined by the first partial grid, which is designed for vision at a first object distance and through which the spectacle wearer gazes for the purposes of seeing an object arranged at this distance in focus in the case of intended use, is determined in the present exemplary embodiment by the totality of the object-side (and eye-side) surfaces of the cuboid volume elements 1a, 1b, 1c ... 1t, 1u. According to the
 30 invention, this surface region should be between 0.3 cm^2 and 7 cm^2 , preferably between 0.5 cm^2 and 6 cm^2 , further preferably between 0.8 cm^2 and 5 cm^2 and, finally, even more preferably between 1 cm^2 and 4 cm^2 .

The part of the spectacle lens defined by the second partial grid is determined by the totality of the volumes of the cuboid volume elements 2a, 2b, 2c ... 2t, 2u in the present exemplary embodiment. Expressed differently, the region of the spectacle lens defined by the second partial grid, which is designed for vision at a second object distance and through which the spectacle
 5 wearer gazes for the purposes of seeing an object arranged at this distance in focus in the case of intended use, is determined in the present exemplary embodiment by the totality of the object-side (and eye-side) surfaces of the cuboid volume elements 2a, 2b, 2c ... 2t, 2u. According to the invention, this surface region should be between 0.3 cm² and 7 cm², preferably between 0.5 cm² and 6 cm², further preferably between 0.8 cm² and 5 cm² and, finally, even more preferably
 10 between 1 cm² and 4 cm².

From a macroscopic point of view, the surface region defined by the first partial grid and the surface region defined by the second partial grid coincide, and so there is no macroscopic separation between the part of the spectacle lens designed for the first object distance and the
 15 part of the spectacle lens designed for the second object distance. In contrast to the conventional type of bifocal or varifocal lens that is designed for a presbyopic wearer, near and far part coincide from the macroscopic point of view.

By way of example, WO 2015/102938 A1 describes in detail how such grid structures are
 20 produced. Thus, a 3D printer equipped with one or more processors receives a CAD model with data of, in the present exemplary embodiment, a single layer which comprises a multiplicity of volume elements. Thus, the data contain, for example, the information that the first volume elements 1a, 1b, 1c ... 1t, 1u, specified above, should be manufactured from a first material with a first dielectric constant, corresponding to a first printer ink, and the information that the second
 25 volume elements 2a, 2b, 2c ... 2t, 2u, specified above, should be manufactured from a second material with a second dielectric constant, corresponding to a second printer ink. From the data, the processor or processors of the 3D printer calculate the respective location at which the respective printer ink should be placed, the temperature and/or the UV light requirements and the corresponding times to cure the placed printer ink for the purposes of generating the respective
 30 volume element 1a, 1b, 1c ... 1t, 1u, 2a, 2b, 2c ... 2t, 2u.

Figure 2 shows a further exemplary embodiment for the arrangement of volume elements of partial grids, displaced within one another in penetrative fashion. In this exemplary embodiment, the overall grid is formed from four partial grids. The four partial grids comprise volume

elements of the first, second, third and fourth volume element groups. The first partial grid, which is based on the hexagonal volume elements 11a, 11b, 11c, 11d, the second partial grid, which is based in the hexagonal volume elements 12a, 12b, 12c, 12d, the third partial grid, which is based on the hexagonal volume elements 13a, 13b, and the fourth partial grid, which is based on the hexagonal volume elements 14a, 14b, have an identical embodiment in the present exemplary embodiment. The volumes of the hexagonal volume elements 11a, 11b, 11c, 11d, 12a, 12b, 12c, 12d, 13a, 13b, 14a, 14b are in the range of between $1000 \mu\text{m}^3$ and 1 mm^3 .

The part of the spectacle lens defined by the first partial grid is determined by the totality of the volumes of the volume elements 11a, 11b, 11c, 11d in the present exemplary embodiment. Expressed differently, the region of the spectacle lens defined by the first partial grid, which is designed for vision at a first object distance and through which the spectacle wearer gazes for the purposes of seeing an object arranged at this distance in focus in the case of intended use, is determined in the present exemplary embodiment by the totality of the object-side (and eye-side) surfaces of the volume elements 11a, 11b, 11c, 11d. According to the invention, this surface region should be between 0.3 cm^2 and 7 cm^2 , preferably between 0.5 cm^2 and 6 cm^2 , further preferably between 0.8 cm^2 and 5 cm^2 and, finally, even more preferably between 1 cm^2 and 4 cm^2 .

The part of the spectacle lens defined by the second partial grid is determined by the totality of the volumes of the volume elements 12a, 12b, 12c, 12d in the present exemplary embodiment. Expressed differently, the region of the spectacle lens defined by the second partial grid, which is designed for vision at a second object distance and through which the spectacle wearer gazes for the purposes of seeing an object arranged at this distance in focus in the case of intended use, is determined in the present exemplary embodiment by the totality of the object-side (and eye-side) surfaces of the volume elements 12a, 12b, 12c, 12d. According to the invention, this surface region should be between 0.3 cm^2 and 7 cm^2 , preferably between 0.5 cm^2 and 6 cm^2 , further preferably between 0.8 cm^2 and 5 cm^2 and, finally, even more preferably between 1 cm^2 and 4 cm^2 .

The part of the spectacle lens defined by the third partial grid is determined by the totality of the volumes of the volume elements 13a, 13b in the present exemplary embodiment. Expressed differently, the region of the spectacle lens defined by the third partial grid, which is designed for vision at a third object distance and through which the spectacle wearer gazes for the purposes of

seeing an object arranged at this distance in focus in the case of intended use, is determined in the present exemplary embodiment by the totality of the object-side (and eye-side) surfaces of the volume elements 13a, 13b. According to the invention, this surface region should be between 0.3 cm² and 7 cm², preferably between 0.5 cm² and 6 cm², further preferably between 0.8 cm² and 5 cm² and, finally, even more preferably between 1 cm² and 4 cm².

The part of the spectacle lens defined by the fourth partial grid is determined by the totality of the volumes of the volume elements 14a, 14b in the present exemplary embodiment. Expressed differently, the region of the spectacle lens defined by the fourth partial grid, which is designed for vision at a fourth object distance and through which the spectacle wearer gazes for the purposes of seeing an object arranged at this distance in focus in the case of intended use, is determined in the present exemplary embodiment by the totality of the object-side (and eye-side) surfaces of the volume elements 14a, 14b. According to the invention, this surface region should be between 0.3 cm² and 7 cm², preferably between 0.5 cm² and 6 cm², further preferably between 0.8 cm² and 5 cm² and, finally, even more preferably between 1 cm² and 4 cm².

From a macroscopic point of view, the surface region defined by the first partial grid, the surface region defined by the second partial grid, the surface region defined by the third partial grid and the surface region defined by the fourth partial grid coincide, and so there is no macroscopic separation between the part of the spectacle lens designed for the first object distance, the part of the spectacle lens designed for the second object distance, the part of the spectacle lens designed for the third object distance and the part of the spectacle lens designed for the fourth object distance.

Figure 3 shows a second exemplary embodiment for the arrangement of two partial grids formed by volume elements of the first and second volume element groups, displaced within one another in penetrative fashion. The first partial grid, which is based on the volume elements 21a, 21b, 21c, 21d ... 21x, 21y, 21z, comprises a cylindrical volume element 21a and a plurality of ring-segment-shaped volume elements 21b, 21c, 21d, ... 21x, 21y, 21z. The second partial grid only comprises a plurality of ring-segment-shaped volume elements 22a, 22b, 22y, 22z. Like the exemplary embodiments shown in figures 2 and 3, all volume elements 21b, 21c, 21d, ... 21x, 21y, 21z, 22a, 22b, 22y, 22z are arranged in one plane.

Figure 4 shows a third exemplary embodiment for the arrangement of two partial grids formed by volume elements of the first and second volume element groups, displaced within one another in penetrative fashion.

5 In the present exemplary embodiment, the first partial grid that is based on the cuboid volume elements 1a, 1b, 1c ... 1x, 1y, 1z and the second partial grid that is based on the cuboid volume elements 2a, 2b, 2c ... 2y, 2z have an identical embodiment. Both partial grids represent a sequence of three-dimensional cubic structures, the respective volume elements 21b, 21c, 21d, ... 21x, 21y, 21z, 22a, 22b, 22y, 22z of which are arranged adjacent to one another and within
 10 one another, penetrating one another in each case. Accordingly, the final grid comprises a plurality of layers of the type shown in figure 1. In the present case, let the surface 3 visible in figure 1 be the surface facing the object in the case of an intended use of the spectacle lens, which is based on the structure shown in figure 1. Accordingly, the surface 4 that is not visible in figure 1 in that case is the surface facing the eye of the spectacle wearer in the case of an
 15 intended use of the spectacle lens.

The part of the spectacle lens defined by the first partial grid is determined by the totality of the volumes of the cuboid volume elements 1a, 1b, 1c ... 1x, 1y, 1z in the present exemplary embodiment. Expressed differently, the region of the spectacle lens defined by the first partial
 20 grid, which is designed for vision at a first object distance and through which the spectacle wearer gazes for the purposes of seeing an object arranged at this distance in focus in the case of intended use, is determined in the present exemplary embodiment by the totality of the object-side (and eye-side) surfaces of the cuboid volume elements 1a, 1b, 1c (i.e., all blackened areas of the surface 3). According to the invention, this surface region should be between 0.3 cm² and 7
 25 cm², preferably between 0.5 cm² and 6 cm², further preferably between 0.8 cm² and 5 cm² and, finally, even more preferably between 1 cm² and 4 cm².

The part of the spectacle lens defined by the second partial grid is determined by the totality of the volumes of the cuboid volume elements 2a, 2b, 2c ... 2x, 2y, 2z in the present exemplary
 30 embodiment. Expressed differently, the region of the spectacle lens defined by the second partial grid, which is designed for vision at a second object distance and through which the spectacle wearer gazes for the purposes of seeing an object arranged at this distance in focus in the case of intended use, is determined in the present exemplary embodiment by the totality of the object-side (and eye-side) surfaces of the cuboid volume elements 2a, 2b, 2c (i.e., all white areas of the

surface 3). According to the invention, this surface region should be between 0.3 cm^2 and 7 cm^2 , preferably between 0.5 cm^2 and 6 cm^2 , further preferably between 0.8 cm^2 and 5 cm^2 and, finally, even more preferably between 1 cm^2 and 4 cm^2 .

- 5 From a macroscopic point of view, the surface region defined by the first partial grid (i.e., all blackened areas of the surface 3) and the surface region defined by the second partial grid (i.e., all white areas of the surface 3) coincide, and so there is no macroscopic separation between the part of the spectacle lens designed for the first object distance and the part of the spectacle lens designed for the second object distance. In contrast to the conventional type of bifocal or
10 varifocal lens that is designed for a presbyopic wearer, near and far part coincide from the macroscopic point of view.

Particularly in the case where the object-side and eye-side surfaces 3, 4 of the first and second parts of the spectacle lens form plane surfaces, a design for different object distances can be
15 realized exclusively by a corresponding variation in the refractive index. Accordingly, GRIN structures that are nested in one another are required. Instead of or in addition to appropriately adapted refractive index variations, it is also possible to produce nested focal regions using volume elements, whose object-side and/or eye-side surfaces are embodied with the necessary curvature.

20 The structure shown in figure 4 represents a very complex system because the foci of the different materials influence one another again with each layer. This structure is of interest if single vision lenses are considered. Then, these 3D checkerboard patterns could be used at the edge. Since 3D printers can only print in binary fashion, i.e., only one or
25 the other material, “smooth substance changes” must be realized by sufficiently small volume elements.

Figure 5 shows a fourth exemplary embodiment for the arrangement of two partial grids formed by volume elements of the first and second volume element groups, displaced within one another
30 in penetrative fashion. Figure 5a) shows the basic arrangement of the volume elements 51a, 51b, ... 51t, 51u, 52a, 52b, 52c, ... 52t, 52u in the style of a checkerboard pattern, as described in detail above in relation to figure 1. Deviating from the embodiment variant according to figure 1 (or optionally in addition thereto as well), in which the individual volume elements are designed by the corresponding variation of the refractive index in such a way that fusing parts that

facilitate in-focus vision for different object distances arise, volume elements 51a, 51b, ... 51t, 51u, 52a, 52b, 52c, ... 52t, 52u whose object-side surfaces (and optionally eye-side surfaces, too) have different curvatures such that neighboring first and second volume elements adjoin one another not continuously but at an angle and optionally with jumps are included in the embodiment according to figure 5. Figure 5a) shows a magnified illustration of in each case one of the first and second volume elements 52c and 52i, which have object-side surfaces 53c and 54c that have a different curvature at the transition at which two neighboring first and second volume elements adjoin one another.

Figure 6 shows a first exemplary embodiment of a spectacle lens 60 in a plan view from the object side in the form of a schematic sketch. The visible surface is denoted by the reference sign 63. The exemplary embodiment has a region 61, which is embodied in the form according to the invention. It is possible to see a nested arrangement of two partial grids in the style of a “checkerboard pattern”, as shown in figure 1. Volume elements of the first partial grid are denoted in exemplary fashion by reference signs 61a, 61b and volume elements of the second partial grid are denoted in exemplary fashion by reference signs 62a, 62b.

According to the invention, the region 61 is designed for in-focus vision at two different object distances.

Figure 7 shows a second exemplary embodiment of a spectacle lens 70 in cross section (schematic sketch). In this exemplary embodiment, the entire spectacle lens 70 consists of a first volume element group with a plurality of first volume elements 71a, 71b, which are arranged in the style of grid points of a geometric grid, forming a first partial grid, and of a second volume element group with a plurality of second volume elements 72a, 72b, which are arranged in the style of grid points of a geometric grid, forming a second partial grid. In principle, the embodiment corresponds to the arrangement of the two partial grids in relation to one another as shown in figure 4.

Together, the first volume elements 71a, 71b form a first part of the spectacle lens, which has the dioptric power for vision at a first object distance. Together, the second volume elements form a second part of the spectacle lens, which has the dioptric power for vision at a second object distance that differs from the first object distance. Since the first volume element group and the second volume element group penetrate one another, they form a common macroscopic viewing

region that facilitates, firstly, in-focus vision of an object arranged at the first object distance d_1 and in-focus vision of an object arranged at a second object distance d_2 . The corresponding focal planes are denoted by reference signs 73 and 74 in the drawing.

5 Figure 8 shows a third exemplary embodiment of a spectacle lens 80 in cross section (as a schematic sketch). In this exemplary embodiment, the structure 81 according to the invention is applied to the back side (eye side) 84 of a transparent carrier 85 in the form of a buried structure. The front side (object side) 83 of the spectacle lens 80 can have a spherical, toric, rotationally symmetric aspherical or aspherical embodiment (e.g., as a free-form surface).

10 A fourth exemplary embodiment of a spectacle lens 90 in cross section (in the form of a schematic sketch) can be gathered from figure 9. In this exemplary embodiment, the structure 91 according to the invention is applied to the front side (object side) 93 of a transparent carrier 95 in the form of a buried structure. The back side (eye side) 94 of the spectacle lens 90 can have a spherical, toric or aspherical embodiment (e.g., as a free-form surface).

Coatings, such as, for example, hard coats, antireflection coatings, lotus-effect-type coatings and the like, can be applied to one or both optically effective surfaces 83, 84, 93, 94 of the spectacle lenses 80, 90.

20 Figure 10 shows a fifth exemplary embodiment of a spectacle lens 102 according to the invention in cross section in the form of a schematic sketch. In this exemplary embodiment, the structure 101 according to the invention is applied to a part of the back side (eye side) 104 of a transparent carrier 105 in the form of a buried structure. The front side (eye side) 103 of the spectacle lens 102 can have a spherical, toric or aspherical embodiment (e.g., as a free-form surface). A smoothing hard coat 106 that also fills the interstices 106a of the buried structure, an adhesion promoter layer 107 and an antireflection coating 108 consisting of a plurality of individual layers is applied to the buried structure 101.

30 Express reference is made herewith to the fact that structures 102 can also be applied to the carrier 105 on both the front and the back.

An exemplary embodiment of spectacles 100 with spectacle lenses 110a, 110b according to the invention can be gathered from figure 11. In addition to the two spectacle lenses 110a, 110b, the

spectacles 100 comprise a spectacle frame 120, the bridge 125 and the two earpieces 130a, 130b of which are shown. Each spectacle lens 110a, 110b comprises a carrier 66a, 66b, each of which carries a structure 61a, 61b according to the invention of the type shown in figure 6. All constituent parts of the spectacles can be produced with the aid of a 3D printing method.

5 In summary, the concept of the invention consists of constructing a three-dimensional structure using a manufacturing method (e.g., polyjet printing) that allows controlling the dioptric power of the spectacle lens, in particular controlling the refractive index for each individual volume element and the relative orientation of the surfaces of the volume elements, the far and near
10 regions of said three-dimensional structure being present nested in one another. The change from one focus to the next can be implemented gradually or with a jump. In the first case, small transition zones arise, said transition zones having similar properties to the progression channel in the case of a conventional varifocal lens and the optical properties connected therewith. Secondly, the change in properties can be implemented with a jump by changing the material or
15 changing the orientation of the optical surface.

The surface elements can be arranged as desired. For example, but not exclusively, as a checkerboard, as hexagons or as concentric circles.

20 In a preferred embodiment, the discontinuous of the surfaces can be embodied as buried structures having two materials; firstly, this substantially simplifies the subsequent hard and antireflection coating (it is possible to use conventional smoothing hard coat systems) and secondly the discontinuities of the surfaces do not form cavities for subsequent accumulation of dirt on the surface.

25 This yields various combinations of optical surfaces:

- two discontinuous surfaces on the front and back side,
- one discontinuous surface on the front or back side, together with a spherical, toric or
30 aspherical (free-form) surface on the other side of the lens.

Which combination yields the ideal correction emerges from the combination of the individual parameters (spherical, astigmatic, prismatic power, addition, etc.) with the possibilities of the different surface properties.

The hard coat must be set in such a way that the edges of the optically effective surfaces are not smoothed or not smoothed any more than what is absolutely unavoidable. If the change in the refractive power is provided by way of the refractive index of the material, possible

embodiments are found in the patent applications WO 2015/014381 A1 and WO 2014/179780 A1. If the desired power difference (addition) between two or more surface elements is insufficient to obtain the desired effect when only one of the two principles (material variation versus discontinuous surface) is applied, it is possible to combine the two approaches with one another.

The spectacle lens should continue to comprise the conventional finishing, hard coating and antireflection coating. Transferring the approaches according to the invention to hybrid lenses lends itself as a possible embodiment. A precondition is the availability of a preformed carrier of the structure according to the invention that fits to the surface of the spectacle lens.

Further aspects of the invention in the form of clauses within the meaning of decision J15/81 of the Legal Board of Appeal of the European Patent Office are presented below:

Clause 1. A spectacle lens (60, 70, 80, 90, 102, 110a, 110b), comprising

- a first volume element group, wherein the first volume element group comprises a plurality of first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b), wherein the plurality of first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b) are arranged in the style of grid points of a geometric grid so as to form a first partial grid, wherein the first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b) together form a first part of the spectacle lens (60, 70, 80, 90, 102, 110a, 110b), said first part of the spectacle lens having the dioptric power for vision at a first object distance (d_1),

- a second volume element group, wherein the second volume element group comprises a plurality of second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b), wherein the plurality of second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b) are arranged in the style of grid points of a geometric grid so as to form a second partial grid, wherein the second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b) together form a second part of the spectacle lens (60, 70, 80, 90, 110a, 110b), said second part of the spectacle lens having the

dioptric power for vision at a second object distance (d_2) that differs from the first object distance (d_1),

characterized in that

- the first partial grid and the second partial grid are arranged within one another,
penetrating one another in each case.

Clause 2. The spectacle lens (60, 70, 80, 90, 102, 110a, 110b) according to clause 1, characterized in that the first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b) consist of a first material and in that the second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b) consist of a second material that differs from the first material.

Clause 3. The spectacle lens (60, 70, 80, 90, 102, 110a, 110b) according to either of clauses 1 and 2, characterized in that the first material has a first refractive index and in that the second material has a second refractive index that differs from the first refractive index.

Clause 4. The spectacle lens (60, 70, 80, 90, 102, 110a, 110b) according to any one of the preceding clauses, characterized in that the first volume elements (51a, 51b, 51i, 51t, 51u) each have a first surface element (54c) and in that the second volume elements (52a, 52b, 52c, 52t, 52u) each have a second surface element (53c) and in that respectively one of the first surface elements (54c) and respectively one of the second surface elements (53c), which adjoin one another, are arranged at an angle to one another.

Clause 5. The spectacle lens (60, 102, 110a, 110b) according to any one of the preceding clauses, characterized in that the first partial grid has a two-dimensional embodiment and/or in that the second partial grid has a two-dimensional embodiment.

Clause 6. The spectacle lens (70, 80, 90) according to any one of the preceding clauses, characterized in that the first partial grid has a three-dimensional embodiment and/or in that the second partial grid has a three-dimensional embodiment.

Clause 7. The spectacle lens (60, 70, 80, 90, 102, 110a, 110b) according to any one of the preceding clauses, characterized in that the first object distance (d_1) differs from the second

object distance (d_2) by more than a value from the group of 10 cm, 15 cm, 20 cm, 30 cm and 50 cm.

Clause 8. The spectacle lens (60, 80, 90, 102, 110a, 110b) according to any one of the preceding clauses, characterized in that the first volume element group and the second volume element group are arranged on a surface of a carrier (85, 95, 105, 66a, 66b).

Clause 9. The spectacle lens (60, 80, 90, 102, 110a, 110b) according to clause 8, characterized in that

- the carrier (85) has an object-side spherical or toric or free-form surface and in that the surface on which the first volume element group and the second volume element group are arranged is the eye-side surface of the carrier (85), or in that
- the carrier (95, 105) has an eye-side spherical or toric or free-form surface and in that the surface (104) on which the first volume element group and the second volume element group are arranged is the object-side surface of the carrier (95, 105), or in that
- the surface on which the first volume element group and the second volume element group are arranged is the eye-side and/or the object-side surface of the carrier.

Clause 10. The spectacle lens (60, 80, 90, 102, 110a, 110b) according to either of clauses 8 and 9, characterized in that the carrier (85, 95, 105, 66a, 66b) has a refractive index gradient.

Clause 11. The spectacle lens (60, 70, 80, 90, 102, 110a, 110b) according to any one of the preceding clauses, characterized in that a coat (106, 106a, 107, 108) is arranged on the first volume element group and the second volume element group.

Clause 12. The spectacle lens (60, 70, 80, 90, 102, 110a, 110b) according to any one of the preceding clauses, characterized in that the first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b) each have a volume of between $1000 \mu\text{m}^3$ and 1 mm^3 and/or in that the second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b) each have a volume of between $1000 \mu\text{m}^3$ and 1 mm^3 .

Clause 13. The spectacle lens (60, 70, 80, 90, 102, 110a, 110b) according to clause 12, characterized in that

- the first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b) each have an object-side surface of between $100\text{ }\mu\text{m}^2$ and 1 mm^2 and/or in that the second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b) each have an object-side surface of between $100\text{ }\mu\text{m}^2$ and 1 mm^2 , and/or in that
- 5 - the first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b) each have an eye-side surface of between $100\text{ }\mu\text{m}^2$ and 1 mm^2 and/or in that the second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b) each have an eye-side surface of between $100\text{ }\mu\text{m}^2$ and 1 mm^2 .
- 10 Clause 14. A method for producing a spectacle lens (60, 70, 80, 90, 102, 110a, 110b), including the steps of:
 - additive manufacturing of a first volume element group, wherein the first volume element group comprises a plurality of first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b), wherein the plurality of first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b) are arranged in the style of grid points of a geometric grid so as to form a first partial grid, wherein the first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b) together form a first part of the spectacle lens (60, 70, 80, 90, 110a, 110b), said first part of the spectacle lens having the dioptric power for vision at a first object distance (d_1),
 - 15 - additive manufacturing of a second volume element group, wherein the second volume element group comprises a plurality of second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b), wherein the plurality of second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b) are arranged in the style of grid points of a geometric grid so as to form a second partial grid, wherein the second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b) together form a second part of the spectacle lens (60, 70, 80, 90, 110a, 110b), said second part of the spectacle lens having the dioptric power for vision at a second object distance (d_2) that differs from the first object distance (d_1),
 - 20 characterized in that
 - 25 - the first partial grid and the second partial grid are arranged within one another, penetrating one another in each case, during the additive manufacturing.
 - 30

Clause 15. The method according to clause 14, characterized by the step of:

- additive manufacturing of a carrier (66a, 66b) with a surface (104), on which the first volume element group and the second volume element group are arranged.

Patent claims:

1. A method for producing a spectacle lens (60, 70, 80, 90, 102, 110a, 110b), including the steps of:

- 5 - additive manufacturing of a first volume element group, wherein the first volume element group comprises a plurality of first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b), wherein the plurality of first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b) are arranged in the style of grid points of a geometric grid so as to form a first partial grid, wherein the first volume elements
- 10 (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b) together form a first part of the spectacle lens (60, 70, 80, 90, 110a, 110b), said first part of the spectacle lens having the dioptric power for vision at a first object distance (d_1),
- additive manufacturing of a second volume element group, wherein the second volume element group comprises a plurality of second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b), wherein the plurality of second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b) are arranged in the style of grid points of a geometric grid so as to form a second partial grid, wherein the second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b) together form a
- 15 second part of the spectacle lens (60, 70, 80, 90, 110a, 110b), said second part of the spectacle lens having the dioptric power for vision at a second object distance (d_2) that differs from the first object distance (d_1),
- 20 characterized in that
- the first partial grid and the second partial grid are arranged within one another, penetrating one another in each case, during the additive manufacturing.

- 25
2. The method as claimed in claim 1, characterized by the step of:
- additive manufacturing of a carrier (66a, 66b) with a surface (104), on which the first volume element group and the second volume element group are arranged.
- 30
3. A spectacle lens (60, 70, 80, 90, 102, 110a, 110b), comprising
- a first volume element group, wherein the first volume element group comprises a plurality of first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b), wherein the plurality of first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b) are arranged in the style of grid points of a geometric grid so as to

form a first partial grid, wherein the first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b) together form a first part of the spectacle lens (60, 70, 80, 90, 102, 110a, 110b), said first part of the spectacle lens having the dioptric power for vision at a first object distance (d_1),

5 - a second volume element group, wherein the second volume element group comprises a plurality of second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b), wherein the plurality of second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b) are arranged in the style of grid points of a geometric grid so as to form a second partial grid, wherein the second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b) together form a second part of the spectacle lens (60, 70, 80, 90, 110a, 110b), said second part of the spectacle lens having the dioptric power for vision at a second object distance (d_2) that differs from the first object distance (d_1), wherein

10 - the first partial grid and the second partial grid are arranged within one another, penetrating one another in each case, characterized in that

15 - the first partial grid has a three-dimensional embodiment and/or in that the second partial grid has a three-dimensional embodiment.

20 4. A spectacle lens (60, 70, 80, 90, 102, 110a, 110b), comprising

- a first volume element group, wherein the first volume element group comprises a plurality of first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b), wherein the plurality of first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b) are arranged in the style of grid points of a geometric grid so as to form a first partial grid, wherein the first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b) together form a first part of the spectacle lens (60, 70, 80, 90, 102, 110a, 110b), said first part of the spectacle lens having the dioptric power for vision at a first object distance (d_1),

25 - a second volume element group, wherein the second volume element group comprises a plurality of second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b), wherein the plurality of second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b) are arranged in the style of grid points of a geometric grid so as to form a second partial grid, wherein the second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b) together form a second part of the spectacle

lens (60, 70, 80, 90, 110a, 110b), said second part of the spectacle lens having the dioptric power for vision at a second object distance (d_2) that differs from the first object distance (d_1), wherein

- the first partial grid and the second partial grid are arranged within one another, penetrating one another in each case, wherein

- the first volume elements (51a, 51b, 51i, 51t, 51u) each have a first surface element (54c) and the second volume elements (52a, 52b, 52c, 52t, 52u) each have a second surface element (53c), characterized in that

- respectively one of the first surface elements (54c) and respectively one of the second surface elements (53c), which adjoin one another, are arranged at an angle to one another or arranged so as to form a step.

5. A spectacle lens (60, 70, 80, 90, 102, 110a, 110b), comprising

- a first volume element group, wherein the first volume element group comprises a plurality of first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b), wherein the plurality of first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b) are arranged in the style of grid points of a geometric grid so as to form a first partial grid, wherein the first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b) together form a first part of the spectacle lens (60, 70, 80, 90, 102, 110a, 110b), said first part of the spectacle lens having the dioptric power for vision at a first object distance (d_1),

- a second volume element group, wherein the second volume element group comprises a plurality of second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b), wherein the plurality of second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b) are arranged in the style of grid points of a geometric grid so as to form a second partial grid, wherein the second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b) together form a second part of the spectacle lens (60, 70, 80, 90, 110a, 110b), said second part of the spectacle lens having the dioptric power for vision at a second object distance (d_2) that differs from the first object distance (d_1), wherein

- the first partial grid and the second partial grid are arranged within one another, penetrating one another in each case, wherein

(i) the first volume elements (51a, 51b, 51i, 51t, 51u) each have a first surface element (54c) and the second volume elements (52a, 52b, 52c, 52t, 52u) each have a second surface element (53c), and/or

(ii) the first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b) consist of a first material and the second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b) consist of a second material that differs from the first material,

characterized in that

- a transition between one of the first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b) and an adjoining one of the second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b) is implemented by gradual change in the material and/or by a gradual change of an orientation of the respective first and second surface elements (53c, 54c), adjoining one another, of the first and second volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b; 2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b) that adjoin one another.

6. A spectacle lens (60, 70, 80, 90, 102, 110a, 110b), comprising

- a first volume element group, wherein the first volume element group comprises a plurality of first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b), wherein the plurality of first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b) are arranged in the style of grid points of a geometric grid so as to form a first partial grid, wherein the first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b) together form a first part of the spectacle lens (60, 70, 80, 90, 102, 110a, 110b), said first part of the spectacle lens having the dioptric power for vision at a first object distance (d_1),

- a second volume element group, wherein the second volume element group comprises a plurality of second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b), wherein the plurality of second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b) are arranged in the style of grid points of a geometric grid so as to form a second partial grid, wherein the second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b) together form a second part of the spectacle lens (60, 70, 80, 90, 110a, 110b), said second part of the spectacle lens having the dioptric power for vision at a second object distance (d_2) that differs from the first object distance (d_1), wherein

- the first partial grid and the second partial grid are arranged within one another, penetrating one another in each case, characterized in that
- a smoothing hard coat (106, 106a, 107, 108) is arranged on the first volume element group and on the second volume element group.

7. A spectacle lens (60, 70, 80, 90, 102, 110a, 110b), comprising

- a first volume element group, wherein the first volume element group comprises a plurality of first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b), wherein the plurality of first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b) are arranged in the style of grid points of a geometric grid so as to form a first partial grid, wherein the first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b) together form a first part of the spectacle lens (60, 70, 80, 90, 102, 110a, 110b), said first part of the spectacle lens having the dioptric power for vision at a first object distance (d_1),
- a second volume element group, wherein the second volume element group comprises a plurality of second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b), wherein the plurality of second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b) are arranged in the style of grid points of a geometric grid so as to form a second partial grid, wherein the second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b) together form a second part of the spectacle lens (60, 70, 80, 90, 110a, 110b), said second part of the spectacle lens having the dioptric power for vision at a second object distance (d_2) that differs from the first object distance (d_1), wherein
- the first partial grid and the second partial grid are arranged within one another, penetrating one another in each case, wherein
- the first volume element group and the second volume element group are arranged on a surface of a carrier (85, 95, 105, 66a, 66b), characterized in that
- the carrier (85, 95, 105, 66a, 66b) has a refractive index gradient.

8. The spectacle lens (60, 70, 80, 90, 102, 110a, 110b) as claimed in any one of claims 3 to 7, characterized in that the first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b) consist of a first material and in that the second volume elements (2a, 2b, ...; 12a, 12b,

...; 52a, 52b, ...; 62a, 62b; 72a, 72b) consist of a second material that differs from the first material.

9. The spectacle lens (60, 70, 80, 90, 102, 110a, 110b) as claimed in claim 8, characterized in that the first material has a first refractive index and in that the second material has a second refractive index that differs from the first refractive index.

10. The spectacle lens (60, 70, 80, 90, 102, 110a, 110b) as claimed in any one of claims 3 and 5 to 7, and 8 and 9, provided they refer back to any one of claims 3 and 5 to 7, characterized in that the first volume elements (51a, 51b, 51i, 51t, 51u) each have a first surface element (54c) and in that the second volume elements (52a, 52b, 52c, 52t, 52u) each have a second surface element (53c) and in that respectively one of the first surface elements (54c) and respectively one of the second surface elements (53c), which adjoin one another, are arranged at an angle to one another.

11. The spectacle lens (60, 102, 110a, 110b) as claimed in any one of claims 4 to 7, and 8 to 10, provided they refer back to any one of claims 4 to 7, characterized in that the first partial grid has a two-dimensional embodiment and/or in that the second partial grid has a two-dimensional embodiment.

12. The spectacle lens (70, 80, 90) as claimed in any one of claims 4 to 7, and 8 to 10, provided they refer back to any one of claims 4 to 7, characterized in that the first partial grid has a three-dimensional embodiment and/or in that the second partial grid has a three-dimensional embodiment.

13. The spectacle lens (60, 70, 80, 90, 102, 110a, 110b) as claimed in any one of claims 3 to 12, characterized in that the first object distance (d_1) differs from the second object distance (d_2) by more than a value from the group of 10 cm, 15 cm, 20 cm, 30 cm and 50 cm.

14. The spectacle lens (60, 80, 90, 102, 110a, 110b) as claimed in any one of claims 3 to 13, characterized in that the first volume element group and the second volume element group are arranged on a surface of a carrier (85, 95, 105, 66a, 66b).

15. The spectacle lens (60, 80, 90, 102, 110a, 110b) as claimed in claim 14, characterized in that

- the carrier (85) has an object-side spherical or toric or free-form surface and in that the surface on which the first volume element group and the second volume element group are arranged is the eye-side surface of the carrier (85), or in that

- the carrier (95, 105) has an eye-side spherical or toric or free-form surface and in that the

5 surface (104) on which the first volume element group and the second volume element group are arranged is the object-side surface of the carrier (95, 105), or in that

- the surface on which the first volume element group and the second volume element group are arranged is the eye-side and/or the object-side surface of the carrier.

10 16. The spectacle lens (60, 80, 90, 102, 110a, 110b) as claimed in either of claims 14 and 15, characterized in that the carrier (85, 95, 105, 66a, 66b) has a refractive index gradient.

17. The spectacle lens (60, 70, 80, 90, 102, 110a, 110b) as claimed in any one of claims 3 to 16, characterized in that a coat (106, 106a, 107, 108) is arranged on the first volume element group
15 and the second volume element group.

18. The spectacle lens (60, 70, 80, 90, 102, 110a, 110b) as claimed in any one of claims 3 to 17, characterized in that the first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b) each have a volume of between $1000\ \mu\text{m}^3$ and $1\ \text{mm}^3$ and/or in that the second volume
20 elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b) each have a volume of between $1000\ \mu\text{m}^3$ and $1\ \text{mm}^3$.

19. The spectacle lens (60, 70, 80, 90, 102, 110a, 110b) as claimed in claim 18, characterized in that

25 - the first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b) each have an object-side surface of between $100\ \mu\text{m}^2$ and $1\ \text{mm}^2$ and/or in that the second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b) each have an object-side surface of between $100\ \mu\text{m}^2$ and $1\ \text{mm}^2$, and/or in that

- the first volume elements (1a, 1b, ...; 11a, 11b, ...; 51a, 51b, ...; 61a, 61b; 71a, 71b) each have
30 an eye-side surface of between $100\ \mu\text{m}^2$ and $1\ \text{mm}^2$ and/or in that the second volume elements (2a, 2b, ...; 12a, 12b, ...; 52a, 52b, ...; 62a, 62b; 72a, 72b) each have an eye-side surface of between $100\ \mu\text{m}^2$ and $1\ \text{mm}^2$.