

Description

This invention relates generally to slide fasteners and more particularly to a slider therefor.

Numerous types of sliders for opening and closing the slide fasteners have been proposed which are provided with means for locking the slider in position against unintentional movement subject to a force tending to spread or open the fastener. One such locking means was formed on a pull tab attached to and adapted to facilitate movement of the slider body. For slide fasteners, however, having ladder-type or meandering coupling elements in two rows, one on the upper and the other on the lower side of the fastener, the locking means was preferably provided on or in connection with the flange portion of the slider body. A slider with the latter type of locking means was disclosed in U.S. Patent No. 3,798,714 in which the slider (as shown in Figure 6) has a pair of locking tabs or projections 100 and 101, one of upper opposed flanges 102 on an upper wing member and the other tab or projection on a corresponding extreme end of one of lower opposed flanges 103 on a lower wing member, the locking tabs 100 and 102 being engageable with the heel portions 104 of the coupling elements E respectively on the upper and lower sides of the fastener to prevent spontaneous spreading-apart action of the confronting stringers. Whilst this prior flange-lock slider has its own advantages, it has a drawback in that either one of the pair of locking tabs would fail to lockably engage with the heel portion of the coupling element in the event that the opposed stringers are coupled together with the coupling elements in one row misaligned with respect to those in the other row; that is when the elements on one stringer are interengaged with their counterparts on the other stringer with one element pitch shifted out of position either in the opening or the closing direction of the fastener, or stated otherwise when the coupling elements on the right side are disposed half an element pitch out of alignment with respect to those on the left side as visualized in Figure 6, in which instance only one of the two locking tabs engages with the heel portion of the element, while the other tab does not because the element to be arrested thereby is displaced half a pitch from the normal position. Thus, such one-sided locking action would not be effective when the fastener is subjected to a lateral pull or force applied to spread its stringers apart.

With the foregoing drawbacks of the prior art in view, the present invention seeks to provide an improved slider for slide fasteners which has means for locking the slider positively in place against unintentional movement under the influence of a force tending to spread open the fastener.

More specifically, the invention seeks to provide an improved slider for a ladder-type or meandering-element slide fastener which has a dual locking means capable of retaining the slider in locked position even when a row of coupling elements on one stringer is displaced or shifted out of the normal pitch relation to an opposite row of elements on the other stringer.

Other features and advantages of the invention will be apparent from the following detailed description taken in connection with the accompanying drawings which illustrate by way of example some preferred embodiments which the invention assume in practice.

According to the invention, there is provided a slider for a slide fastener of the type comprising a pair of oppositely disposed stringers each carrying a row of ladder-like or meandering coupling elements, each of which elements has a head portion and a heel portion, the slider comprising upper and lower wing members spaced in parallel and joined together at their one or front ends by a connecting post, a pair of opposed lateral flanges extending from each of the wing members and inwardly directed to define with the wing members a substantially Y-shaped guide channel for the passage of the stringers, and means of locking the slider in place against inadvertent movement comprising a locking lug extending from one end of at least either one of the upper and lower flanges, a first locking projection extending from one end of at least either one of the upper and lower flanges opposite to the locking lug and a second locking projection spaced one element pitch apart from the first locking projection.

Figure 1 is a fragmentary side elevational view on enlarged scale of a double pull tab slider embodying the invention;

Figure 2 is an enlarged sectional view taken on the line II - II of Figure 1 with fastener tapes removed and showing one mode of locking action;

Figure 3 is an enlarged sectional view taken on the line III- III of Figure 1 with fastener tapes removed;

Figure 4 is a view similar to Figure 2 but is utilized to explain another mode of locking action;

Figures 5a and 5b each are a diagrammatic view showing alternative positions of locking means according to the invention; and

Figure 6 is a fragmentary sectional view similar to Figure 2 but of a prior art slider.

Referring now to the accompanying drawings and Figure 1 in particular, there is shown a slider generally designated 10 which is mounted on a ladder-type slide fastener F comprising a pair of oppositely disposed support tapes T each carrying

a row of meandering or zig-zag coupling elements E, the tape together with the coupling elements constituting what is commonly termed a stringer. The slider 10 has two pull tabs 11, 12 pivotally mounted on its upper and lower surfaces, respectively, so as to enable movement of the slider conveniently from either side of the fastener F.

The slider 10 comprises an upper plate or wing member 13 and a lower wing member 14 which are spaced in parallel and joined together at their one or upper ends (as viewed in Figures 2 - 4) by a connecting post 15 commonly known as a "diamond". The upper and lower wing members 13, 14 each have lateral side flanges 16, 17 and 18, 19 respectively, which are inwardly directed to define together with their wings and the post 15 a substantially Y-shaped guide channel 20 for the passage therethrough of the fastener stringers.

Figure 3 shows the upper wing member 13 as viewed from its interior, from which it will be seen that the coupling elements E in opposed rows on their support tapes (not shown) are separated as they move past the post 15 upwardly or in a direction to open the fastener F and become interengaged as they are drawn into the guide channel 20 or moved downwardly or in a direction to close the fastener F. To facilitate this alternative movement of the coupling elements E relative to the slider 10, the flanges 16, 17 (18, 19) are flared upwardly or toward the post 15 to provide outwardly curved inner abutment walls 16a, 17a (18a, 19a) for smooth progressive sliding contact with the heel portions E1 of the coupling elements E while the head portions E2 thereof on one support tape are brought into or out of engagement with those on the other mating tape as is well known. Straight inner abutment walls 16b, 17b (18b, 19b) are formed contiguous with the curved walls 16a, 17a and adapted, as well known, to orient and maintain the opposed rows of elements E in fully interengaged position.

A locking means is provided for locking the slider in place against inadvertent movement which would otherwise occur under the influence of a force tending to spread apart the halves of the fastener F, the locking means comprising a locking lug 21 formed on the upper end of one of the opposed flanges 18 of the lower wing member 14, a first locking projection 22 formed on the upper end of the other flange 19 and a second locking projection 23 spaced from the first projection 22 by a distance substantially corresponding to one element-to-element pitch P. The locking lug 21, first and second locking projections 22 and 23 are all inwardly directed toward the channel 20 to arrest the coupling elements E and lock the slider 10 in place and have flat abutment surfaces 21a, 22a and 23a, respectively, these surfaces being sub-

stantially parallel with the longitudinal axis of the slider or with the direction of linear movement of the interengaged rows of elements to allow contact with the heel portions E1 of the coupling elements with minimum of friction.

The first projection 22 on the flange 19 is registered in position with locking lug 21 on the confronting flange 18, but is reduced in width to provide space for the formation of the second projection 23 which lies substantially one pitch P apart from the first projection 22 for purposes hereafter described.

In operation, the slider 10 with the fastener F applied to a garment article will automatically lock itself against inadvertent movement by the cooperative action of the locking lug 21 and the first and second locking projections 22 and 23, in which the lug 21 arrests the coupling element E on one stringer close at the leading end of its heel portion E1, while the first projection 22 similarly arrests the coupling element E on the other stringer as shown in Figure 2 where there is no disruption in the normal pitch relation between the two opposed rows of elements E. In the event however that the coupling elements E in the respective rows are shifted out of the normal pitch relation, the particular element Ea on one stringer, which would otherwise be located with its heel portion E1 at the first locking projection 22, becomes displaced so that no locking action takes place thereat, while the corresponding element E on the other stringer is arrested by the locking lug 21, in which instance the ensuing element Eb is arranged to come into contact with the second locking projection 23 as shown in Figure 4, thus establishing effective positive lock of the slider 10.

The flanges 16, 17 of the upper wing member 13 are reduced in their overall length with a view to preserving aesthetically attractive front surface appearance of the slider 10.

Various changes and modifications may be made in the specific form and construction hereinabove advanced, without departing from the scope of the appended claims.

For example, the locking lugs 21, first and second projections 22 and 23 may be provided at both upper and lower flanges of the slider 10 in different locations as shown in Figure 5a, or alternatively they may be provided only at the upper flanges as shown in Figure 5b.

Claims

1. A slider (10) for a slide fastener (F) of the type comprising a pair of oppositely disposed stringers each carrying a row of ladder-like or meandering coupling elements (E), each of which elements (E) has a head portion (E₂)



a row of meandering or zig-zag coupling elements E, the tape together with the coupling elements constituting what is commonly termed a stringer. The slider 10 has two pull tabs 11, 12 pivotally mounted on its upper and lower surfaces, respectively, so as to enable movement of the slider conveniently from either side of the fastener F.

The slider 10 comprises an upper plate or wing member 13 and a lower wing member 14 which are spaced in parallel and joined together at their one or upper ends (as viewed in Figures 2 - 4) by a connecting post 15 commonly known as a "diamond". The upper and lower wing members 13, 14 each have lateral side flanges 16, 17 and 18, 19 respectively, which are inwardly directed to define together with their wings and the post 15 a substantially Y-shaped guide channel 20 for the passage therethrough of the fastener stringers.

Figure 3 shows the upper wing member 13 as viewed from its interior, from which it will be seen that the coupling elements E in opposed rows on their support tapes (not shown) are separated as they move past the post 15 upwardly or in a direction to open the fastener F and become interengaged as they are drawn into the guide channel 20 or moved downwardly or in a direction to close the fastener F. To facilitate this alternative movement of the coupling elements E relative to the slider 10, the flanges 16, 17 (18, 19) are flared upwardly or toward the post 15 to provide outwardly curved inner abutment walls 16a, 17a (18a, 19a) for smooth progressive sliding contact with the heel portions E1 of the coupling elements E while the head portions E2 thereof on one support tape are brought into or out of engagement with those on the other mating tape as is well known. Straight inner abutment walls 16b, 17b (18b, 19b) are formed contiguous with the curved walls 16a, 17a and adapted, as well known, to orient and maintain the opposed rows of elements E in fully interengaged position.

A locking means is provided for locking the slider in place against inadvertent movement which would otherwise occur under the influence of a force tending to spread apart the halves of the fastener F, the locking means comprising a locking lug 21 formed on the upper end of one of the opposed flanges 18 of the lower wing member 14, a first locking projection 22 formed on the upper end of the other flange 19 and a second locking projection 23 spaced from the first projection 22 by a distance substantially corresponding to one element-to-element pitch P. The locking lug 21, first end locking projections 22 and 23 are all inwardly directed toward the channel 20 to arrest the coupling elements E and lock the slider 10 in place and have flat abutment surfaces 21a, 22a and 23a, respectively, these surfaces being sub-

stantially parallel with the longitudinal axis of the slider or with the direction of linear movement of the interengaged rows of elements to allow contact with the heel portions E1 of the coupling elements with minimum of friction.

The first projection 22 on the flange 19 is registered in position with locking lug 21 on the confronting flange 18, but is reduced in width to provide space for the formation of the second projection 23 which lies substantially one pitch P apart from the first projection 22 for purposes hereafter described.

In operation, the slider 10 with the fastener F applied to a garment article will automatically lock itself against inadvertent movement by the cooperative action of the locking lug 21 and the first and second locking projections 22 and 23, in which the lug 21 arrests the coupling element E on one stringer close at the leading end of its heel portion E1, while the first projection 22 similarly arrests the coupling element E on the other stringer as shown in Figure 2 where there is no disruption in the normal pitch relation between the two opposed rows of elements E. In the event however that the coupling elements E in the respective rows are shifted out of the normal pitch relation, the particular element Ea on one stringer, which would otherwise be located with its heel portion E1 at the first locking projection 22, becomes displaced so that no locking action takes place thereat, while the corresponding element E on the other stringer is arrested by the locking lug 21, in which instance the ensuing element Eb is arranged to come into contact with the second locking projection 23 as shown in Figure 4, thus establishing effective positive lock of the slider 10.

The flanges 16, 17 of the upper wing member 13 are reduced in their overall length with a view to preserving aesthetically attractive front surface appearance of the slider 10.

Various changes and modifications may be made in the specific form and construction hereinabove advanced, without departing from the scope of the appended claims.

For example, the locking lugs 21, first and second projections 22 and 23 may be provided at both upper and lower flanges of the slider 10 in different locations as shown in Figure 5a, or alternatively they may be provided only at the upper flanges as shown in Figure 5b.

Claims

1. A slider (10) for a slide fastener (F) of the type comprising a pair of oppositely disposed stringers each carrying a row of ladder-like or meandering coupling elements (E), each of which elements (E) has a head portion (E2)



and a heel portion (E₁), said slider comprising upper and lower wing members (13, 14) spaced in parallel and joined together at their one or front ends by a connecting post (15), a pair of opposed lateral flanges (16, 17; 18, 19) extending from each of said wing members and inwardly directed to define with said wing members a substantially Y-shaped guide channel (20) for the passage of said stringers, and means of locking the slider in place against inadvertent movement comprising a locking lug (21) extending from one end of at least either one of said upper and lower flanges, a first locking projection (22) extending from one end of at least either one of said upper and lower flanges opposite to said locking lug (21) and a second locking projection (23) spaced one element pitch (P) apart from said first locking projection.

2. A slider (10) as claimed in claim 1 wherein each of said locking lug (21) and said first and second locking projections (22, 23) has an inner surface lying substantially parallel with the longitudinal axis of the slider (10).
3. A slider (10) as claimed in claim 1 or 2 wherein said first locking projection (22) is reduced in width to provide space for the formation of said second locking projection (23).
4. A slider (10) as claimed in one of the preceding claims including a pair of pull tabs (11, 12) mounted on said upper and lower wing members (13, 14) to facilitate movement of the slider from either side of the fastener.
5. A slider (10) as claimed in one of the preceding claims wherein said first and second locking projections (22, 23) each are arranged to arrest the coupling element (E) at the leading end of its heel portion (E₁).
6. A slider (10) as claimed in one of the preceding claims wherein the pair of flanges on said upper wing member (13) are shorter in length than that on said lower wing member (14).

Patentansprüche

1. Schieber (10) für einen Reißverschluß (F) einer Bauart mit zwei gegenüberliegend angeordneten Reißverschlußbändern, die jeweils eine leiterartige oder mäanderförmige Reihe von Kuppelgliedern (E) tragen, wobei jedes Kuppelglied (E) einen Kupplungsbereich (E₂) und einen Verbindungsbereich (E₁) hat, wobei der Schieber umfaßt: einen Oberschild und einen

Unterschild (13, 14), die im Abstand parallel angeordnet und an ihrem einen oder vorderen Ende durch einen Schieberkeil (15) miteinander verbunden sind, zwei gegenüberliegende Seitenflansche (16, 17; 18, 19), die sich von jedem Schild erstrecken und nach innen gerichtet sind, um mit den Schilden einen im wesentlichen Y-förmigen Führungskanal für den Durchgang der Reißverschlußbänder zu schaffen, und Mittel zum Verriegeln des Schiebbers gegen eine unbeabsichtigte Bewegung, die eine Sperrnase (21) aufweisen, die sich von einem Ende mindestens eines der oberen und unteren Flansche erstrecken, einen ersten Sperrvorsprung (22) aufweisen, der sich von einem Ende mindestens eines der oberen und unteren Flansche gegenüber der Sperrnase (21) erstreckt, und einen zweiten Sperrvorsprung (23) aufweisen, der um eine Kuppelgliederteilung (P) gegen den ersten Sperrvorsprung versetzt ist.

2. Schieber (10) nach Anspruch 1, wobei die Sperrnase (21) und der erste und der zweite Sperrvorsprung (22, 23) eine Innenfläche hat, die zur Längsachse des Schiebbers (10) im wesentlichen parallel ist.
3. Schieber (10) nach Anspruch 1 oder 2, wobei die Breite des ersten Sperrvorsprungs (22) verringert ist, um einen Zwischenraum zur Ausbildung des zweiten Sperrvorsprungs (23) zu schaffen.
4. Schieber (10) nach einem der vorhergehenden Ansprüche, mit zwei Griffen (11, 12), die an dem Ober- bzw. Unterschild (13, 14) angeordnet sind, um die Bewegung des Schiebbers von jeder Seite des Reißverschlusses her zu erleichtern.
5. Schieber (10) nach einem der vorhergehenden Ansprüche, wobei der erste und der zweite Sperrvorsprung (22, 23) jeweils so angeordnet ist, um das Kuppelglied (E) am vorderen Ende seines Verbindungsbereichs (E₁) zu arretieren.
6. Schieber (10) nach einem der vorhergehenden Ansprüche, wobei die beiden Flansche am Oberschild (13) kürzer sind als diejenigen am Unterschild (14).

Revendications

1. Curseur (10) de fermeture à glissière (F) du type comportant une paire de bandes d'accrochage disposées en face l'une de l'autre, portant chacune une rangée d'éléments d'accou-



plement (E) analogue à une échelle ou formant des méandres, chacun desdits éléments (E) ayant une partie (E₂) formant une tête et une partie (E₁) formant un talon, ledit curseur comportant des éléments (13, 14) supérieur et inférieur formant ailes espacés parallèlement et réunis à l'une de leurs extrémités, ou extrémité avant, par un pilier de liaison (15), une paire de rebords latéraux (16, 17 ; 18, 19) qui sont disposés face-à-face, s'étendant à partir de chacun des éléments formant ailes et orientés vers l'intérieur afin de définir, avec lesdits éléments formant ailes, un canal de guidage (20) sensiblement en forme de Y pour le passage desdites bandes d'accrochage, et des moyens de verrouillage du curseur à l'endroit où il se trouve à l'encontre des déplacements involontaires, comportant un ergot de blocage (21) s'étendant à partir de l'une des extrémités d'au moins l'un ou l'autre desdits rebords supérieur et inférieur, une première saillie de blocage (22) qui s'étend à partir de l'une des extrémités d'au moins un desdits rebords supérieur et inférieur, en face dudit ergot de blocage (21) et une seconde saillie de blocage (23) espacée de ladite première saillie de blocage d'un pas (P) des éléments.

bords de la paire de rebords située sur ledit élément (13) supérieur formant aile sont plus courts que ceux situés sur ledit élément (14) inférieur formant aile.

2. Curseur (10) selon la revendication 1 dans lequel chacun desdits ergots de blocage (21) et lesdites première et seconde saillies de blocage (22, 23) comportent une surface intérieure sensiblement parallèle à l'axe longitudinal du curseur (10).
3. Curseur (10) selon la revendication 1 ou 2 dans lequel ladite première saillie de blocage (22) a une largeur réduite afin de procurer de l'espace pour la réalisation de ladite seconde saillie de blocage (23).
4. Curseur (10) selon l'une quelconque des revendications précédentes, comportant une paire de tirettes (11, 12) montées sur lesdits éléments supérieur et inférieur (13, 14) formant ailes afin de faciliter le déplacement du curseur à partir de l'un ou de l'autre côté de la fermeture à glissière.
5. Curseur (10) selon l'une quelconque des revendications précédentes dans lequel les première et seconde saillies de blocage (22, 23) sont agencées chacune de manière à bloquer l'élément d'accouplement (E) à l'extrémité avant de sa partie (E₁) formant talon.
6. Curseur (10) selon l'une quelconque des revendications précédentes dans lequel les re-