

Description

TOURBILLON FOR TIMEPIECE

Technical field

[0001] The invention concerns a tourbillon for clock movement, a clock movement and a timepiece equipped with such a tourbillon.

State of the art

[0002] Various systems are known for reducing the running rate variation of a wristwatch while it is being worn. The tourbillon is one of the most commonly used systems as the rotating of the regulating device (generally 1 revolution per minute) enables the rate differences in vertical positions to be practically eliminated.

[0003] The carriage of the tourbillon is generally either held in place by two pivots, one in the plate and the other in a bridge, or pivoted in a ball bearing, which makes it more visible on the dial side.

Disclosure of the invention

[0004] The purpose of the invention is to eliminate the guidance of the carriage of the tourbillon at the centre and improve the guidance of the carriage and the general aesthetics of the movement of the watch.

[0005] This invention thus provides for the guidance of the carriage to be carried out on the periphery of the tourbillon, thus improving the visibility of the carriage,

[0006] The tourbillon according to the invention, for clock movement of the type comprising a frame on which the tourbillon is designed to be fitted, comprises a carriage, carrying a balance spring, a spiral and an escapement, and comprising a bridge designed to present a movement of rotation with respect to the frame of the clock movement. The tourbillon is characterised by the fact that the bridge presents a circular periphery capable of cooperating with at least three rollers mounted so as to pivot on the clock movement to ensure the suspension and positioning of the tourbillon on the frame.

[0007] The invention also concerns a clock movement comprising at least three rollers pivoting with respect to the frame of the movement and between

which a tourbillon presenting the above characteristics is suspended and guided,

- [0008] According to a preferred mode of execution, one of the pivoting rollers is mobile in a transverse direction with respect to its axis of rotation, in such a way as to enable the engagement and mounting of the carriage between the rollers.
- [0009] The clock movement may advantageously present an eccentric enabling the position of the mobile roller on the frame to be adjusted precisely, in order to carry out adjustment of the clearances of the assembly.
- [0010] The mobile roller may be mounted on an arm pivoting between an opening position and a carriage locking position.
- [0011] The carriage may present an upper bridge, a lower bridge and an escapement bridge supporting a balance spring, a spiral, an escapement wheel and a pallet assembly,
- [0012] Preferably, the lower bridge presents a circular configuration and its periphery is designed to fit into a groove on the outer edge of each of the rollers.
- [0013] The tourbillon may be driven by a pinion attached under the carriage. Alternatively, the tourbillon may be driven by a toothed ring attached to a bridge of the carriage, preferably a lower bridge, that is to say located on the bridge side of a movement in which the tourbillon is mounted.
- [0014] With the tourbillon according to the invention, the guidance of the carriage at the centre is replaced by the guidance of the three rollers positioning the lower bridge of the carriage axially and radially from the outside. The guidance of the carriage is thus better and more precise than the guidance provided by the central pivots. In addition, the visibility of the tourbillon in a timepiece integrating it is thus considerably improved both from the dial side and from the timepiece back; side.

Brief description of the drawings

- [0015] The drawing represents, as an example, two modes of execution of a suspended tourbillon according to the invention.
- [0016] Figure 1 is a perspective view of a suspended tourbillon with driving of the carriage of the tourbillon by a central pinion attached to said carriage,

- [0017] Figure 2 is a section of the tourbillon shown in figure 1 in a sectional plane containing the axes of rotation of the carriage and the escapement wheel,
- [0018] Figure 3 is a perspective view of a second mode of execution of a suspended tourbillon with driving of the tourbillon carriage by an outer toothed ring attached to the lower bridge of the carriage, and
- [0019] Figure 4 is a section of the tourbillon shown in figure 3 in a sectional plane containing the axes of rotation of the carriage and the escapement wheel.

Detailed description of the invention

- [0020] For a better understanding of the two modes of execution of the mechanism illustrated in figures 1 to 4, the frame elements of the clock movement, notably the plate and the bridges, have not been shown in the perspective views in figures 1 and 3. The tourbillon illustrated in the drawing was developed for a wristwatch. This use is not limitative, however, and the tourbillon illustrated in the drawing may be mounted in pocket watches or small clocks.
- [0021] The suspended tourbillon illustrated in the two variants of the drawing comprises a tourbillon carriage essential consisting of an upper bridge 1, a lower bridge 2 and an escapement bridge 3 carrying a balance spring 4, an escapement wheel 5 and a pallet assembly 6. The carriage is driven either by a pinion 7 attached under the carriage (Fig. 1) or by a toothed ring 8 attached to the lower bridge 2 of the carriage. (Fig.3). The lower bridge of the carriage 2 is designed to be able to be positioned axially and radially by means of two fixed rollers 9 and 10 and a mobile roller 11.
- [0022] The latter is connected to the frame of the movement in such a way as to be mobile between two extreme positions in a transverse direction with respect to its axis of rotation. As shown as an example, the mobile roller is carried by an arm 11a pivoting between an opening position enabling the engagement of the carriage between the rollers and a locking position which can be adjusted by means of an eccentric 12 placed on the pivoting arm. In a known manner, a modification of the orientation of the eccentric makes it possible to adjust the position of the mobile roller with respect to the frame of the movement. The regulating device of the tourbillon carriage is placed in motion in a conventional manner by means of a fixed wheel 13

attached to the plate, not shown, and arranged in engagement with the escapement wheel 5.

- [0023] As shown in the drawing, the lower bridge 2 presents a circular periphery designed to fit in an annular groove on the outer edge of each of the rollers 9, 10 and 11. Advantageously, the surfaces of the periphery of the bridge 2, on the one hand, and of the grooves, on the other hand, may be of substantially complementary shapes.
- [0024] The one skilled in the art will be able to assemble the rollers on the frame of the movement in the manner most appropriate to his needs without departing from the scope of this invention. In particular, the fixed rollers 9 and 10 may be mounted on shafts pivoting in jewels of the frame, one in the plate and the other in a bridge, or on single bearings of the ball bearing type, for example.
- [0025] The positioning and the guidance of the carriage, carried out on the outside of said carriage, thus make its functioning visible on the bottom of the movement as well as on the top.

Claims

1. Tourbillon for clock movement comprising a frame on which the tourbillon is designed to be fitted, the tourbillon comprising a carriage carrying a balance spring, a spiral and an escapement wheel and comprising a bridge designed to present a movement of rotation with respect to the frame of the clock movement, characterised in that said bridge presents a circular periphery capable of cooperating with at least three rollers mounted pivoting on the clock movement to ensure the suspension and positioning of the tourbillon on the frame.
2. Tourbillon according to claim 1, characterised in that said circular periphery presents a surface shaped in such a way as to be substantially complementary to a surface of each roller of the clock movement with which it is intended to be in contact.
3. Tourbillon according to claims 1 or 2, characterised in that it comprises a lower bridge, an upper bridge and an escapement bridge supporting the balance spring, an escapement wheel and a pallet assembly, said lower bridge being designed to cooperate with the rollers of the clock movement.
4. Clock movement comprising a frame on which a tourbillon is mounted in rotation, this tourbillon comprising a carriage carrying a balance spring, a spiral and an escapement wheel and comprising a bridge, characterised in that said bridge presents a circular periphery cooperating with at least three rollers mounted so as to pivot on said frame in such a way as to suspend and position said tourbillon with respect to said frame.
5. Clock movement according to claim 4, characterised in that at least one of said rollers is arranged on said frame in such a way as to be mobile between two extreme positions in a transverse direction with respect to its axis of rotation.
6. Clock movement according to claim 5, characterised in that it comprises an eccentric of which the orientation makes it possible to adjust the position of said mobile roller with respect to said frame.

7. Clock movement according to claim 5, characterised in that said mobile roller is mounted in rotation on an arm pivoting on said frame between an opening position and a locking position of said tourbillon carriage.
8. Clock movement according to any one of claims 4 to 7, characterised in that said circular periphery of said bridge presents a surface shaped in such a way as to be substantially complementary to a surface of each of said rollers with which it is intended to be in contact.
9. Clock movement according to any one of claims 4 to 7, characterised in that each of said rollers presents an annular groove designed to cooperate with said circular periphery of said bridge,
10. Timepiece comprising a case containing a clock movement according to any one of claims 4 to 7,
11. Timepiece comprising a case containing a clock movement according to claim 8.
12. Timepiece comprising a case containing a dock movement according to claim 9.