Claims

1. A video image decoding device comprising:

a variable length decoder that performs a variable-length decoding process on coded data multiplexed into a bitstream to obtain coding mode which indicates a prediction process performed to generate a prediction image and index information which specifies a motion vector for a coding block; and

a motion compensator that performs a motion compensation prediction process on said coding block to generate a prediction image using a motion vector selected from one or more selectable motion vector candidates when said coding mode indicates inter prediction, said motion compensator selecting said motion vector from said motion vector candidates according to said index information;

wherein

said motion compensator prepares a list of said motion vector candidates including one or more spatial motion vectors which are obtained from a decoded block located around said coding block and/or a temporal motion vector which is obtained from a different picture which can be referred to by said coding block, said motion vector candidates being listed in accordance with a predetermined order, and said index information specifying a position in which one of said motion vector candidates exists within said list.

2. A video image decoding method comprising:

performing a variable-length decoding process on coded data multiplexed into a bitstream to obtain coding mode which indicates a prediction process performed to generate a prediction image and index information which specifies a motion vector for a coding block; and

performing a motion compensation prediction process on said coding block to generate a prediction image using a motion vector selected from one or more selectable motion vector candidates when said coding mode indicates inter prediction, said motion vector being selected from said motion vector candidates according to said index

information;

wherein

said motion vector candidates include one or more spatial motion vectors which are obtained from a decoded block located around said coding block and/or a temporal motion vector which is obtained from a decoded picture which can be referred to by said coding block, said motion vector candidates being listed in accordance with a predetermined order, and said index information specifying a position in which one of said motion vector candidates exists within said list.

3. A video image encoding device comprising:

a motion compensator that performs a motion compensation prediction process on a coding block to generate a prediction image using a motion vector selected from one or more selectable motion vector candidates, said motion compensator selecting said motion vector from said motion vector candidates;

a variable encoder that performs a variable-coding process to generate coding mode which indicates a prediction process performed to generate said prediction image and index information which specifies selected one of said motion vector candidates;

wherein

said motion compensator prepares a list of said motion vector candidates including one or more spatial motion vectors which is obtained from a coded block located around said coding block and/or a temporal motion vector which is obtained from a different picture which can be referred to by said coding block, said motion vector candidates being listed in accordance with a predetermined order, and said index information specifying a position in which one of said motion vector candidates exists within said list.

4. A video image encoding method comprising:

performing a motion compensation prediction process on a coding block to generate a prediction image using a motion vector selected from one or more selectable motion vector candidates, said motion compensator selecting said motion vector from said motion vector candidates;

performing a variable-coding process to generate coding mode which indicates a prediction process performed to generate said prediction image and index information which specifies selected one of said motion vector candidates;

wherein

said motion compensator prepares a list of said motion vector candidates including one or more spatial motion vectors which is obtained from a coded block located around said coding block and/or a temporal motion vector which is obtained from a different picture which can be referred to by said coding block, said motion vector candidates being listed in accordance with a predetermined order, and said index information specifies a position in which one of said motion vector candidates exists within said list.

5. A non-transitory computer-readable storage medium storing a bit stream comprising:

coding mode which indicates a prediction process performed to generate a prediction image

a compressed data generated by performing compression process on a difference between an image and said prediction image;

index information which specifies a motion vector used to perform a motion compensation prediction process to generate said prediction image;

wherein when said motion vector is selected from one or more motion vector candidates including one or more spatial motion vectors which is obtained from a coded block located around said coding block and/or a temporal motion vector which is obtained from a different picture which can be referred to by said coding block, said index information specifies selected one of said motion vector candidates, and wherein said motion vector candidate being listed in accordance with a predetermined order, and said index information specifying a position in which one of said motion vector candidates exists within said list.