

ENHANCED SOLUBLE C₅ SACCHARIDE YIELDS

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application claims benefit to U.S. Application No. 61/482,437 filed May 4, 2011, the entire disclosure of which is incorporated by reference.

FIELD OF THE INVENTION

[0002] The present invention generally relates to methods of increasing the yields of fermentable C₅ sugars from lignocellulosic biomass. More particularly, it relates to methods of increasing the yields of fermentable C₅ sugars from lignocellulosic biomass using steps that maximize monomer formation and minimize the formation of degradation products.

BACKGROUND OF THE INVENTION

[0003] There exist methods for converting lignocellulosic biomass into fermentable C₅ sugars. Several of these methods first produce oligomers of the C₅ sugars, which are then hydrolyzed to form fermentable streams of monomers of C₅ sugars. Problems exist with current methods, including, *inter alia*, that the soluble higher molecular weight oligomers recondense back to insoluble oligomers. To counter this problem, the methods may be performed to drive the hydrolysis of the biomass towards monomer. However, these more stringent conditions often lead to degradation products, such as acids that inhibit fermentation. Also, there are separation challenges as well. It would, therefore, be beneficial to develop methods that avoid this tradeoff to maximize monomer formation and to minimize the formation of degradation products. The methods and compositions of the present invention are directed toward these, as well as other, important ends.

SUMMARY OF THE INVENTION

[0004] In one embodiment, the invention is directed to methods of increasing the level of soluble C₅ saccharides produced from lignocellulosic biomass, comprising:

providing a fractionated lignocellulosic biomass comprising:

a solid fraction comprising:

optionally, insoluble C₅ oligosaccharide;

cellulose; and

lignin; and

a first liquid fraction at a first temperature and a first pressure comprising:

soluble C₅ saccharides selected from the group consisting of C₅ oligosaccharides, xylose, arabinose, lyxose, ribose, and mixtures thereof;

wherein said soluble C₅ saccharides are present at a first level;

acidifying said fractionated lignocellulosic biomass to form a second liquid fraction comprising said soluble C₅ saccharides at a second level and at a second temperature;

wherein said second level is higher than said first level;

optionally, separating said solid fraction from said second liquid fraction; and

optionally, hydrolyzing said second liquid fraction to form C₅ saccharides selected from the group consisting of C₅ oligosaccharides having fewer mer units, C₅ monosaccharides, and mixtures thereof.

[0005] In another embodiment, the invention is directed to methods of increasing the level of soluble C₅ saccharides produced from lignocellulosic biomass, comprising:

providing a fractionated lignocellulosic biomass comprising:

a solid fraction comprising:

optionally, insoluble C₅ oligosaccharide;

cellulose; and

lignin; and

a first liquid fraction at a first temperature and a first pressure comprising:

soluble C₅ saccharides selected from the group consisting of C₅ oligosaccharides, xylose, arabinose, lyxose, ribose, and mixtures thereof;

wherein said soluble C₅ saccharides are present at a first level;
optionally, separating said solid fraction from said first liquid fraction at a second pressure;
wherein said first pressure and said second pressure are substantially the same;
contacting said first liquid fraction with a solid acid catalyst to form a second liquid fraction comprising said soluble C₅ saccharides at a second level and at a second temperature;
wherein said second level is greater than said first level;
optionally, hydrolyzing said second liquid fraction to form C₅ saccharides selected from the group consisting of C₅ oligosaccharides having fewer mer units, C₅ monosaccharides, and mixtures thereof.

[0006] In yet other embodiments, the invention is directed to methods of increasing the level of fermentative product or catalytic product produced from lignocellulosic biomass, comprising:

providing a fractionated lignocellulosic biomass comprising:
a solid fraction comprising:
optionally, insoluble C₅ oligosaccharide;
cellulose; and
lignin; and
a first liquid fraction at a first temperature and a first pressure comprising:
soluble C₅ saccharides selected from the group consisting of C₅ oligosaccharides, xylose, arabinose, lyxose, ribose, and mixtures thereof;
wherein said soluble C₅ saccharides are present at a first level;
acidifying said fractionated lignocellulosic biomass to form a second liquid fraction comprising said soluble C₅ saccharides at a second level and at a second temperature;
wherein said second level is greater than said first level;
optionally, separating said solid fraction from said second liquid fraction;
hydrolyzing said second liquid fraction to form C₅ oligosaccharides having fewer mer units, C₅ monosaccharides, and mixtures thereof; and
fermenting, catalyzing, or fermenting and catalyzing said C₅ saccharides to form said fermentation product, said catalytic product, or a combination thereof.

[0007] In yet other embodiments, the invention is directed to products produced by the methods of the invention.

[0008] In yet other embodiments, the invention is directed to compositions, comprising:

soluble C₅ oligosaccharides capable of being membrane separated, preferably having have about 2 mer units to about 15 mer units; and

water;

wherein said composition has a pH of about 1.5 to about 6.0; and

wherein said soluble C₅ oligosaccharides have about 2 mer units to about 15 mer units.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention. In the drawings:

[0010] **FIGURE 1** is a schematic diagram showing the acidification step after separation of the solid fraction from first liquid fraction for one embodiment of the invention.

[0011] **FIGURE 2** is a schematic diagram showing the acidification step using a solid acid catalyst for one embodiment of the invention.

[0012] **FIGURE 3** is a schematic diagram showing the acidification step using an immobilized enzyme for one embodiment of the invention.

[0013] **FIGURE 4** is a schematic diagram showing the acidification step before the separation of the solid fraction from first fraction for one embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

[0014] As employed above and throughout the disclosure, the following terms, unless otherwise indicated, shall be understood to have the following meanings.

[0015] As used herein, the singular forms “a,” “an,” and “the” include the plural reference unless the context clearly indicates otherwise.

[0016] While the present invention is capable of being embodied in various forms, the description below of several embodiments is made with the understanding that the present disclosure is to be considered as an exemplification of the invention, and is not intended to limit the invention to the specific embodiments illustrated. Headings are provided for convenience only and are not to be construed to limit the invention in any manner. Embodiments illustrated under any heading may be combined with embodiments illustrated under any other heading.

[0017] The use of numerical values in the various quantitative values specified in this application, unless expressly indicated otherwise, are stated as approximations as though the minimum and maximum values within the stated ranges were both preceded by the word “about.” In this manner, slight variations from a stated value can be used to achieve substantially the same results as the stated value. Also, the disclosure of ranges is intended as a continuous range including every value between the minimum and maximum values recited as well as any ranges that can be formed by such values. Also disclosed herein are any and all ratios (and ranges of any such ratios) that can be formed by dividing a recited numeric value into any other recited numeric value. Accordingly, the skilled person will appreciate that many such ratios, ranges, and ranges of ratios can be unambiguously derived from the numerical values presented herein and in all instances such ratios, ranges, and ranges of ratios represent various embodiments of the present invention.

[0018] A supercritical fluid is a fluid at a temperature above its critical temperature and at a pressure above its critical pressure. A supercritical fluid exists at or above its “critical point,” the point of highest temperature and pressure at which the liquid and vapor (gas) phases can exist in

equilibrium with one another. Above critical pressure and critical temperature, the distinction between liquid and gas phases disappears. A supercritical fluid possesses approximately the penetration properties of a gas simultaneously with the solvent properties of a liquid. Accordingly, supercritical fluid extraction has the benefit of high penetrability and good solvation.

[0019] Reported critical temperatures and pressures include: for pure water, a critical temperature of about 374.2°C, and a critical pressure of about 221 bar; for carbon dioxide, a critical temperature of about 31°C and a critical pressure of about 72.9 atmospheres (about 1072 psig). Near-critical water has a temperature at or above about 300°C and below the critical temperature of water (374.2°C), and a pressure high enough to ensure that all fluid is in the liquid phase. Sub-critical water has a temperature of less than about 300°C and a pressure high enough to ensure that all fluid is in the liquid phase. Sub-critical water temperature may be greater than about 250°C and less than about 300°C, and in many instances sub-critical water has a temperature between about 250°C and about 280°C. The term “hot compressed water” is used interchangeably herein for water that is at or above its critical state, or defined herein as near-critical or sub-critical, or any other temperature above about 50°C but less than subcritical and at pressures such that water is in a liquid state

[0020] As used herein, a fluid which is “supercritical” (*e.g.* supercritical water, supercritical CO₂, *etc.*) indicates a fluid which would be supercritical if present in pure form under a given set of temperature and pressure conditions. For example, “supercritical water” indicates water present at a temperature of at least about 374.2°C and a pressure of at least about 221 bar, whether the water is pure water, or present as a mixture (*e.g.* water and ethanol, water and CO₂, *etc.*). Thus, for example, “a mixture of sub-critical water and supercritical carbon dioxide” indicates a mixture of water and carbon dioxide at a temperature and pressure above that of the critical point for carbon dioxide but below the critical point for water, regardless of whether the supercritical phase contains water and regardless of whether the water phase contains any carbon dioxide. For example, a mixture of sub-critical water and supercritical CO₂ may have a temperature of about 250°C to about 280°C and a pressure of at least about 225 bar.

[0021] As used herein, “continuous” indicates a process which is uninterrupted for its duration, or interrupted, paused or suspended only momentarily relative to the duration of the process. Treatment of biomass is “continuous” when biomass is fed into the apparatus without interruption or without a substantial interruption, or processing of said biomass is not done in a batch process.

[0022] As used herein, “resides” indicates the length of time which a given portion or bolus of material is within a reaction zone or reactor vessel. The “residence time,” as used herein, including the examples and data, are reported at ambient conditions and are not necessarily actual time elapsed.

[0023] As used herein, “lignocellulosic biomass or a component part thereof” refers to plant biomass containing cellulose, hemicellulose, and lignin from a variety of sources, including, without limitation (1) agricultural residues (including corn stover and sugarcane bagasse), (2) dedicated energy crops, (3) wood residues (including sawmill and paper mill discards), and (4) municipal waste, and their constituent parts including without limitation, lignocellulose biomass itself, lignin, C₆ saccharides (including cellulose, cellobiose, C₆ oligosaccharides, C₆ monosaccharides, and C₅ saccharides (including hemicellulose, C₅ oligosaccharides, and C₅ monosaccharides).

[0024] In one embodiment, the invention is directed to methods of increasing the level of soluble C₅ saccharides produced from lignocellulosic biomass, comprising:

providing a fractionated lignocellulosic biomass comprising:

a solid fraction comprising:

optionally, insoluble C₅ oligosaccharide;

cellulose; and

lignin; and

a first liquid fraction at a first temperature and a first pressure comprising:

soluble C₅ saccharides selected from the group consisting of C₅ oligosaccharides, xylose, arabinose, lyxose, ribose, and mixtures thereof;

wherein said soluble C₅ saccharides are present at a first level;

acidifying said fractionated lignocellulosic biomass to form a second liquid fraction comprising said soluble C₅ saccharides at a second level and at a second temperature;

wherein said second level is greater than said first level;

optionally, separating said solid fraction from said second liquid fraction; and

optionally, hydrolyzing said second liquid fraction to form C₅ saccharides selected from the group consisting of C₅ oligosaccharides having fewer mer units, xylose, arabinose, lyxose, ribose, and mixtures thereof. The method is shown schematically in **FIGURE 1**.

[0025] In another embodiment, the invention is directed to methods of increasing the level of soluble C₅ saccharides produced from lignocellulosic biomass, comprising:

providing a fractionated lignocellulosic biomass comprising:

a solid fraction comprising:

optionally, insoluble C₅ oligosaccharide;

cellulose; and

lignin; and

a first liquid fraction at a first temperature and a first pressure comprising:

soluble C₅ saccharides selected from the group consisting of C₅ oligosaccharides, xylose, arabinose, lyxose, ribose, and mixtures thereof;

wherein said soluble C₅ saccharides are present at a first level;

optionally, separating said solid fraction from said first liquid fraction at a second pressure;

wherein said first pressure and said second pressure are substantially the same;

contacting said first liquid fraction with a solid acid catalyst to form a second liquid fraction comprising said soluble C₅ saccharides at a second level and at a second temperature (acidifying step);

wherein said second level is greater than said first level; and

optionally, hydrolyzing said second liquid fraction to form C₅ saccharides selected from the group consisting of C₅ oligosaccharides having fewer mer units, xylose, arabinose, lyxose, ribose, and mixtures thereof. The method is shown schematically in **FIGURE 1**.

[0026] In yet other embodiments, the invention is directed to methods of increasing the level of fermentation product or catalytic product produced from lignocellulosic biomass, comprising:

providing a fractionated lignocellulosic biomass comprising:

a solid fraction comprising:

optionally, insoluble C₅ oligosaccharide;

cellulose; and

lignin; and

a first liquid fraction at a first temperature and a first pressure comprising:

soluble C₅ saccharides selected from the group consisting of C₅ oligosaccharides, xylose, arabinose, lyxose, ribose, and mixtures thereof;

wherein said soluble C₅ saccharides are present at a first level;

acidifying said fractionated lignocellulosic biomass to form a second liquid fraction comprising said soluble C₅ saccharides at a second level and at a second temperature;

wherein said second level is greater than said first level;

optionally, separating said solid fraction from said second liquid fraction;

hydrolyzing said second liquid fraction to form C₅ saccharides selected from the group consisting of C₅ oligosaccharides having fewer mer units, xylose, arabinose, lyxose, ribose, and mixtures thereof; and

fermenting, catalyzing, or fermenting and catalyzing said C₅ saccharides to form said fermentation product, said catalytic product, or a combination thereof.

[0027] The acidifying step may be accomplished in a number of ways, including adding an aqueous acid (as shown schematically in **FIGURE 1** and **FIGURE 4**), contacting with a gaseous compound that forms acid *in situ*, and/or contacting with a solid acid catalyst (as shown schematically in **FIGURE 2**). The addition of acid hydrolyzes soluble higher molecular weight C₅ oligosaccharides and/or insoluble C₅ oligosaccharides to form more soluble lower molecular weight C₅ oligosaccharides, such that the second level of the soluble C₅ saccharides is greater than the first level of the soluble C₅ saccharides. The addition of acid shifts MW distribution of soluble higher molecular weight C₅ oligosaccharides to a lower average molecular weight, such that the soluble C₅ saccharides in second liquid fraction have an average molecular weight that is lower than the average molecular weight of the soluble C₅ saccharides in the first liquid

fraction. For example, the C₅ oligosaccharides in the first liquid fraction have about 2 mer units to about 25 mer units; and the C₅ oligosaccharides in the second liquid fraction have about 2 mer units to about 15 mer units.

[0028] In certain embodiments, the acidifying step comprises adding to the fractionated lignocellulosic biomass (as shown schematically in **FIGURE 4**) or to the first liquid fraction (as shown schematically in **FIGURE 1**) at least one aqueous acid selected from the group consisting of an organic acid, an inorganic acid, and mixtures thereof. Suitable inorganic acids include, but are not limited to: sulfuric acid, sulfonic acid, phosphoric acid, phosphonic acid, nitric acid, nitrous acid, hydrochloric acid, hydrofluoric acid, hydrobromic acid, hydroiodic acid. Suitable organic acids include, but are not limited to, aliphatic carboxylic acids (such as acetic acid and formic acid), aromatic carboxylic acids (such as benzoic acid and salicylic acid), dicarboxylic acids (such as oxalic acid, phthalic acid, sebacic acid, and adipic acid), aliphatic fatty acids (such as oleic acid, palmitic acid, and stearic acid), aromatic fatty acids (such as phenylstearic acid), and amino acids. In certain embodiments, the acid is preferably sulfuric acid, hydrochloric acid, phosphoric acid, nitric acid, or a combination thereof. Sulfuric acid is especially preferred. In certain embodiments, the acid is present at a level of about 0.05%, by weight, to about 2.0%, by weight, based on the total weight of the fraction to which the acid is added (either fractionated lignocellulosic biomass or first liquid fraction). In certain other embodiments, the amount of acid may be present in an amount from about 0.07% to about 2%, about 0.1% to about 1.5%, about 0.1% to about 1%, about 0.1% to about 0.5%, about 0.1% to about 0.4%, about 0.1% to about 0.3%, about 0.1% to about 0.2%, about 0.5% to about 2%, about 0.5% to about 1.5%, about 0.5% to about 1%, less than about 2%, less than about 1.5%, less than about 1%, less than about 0.5%, less than about 0.4%, less than about 0.3%, less than about 0.2%, or less than about 0.1%.

[0029] In certain other embodiments, the acidifying step comprises contacting said fractionated lignocellulosic biomass with a gaseous compound that forms acid *in situ*. Gaseous compounds that form acid *in situ* include, but are not limited to, SO₂, CO₂, NO₂, HX (where X is Cl, Br, F, or I), or a combination thereof. In certain embodiments, the acid is present at a level of about 0.05%, by weight, to about 2.0%, by weight, based on the weight of the liquid fraction. In certain other embodiments, the amount of acid may be present in an amount from about 0.07% to

about 2%, about 0.1% to about 1.5%, about 0.1% to about 1%, about 0.1% to about 0.5%, about 0.1% to about 0.4%, about 0.1% to about 0.3%, about 0.1% to about 0.2%, about 0.5% to about 2%, about 0.5% to about 1.5%, about 0.5% to about 1%, less than about 2%, less than about 1.5%, less than about 1%, less than about 0.5%, less than about 0.4%, less than about 0.3%, less than about 0.2%, or less than about 0.1%.

[0030] In yet other embodiments, the acidifying step comprises contacting said fractionated lignocellulosic biomass with a solid acid catalyst (as shown schematically in **FIGURE 2**). Suitable solid acid catalysts include, but are not limited to, zeolites, anionic exchange resins, and combinations thereof.

[0031] The methods of the invention are preferably run continuously, although they may be run as batch or semi-batch processes.

[0032] The methods of the invention may be carried out in any suitable reactor, including, but not limited to, a tubular reactor, a digester (vertical, horizontal, or inclined), or the like. Suitable digesters include the digester system described in US-B-8,057,639, which include a digester and a steam explosion unit, the entire disclosure of which is incorporated by reference.

[0033] In certain embodiments, the fractionated lignocellulosic biomass is formed by contacting said lignocellulosic biomass with a first reaction fluid comprising hot compressed water and, optionally, carbon dioxide;

wherein said first reaction fluid further comprises acid (either inorganic acid or organic acid, when said lignocellulosic biomass comprises softwood;

wherein said first reaction fluid is at a temperature of at least 100°C under a pressure sufficient to maintain said first reaction fluid in liquid form.

When the lignocellulosic biomass comprises hardwoods or components other than softwood, the method is preferably carried out without the addition of acid (either inorganic or organic) or formed *in situ* (other than carbonic acid formed from carbon dioxide). Suitable inorganic acid include, but are not limited to: sulfuric acid, sulfonic acid, phosphoric acid, phosphonic acid, nitric acid, nitrous acid, hydrochloric acid, hydrofluoric acid, hydrobromic acid, hydroiodic acid.

Suitable organic acids include, but are not limited to, aliphatic carboxylic acids (such as acetic acid and formic acid), aromatic carboxylic acids (such as benzoic acid and salicylic acid), dicarboxylic acids (such as oxalic acid, phthalic acid, sebacic acid, and adipic acid), aliphatic fatty acids (such as oleic acid, palmitic acid, and stearic acid), aromatic fatty acids (such as phenylstearic acid), and amino acids. In preferred embodiments, the fractionating step is carried out at a temperature no greater than about 240°C to prevent lignin fouling of the processing equipment. In other preferred embodiments, the fractionating step is carried out without the optional carbon dioxide.

[0034] In certain embodiments of the methods, the first temperature and the second temperature are substantially the same. Preferably, the first temperature and said second temperature are both no greater than about 240°C. More preferably, the first temperature and said second temperature are about 220°C to about 240°C.

[0035] In certain embodiments of the methods, the second temperature is less than the first temperature. Preferably, the first temperature and said second temperature are both no greater than about 240°C. More preferably, the first temperature and said second temperature are both no greater than about 180°C.

[0036] In certain embodiments, the methods further comprise the step of reducing the first pressure of the first liquid fraction prior to separating the solid fraction from the second liquid fraction.

[0037] In certain embodiments, the second liquid fraction is hydrolyzed to form C₅ saccharides (oligosaccharides and monosaccharides) enzymatically (as shown schematically in **FIGURE 3** with immobilized enzyme) or chemically. In certain embodiments, the second liquid fraction is hydrolyzed to form C₅ saccharides using, for example, the addition of acid (either inorganic or organic) or formed *in situ* (other than carbonic acid formed from carbon dioxide). Suitable inorganic acids include, but are not limited to: sulfuric acid, sulfonic acid, phosphoric acid, phosphonic acid, nitric acid, nitrous acid, hydrochloric acid, hydrofluoric acid, hydrobromic acid, hydroiodic acid. Suitable organic acids include, but are not limited to, aliphatic carboxylic

acids (such as acetic acid and formic acid), aromatic carboxylic acids (such as benzoic acid and salicylic acid), dicarboxylic acids (such as oxalic acid, phthalic acid, sebacic acid, and adipic acid), aliphatic fatty acids (such as oleic acid, palmitic acid, and stearic acid), aromatic fatty acids (such as phenylstearic acid), and amino acids. using, for example, a dilute acid. In preferred embodiments, the C₅ oligosaccharides are contacted with dilute sulfuric acid (at a level of about 0.05% to about 2%, by weight, based on the total weight of the second liquid fraction) for a time sufficient to hydrolyze said C₅ oligosaccharides to C₅ monosaccharides (xylose, arabinose, lyxose, ribose, or mixtures thereof).

[0038] In certain embodiments, the C₅ oligosaccharides and monosaccharides (xylose, arabinose, lyxose, ribose, or mixtures thereof) may be fermented to ethanol, butanol, and the like and mixtures thereof, using techniques known to those skilled in the art, including, but not limited to, yeast fermentations using *Saccharomyces cerevisiae* and *Clostridium sp.* In certain preferred embodiments, an oligomer fermentor is able to uptake oligomers directly (generally up to a maximum size, for example, of 6 mer units, for *Clostridium thermocellum*). Thus, by shifting the distribution to oligomers having fewer mer units, the solubility at lower temperatures is enhanced thereby preventing precipitation, but more of the oligomers are accessible to fermentation by organism able to uptake oligomers, such as *Clostridium thermocellum*.

[0039] Preferably, the yield of xylose is at least 68%, more preferably, at least 70%, of theoretical yield. Preferably, the yield of the soluble C₅ saccharides is at least 68%, more preferably, at least 70%, of theoretical yield.

[0040] In certain embodiments, the methods further comprise the step of producing at least one of acetic acid and furfural from said soluble C₅ saccharides into at least one of said acetic acid and furfural by conventional methods well known to those in the art. For example, furfural may be produced, for example, by dehydration with an inorganic acid (such as sulfuric acid at pH 1-2) at elevated temperatures (*e.g.*, greater than about 240°C to about 300°C) for about 10 seconds. The acetic acid may be released from the hemicellulose in the lignocellulosic biomass.

[0041] In certain embodiments, the invention is directed to the products produced by the methods of the invention. In particular, the products are compositions with soluble C₅ saccharides having a lower average molecular weight than conventional methods. The methods of the invention lead to soluble oligomers that are less likely to recondense back to insoluble, higher molecular weight oligomers, thereby maximizing monomer formation and minimizing the formation of degradation products. In certain embodiments, the C₅ saccharides are preferably maintained as a soluble lower molecular weight oligomers rather than as monosaccharides to permit facile separation. Furfural and formic acid are major degradation products in the dehydration route. Glycolaldehyde, glyceraldehyde, dihydroxyacetone, and pyruvaldehyde, which are products produced via retro-aldol route, are also other possible degradation.

[0042] In certain embodiments, the compositions comprise water and soluble C₅ oligosaccharides capable of being membrane separated. In certain embodiments, the C₅ oligosaccharides have about 2 mer units to about 15 mer units. In certain preferred embodiments, the compositions have a pH of about 1.5 to about 6.0, preferably about 2.0 to about 2.5.

[0043] In certain embodiments, the distribution of said C₅ oligosaccharides is shifted such that the largest oligomers in the distribution remain soluble at lower temperatures for post processing and separation. For example, it is preferable for purposes for separation to have soluble C₅ oligosaccharides rather than monosaccharide because the soluble C₅ oligosaccharides may be separated using membrane separation, nanofiltration, and other size exclusion techniques.

[0044] While the preferred forms of the invention have been disclosed, it will be apparent to those skilled in the art that various changes and modifications may be made that will achieve some of the advantages of the invention without departing from the spirit and scope of the invention. Therefore, the scope of the invention is to be determined solely by the claims to be appended.

[0045] When ranges are used herein for physical properties, such as molecular weight, or chemical properties, such as chemical formulae, all combinations, and subcombinations of ranges specific embodiments therein are intended to be included.

[0046] The disclosures of each patent, patent application, and publication cited or described in this document are hereby incorporated herein by reference, in their entirety.

[0047] Those skilled in the art will appreciate that numerous changes and modifications can be made to the preferred embodiments of the invention and that such changes and modifications can be made without departing from the spirit of the invention. It is, therefore, intended that the appended claims cover all such equivalent variations as fall within the true spirit and scope of the invention.

CLAIMS

What is claimed is:

1. A method of increasing the level of soluble C₅ saccharides produced from lignocellulosic biomass, comprising:
 - providing a fractionated lignocellulosic biomass comprising:
 - a solid fraction comprising:
 - optionally, insoluble C₅ oligosaccharide;
 - cellulose; and
 - lignin; and
 - a first liquid fraction at a first temperature and a first pressure comprising:
 - soluble C₅ saccharides selected from the group consisting of C₅ oligosaccharides, xylose, arabinose, lyxose, ribose, and mixtures thereof;
 - wherein said soluble C₅ saccharides are present at a first level;
 - acidifying said fractionated lignocellulosic biomass to form a second liquid fraction comprising soluble C₅ saccharides at a second level and at a second temperature;
 - wherein said second level is higher than said first level;
 - optionally, separating said solid fraction from said second liquid fraction; and
 - optionally, hydrolyzing said second liquid fraction to form C₅ saccharides selected from the group consisting of C₅ oligosaccharides having fewer mer units, xylose, arabinose, lyxose, ribose, and mixtures thereof.
2. A method of claim 1,
 - wherein said acidifying comprises adding to said fractionated lignocellulosic biomass at least one aqueous acid selected from the group consisting of an organic acid, an inorganic acid, and mixtures thereof.
3. A method of claim 2,
 - wherein said inorganic acid is sulfuric acid, hydrochloric acid, phosphoric acid, nitric acid, or a combination thereof.

4. A method of claim 3,
wherein said inorganic acid is present at a level of about 0.05%, by weight, to about 2.0%, by weight, based on the weight of said first liquid fraction.
5. A method of claim 1,
wherein said acidifying comprises contacting said fractionated lignocellulosic biomass with a gaseous compound that forms acid *in situ*.
6. A method of claim 5,
wherein said gaseous compound is SO₂, CO₂, NO₂, HX wherein X is Cl, Br, F, or I, or a combination thereof.
7. A method of claim 1,
wherein said acidifying comprises contacting said fractionated lignocellulosic biomass with a solid acid catalyst.
8. A method of claim 7,
wherein said solid acid catalyst is a zeolite, an anionic exchange resin, or a combination thereof.
9. A method of claim 1,
wherein said method is continuous.
10. A method of claim 1,
wherein said second level of said soluble C₅ saccharides is greater than said first level of said soluble C₅ saccharides.

11. A method of claim 1,
wherein said soluble C₅ saccharides in second liquid fraction have an average molecular weight that is lower than the average molecular weight of said soluble C₅ saccharides in said first liquid fraction.
12. A method of claim 1,
wherein said C₅ oligosaccharides in said first liquid fraction have about 2 mer units to about 25 mer units; and
wherein said C₅ oligosaccharides in said second liquid fraction have about 2 mer units to about 15 mer units.
13. A method of claim 1,
wherein said fractionated lignocellulosic biomass is formed by contacting said lignocellulosic biomass with a first reaction fluid comprising hot compressed water and, optionally, carbon dioxide;
wherein said first reaction fluid further comprises acid, when said lignocellulosic biomass comprises softwood;
wherein said first reaction fluid is at a temperature of at least 100°C under a pressure sufficient to maintain said first reaction fluid in liquid form.
14. A method of claim 1,
wherein said first temperature and said second temperature are substantially the same.
15. A method of claim 14,
wherein said first temperature and said second temperature are both no greater than about 240°C.
16. A method of claim 1,
wherein said second temperature is less than said first temperature.

17. A method of claim 16,
wherein said first temperature and said second temperature are both no greater than about 240°C.
18. A method of claim 1, further comprising:
reducing said first pressure of said first liquid fraction prior to separating said solid fraction from said second liquid fraction.
19. A method of claim 1,
wherein said hydrolyzing said second liquid fraction to form C₅ saccharides comprises contacting said C₅ oligosaccharides with dilute acid for a time sufficient to hydrolyze said C₅ oligosaccharides to C₅ oligosaccharides having fewer mer units, C₅ monosaccharides, and mixtures thereof.
20. A method of claim 1,
wherein said hydrolyzing said second liquid fraction to form C₅ saccharides comprises enzymatic hydrolysis.
21. A method of claim 1,
wherein the yield of said xylose is at least 68% of theoretical yield.
22. A method of claim 1,
wherein the yield of said soluble C₅ saccharides is at least 68% of theoretical yield.
23. A method of claim 1, further comprising:
producing at least one of said acetic acid and furfural from said soluble C₅ saccharides.
24. A product produced by the method of claim 1.

25. A composition, comprising:
- soluble C₅ oligosaccharides capable of being membrane separated; and
 - water;
 - wherein said composition has a pH of about 1.5 to about 6.0; and
 - wherein said soluble C₅ oligosaccharides have about 2 mer units to about 15 mer units.
26. A method of increasing the level of soluble C₅ saccharides produced from lignocellulosic biomass, comprising:
- providing a fractionated lignocellulosic biomass comprising:
 - a solid fraction comprising:
 - optionally, insoluble C₅ oligosaccharide;
 - cellulose; and
 - lignin; and
 - a first liquid fraction at a first temperature and a first pressure comprising:
 - soluble C₅ saccharides selected from the group consisting of C₅ oligosaccharides, xylose, arabinose, lyxose, ribose, and mixtures thereof;
 - wherein said soluble C₅ saccharides are present at a first level;
 - optionally, separating said solid fraction from said first liquid fraction at a second pressure;
 - wherein said first pressure and said second pressure are substantially the same;
 - contacting said first liquid fraction with a solid acid catalyst to form a second liquid fraction comprising said soluble C₅ saccharides at a second level and at a second temperature;
 - wherein said second level is greater than said first level; and
 - optionally, hydrolyzing said second liquid fraction to form C₅ saccharides selected from the group consisting of C₅ oligosaccharides having fewer mer units, xylose, arabinose, lyxose, ribose, and mixtures thereof.

27. A method of claim 26,
wherein said solid acid catalyst is a zeolite, an anionic exchange resin, or a combination thereof.
28. A method of claim 26,
wherein said method is continuous.
29. A method of claim 26,
wherein said second level of said soluble C₅ saccharides is greater than said first level of said soluble C₅ saccharides.
30. A method of claim 26,
wherein said soluble C₅ saccharides in second liquid fraction have an average molecular weight that is lower than the average molecular weight of said soluble C₅ saccharides in said first liquid fraction.
31. A method of claim 26,
wherein said C₅ oligosaccharides in said first liquid fraction have about 2 mer units to about 25 mer units; and
wherein said C₅ oligosaccharides in said second liquid fraction have about 2 mer units to about 15 mer units.
32. A method of claim 26,
wherein said fractionated lignocellulosic biomass is formed by contacting said lignocellulosic biomass with a first reaction fluid comprising hot compressed water and, optionally, carbon dioxide;
wherein said first reaction fluid further comprises acid, when said lignocellulosic biomass comprises softwood;
wherein said first reaction fluid is at a temperature of at least 100°C under a pressure sufficient to maintain said first reaction fluid in liquid form.

33. A method of claim 26,
wherein said first temperature and said second temperature are substantially the same.
34. A method of claim 33,
wherein said first temperature and said second temperature are both no greater than about 240°C.
35. A method of claim 26,
wherein said second temperature is less than said first temperature.
36. A method of claim 35,
wherein said first temperature and said second temperature are both no greater than about 240°C.
37. A method of claim 26, further comprising:
reducing said first pressure of said first liquid fraction prior to separating said solid fraction from said second liquid fraction.
38. A method of claim 26,
wherein said hydrolyzing said second liquid fraction to form C₅ saccharides comprises contacting said C₅ oligosaccharides with dilute acid for a time sufficient to hydrolyze said C₅ oligosaccharides to C₅ oligosaccharides having fewer mer units, xylose, arabinose, lyxose, ribose, and mixtures thereof.
39. A method of claim 26,
wherein said hydrolyzing said second liquid fraction to form C₅ saccharides comprises enzymatic hydrolysis.
40. A method of claim 26,
wherein the yield of said xylose is at least 68% of theoretical yield.

41. A method of claim 26,
wherein the yield of said soluble C₅ saccharides is at least 68% of theoretical yield.
42. A method of claim 26, further comprising:
producing at least one of said acetic acid and furfural from said soluble C₅ saccharides.
43. A product produced by the method of claim 26.
44. A method of increasing the level of fermentative or catalytic product produced from lignocellulosic biomass, comprising:
providing a fractionated lignocellulosic biomass comprising:
a solid fraction comprising:
optionally, insoluble C₅ oligosaccharide;
cellulose; and
lignin; and
a first liquid fraction at a first temperature and a first pressure comprising:
soluble C₅ saccharides selected from the group consisting of C₅ oligosaccharides, xylose, arabinose, lyxose, ribose, and mixtures thereof;
wherein said soluble C₅ saccharides are present at a first level;
acidifying said fractionated lignocellulosic biomass to form a second liquid fraction comprising said soluble C₅ saccharides at a second level and at a second temperature;
wherein said second level is greater than said first level;
optionally, separating said solid fraction from said second liquid fraction;
hydrolyzing said second liquid fraction to form C₅ saccharides selected from the group consisting of C₅ oligosaccharides having fewer mer units, xylose, arabinose, lyxose, ribose, and mixtures thereof; and

fermenting, catalyzing, or fermenting and catalyzing said C₅ saccharides to form said fermentation product, said catalytic product, or a combination thereof.

45. A method of claim 44,
wherein said fermentative product or said catalytic product is ethanol, butanol, or a combination thereof.
46. A method of claim 44,
wherein said acidifying comprises adding to said fractionated lignocellulosic biomass at least one aqueous acid selected from the group consisting of an organic acid, an inorganic acid, and mixtures thereof.
47. A method of claim 46,
wherein said inorganic acid is sulfuric acid, hydrochloric acid, phosphoric acid, nitric acid, or a combination thereof.
48. A method of claim 46,
wherein said inorganic acid is present at a level of about 0.05%, by weight, to about 2.0%, by weight, based on the weight of the second liquid fraction.
49. A method of claim 44,
wherein said acidifying comprises contacting said fractionated lignocellulosic biomass with a gaseous compound that forms acid *in situ*.
50. A method of claim 49,
wherein said gaseous compound is SO₂, CO₂, NO₂, HX wherein X is Cl, Br, F, or I, or a combination thereof.
51. A method of claim 44,
wherein said acidifying comprises contacting said fractionated lignocellulosic biomass with a solid acid catalyst.

52. A method of claim 51,
wherein said solid acid catalyst is a zeolite, an anionic exchange resin, or a combination thereof.
53. A method of claim 44,
wherein said method is continuous.
54. A method of claim 44,
wherein said second level of said soluble C₅ saccharides is greater than said first level of said soluble C₅ saccharides.
55. A method of claim 44,
wherein said soluble C₅ saccharides in second liquid fraction have an average molecular weight that is lower than the average molecular weight of said soluble C₅ saccharides in said first liquid fraction.
56. A method of claim 44,
wherein said C₅ oligosaccharides in said first liquid fraction have about 2 mer units to about 25 mer units; and
wherein said C₅ oligosaccharides in said second liquid fraction have about 2 mer units to about 15 mer units.
57. A method of claim 44,
wherein said fractionated lignocellulosic biomass is formed by contacting said lignocellulosic biomass with a first reaction fluid comprising hot compressed water and, optionally, carbon dioxide;
wherein said first reaction fluid further comprises acid, when said lignocellulosic biomass comprises softwood;
wherein said first reaction fluid is at a temperature of at least 100°C under a pressure sufficient to maintain said first reaction fluid in liquid form.

58. A method of claim 44,
wherein said first temperature and said second temperature are substantially the same.
59. A method of claim 58,
wherein said first temperature and said second temperature are both no greater than about 240°C.
60. A method of claim 44,
wherein said second temperature is less than said first temperature.
61. A method of claim 60,
wherein said first temperature and said second temperature are both no greater than about 240°C.
62. A method of claim 44, further comprising:
reducing said first pressure of said first liquid fraction prior to separating said solid fraction from said second liquid fraction.
63. A method of claim 44,
wherein said hydrolyzing said second liquid fraction to form C₅ saccharides comprises contacting said C₅ oligosaccharides with dilute acid for a time sufficient to hydrolyze said C₅ oligosaccharides to C₅ oligosaccharides having fewer mer units, xylose, arabinose, lyxose, ribose, and mixtures thereof.
64. A method of claim 44,
wherein said hydrolyzing said second liquid fraction to form C₅ saccharides comprises enzymatic hydrolysis.