

Description

This invention relates to pipe joints and more particularly to joints to be used downhole in a producing well.

The invention may be used with drill pipe, tubing or a casing, all of which are referred to herein as "pipe".

The trend towards deeper and deeper wells, along with higher pressures and more severe environments found at these depths, has created a requirement for heavy wall tubular goods. The depths and pressures require high strength pipe; on the other hand, the severe H₂S conditions require that the material be of low hardness. Low hardness inherently demands softer, and therefore, lower strength materials. Hence "ultra heavy walls" are required to develop the strengths needed.

To utilise the full pipe strength of these ultra heavy wall materials, connections must be developed that utilise as many of the required features of the pipe, while sacrificing as few features as possible. The desired features are that the connections develop full pipe strength and tensile strength, internal pressure rating, and collapse rating. The connection should also be able to withstand high temperatures and/or bending.

Pipe joints which comprises a pipe and box with tapered threads and which include in addition to a frusto-conical metal-to-metal seal between the pipe and box a secondary resilient type seal therebetween are known and described in, for example, EP-A-0044778 and US-A-3850461. Furthermore in US-A-3850461 the seal is in a groove located in the box at the last thread thereof, and the pipe thread extends into this groove when the point is made up.

The present pipe joint is designed such that the box of the joint will have approximately the same internal pressure rating at the point of maximum metal-to-metal seal, that is, resistance to ballooning, as does the full wall thickness of the pipe between a pair of connectors. The thread system may be designed without regard to the seal surfaces between pipe and box and a step surface may joint the metal-to-metal seal system and the thread system.

It is frequently desirable to include in addition to the metal-to-metal seal in a pipe joint a secondary seal of plastic or resilient material.

In accordance with this invention, the pipe joint is designed such that a resilient or plastic seal may be utilised. Where a plastic material inert to well fluids is utilised which must be compressed to be effective, the invention provides for maintaining such material under compression without the plastic seal interfering with the normal engagement and sealing function of the metal-to-metal seal.

It is an object of this invention to provide a pipe joint in which the box is designed to have a resistance to ballooning equal to or greater than the pipe connected together by the pipe joint.

According to the present invention there is provided a pipe joint comprising, a box having a tapered thread and an annular primary seal surface, an annular seal groove in the box at the last thread, an annular seal member of compressible material in said seal groove, a step between said primary seal surface and said seal groove, an annular secondary seal surface between said step and seal groove, a pipe having a tapered thread and an annular primary seal surface for sealing engagement with the primary seal surface of the box, said pipe thread extending into said seal groove when the pipe joint is fully made up, an annular secondary seal surface on said pipe between the thread and primary seal surface for engaging said secondary seal surface in the box, a step between said primary and secondary seal surfaces on said pipe and spaced from said step in the box when the joint is fully made up to provide a space for receiving any seal material extruded past said secondary seal surfaces, said box and pipe having the following approximate relationship:

$$\frac{t_b}{D_b} = \frac{t_p}{D_p}$$

wherein, t_b is the thickness of the box wall at the largest diameter point of sealing engagement between said primary sealing surfaces, D_b is the outer diameter of the box at the point where t_b is measured, t_p is the full wall thickness of the pipe, and D_p is the diameter of the pipe at the full wall thickness, characterised in that said primary seal surfaces are provided by frusto-conical surfaces extending at a first taper, said secondary seal surfaces are provided by frusto-conical surfaces extending at a second taper which is less than said first taper, and said secondary seal surfaces engage during make-up of the joint prior to the engagement of said primary seal surfaces and prior to any significant extrusion of said resilient seal.

The resistance to ballooning of the box at the maximum diameter of the metal-to-metal seal is at least equal to the resistance to ballooning of the pipe being connected together and the thread system may be designed for optimum strength without regard to the metal-to-metal seal.

In the invention a pipe joint has a metal-to-metal seal with a back-up seal of compressible material in which the material is placed under compression without interfering with the normal engagement and sealing of the metal-to-metal seal surfaces.

As the joint is made up, excess compressible material is extruded from the zone of the back-up seal until just before final make-up of the joint at which time the compressible material is confined and placed in compression during final make-up and in which means are provided for receiving the extruded material so that it will not reach the primary metal-to-metal sealing surfaces and possible interfere with their normal engagement and sealing functions.

The pipe joint has primary and secondary

metallic seal surfaces with each of a cooperating pair of seal surfaces extending at complementary tapers and a resilient seal entrapped between the secondary seal surfaces and the thread system of the joint. The interference between the seal surfaces and the roots and crests of the thread of the joint are such that the thread interference does not affect the sealing characteristics of the metallic seals and the secondary seal likewise does not interfere with the primary seal.

The pipe joint can be coated with a malleable anodic metal such as cadmium.

Also as the joint is made up, excess compressible material can be extruded from the back-up seal area after which a secondary metal-to-metal seal becomes effective to act as a secondary metal-to-metal seal for the joint and to confine the compressible material against further extrusion so that as the joint is finally made up, the material may be placed under substantial compression.

Means can be provided for receiving the extruded seal material so that it will not reach the area of the primary metal-to-metal seal and possibly interfere with full make-up and sealing of the metal-to-metal seal.

A pipe joint constructed in accordance with this invention will have a wall thickness at the greatest diameter section of the metal-to-metal seal such that this thickness relative to the diameter of the box is equal to or slightly greater than the ratio of the full wall thickness of the pipe to the diameter of the pipe.

Thus, the pipe will be constructed according to the relationship

$$\frac{tb}{Db} = \frac{tp}{Dp}$$

wherein: tb is the thickness of the box wall at the largest diameter point of sealing engagement between the sealing surfaces in the box and on the outer diameter surface of the pipe, Db is the outer diameter of the box at the point where tb is measured, tp is the full wall thickness of the pipe, and Dp is the diameter of the pipe at the full wall thickness.

The invention will now be described by way of example only and with particular reference to the accompanying drawings. In the drawings:

Figure 1 is a quarter-section view of a pipe joint including a coupling between two pipes;

Figures 2, 3 and 4 are fragmentary quarter-section views showing sequentially the make-up of the pipe joint of Figure 1;

Figures 5, 6 and 7 are sectional views of the modified pipe joint of Figures 5 and 7a, showing in Figure 5, the condition of the seal system prior to engagement of the compressible material by the pin thread, and in Figure 6, the seal material being extruded past the secondary seal during make-up, and in Figure 7, the fully made-up joint with extruded material contained within the excess seal groove.

Figure 5A is a fragmentary sectional view on an

enlarged scale of a modified form of pipe joint of Figures 5, 6 and 7 in which a compressible member provides a back-up seal; prior to the pin threads engaging the compressible material;

Figure 7A is a view similar to Figure 5a showing the pipe joint in fully made-up position with the seal material under compression and with excess seal material which was extruded during make-up contained within an excess seal groove and the primary and secondary metal seals in sealing engagement;

Figures 5AA and 7AA are views similar to Figures 5A and 7A illustrating a modified form of joint which embodies the invention.

The pipe 10 is provided with an external tapered thread 11 thereon. Preferably, this thread is of the buttress type having its load bearing surface extending substantially normal to the center line of the pipe. In some instances, the taper of the threads may be that normally used, that is on the order of three-quarters of an inch per foot. In many instances, where very heavy wall pipe is used, it will be preferred to use a larger taper such as one and one-quarter inch per foot. The use of the steeper taper permits a shorter threaded section of the pipe and box of the coupling. The shorter threaded section in turn reduces the overall length of the coupling and permits greater control and accuracy in cutting threads and other surfaces.

Adjacent the smaller diameter end of thread 11, the outer diameter of the pipe steps down at 12 to a smaller diameter surface 13 which may be smaller than the diameter of the smallest box thread. This surface 13 is a sealing surface and extends annularly about the pipe and longitudinally for a short distance adjacent the end of the pipe. This surface 13 should be contoured to result in a firm sealing contact with the box of the coupling when the joint is made up. For instance, the surface may be on a slight taper or it may be on a radius to provide the sealing contact.

Preferably, the pipe is stressed radially outwardly to ensure the sealing characteristics of the surface 13 and for this purpose, the end of the pipe 14 forms an acute angle with the surface 13. By way of example, the sealing surface 13 may be formed on an angle slightly less than 3° and the abutment surface 14 on an angle of approximately 15°.

The box 15 of the coupling will have an internal thread 16 complementary to and mating with the thread 11 on the pipe.

The box will step down at 17 to a smaller diameter sealing surface 18 which sealingly engages with the sealing surface 13 on the pipe.

The box is provided with a torque shoulder 19 extending inwardly from the seal surface 18 to the bore 21 through the coupling. The shoulder 19 should have a matching taper with the shoulder 14 on the end of the pipe which when the pipe is bottomed in the box, limits make-up of the pipe and box and preferably, due to its inclined surface, urges the pipe toward sealing position between the surfaces 13 and 18 which provide the

seal. Also, the torque shoulder 13 and the end of the pipe 14 may provide a seal, particularly against external pressure.

In the illustrated embodiment of Figure 1, the surfaces 13 and 18 should seal along their entire engaged length. Due to the slight taper of the surfaces, the maximum diameter point of sealing engagement is their point of engagement remote from the abutment shoulder 19. This is the point of best metal-to-metal sealing engagement against pressure within the tubing.

The box is designed such that its strength at this point of maximum sealing diameter resistant to ballooning is equal to or greater than the strength of the pipe to resist ballooning.

The wall thickness (tb) of the box at the point of maximum diameter of the engaged and sealing surfaces 13 and 18 relative to the outer diameter (Db) of the coupling is approximately equal to or greater than the ratio of the full wall thickness of the pipe (tp) relative to the outer diameter of the pipe (Dp) so that the box will be as resistant to ballooning under internal pressure as will the pipe. This will prevent ballooning of the coupling and the possible resultant disengagement of the threads 11 and 16. Thus, so long as the seal provided by surfaces 13 and 18 remains effective, there should be no danger of the threads disengaging due to ballooning of the coupling.

In the form shown in Figure 1 the internal diameter flange 20 results in a larger tb measured at the flange. As the flange is adjacent the point of maximum sealing of surfaces 13 and 18, the flange supports the sealing surfaces against ballooning, resulting in the coupling having a greater t/D ratio than the pipe.

Preferably, a resilient seal is provided by a plastic ring 22 in the groove 23 in the box. This ring is preferably of a plastic material such as tetrafluoroethylene. The groove 23 is positioned such that as the pipe is rotated to full make-up position, the small diameter end of thread of thread 11 enters the area of groove 22 and places the ring under substantial compression. The pipe has an annular surface 24 below thread 11 which overlies the seal 22 before the thread 11 begins to compress the seal 22. Preferably, the surface 24 on the pipe is spaced a slight distance from the complementary surface 25 in the box so that the plastic material would be permitted to flow under pressure into the space thus provided. Thus, the seal material forced into the space between surfaces 24 and 25 provides a primary plastic seal backed up by seal material in the thread 11 and groove 23. This plastic seal provides a back-up for the metal-to-metal seals.

It may be desirable to avoid any chance of pressure fluid from within the pipe joint reaching threads 11 and 16. In the make-up of the threads, dope is utilized which might result in a seal between the threads. If the other seals permitted fluid to flow into the threaded area, and a seal inadvertently occurred somewhere along the thread system, then the pressure from within the joint would be acting outwardly on the threaded

section of the box and might result in disengagement of the threads due to ballooning of the threaded section of the box. To avoid this possibility, a bleed port 26 may be provided in the box, preferably immediately adjacent the resilient seal 22 so that any leakage of fluid past the seals would be vented to the exterior of the joint and would not cause ballooning of the threaded section of the box.

If desired, the surfaces 18 could be extended away from the torque shoulder 19 and a groove provided in this extended surface for the plastic seal. If the step 17 was of substantial dimension, this would position the plastic seal immediately adjacent the metal-to-metal seal and the value of tb would be approximately the same for the metal-to-metal seal and for the plastic seal.

The relative area of the torque shoulder 19 and the make-up torque should be such that the induced pressure on the shoulder 19 is substantially greater than the internal pressure to be sealed against. For deep high pressure wells, this induced pressure might be on the order of 30,000 to 50,000 psi.

Figures 2, 3 and 4 show the make-up of the pipe and box of Figure 1. In Figure 2 the pipe 10 has been threaded into the box 15 to the point where the surface 24 overlies the seal 22 to hold it in its groove during final make-up. In Figure 3 the pipe 10 is shown to be inserted into the box 15 to the extent that the seal 22 has been extruded into the space between the surfaces 24 and 25 and the sealing surfaces 13 and 18 are beginning their make-up. In Figure 4 the pipe 10 is shown to be in the final fully sealed position in the box with the nose of the pipe in firm engagement with the torque shoulder 18 and the pipe made-up preferably to exert a pressure per square inch against the torque shoulder greater than the pressure within the tubing.

Only the upper portion of pipe 27 is shown in the lower end of the coupling. It will be understood that the pipe 27 is identical to pipe 10 and that the coupling is symmetrical and is identical below the flange 20 to the portion of coupling shown above flange 20.

The t/D of the coupling is preferably equal to that of the pipe. However, it will be appreciated that the t/D ratio of the coupling need only approximate that of the pipe. Where the torque shoulder and associated flange is employed, the t/D ratio of the coupling may be slightly less than that of the pipe at the point of maximum sealing diameter because of the support of the flange for the sealing surface which would make the coupling stronger than the pipe if the t/D ratio of the coupling were equal to that of the pipe. Obviously, the t/D ratio may be slightly greater in the coupling relative to the pipe as this provides additional strength and might be preferred where the torque shoulder and its associated flange are not utilized. Also, in some designs it might be acceptable to have a coupling which had a t/D ratio approaching that of the pipe, but which was slightly less. Therefore, the invention encom-

passes a provision of a V/D ratio in the coupling which is approximately the V/D ratio of the pipe.

To provide the coupling with tensile strength equal to the pipe, the amount of metal in the coupling measured at the last full thread or at the plastic seal groove when the groove overlies the threads of the pin is preferably at least equal to the area or amount of metal in the pipe measured at the full wall thickness of the pipe and in planes normal to the joint axis.

In Figures 5 to 7, 5a and 7a, modified forms of joint are shown which employ a compressible back-up seal. In this form of the invention, the box 15 is provided at the last thread with a seal receiving groove 23a and a seal member 22a of compressible material. In some services, the well fluids being produced are such that they can be sealed against only by special materials which are not subject to attack by the well fluids. For instance, it may be desirable to use a seal material primarily or entirely of tetrafluoroethylene, commonly known by its trademark Teflon. Teflon will withstand fluids found in many wells and is a desirable seal material. To function properly, Teflon and like materials should be placed under substantial compression and the design of the joint of Figures 5 to 7 provide for using a compressible material which may be placed under substantial compression.

To prevent any substantial extrusion of the compressed material between the threads, they should be carefully formed and the joint should be made up as is customary with lubricant which will fill and seal between the pin and box threads. Preferably, the relationship is such that when the joint is made up, the roots and crests, as well as load flanks of the threads 11 and 16 are in substantial engagement with each other. The stabbing flanks 11a on the pin and the complementary flanks 16a on the box will have a few thousandths of an inch clearance. With this relationship and the lubricants normally employed in making up threaded joints for use in petroleum wells, the thread system will not provide an avenue for escape of the seal material 22a when placed in substantial compression and no substantial amount of seal material will be extruded into the thread system during final make-up when the seal material is placed under a substantial compression.

The seal material 22a is slightly larger in volume than the volume of the groove 23a as defined by the pipe and threads extending into the groove 23a when the joint is fully made-up. This excess amount of material is extruded between the surface 24a on the pin and the surface 25a on the box as the pin moves towards final sealing engagement as shown in Figure 6.

These secondary seal surfaces 24a and 25a are formed on slightly different tapers so that they may engage and seal with each other in a non-critical manner as the pin moves to its final made-up position shown in Figures and 7a. Prior to reaching this position, the seal material 22a will have been placed under compression and

extruded through the space between the two secondary seal surfaces 24a and 25a as the pin threads move into and reduce the volume within the groove 23a. The excess seal material will extrude between the two secondary seal surfaces and as the pin is rotating relative to the box, the extruded material will also be torn, usually at a number of places.

As the thread system moves toward the final make-up position shown in Figure 7 and 7a, the secondary seal surfaces 24a and 25a will have come into sealing engagement slightly before final make-up of the pin and box and, as additional area of the groove 23a is occupied by the pin thread 11, the seal material 22a will be placed in substantial compression so that it will function with maximum performance as a seal. Also, the surfaces 24a and 25a will now provide not only a seal for confining the compressible material 22a in the groove 23a but will also provide an additional metal-to-metal seal against loss of the fluid being conveyed through the joint.

To guard against the extruded seal material reaching the primary seal provided by the primary seal surface 18 in the box and the primary seal 13 on the pin, means are provided for receiving at least a part of this excess seal material. Preferably, this means is a groove 38 positioned between the secondary sealing surfaces 24a and 25a and the primary sealing surfaces 13 and 18. Thus, as the material is extruded past the secondary sealing surfaces 24a and 25a, it will gather in the excess seal material groove 38 and be prevented from reaching and interfering with the primary seal surfaces 13 and 18. No particular form of groove 38 is required. Preferably it will receive all extruded material. It is preferably spaced as far as possible from the primary seal surfaces 13 and 18 and more preferably immediately adjacent to the secondary seal surfaces 24a and 25a as shown in the drawings. While a special groove 38 is illustrated, it will be appreciated that this function could be provided by enlarging the space 39 between the pin and box. It has been found that a small groove 38 positioned immediately adjacent the secondary surfaces 24a and 25a will adequately receive the extruded material. It is preferable to leave the space indicated at 39 small so that extruded material will tend to collect in the groove 38 instead of passing into the space 39.

In the pipe joint of Figures 5 to 7 and 5a and 7a, excess seal material may be used so that the amount of material and the presence of pipe dope is not critical and the seal material as well as any pipe dope which may be trapped within the groove 23a may be placed under substantial compression after the secondary seal surfaces 24a and 25a are in engagement. These surfaces provide a means for entrapping the seal material to permit it to be placed under compression as well as providing a secondary metal-to-metal seal against loss of fluid being conveyed through the joint. The excess seal groove 38 will trap the extruded seal material and prevent it from reach-

in the primary seal surfaces 13 and 18. It will be appreciated with this type of seal that a triple seal is provided, that is, the primary seal of surfaces 13 and 18, the secondary seal of surfaces 24a and 25a and the compressed material of seal 22a.

A bleed port such as port 26 (Figure 1) may be utilized if desired.

Referring now to Figure 5AA and Figure 7AA, there is shown a further modified form of joint. The joint is similar to that shown in Figures 5A and 7A and the description of these Figures and the reference numerals referring to the description of Figures 5A and 7A have been repeated in Figure 5AA and Figure 7AA with the changed structure indicated by the suffix (b).

In the box the secondary seal surface 25b cooperates with a secondary surface 24b on the pin which surfaces are on identical tapers. The relative diameter of the surfaces are such as to provide interference therebetween during make-up and for engagement of the lower end of the pin surface 24b with the upper end of the box surface 25b as viewed in Figure 7AA during make-up and before the threads 11 exert any significant pressure on the seal 22a which would cause the seal to be significantly extruded into the space between the secondary seal surfaces 24b and 25b.

To lessen the tendency of the threads 11 to tend to urge the seal 22a axially toward the secondary seal surfaces, the last thread 11b is truncated, as shown, to reduce its height, and thus the tendency of the threads to urge the resilient seal toward the secondary seal surfaces.

Between the secondary seal surfaces 24b and 25b and the primary seal surfaces 13 and 18, the box is provided with a step 41b which cooperates with a complementary step 42b on the pin to provide therebetween a space 39b. This space is provided so that in the event there is any of the resilient seal 22a extruded past the secondary seal surfaces 24b and 25b, such extruded material will be received within the annular space 39b and not driven into the space between the primary seals 13 and 18. Also, it is customary in making up threaded joints to apply thread dope to the threads and some of this dope might also be driven past the secondary seal surfaces. If so, the thread dope which passes the secondary seal surfaces would be accumulated in the space 39b and not interfere with make-up of the primary seal surfaces 13 and 18.

The step 41b and 42b also facilitates a primary objective of this invention to have at the seal surfaces 13 and 18 a t/D ratio in the box which is at least as great as the t/D ratio of the pipe so that the coupling at the point of primary seal will be as strong as the pipe. In conjunction with this desired ratio, it is also desirable to have a thread system which is not too steeply tapered and does not extend over an excessive length. If the thread system is too long this results in a long coupling and difficulties in maintaining tolerances when cutting the seal surfaces. With the present invention the desired degree of taper of the threads may be employed and the step permits the

increase of wall thickness of the coupling at the primary seal permitting the length of the thread system to be limited to that needed for the desired strength in the joint.

With the use of a torque shoulder which drives the primary seal surfaces into tighter engagement, it is advantageous to have the end of the pipe thin walled, as shown. At the area of the secondary seal, however, it is desirable that the pipe wall be thickened as the effect of the torque shoulder on the secondary seal is minimal if it effects the secondary seal at all. For this purpose the ID of the pipe is maintained down to the step 43b where it is increased slightly, as is conventional.

It might be noted that while in Figures 5AA and 7AA the primary seal is shown on the periphery of the pin, such seal might be provided by a chamfer on the end of the pin member. In accordance with one pipe joint commercially available, the primary seal is provided at the chamber 29, and the pin and box are spaced apart slightly immediately above this chamber. This invention, and particularly in the form shown in Figures 5AA and 7AA, could be utilized with the primary seal provided by such a chamfer.

The interference between the thread system and the surfaces of the primary and secondary seals should be carefully controlled. Interference is desired between the roots and crest of the buttress-type teeth shown in the thread system so that they will resist backing out of the joint. It is preferred, however, that this interference not tend to balloon the coupling to an extent that would interfere with sealing of the secondary seal surfaces 24b and 25b. In like manner the interference between the surfaces 24b and 25b should not be sufficient to interfere with the sealing characteristics of the primary seal surfaces 13 and 18. For this purpose, with the form of coupling shown in Figures 5AA and 7AA, it is preferred that the interference between the secondary seal surfaces be less than the interference between the primary seal surfaces and that the interference between the roots and crest of the thread system be less than the interference between the secondary seal surfaces. Where the chamfer-type primary seal surface is utilized, it would continue to be preferred that the interference between the secondary seal surfaces be less than that between the primary seal surfaces, but the interference may be substantially equal because the primary seal surfaces are energized by axial movement of the pin into the box to engage the torque shoulders which tend to spread the pin radially outwardly to tighten the primary seal surfaces against each other.

The primary and secondary seal surfaces are preferably provided by complementary conical surfaces. To protect the primary seal surfaces during make-up of the joint, it is preferred that the primary seal surfaces extend at a greater taper than the secondary seal surfaces. This will result in the secondary seal surfaces engaging first and tend to prevent damage of the primary seal

surfaces during stabbing of the pin into the box and during the initial thread make-up.

Preferably, at least one of the primary and one of the secondary seal surfaces are coated with a malleable metal which provides an anode in the joint. The malleable metal will assist in filling minute voids, scratches, etc., on the seal surfaces to provide a better seal. Use of a metal which acts as an anode will provide cathodic protection for the joint against corrosive fluids, such as sulphur containing compounds. Preferably, the coating material is cadmium, but other suitable materials may be utilized.

By providing the frusto-conical primary and secondary seal surfaces with the surfaces of each system extending at the same taper, a seal at both the primary and secondary area is assured.

The seal at the secondary area being provided before any significant extrusion of the resilient seal member 22a traps this seal member between the secondary seal and the thread system.

The resilient seal element 22a should be sized such that it will not be significantly extruded prior to the time that the secondary seal surfaces come into engagement with each other. The sizing should further be such that as the joint is finally made up the resilient seal member is trapped and the thread 11 exerts a substantial force on the resilient seal member to maintain it under a high internal pressure.

Claims

1. A pipe joint comprising, a box (15) having a tapered thread (16) and an annular primary seal surface (18), an annular seal groove (23a) in the box at the last thread, an annular seal member (22a) of compressible material in said seal groove, a step (41b) between said primary seal surface and said seal groove, an annular secondary seal surface (25b) between said step and seal groove, a pipe having a tapered thread (11) and an annular primary seal surface (13) for sealing engagement with the primary seal surface of the box, said pipe thread extending into said seal groove when the pipe joint is fully made up, an annular secondary seal surface (24b) on said pipe between the thread and primary seal surface for engaging said secondary seal surface in the box, a step (42b) between said primary and secondary seal surfaces on said pipe and spaced from said step in the box when the joint is fully made up to provide a space for receiving any seal material extruded past said secondary seal surfaces, said box and pipe having the following approximate relationship:

$$\frac{tb}{Db} = \frac{tp}{Dp}$$

wherein, tb is the thickness of the box wall at the largest diameter point of sealing engagement between said primary sealing surfaces, Db is the

outer diameter of the box at the point where tb is measured, tp is the full wall thickness of the pipe, and Dp is the diameter of the pipe at the full wall thickness, said primary seal surfaces (13, 18) being provided by frusto-conical surfaces extending at a first taper, said secondary seal surfaces are provided by frusto-conical surfaces extending at a second taper which is less than said first taper, and said secondary seal surfaces (24b, 25b) engage during make-up of the joint prior to the engagement of said primary seal surfaces and prior to any significant extrusion of said resilient seal.

2. A pipe joint according to claim 1, characterised in that said threads are buttress-type and wherein said primary seal surfaces (18, 13) have greater interference than said secondary seal surfaces (24b, 25b) and said secondary seal surfaces have greater interference than the roots and crest of said threads.

3. A pipe joint according to claim 1, characterised in that said threads are buttress-type and the roots and crest of said threads have less interference than the interference of said primary or said secondary seal surfaces.

4. A pipe joint according to any one of claims 1 to 3, characterised in that a torque shoulder (32) is provided in the box engaging the end of the pipe at full make-up of the joint.

5. A pipe joint according to claim 1, characterised in that at least one of the pin and box surfaces of said primary and secondary seal surfaces are plated with an anode-type malleable metal.

6. A pipe joint according to claim 1, characterised in that at least one of the pin and box surfaces of said primary and secondary seal surfaces are plated with cadmium.

7. A pipe joint according to claim 1, characterised in that the pipe wall is substantially thicker in the area of the secondary seal than in the area of the primary seal.

Patentansprüche

1. Rohrverbindung, umfassend eine Muffe (15) mit einem Kegелgewinde (16) und einer ringförmigen Primärdichtfläche (18), eine ringförmige Dichtnut (23a) in der Muffe am letzten Gewingegang, ein ringförmiges Dichtorgan (22a) aus kompressiblem Material in der Dichtnut, eine Stufe (41b) zwischen der Primärdichtfläche und der Dichtnut, eine ringförmige Sekundärdichtfläche (25b) zwischen der Stufe und der Dichtnut, ein Rohr mit einem Kegелgewinde (11) und einer ringförmigen Primärdichtfläche (13) zum Dichteingriff mit der Primärdichtfläche der Muffe, wobei das Rohrgewinde in die Dichtnut hineinverläuft, wenn die Rohrverbindung vollständig hergestellt ist, eine ringförmige Sekundärdichtfläche (24b) an dem Rohr zwischen dem Gewinde und der Primärdichtfläche zum Angriff an der Sekundärdichtfläche in der Muffe, eine Stufe (42b) zwischen der Primär- und der Sekundärdichtfläche an dem Rohr und im Abstand von der Stufe in

surfaces during stabbing of the pin into the box and during the initial thread make-up.

Preferably, at least one of the primary and one of the secondary seal surfaces are coated with a malleable metal which provides an anode in the joint. The malleable metal will assist in filling minute voids, scratches, etc., on the seal surfaces to provide a better seal. Use of a metal which acts as an anode will provide cathodic protection for the joint against corrosive fluids, such as sulphur containing compounds. Preferably, the coating material is cadmium, but other suitable materials may be utilized.

By providing the frusto-conical primary and secondary seal surfaces with the surfaces of each system extending at the same taper, a seal at both the primary and secondary area is assured.

The seal at the secondary area being provided before any significant extrusion of the resilient seal member 22a traps this seal member between the secondary seal and the thread system.

The resilient seal element 22a should be sized such that it will not be significantly extruded prior to the time that the secondary seal surfaces come into engagement with each other. The sizing should further be such that as the joint is finally made up the resilient seal member is trapped and the thread 11 exerts a substantial force on the resilient seal member to maintain it under a high internal pressure.

Claims

1. A pipe joint comprising, a box (15) having a tapered thread (16) and an annular primary seal surface (18), an annular seal groove (23a) in the box at the last thread, an annular seal member (22a) of compressible material in said seal groove, a step (41b) between said primary seal surface and said seal groove, an annular secondary seal surface (25b) between said step and seal groove, a pipe having a tapered thread (11) and an annular primary seal surface (13) for sealing engagement with the primary seal surface of the box, said pipe thread extending into said seal groove when the pipe joint is fully made up, an annular secondary seal surface (24b) on said pipe between the thread and primary seal surface for engaging said secondary seal surface in the box, a step (42b) between said primary and secondary seal surfaces on said pipe and spaced from said step in the box when the joint is fully made up to provide a space for receiving any seal material extruded past said secondary seal surfaces, said box and pipe having the following approximate relationship:

$$\frac{tb}{Db} = \frac{tp}{Dp}$$

wherein, tb is the thickness of the box wall at the largest diameter point of sealing engagement between said primary sealing surfaces, Db is the

outer diameter of the box at the point where tb is measured, tp is the full wall thickness of the pipe, and Dp is the diameter of the pipe at the full wall thickness, said primary seal surfaces (13, 18) being provided by frusto-conical surfaces extending at a first taper, said secondary seal surfaces are provided by frusto-conical surfaces extending at a second taper which is less than said first taper, and said secondary seal surfaces (24b, 25b) engage during make-up of the joint prior to the engagement of said primary seal surfaces and prior to any significant extrusion of said resilient seal.

2. A pipe joint according to claim 1, characterised in that said threads are buttress-type and wherein said primary seal surfaces (18, 13) have greater interference than said secondary seal surfaces (24b, 25b) and said secondary seal surfaces have greater interference than the roots and crest of said threads.

3. A pipe joint according to claim 1, characterised in that said threads are buttress-type and the roots and crest of said threads have less interference than the interference of said primary or said secondary seal surfaces.

4. A pipe joint according to any one of claims 1 to 3, characterised in that a torque shoulder (32) is provided in the box engaging the end of the pipe at full make-up of the joint.

5. A pipe joint according to claim 1, characterised in that at least one of the pin and box surfaces of said primary and secondary seal surfaces are plated with an anode-type malleable metal.

6. A pipe joint according to claim 1, characterised in that at least one of the pin and box surfaces of said primary and secondary seal surfaces are plated with cadmium.

7. A pipe joint according to claim 1, characterised in that the pipe wall is substantially thicker in the area of the secondary seal than in the area of the primary seal.

Patentansprüche

1. Rohrverbindung, umfassend eine Muffe (15) mit einem Kegelgewinde (16) und einer ringförmigen Primärdichtfläche (18), eine ringförmige Dichtnut (23a) in der Muffe am letzten Gewingegang, ein ringförmiges Dichtorgan (22a) aus kompressiblem Material in der Dichtnut, eine Stufe (41b) zwischen der Primärdichtfläche und der Dichtnut, eine ringförmige Sekundärdichtfläche (25b) zwischen der Stufe und der Dichtnut, ein Rohr mit einem Kegelgewinde (11) und einer ringförmigen Primärdichtfläche (13) zum Dichteingriff mit der Primärdichtfläche der Muffe, wobei das Rohrgewinde in die Dichtnut hineinverläuft, wenn die Rohrverbindung vollständig hergestellt ist, eine ringförmige Sekundärdichtfläche (24b) an dem Rohr zwischen dem Gewinde und der Primärdichtfläche zum Angriff an der Sekundärdichtfläche in der Muffe, eine Stufe (42b) zwischen der Primär- und der Sekundärdichtfläche an dem Rohr und im Abstand von der Stufe in



der Muffe, wenn die Verbindung vollständig hergestellt ist, unter Bildung eines Zwischenraums zur Aufnahme von Dichtmaterial, das an den Sekundärdichtflächen vorbei extrudiert wird, wobei Muffe und Rohr die folgende angenäherte Beziehung haben:

$$\frac{tb}{Db} = \frac{tp}{Dp}$$

wobei tb die Stärke der Muffenwand an der durchmessergrößten Stelle des Dichteingriffs zwischen den Primärdichtflächen, Db der Außendurchmesser der Muffe an der Stelle, an der tb gemessen wird, tp die volle Wandstärke des Rohrs und Dp der Rohrdurchmesser bei der vollen Wandstärke sind, wobei die Primärdichtflächen (13, 18) durch mit einer ersten Konizität verlaufende Kegelstumpfflächen gebildet sind, die Sekundärdichtflächen durch mit einer zweiten Konizität, die geringer als die erste Konizität ist, verlaufende Kegelstumpfflächen gebildet sind, und die Sekundärdichtflächen (24b, 25b) während der Herstellung der Verbindung vor dem Eingriff der Primärdichtflächen und vor einer signifikanten Extrusion der elastischen Dichtung in Eingriff gelangen.

2. Rohrverbindung nach Anspruch 1, dadurch gekennzeichnet, daß die Gewinde Sägezahngewinde sind, und wobei die Primärdichtflächen (18, 13) größeres Übermaß als die Sekundärdichtflächen (24b, 25b) und die Sekundärdichtflächen größeres Übermaß als die Füße und Spitzen der Gewinde haben.

3. Rohrverbindung nach Anspruch 1, dadurch gekennzeichnet, daß die Gewinde Sägezahngewinde sind und daß die Füße und Spitzen der Gewinde geringeres Übermaß als das Übermaß der Primär- oder der Sekundärdichtflächen haben.

4. Rohrverbindung nach einem der Ansprüche 1—3, dadurch gekennzeichnet, daß in der Muffe eine Verdrehschulter (32) vorgesehen ist, die beim vollständigen Verschrauben der Verbindung am Ende des Rohrs anliegt.

5. Rohrverbindung nach Anspruch 1, dadurch gekennzeichnet, daß wenigstens die Innenorgan- oder die Muffenoberfläche der Primär- und der Sekundärdichtflächen mit einem dehnbaren Anodenmetall überzogen ist.

6. Rohrverbindung nach Anspruch 1, dadurch gekennzeichnet, daß wenigstens die Innenorgan- oder die Muffenoberfläche der Primär- und der Sekundärdichtflächen einen Cadmiumüberzug aufweist.

7. Rohrverbindung nach Anspruch 1, dadurch gekennzeichnet, daß die Rohrwandung im Bereich der Sekundärdichtung wesentlich stärker als im Bereich der Primärdichtung ist.

Revendications

1. Raccord de tube comportant une collerette (15) ayant un filetage tronconique (16) et une

surface de scellement primaire annulaire (18), une rainure de scellement annulaire (23a) dans la collerette au niveau du dernier filet, un élément de scellement annulaire (22a) en un matériau compressible dans ladite rainure de scellement, un gradin (41b) entre ladite surface de scellement primaire et ladite rainure de scellement, une surface de scellement secondaire annulaire (25b) entre ledit gradin et la rainure de scellement, un tube ayant un filetage tronconique (11) et une surface de scellement primaire annulaire (13) pour une réunion de scellement avec la surface de scellement primaire de la collerette, ledit filetage du tube s'étendant à l'intérieur de ladite rainure de scellement lorsque le raccord de tube est entièrement réalisé, une surface de scellement secondaire annulaire (24b) sur ledit tube entre le filetage et la surface de scellement primaire pour rencontrer ladite surface de scellement secondaire dans la collerette, un gradin (42b) entre lesdites surfaces de scellement primaire et secondaire sur ledit tube et espacé dudit gradin dans la collerette lorsque le raccord est entièrement réalisé pour procurer un espace afin de recevoir tout matériau de scellement extrudé au-delà desdites surfaces de scellement secondaires, lesdits tube et collerette présentant la relation approximative suivante:

$$\frac{tb}{Db} = \frac{tp}{Dp}$$

dans laquelle tb est l'épaisseur de la paroi de la collerette au point de diamètre maximal de la réunion de scellement entre lesdites surfaces de scellement primaires, Db est le diamètre extérieur de la collerette au point où tb est mesurée, tp est la pleine épaisseur de paroi du tube, et Dp est le diamètre du tube au niveau de la pleine épaisseur de la paroi, lesdites surfaces de scellement primaires (13, 18) étant formées par des surfaces tronconiques s'étendant suivant une première inclinaison, lesdites surfaces de scellement secondaires étant formées par des surfaces tronconiques s'étendant suivant une deuxième inclinaison qui est inférieure à ladite première inclinaison, et lesdites surfaces de scellement secondaires (24b, 25b) venant en contact durant la réalisation du raccord avant la rencontre desdites surfaces de scellement primaires et avant toute extrusion significative dudit joint élastique.

2. Raccord de tube selon la revendication 1, caractérisé en ce que lesdits filetages sont du type à contreforts et dans lequel lesdites surfaces de scellement primaires (18, 13) présentent une plus grande interférence que lesdites surfaces de scellement secondaires (24b, 25b) et lesdites surfaces de scellement secondaires présentent une plus grande interférence que les fonds et les crêtes desdits filetages.

3. Raccord de tube selon la revendication 1, caractérisé en ce que lesdits filetages sont du type à contreforts et en ce que les fonds et les crêtes desdits filetages présentent une interférence



moindre que l'interférence desdites surfaces de scellement primaires ou desdites surfaces de scellement secondaires.

4. Raccord de tube selon l'une quelconque des revendications 1 à 3, caractérisée en ce qu'un épaulement de couple (32) est disposé dans la collerette, venant en contact avec l'extrémité du tube lors de la réalisation complète du raccord.

5. Raccord de tube selon la revendication 1, caractérisé en ce qu'au moins une des surfaces de la partie mâle et de la collerette desdites surfaces

de scellement primaires et secondaires sont plaquées avec un métal malléable du type anodique.

6. Raccord de tube selon la revendication 1, caractérisé en ce qu'au moins une des surfaces de la partie mâle et de la collerette desdites surfaces de scellement primaires et secondaires est plaquée avec du cadmium.

7. Raccord de tube selon la revendication 1, caractérisé en ce que la paroi du tube est substantiellement plus épaisse dans la zone du joint secondaire que dans la zone du joint primaire.

15

20

25

30

35

40

45

50

55

60

65

9



* C L M S *