

METHODS FOR PERFORMING NETWORK CONFIGURATION ON APPARATUS AND NETWORK CONFIGURATION SYSTEMS

[0001] The present disclosure claims priority the Chinese patent application No. 201810241222.0, filed on March 22, 2018, entitled "Methods for Performing Network configuration on Apparatus and Network Configuration Systems", which is hereby incorporated by reference in its entirety.

TECHNICAL FIELD

[0002] The present disclosure relates to the technical field of network connections, in particular to methods for performing network configurations on apparatuses, apparatuses performing network configurations, terminals for performing network configurations on apparatuses, servers for performing network configurations on apparatuses, routers for performing network configurations on apparatuses, network configuration systems, systems, and machine-readable media.

BACKGROUND

[0003] With the development of science and technology, the number of apparatuses having Wi-Fi function is increasing. An apparatus with Wi-Fi function can be configured on a router, so that a user's cell phone can control the apparatus through the router. The process of configuring the apparatus with Wi-Fi function to the router can be called network configuration.

[0004] In conventional techniques, network configuration solutions roughly include the following two categories: SmartConfig (Wi-Fi broadcast or multicast encoding network configuration) solution and SoftAP solution:

[0005] The SmartConfig solution refers to that an APP terminal of a cell phone sends a UDP broadcast packet or multicast packet containing SSID (Service Set Identifier, which generally refers to a name of a router hotspot) and PASSWD (the password of the router hotspot), and a Wi-Fi module of an apparatus can receive the UDP packet and decrypt the SSID and the PASSWD through the received UDP packet if the organization form of the UDP is known, and the apparatus then configures the received SSID and PASSWD to a designated Wi-Fi AP (Wireless Access Point). However, the Wi-Fi connection is not established during the communication process of the SmartConfig solution, and the communication reliability cannot be guaranteed. In addition, if the apparatus loses a packet representing any byte of the SSID and the PASSWD, the AP information cannot be parsed, resulting in a low success rate of network configuration.

[0006] The SoftAP solution requires that the network configuration hotspot be turned on in the apparatus, and the TCP/UDP server must be turned on at the same time. A user uses a cell phone to connect to the network configuration hotspot of the apparatus, and configures the apparatus based on the TCP/UDP server of the apparatus. In this process, the user needs to manually disconnect the cell phone from an original Wi-Fi hotspot, and then manually connect the cell phone to a hotspot of the apparatus, and the cell phone cannot connect to

the Internet during the network configuration process, resulting in complicated operations and poor user experience.

[0007] In addition, both the SmartConfig solution and the SoftAP solution require the user to actively initiate the network configuration. During the network configuration process, the user needs to manually input the SSID and the PASSWD. Therefore, there is a risk of input errors and the user experience is poor. In addition, before the network configuration, the user needs to actively sense the existence of the apparatus and actively start the network configuration. This process requires the user to have the willingness to actively start the network configuration, and thus is difficult to promote.

SUMMARY

[0008] In view of the above-mentioned problems, the embodiments of the present disclosure are proposed in order to provide methods for performing network configuration on apparatus, corresponding apparatus for network configuration, terminals for performing network configuration on apparatus, servers for performing network configuration on apparatus, routers for performing network configuration on apparatus, network configuration systems, systems, and machine-readable media that overcome the above-mentioned problems or at least partially solves the above-mentioned problems.

[0009] In order to solve the above-mentioned problems, the embodiments of the present disclosure disclose a method for performing network configuration on apparatus, and the method comprises:

[0010] connecting, by an apparatus, to a network configuration hotspot provided by a router;

[0011] sending first apparatus information of the apparatus to a server through the network configuration hotspot;

[0012] receiving a hotspot switching command sent by the server according to the first apparatus information, wherein the hotspot switching command includes hotspot information of an online hotspot;

[0013] connecting to the online hotspot based on the hotspot switching command when a designated network configuration condition is met.

[0014] Preferably, connecting, by the apparatus, to the network configuration hotspot provided by the router comprises:

[0015] obtaining a network configuration hotspot list, wherein the network configuration hotspot list includes at least one network configuration hotspot and/or signal strength of the network configuration hotspot;

[0016] connecting to the network configuration hotspot with the strongest signal strength;

[0017] when the connecting fails, connecting to the network configuration hotspot with a second strongest signal strength until the connecting to the network configuration hotspot succeeds.

[0018] Preferably, sending first apparatus information of the apparatus to the server through the network configuration hotspot comprises:

[0019] sending a connection request to the server through the network configuration hotspot to establish a secure connection between the apparatus and the server;

[0020] obtaining the first apparatus information of the apparatus;

[0021] sending the first apparatus information and the network configuration hotspot list to the server.

[0022] Preferably, before receiving the hotspot switching command sent by the server, the method further comprises:

[0023] when a touch operation of a user is detected, entering a network configuration mode.

[0024] Preferably, the designated network configuration condition at least includes the following condition:

[0025] the apparatus entering the network configuration mode, and duration of entering the network configuration mode does not exceed a preset duration.

[0026] Preferably, the method further comprises:

[0027] generating network configuration error information when the designated network configuration condition is not met;

[0028] sending the network configuration error information to the server.

[0029] Preferably, after connecting to the online hotspot based on the hotspot switching command when the designated network configuration condition is met, the method further comprises:

[0030] obtaining second apparatus information of the apparatus;

[0031] announcing the second apparatus information to the outside locally, and/or establishing a secure connection with the server based on the online hotspot, and sending the second apparatus information to the server.

[0032] The embodiments of the present disclosure also disclose a method for performing network configuration on apparatus, and the method comprises:

[0033] determining, by a network configuration application, a target network configuration apparatus, wherein the target network configuration apparatus connects to a network configuration hotspot provided by a router in advance and sends first apparatus information of the target network configuration apparatus to a server;

[0034] generating a network configuration request based on the first apparatus information and hotspot information of a currently connected online hotspot;

[0035] sending the network configuration request to the server to request the server to perform network configuration on the apparatus according to the hotspot information of the online hotspot.

[0036] Preferably, after sending the network configuration request to the server to request the server to perform the network configuration on the apparatus according to the hotspot information of the online hotspot, the method further comprises:

[0037] receiving network configuration response information returned by the server based on the network configuration request, wherein the network configuration response information includes network configuration approval

information, and the network configuration approval information includes instruction information of user touch operation;

[0038] display the network configuration approval information;

[0039] upon determining that a user performs a touch operation based on the network configuration approval information, generating network configuration preparation information;

[0040] sending the network configuration preparation information to the server to notify the server to perform the network configuration on the apparatus.

[0041] Preferably, the network configuration response information further includes network configuration rejection information, and the method further comprises:

[0042] displaying the network configuration rejection information to prompt the user to prohibit operating the apparatus.

[0043] Preferably, before determining by the network configuration application the target network configuration apparatus, the method further comprises:

[0044] connecting, by the network configuration application, to the online hotspot of the router and establishing a secure connection with the server.

[0045] Preferably, determining, by the network configuration application, the target network configuration apparatus comprises:

[0046] determining the hotspot information of the online hotspot;

[0047] obtaining a to-be-network-configured apparatus list from the server side based on the hotspot information, the to-be-network-configured apparatus list including one or more apparatus to be network-configured, and first apparatus information of the apparatus;

[0048] displaying the to-be-network-configured apparatus list;

[0049] setting the apparatus selected by a user in the to-be-network-configured apparatus list as the target network configuration apparatus.

[0050] Preferably, the method further comprises:

[0051] obtaining second apparatus information of the apparatus, wherein the second apparatus information is apparatus information after the network configuration of the apparatus succeeds;

[0052] determining that the network configuration of the apparatus succeeds based on the second apparatus information;

[0053] generating network configuration success information, and displaying the network configuration success information.

[0054] Preferably, obtaining the second apparatus information of the apparatus comprises:

[0055] receiving the second apparatus information broadcast by the apparatus;

[0056] or

[0057] broadcasting a query request in local, and receiving the second apparatus information returned by the apparatus based on the query request.

[0058] Preferably, the method further comprises:

[0059] generating a binding request based on the second apparatus information;

[0060] sending the binding request to the server to request the server to bind the second apparatus information and a corresponding apparatus;

[0061] receiving a binding result returned by the server based on the binding request.

[0062] The embodiments of the present disclosure also disclose a method for performing network configuration on apparatus, and the method comprises:

[0063] receiving a network configuration request sent by a network configuration application, wherein the network configuration request includes hotspot information of an online hotspot;

[0064] generating a hotspot switching command based on the network configuration request;

[0065] sending the hotspot switching command to an apparatus needing network configuration through a network configuration hotspot, to make the apparatus switch a hotspot that the apparatus currently connects to from the network configuration hotspot to the online hotspot.

[0066] Preferably, before sending the hotspot switching command to the apparatus needing network configuration through the network configuration hotspot, the method further comprises:

[0067] establishing, by a server, a secure connection with the apparatus needing network configuration through the network configuration hotspot of a

router; receiving first apparatus information sent by the apparatus and a network configuration hotspot list obtained by the apparatus;

[0068] generating an association relationship between the first apparatus information and the network configuration hotspot list;

[0069] saving the first apparatus information, the network configuration hotspot list, and the association relationship.

[0070] Preferably, each network configuration hotspot in the network configuration hotspot list includes a Basic Service Set Identifier (BSSID);

[0071] before receiving the network configuration request sent by the network configuration application, the method further comprises:

[0072] establishing a secure connection with the network configuration application through the online hotspot of a router;

[0073] receiving the hotspot information of the online hotspot sent by the network configuration application, wherein the hotspot information of the online hotspot includes the BSSID of the online hotspot;

[0074] matching the BSSID of the online hotspot with BSSIDs in the network configuration hotspot list corresponding to all apparatuses stored in the server to obtain a to-be-network-configured apparatus list;

[0075] sending the to-be-network-configured apparatus list to be configured to the network configuration application.

[0076] Preferably, after receiving the network configuration request sent by the network configuration application, the method further comprises:

[0077] serializing all network configuration requests received for the same apparatus;

[0078] processing the network configuration requests for the same apparatus one by one according to a preset processing sequence; during the processing, when a certain network configuration request is approved, temporarily storing or rejecting other network configuration requests for the same apparatus within a preset duration for processing the network configuration request until the approved network configuration request is processed or timed out.

[0079] Preferably, generating the hotspot switching command based on the network configuration request comprises:

[0080] generating network configuration approval information when the network configuration request is approved, wherein the network configuration approval information includes instruction information of user touch operation, and the network configuration approval information is configured to prompt the user to perform a touch operation on the apparatus;

[0081] generating a network configuration rejection information when the network configuration request is rejected, wherein the network configuration rejection information is configured to prompt the user to prohibit operating the apparatus;

[0082] generating network configuration response information based on the network configuration approval information or the network configuration rejection information, and sending the network configuration response information to the network configuration application;

[0083] receiving network configuration preparation information sent by the network configuration application based on the network configuration approval information, wherein the network configuration preparation information is information generated after the network configuration application determining that the user performs the touch operation based on the network configuration approval information;

[0084] generating the hotspot switching command according to the network configuration preparation information.

[0085] Preferably, after sending the hotspot switching command to the apparatus, the method further comprises:

[0086] receiving network configuration error information sent by the apparatus, wherein the network configuration error information is information generated when the apparatus determines that a designated network configuration condition is not met after receiving the hotspot switching command.

[0087] Preferably, after sending the hotspot switching command to the apparatus, the method further comprises:

[0088] determining that the network configuration of apparatus succeeds when second apparatus information sent by the apparatus is received;

[0089] receiving a binding request sent by the network configuration application, wherein the binding request includes second apparatus information of the apparatus;

[0090] upon determining that the second apparatus information sent by the apparatus is consistent with the second apparatus information sent by the network configuration application, generating a binding relationship between the second apparatus information and the apparatus, and returning a binding result to the network configuration application.

[0091] The embodiments of the present disclosure also disclose a method for performing network configuration on apparatus, and the method comprises:

[0092] intercepting a connection request sent by an apparatus to a corresponding server when a router detects that the apparatus is connected to a network configuration hotspot of the router;

[0093] determining whether a server corresponding to the connection request meets a preset condition;

[0094] when the server meets the preset condition, sending the connection request to the server to make the server establish a secure connection with the apparatus and perform network configuration on the apparatus.

[0095] Preferably, the method further comprises:

[0096] discarding the connection request when the server does not meet the preset condition.

[0097] Preferably, determining whether the server corresponding to the connection request meets the preset condition comprises:

[0098] determining vendor information of the server corresponding to the connection request;

[0099] determining whether a vendor corresponding to the vendor information pays for a current network configuration service;

[0100] if yes, determining that the server corresponding to the connection request meets the preset condition;

[0101] if not, determining that the server corresponding to the connection request does not meet the preset condition.

[0102] Preferably, before intercepting the connection request sent by the apparatus to the corresponding server when the router detects that the apparatus is connected to the network configuration hotspot of the router, the method further comprises:

[0103] after the router is powered on, turning on the network configuration hotspot, and setting the network configuration hotspot as a hidden hotspot.

[0104] The embodiments of the present disclosure also disclose an apparatus for network configuration, and the apparatus comprises:

[0105] a network configuration hotspot connection module, configured to connect to a network configuration hotspot provided by a router;

[0106] a first apparatus information sending module, configured to send a first apparatus information of the apparatus to a server through the network configuration hotspot;

[0107] a hotspot switching command receiving module, configured to receive a hotspot switching command sent by the server according to the first apparatus information, the hotspot switching command including hotspot information of an online hotspot;

[0108] a hotspot switching module, configured to connect to the online hotspot based on the hotspot switching command when a designated network configuration condition is met.

[0109] The embodiments of the present disclosure also disclose a terminal for performing network configuration on apparatus, and the terminal comprises:

[0110] a target network configuration apparatus determining module, configured to determine a target network configuration apparatus by using a network configuration application, wherein the target network configuration apparatus connects to a network configuration hotspot provided by a router in advance and sends first apparatus information of the target network configuration apparatus to a server;

[0111] a network configuration request generating module, configured to generate a network configuration request based on the first apparatus information and hotspot information of a currently connected online hotspot;

[0112] a network configuration request sending module, configured to send a network configuration request to the server to request the server to perform network configuration on the apparatus according to the hotspot information of the online hotspot.

[0113] The embodiments of the present disclosure also disclose a server for performing network configuration on apparatus, and the server comprises:

[0114] a network configuration request receiving module, configured to receive a network configuration request sent by a network configuration

application, wherein the network configuration request includes hotspot information of an online hotspot;

[0115] a hotspot switching command generating module, configured to generate a hotspot switching command based on the network configuration request;

[0116] a hotspot switching command sending module, configured to send the hotspot switching command to an apparatus needing network configuration through a network configuration hotspot to make the apparatus switch a hotspot that the apparatus connects to from the network configuration hotspot to the online hotspot.

[0117] The embodiments of the present disclosure also disclose a router that performs network configuration on apparatus, and the router comprises:

[0118] a connection request interception module, configured to intercept a connection request sent by an apparatus to a corresponding server when a router detects that the apparatus connects to a network configuration hotspot of the router;

[0119] a determining module, configured to determine whether a server corresponding to the connection request meets a preset condition;

[0120] a connection request sending module, configured to send the connection request to the server when the server meets the preset condition to make the server establish a secure connection with the apparatus, and perform network configuration on the apparatus.

[0121] The embodiments of the present disclosure disclose a network configuration system comprising the apparatus, the terminal, the server, and the router.

[0122] The embodiments of the present disclosure also disclose a system comprising:

[0123] one or more processors; and

[0124] one or more machine-readable media with instructions stored thereon, when executed by the one or more processors, causing the system to execute the method for performing network configuration on apparatus.

[0125] The embodiments of the present disclosure also disclose one or more machine-readable media having instructions stored thereon, when executed by one or more processors, causing the one or more processors to execute the method for performing network configuration on apparatus.

[0126] The embodiments of the present disclosure provide the following advantages.

[0127] In the embodiments of the present disclosure, the network configuration is realized by providing a network configuration hotspot by a router; sending first apparatus information of an apparatus to a server through the network configuration hotspot after the apparatus connects to the network configuration hotspot; receiving a hotspot switching command from the server; and switching the apparatus to an online hotspot according to hotspot information of the online hotspot contained in the hotspot switching command,

so as to realize a reliable connection during the network configuration process, and improve the success rate of the network configuration of the apparatus.

[0128] In addition, after a network configuration application connected to an online hotspot determines a target network configuration apparatus, the network configuration application can actively obtain the hotspot information of the online hotspot and the first apparatus information of the target network configuration apparatus, generate a network configuration request according to the first apparatus information and the hotspot information, and send the network configuration request to the server to request the server to perform the apparatus network configuration according to the hotspot information of the online hotspot. Therefore, the network configuration process is more automated, which simplifies user operations and reduces the amount of information entered by the user, thereby reducing the probability that user mistypes, and increasing the success rate and the efficiency of the network configuration.

[0129] In addition, in the embodiments of the present disclosure, to realize the network configuration service, the router only needs to turn on the network configuration hotspot. Therefore, there is basically no need to modify the existing routers on the market, which makes the network configuration solution of the embodiments of the present disclosure very easy to promote and to expand the business model of router network configuration.

BRIEF DESCRIPTION OF THE DRAWINGS

[0130] FIG. 1 is a structural block diagram of an example embodiment of a network configuration system of the present disclosure;

[0131] FIG. 2 is a schematic diagram of a network configuration process of the present disclosure;

[0132] FIG. 3 is a flowchart of steps of an example embodiment of a process of discovery of an apparatus of the present disclosure;

[0133] FIG. 4 is a flowchart of steps of an example embodiment of a process of network configuration of an apparatus of the present disclosure;

[0134] FIG. 5 is a flowchart of steps of an example embodiment of a process of binding of an apparatus of the present disclosure;

[0135] FIG. 6 is a flowchart of steps of an example embodiment of a method for performing network configuration on apparatus of the present disclosure;

[0136] FIG. 7 is a flowchart of steps of another example embodiment of a method for performing network configuration on apparatus of the present disclosure;

[0137] FIG. 8 is a flowchart of steps of another example embodiment of a method for performing network configuration on apparatus according to the present disclosure;

[0138] FIG. 9 is a flowchart of the steps of another example embodiment of a method for performing network configuration on apparatus of the present disclosure;

[0139] FIG. 10 is a structural block diagram of an example embodiment of an apparatus for performing network configuration of the present disclosure;

[0140] FIG. 11 is a structural block diagram of an example embodiment of a terminal for performing network configuration on apparatus of the present disclosure;

[0141] FIG. 12 is a structural block diagram of an example embodiment of a server for network configuration on apparatus according to the present disclosure;

[0142] FIG. 13 is a structural block diagram of an example embodiment of a router for performing network configuration on apparatus of the present disclosure; and

[0143] FIG. 14 is a schematic structural diagram of an example embodiment of a system of the present disclosure.

DETAILED DESCRIPTION

[0144] In order to make the above objectives, features, and advantages of the application clearer and more understandable, the application will be further described in detail below with reference to the drawings and example embodiments.

[0145] Referring to FIG. 1, a structural block diagram of an example embodiment of a network configuration system of the present disclosure is shown. Specifically, the network configuration system may at least include: an

apparatus 101, a server 102, a router 103, and a network configuration application (network configuration app) 104 installed on a terminal.

[0146] In the example embodiments of the present disclosure, the router 103 is provided with a network configuration hotspot. In combination with the network configuration hotspot, the router 103 may provide network configuration services, which enriches the functions of the router and may simplify the network configuration process and improve user experience.

[0147] Specifically, referring to the schematic diagram of the network configuration process shown in FIG. 2, the network configuration solution provided by the network configuration system of the present disclosure may include a process of discovery of apparatus, a process of network configuration of apparatus, a process of binding of apparatus, etc. The specific description is as follows.

I. Process of Discovery of Apparatus

[0148] Referring to FIG. 3, a flowchart of steps of an example embodiment of a discovery process of the apparatus is shown, which may specifically include the following steps.

[0149] Step 1, after the router 103 is powered on, turning on a network configuration hotspot, and setting the network configuration hotspot as a hidden hotspot.

[0150] In implementations, the hotspots may be divided into normal hotspots and hidden hotspots. The normal hotspots are visible to surrounding apparatuses (a beacon of a normal hotspot contains SSID of the hotspot, and

the surrounding apparatuses may parse the SSID of the normal hotspot by detecting the beacon), and the hidden hotspots are invisible to surrounding apparatuses (the beacon of a hidden hotspot does not carry the SSID, and the surrounding apparatuses cannot parse the SSID according to the beacon). The hidden hotspots cannot be discovered by surrounding apparatuses, and will not be connected by surrounding apparatuses. The hidden hotspots can only be connected by specific apparatuses.

[0151] In practice, when the network configuration hotspot is set as a hidden hotspot, the network configuration hotspot may be called a hidden network configuration hotspot. After the router is powered on, the hidden network configuration hotspot may be turned on, so that the hidden network configuration hotspot can only be discovered by designated apparatuses.

[0152] Step 2, after the apparatus 101 is powered on, connecting to the network configuration hotspot provided by the router 103.

[0153] In a preferred embodiment of embodiments of the present disclosure, when the apparatus 101 is powered on, connecting to the network configuration hotspot provided by the router 103 may specifically include the following sub-steps:

[0154] Obtaining a network configuration hotspot list, where the network configuration hotspot list includes at least one network configuration hotspot, and signal strength of the network configuration hotspot; connecting to a network configuration hotspot with the strongest signal strength; if the connecting fails, connecting to a network configuration hotspot with a second

strongest signal strength until the connecting to a network configuration hotspot succeeds.

[0155] Specifically, as shown in FIG. 2, when powered on and started, the apparatus 101 will actively scan all the surrounding network configuration hotspots. In implementations, the apparatus will scan the network configuration hotspots on all channels and obtain hotspot information of each network configuration hotspot.

[0156] As an example, the hotspot information of the network configuration hotspot may include at least the following information: BSSID (Basic Service Set Identifier), SSID (Service Set Identifier, which generally refers to the name of the router hotspot), Channel (channel identifier), RSSI (Received Signal Strength Indicator, which refers to the received signal strength indicator), etc.

[0157] In an implementation, for a network configuration hotspot set as a hidden hotspot, the apparatus 101 may use the following methods to detect the hidden network configuration hotspot.

[0158] The apparatus 101 broadcasts a specific Probe-req frame, where the specific Probe-req frame contains the SSID of the hidden network configuration hotspot; the hidden network configuration hotspot parses the SSID after receiving the Probe-req frame, and upon determining that the obtained SSID is the same as its own SSID, the network configuration hotspot replies with a Probe-resp frame containing the SSID, such that the apparatus 101 can, according to the Probe-resp frame, determine that the hidden network configuration hotspot has been detected.

[0159] After scanning the network configuration hotspots on all channels, the apparatus 101 may insert the newly discovered network configuration hotspots into a local network configuration hotspot list in descending order of RSSI to obtain a new network configuration hotspot list.

[0160] Subsequently, the apparatus 101 starts to connect to the network configuration hotspot. First, the apparatus 101 may connect to a network configuration hotspot with the strongest signal strength. If the connecting fails, the network configuration hotspot with signal strength only lower than that of the previous network configuration hotspot is selected and the above steps are repeated until the connecting succeeds.

[0161] Step 3, the apparatus 101 sends a connection request to a corresponding server 102 through the network configuration hotspot to establish a secure connection between the apparatus 101 and the server 102.

[0162] In the example embodiments of the present disclosure, the server 102 may include a cloud server 102 provided by the service vendor of the apparatus 101, which is also called vendor cloud.

[0163] As an example, the connection request may include the domain name or IP address of the server 102. Specifically, when connecting to the network configuration hotspot, the apparatus 101 may initiate domain name resolution (DNS) for the vendor cloud. At this time, the apparatus 101 may use the domain name or IP address of the server 102 to generate a connection request, and send the connection request to the respective server 102 through the router 103 to try to establish a secure connection with the respective cloud, wherein

the secure connection may include a TLS (Transport Layer Security) connection, thereby ensuring data security.

[0164] In the process of establishing the secure connection, the router 103 may intercept the connection request and execute step 4.

[0165] Step 4, the router 103 intercepts the connection request sent by the apparatus 101 to the corresponding server 102, and determines whether the server 102 corresponding to the connection request meets the preset condition; and if the server 102 meets the preset condition, sends the connection request to the server 102.

[0166] In implementations, the router vendor may provide some services, for example, the network configuration service provided by the router 103 in the example embodiments of the present disclosure, to the apparatus vendor through the router 104. Therefore, when the apparatus 101 tries to establish a connection with the corresponding cloud server 102, the connection request will be intercepted by the router 103, and whether the cloud server 102 meets some preset condition required for the service is determined, and if so, the connection request will be sent to the server 102. Otherwise, the connection request is discarded.

[0167] In a preferred embodiment of embodiments of the present disclosure, the determining of whether the server 102 corresponding to the connection request meets a preset condition includes:

[0168] Determining the vendor information of the server 102 corresponding to the connection request; determining whether the vendor corresponding to the

vendor information pays for the current network configuration service; if so, determining that the server corresponding to the connection request meets the preset condition; if not, determining that the server corresponding to the connection request does not meet the preset condition.

[0169] Specifically, the router 103 may intercept a domain name resolution service request of the vendor cloud or a packet whose IP layer destination address is the IP address of the vendor cloud, and then determine whether the vendor corresponding to the vendor cloud pays for the current network configuration service. If the vendor corresponding to the vendor cloud does not pay or the payment is overdue, that the vendor corresponding to the vendor cloud does not meet the preset condition is determined. In this case, the service may be rejected directly, the corresponding connection request may be discarded, and the corresponding vendor may be notified to subscribe to the service or continue to pay. Correspondingly, if the vendor corresponding to the vendor cloud has purchased the network configuration service and the service has not expired, that the vendor corresponding to the vendor cloud meets the preset condition is determined. At this time, the related packet may be forwarded to the cloud server 102 based on the IP address or DNS of the vendor cloud. At the same time, if the router 103 determines that the server 102 meets the preset condition, it may also return a valid IP address of the server 102 to the apparatus 101.

[0170] Through the example embodiments of the present disclosure, there is basically no need to modify the existing routers on the market. To provide the

network configuration service, it is only required to open a network configuration hotspot through an API or a configuration page, thereby making the network configuration solution of the example embodiments of the present disclosure very easy to promote.

[0171] Furthermore, through the network configuration solution of the example embodiments of the present disclosure, the router may clarify the business model corresponding thereto, and the network configuration requirements of future smart cities may be met by just a slight modification.

[0172] Step 5, the server 102 establishes the secure connection with the apparatus 101 based on the connection request.

[0173] In implementations, the process of establishing a TLS secure connection requires multiple interactions, in which apparatus information will be exchanged. The server 102 may verify the legality of the apparatus information during the process of establishing the TLS connection with the apparatus 101.

[0174] If the TLS connection fails, return to 306 and 308 to re-establish the connection until the connection is successfully established.

[0175] Once the apparatus 101 successfully establishes the secure connection with the server 102, it will always remain connected to the current network configuration hotspot, and if an exception occurs, repeat 306 to 310.

[0176] Step 6, the apparatus 101 obtains its own first apparatus information, and sends the first apparatus information and the network configuration hotspot list to the server 102 for storage.

[0177] Specifically, after the apparatus 101 establishes the secure connection with the cloud server 102, the first apparatus information of the apparatus and the scanned network configuration hotspot list may be sent to the server 102, where the network configuration hotspot list may include hotspot information corresponding to each network configuration hotspot.

[0178] As an example, the first apparatus information may include an apparatus key Product_key, an apparatus identifier device_name, and so on. However, it should be noted that the example embodiments of the present disclosure do not specifically limit the first apparatus information, which may be customized by the apparatus vendor, as long as the apparatus is synchronized with the apparatus information on the respective vendor cloud.

[0179] After receiving the first apparatus information and the network configuration hotspot list, the server 102 stores the first apparatus information and the network configuration hotspot list. So far, the process of discovery of the apparatus is completed.

II. Process of Network Configuration of Apparatus

[0180] Referring to FIG. 4, a flow chart of steps of an example embodiment of a process 400 of network configuration of an apparatus is shown, which may specifically include the following steps.

[0181] Step 7, the network configuration App 104 installed in the terminal connects to an online hotspot of the router, establishes a secure connection with the server 102, and starts network configuration.

[0182] It should be noted that the example embodiments of the present disclosure do not specifically limit the specific terminal, which may include cell phones, computers, tablets, etc.

[0183] Before starting the network configuration, the terminal may connect to a default online hotspot of the router 103. In practice, in order to distinguish Wi-Fi for networking and Wi-Fi for network configuration, a hotspot different from the online hotspot may be set as the network configuration hotspot.

[0184] In implementations, the user may install the network configuration App 104 (also known as the vendor app) in the terminal to perform network configuration on the apparatus 101. The network configuration app 104 requires the user to register and log in before using it. After logging in, the user ID and related operation permissions will be displayed.

[0185] Through the online hotspot, the network configuration App 104 may establish a secure connection with the server 102, where the secure connection may include a TLS connection.

[0186] In practice, in the process of establishing the secure connection between the network configuration App 104 and the server 102, the server 102 may check the legality of the user identity based on the user ID and related operation authority.

[0187] Step 8, the network configuration App 104 determines a target network configuration apparatus.

[0188] In a preferred embodiment of embodiments of the present disclosure, the network configuration App 104 determining the target network configuration apparatus may specifically include the following sub-steps:

[0189] Determining the hotspot information of the online hotspot; obtaining a to-be-network-configured apparatus list from the server side based on the hotspot information; displaying the to-be-network-configured apparatus list; and taking an apparatus in the to-be-network-configured apparatus list that is selected by the user as the target network configuration apparatus.

[0190] In implementations, as long as the terminal connects to the online hotspot of the router, the network configuration App 104 may call the system-related API to obtain the hotspot information, such as SSID, BSSID, etc., of the online hotspot.

[0191] Subsequently, the network configuration App 104 may obtain the to-be-network-configured apparatus list from the server 102 according to the BSSID.

[0192] In an example embodiment, the process that the server 102 determines the to-be-network-configured apparatus list may specifically include the following steps:

[0193] Receiving the hotspot information of the online hotspot sent by the network configuration application, where the hotspot information of the online hotspot includes the BSSID of the online hotspot; matching the BSSID of the online hotspot with the BSSID in the network configuration hotspot list corresponding to all the apparatuses stored in the server to obtain the to-be-

network-configured apparatus list; and sending the to-be-network-configured apparatus list to the network configuration application.

[0194] Specifically, during the process of discovery of apparatus, each apparatus 101 uploads the discovered network configuration hotspot list to the server, and each network configuration hotspot in the network configuration hotspot list contains BSSID. Therefore, the matching of the BSSID of the online hotspot may be performed in the network configuration hotspot list uploaded by all the apparatus stored in the server 102, and any apparatus corresponding to the network configuration hotspot matched with the BSSID of the online hotspot is taken as the apparatus needing network configuration. All the apparatuses needing network configuration form the to-be-network-configured apparatus list.

[0195] As an example, the list of apparatus needing network configuration may include one or more apparatuses needing network configuration, and the first apparatus information of each apparatus.

[0196] It should be noted that in the above-mentioned BSSID matching process, the BSSID of each network configuration hotspot in the network configuration hotspot list is matched with the BSSID of the online hotspot. During matching, if the BSSID of the network configuration hotspot is the same as the BSSID of the online hotspot, that the two BSSIDs match is determined. Or, even if the BSSID of the network configuration hotspot is inconsistent with the BSSID of the online hotspot, that the two BSSIDs match

is determined if the two BSSIDs, for example, have at least one of the following correspondences:

[0197] The contents of the first 5 bytes of two BSSIDs are the same, and the content of the last byte of the BSSID of the network configuration hotspot is equal to the content of the last byte of the BSSID of the online hotspot plus or minus a constant; or

[0198] The contents of the last 5 bytes of the two BSSIDs are the same, and the content of the first byte of the BSSID of the network configuration hotspot is equal to the content of the first byte of the BSSID of the online hotspot plus or minus a constant.

[0199] In addition to the above manners, other manners may also be used to determine whether the BSSID of the network configuration hotspot is consistent with the BSSID of the online hotspot, which is not limited by example embodiments in the present disclosure.

[0200] After obtaining the to-be-network-configured apparatus list, the server 102 may send the to-be-network-configured apparatus list to the network configuration App 104, and the network configuration App 104 displays the to-be-network-configured apparatus list to the user, and guides the user to select an apparatus from the to-be-network-configured apparatus list as the target network configuration apparatus.

[0201] Step 9, the network configuration App 104 generates a network configuration request based on the first apparatus information of the target network configuration apparatus and the hotspot information of the currently

connected online hotspot, and sends the network configuration request to the server 102.

[0202] In implementations, after the user selects the target network configuration apparatus that needs network configuration, the network configuration App 104 may also guide the user to input the PASSWD of the online hotspot.

[0203] After receiving the PASSWD of the online hotspot input by the user, the network configuration App 104 may generate a network configuration request based on the first apparatus information of the target network configuration apparatus and the hotspot information (i.e., router information, including SSID, PASSWD, BSSID, etc.) of the currently connected online hotspot, and send the network configuration request to the server 102 to request the server 102 to perform network configuration on the apparatus.

[0204] At 408, the server 102 serializes all the received network configuration requests for the same apparatus; processes the network configuration requests for the same apparatus one by one according to the preset processing sequence; during processing, if a certain network configuration request is approved, within the preset duration for processing the network configuration request, temporarily stores or rejects other network configuration requests for the same apparatus until the approved network configuration request is processed or timed out.

[0205] In an example embodiment, after receiving the network configuration requests, the server 102 may serialize the network configuration

requests for the same apparatus 101 to solve the problem that multiple users perform network configuration on the same apparatus at the same time, and to allow multiple users to perform network configuration on different apparatuses at the same time.

[0206] In an example embodiment, when multiple users simultaneously perform network configuration on the same apparatus, the following methods may be used.

[0207] According to the preset processing sequence, the network configuration requests for the same apparatus are processed one by one. During processing, if a certain network configuration request is approved, within the preset duration for processing the network configuration request, other network configuration requests for the same apparatus will be temporarily stored or rejected until the approved network configuration request is processed or timed out.

[0208] In an implementation, the preset processing sequence may include a first-come-first-served sequence. In an example embodiment, when receiving at least two network configuration requests for the same apparatus, the server 102 may approve the network configuration requests for the same apparatus one by one according to a first-come-first-served rule.

[0209] Further, after the server 102 approves a network configuration request for a certain apparatus, a network configuration window for the current apparatus may be opened in the server 102, and within the preset duration for processing the approved network configuration request, other network

configuration requests for the same apparatus are temporarily stored or rejected, until the currently approved network configuration request is processed or timed out.

[0210] In an example embodiment, the preset duration for processing the approved network configuration request may be the effective duration of the opened network configuration window. For example, the effective duration is set as 60 seconds.

[0211] Step 11, the server 102 generates a hotspot switching command based on the currently processed network configuration request, and sends the hotspot switching command to the corresponding apparatus 101.

[0212] Specifically, when approving the network configuration request, the server 102 may generate a hotspot switching command for the currently approved network configuration request.

[0213] In a preferred embodiment of embodiments of the present disclosure, the server 102 generates a hotspot switching command based on the currently processed network configuration request, which may further include the following sub-steps:

[0214] When the network configuration request is approved, generating network configuration approval information; when the network configuration request is rejected, generating network configuration rejection information; generating network configuration response information based on the network configuration approval information or the network configuration rejection information, and sending the network configuration response information to the

network configuration application; receiving network configuration preparation information sent by the network configuration application based on the network configuration approval information; and generating the hotspot switching command according to the network configuration preparation information.

[0215] Specifically, according to the processing sequence, when rejecting a certain network configuration request, the server 102 may generate network configuration rejection information, and return the network configuration rejection information as the network configuration response information to the network configuration App 104 that sends the network configuration request, wherein the network configuration rejection information is configured to prompt the user not to operate the current apparatus.

[0216] After receiving the network configuration rejection information, the network configuration app 10 prompts the current user that other users are performing network configuration on the current apparatus and warn the user not to operate the apparatus.

[0217] Correspondingly, when approving a certain network configuration request, the server 102 may generate the network configuration approval information, and return the network configuration approval information as the network configuration response information to the network configuration App 104 that sends the network configuration request, wherein the network configuration approval information is configured to prompt the user to perform a touch operation on the apparatus, that is, the network configuration approval information may include instruction information of user touch operation.

[0218] After receiving the network configuration approval information, the network configuration App 104 displays the network configuration approval information to prompt the user to start the network configuration operation and guide the user to touch the apparatus 101.

[0219] It should be noted that the example embodiments of the present disclosure do not specifically limit the touch operation that the user performs on the apparatus 101, as long as the touch operation may make the apparatus 101 enter the network configuration mode. For example, the touch operation may be an operation of touching a network configuration button of the touch apparatus 101, and the like.

[0220] The touch operation performed by the user on the apparatus 101 may make the apparatus 101 enter a network configuration mode. In the network configuration mode, the apparatus 101 opens the network configuration window on the apparatus side and starts the network configuration window, wherein the effective duration of the network configuration window is the preset duration.

[0221] After the user performs the touch operation, a completion operation may be performed in the network configuration App 104 to notify the network configuration App 104 that the touch operation is completed. After detecting the completion of the operation, the network configuration App 104 may determine that the user has performed the touch operation on the apparatus 101. At this time, the network configuration App 104 may generate the network configuration preparation information, and send the network configuration

preparation information to the server 102 to notify the server 102 that the apparatus 101 that needs network configuration has entered a network configuration state, wherein the network configuration preparation information may include apparatus information of the apparatus 101.

[0222] After receiving the network configuration preparation information and determining that the apparatus 101 has entered the network configuration mode, the server 102 may start the network configuration window and generate the hotspot switching command.

[0223] It should be noted that the apparatus only supports the command to switch AP within the effective duration of the network configuration window.

[0224] As an example, the hotspot switching command may include hotspot information, such as SSID, PASSWD, BSSID, etc., of the online hotspot.

[0225] After generating the hotspot switching command, the server sends the hotspot switching command to the corresponding apparatus 101 through a secure connection.

[0226] Step 12, when determining that the designated network configuration condition is met at the current time, the apparatus 101 connects to the online hotspot based on the hotspot switching command.

[0227] Specifically, after receiving the hotspot switching command, the apparatus 101 may first detect whether the designated network configuration condition is met at the current time.

[0228] When determining that the designated network configuration condition is not met at the current time, the apparatus 101 generates network

configuration error information, and sends the network configuration error information to the server 102 to notify the server 102 of a network configuration timeout or error.

[0229] When determining that the designated network configuration condition is met at the current time, the apparatus 101 may access the online hotspot according to the hotspot information, such as SSID, PASSWD, BSSID, etc., of the online hotspot to complete the switch from the network configuration hotspot to the online hotspot.

[0230] As an example, the designated network configuration condition may at least include the following condition:

[0231] The apparatus enters the network configuration mode, and the duration of entering the network configuration mode does not exceed the preset duration.

[0232] Specifically, after receiving the hotspot switching command, the apparatus 101 checks whether it is in the network configuration mode and whether its network configuration window exceeds the effective duration. The apparatus only supports the command of switching AP when it is in the network configuration mode and within the effective duration of the network configuration window, that is, the designated network configuration condition is met.

[0233] So far, the process of network configuration of apparatus is completed.

III. Process of Binding of Apparatus

[0234] Referring to FIG. 5, a flowchart of steps of an example embodiment of the process of binding of apparatus is shown, which may specifically include the following steps.

[0235] Step 13, the apparatus 101 establishes a secure connection with the server based on the online hotspot, and sends second apparatus information to the server.

[0236] After switching to the online hotspot, the apparatus 101 establishes a secure connection between the apparatus 101 and the server 102 based on the online hotspot, where the secure connection may include a TLS connection.

[0237] After switching to the online hotspot, the apparatus 101 may also obtain the second apparatus information. As an example, the second apparatus information may include the first apparatus information and a token of the apparatus 101.

[0238] After obtaining the second apparatus information, the apparatus 101 may report the second apparatus information to the server 102 through a secure connection with the server 102.

[0239] Step 15, locally announcing the second apparatus information to the outside.

[0240] After obtaining the second apparatus information, the apparatus 101 may also announce the second apparatus information to the outside locally, indicating that the network configuration is successful.

[0241] Step 15, after receiving the second apparatus information, the network configuration App 104 determines that the network configuration of the apparatus is successful based on the second apparatus information, generates network configuration success information, and displays the network configuration success information.

[0242] After receiving the second apparatus information announced by the apparatus 101, the network configuration App 104 determines that the network configuration of the apparatus 101 is successful. At this time, the network configuration App 104 may generate the network configuration success information and show the network configuration success information to the user to prompt the user that the network configuration is successful and guide the user to the process of binding.

[0243] It should be noted that when failing to receive the second apparatus information announced by the apparatus 101, the network configuration app 104 may also actively query the second apparatus information locally. In implementations, the network configuration app 104 may broadcast a query request locally to query the apparatus information, and the apparatus 101 replies with its own second apparatus information after receiving the query request.

[0244] Step 16, generating a binding request based on the second apparatus information; sending the binding request to the server, and receiving a binding result returned by the server based on the binding request.

[0245] Specifically, the network configuration App 104 parses out the first apparatus information and the token according to the second apparatus information, and then uses the first apparatus information and the token to generate the binding request, and sends the binding request to the server 102 to request the server 102 to bind the second apparatus information and the corresponding apparatus.

[0246] In order to prevent the network configuration App 104 from maliciously binding apparatus, after receiving the first apparatus information and the token, the server 102 may match the token sent by the network configuration App 104 with the token reported by the apparatus 101. If the two tokens are the same, a binding operation is performed, and the corresponding binding result may be a binding success result. Otherwise, if the two tokens are different, the binding is rejected, and the corresponding binding result may be a binding failure result.

[0247] During the binding operation, the server 102 may bind the apparatus 101 according to the first apparatus information and the token, that is, generate the second apparatus information and a binding relationship of the apparatus. After the binding is completed, the server 102 returns the binding result to the network configuration App 104.

[0248] So far, the process of binding of apparatus is completed.

[0249] In the example embodiments of the present disclosure, a router is configured to assist the network configuration of apparatus, and the network configuration process and communication process are based on a reliable

secure connection to ensure the security of sensitive data. In addition, the operations are simple for users, and the efficiency and the success rate of the network configuration are improved.

[0250] Referring to FIG. 6, a flow chart of steps of an example embodiment of a method for performing network configuration on apparatus of the present disclosure is shown. The example embodiment of the present disclosure is described from the apparatus side, which may specifically include the following steps.

[0251] Step 601, the apparatus connects to a network configuration hotspot provided by a router.

[0252] Step 602, sending first apparatus information of the apparatus to a server through the network configuration hotspot.

[0253] Step 603, receiving a hotspot switching command sent by the server according to the first apparatus information, wherein the hotspot switching command includes hotspot information of an online hotspot.

[0254] Step 604, connecting to the online hotspot based on the hotspot switching command when a designated network configuration condition is met.

[0255] In a preferred embodiment of embodiments of the present disclosure, step 601 may further include the following sub-steps.

[0256] Sub-step S11, obtaining a network configuration hotspot list, wherein the network configuration hotspot list includes at least one network configuration hotspot and/or signal strength of the network configuration hotspot.

[0257] Sub-step S12, connecting to the network configuration hotspot with the strongest signal strength.

[0258] Sub-step S13, if the connecting fails, connecting to the network configuration hotspot with a second strongest signal strength until the connecting to the network configuration hotspot succeeds.

[0259] In a preferred embodiment of embodiments of the present disclosure, after step 602, the example embodiments of the present disclosure may further include the following steps:

[0260] Sending a connection request to the server through the network configuration hotspot to establish a secure connection between the apparatus and the server;

[0261] Obtaining the first apparatus information of the apparatus;

[0262] Sending the first apparatus information and the network configuration hotspot list to the server.

[0263] In a preferred embodiment of embodiments of the present disclosure, before step 603, the example embodiments of the present disclosure may further include the following steps:

[0264] When a touch operation of a user is detected, entering a network configuration mode.

[0265] In a preferred embodiment of embodiments of the present disclosure, the designated network configuration condition includes at least the following condition:

[0266] The apparatus entering the network configuration mode, and duration of entering the network configuration mode does not exceed a preset duration.

[0267] In a preferred embodiment of embodiments of the present disclosure, the example embodiments of the present disclosure may further include the following steps:

[0268] Generating network configuration error information when the designated network configuration condition is not met;

[0269] Sending the network configuration error information to the server.

[0270] In a preferred embodiment of embodiments of the present disclosure, after step 604, the example embodiments of the present disclosure may further include the following steps:

[0271] Obtaining second apparatus information of the apparatus;

[0272] Announcing the second apparatus information to the outside locally, and/or establishing a secure connection with the server based on the online hotspot, and sending the second apparatus information to the server.

[0273] In the example embodiments of the present disclosure, the network configuration hotspot is provided by the router, the apparatus is firstly connected to the network configuration hotspot after powered on, and a secure connection with the corresponding server is established through the network configuration hotspot. Then the hotspot switching command from the server is received, the apparatus may be switched to the online hotspot according to the hotspot information of the online hotspot contained in the hotspot switching

command, so as to complete the network configuration of the apparatus, which realizes the reliable connection of the network configuration process and improves the success rate of the network configuration of the apparatus.

[0274] Referring to FIG. 7, a flow chart of steps of another example embodiment of a method for performing network configuration on apparatus of the present disclosure is shown. The example embodiments of the present disclosure are described from the network configuration application side, which may specifically include the following steps:

[0275] Step 701, the network configuration application determines a target network configuration apparatus, where the target network configuration apparatus connects to a network configuration hotspot provided by a router in advance and sends first apparatus information of the target network configuration apparatus to a server;

[0276] Step 702, generating a network configuration request based on the first apparatus information and hotspot information of a currently connected online hotspot.

[0277] Step 703, sending the network configuration request to the server to request the server to perform network configuration on the apparatus according to the hotspot information of the online hotspot.

[0278] In a preferred embodiment of embodiments of the present disclosure, after step 703, the example embodiments of the present disclosure may further include the following steps:

[0279] Receiving network configuration response information returned by the server based on the network configuration request, wherein the network configuration response information includes network configuration approval information, and the network configuration approval information includes instruction information of user touch operation;

[0280] Displaying the network configuration approval information;

[0281] Upon determining that a user performs a touch operation based on the network configuration approval information, generating network configuration preparation information;

[0282] Sending the network configuration preparation information to the server to notify the server to perform the network configuration on the apparatus.

[0283] In a preferred embodiment of embodiments of the present disclosure, the network configuration response information further includes network configuration rejection information, and the method may further include the following steps:

[0284] Displaying the network configuration rejection information to prompt the user to prohibit operating the apparatus.

[0285] In example embodiments of the present disclosure, before step 701, the example embodiments of the present disclosure may further include the following steps:

[0286] the network configuration application installed in the terminal connects to the online hotspot of the router and establishes a secure connection with the server.

[0287] In a preferred embodiment of embodiments of the present disclosure, 701 may further include the following sub-steps.

[0288] Sub-step S21, determining the hotspot information of the online hotspot;

[0289] Sub-step S22, obtaining a to-be-network-configured apparatus list from the server side based on the hotspot information, the to-be-network-configured apparatus list including one or more apparatus to be network-configured, and first apparatus information of the apparatus;

[0290] Sub-step S23, displaying the to-be-network-configured apparatus list;

[0291] Sub-step S24, setting the apparatus selected by a user in the to-be-network-configured apparatus list as the target network configuration apparatus.

[0292] In a preferred embodiment of embodiments of the present disclosure, the example embodiments of the present disclosure may further include the following steps:

[0293] Obtaining second apparatus information of the apparatus, wherein the second apparatus information is apparatus information after the network configuration of the apparatus succeeds;

[0294] Determining that the network configuration of the apparatus succeeds based on the second apparatus information;

[0295] Generating network configuration success information, and displaying the network configuration success information.

[0296] In a preferred embodiment of embodiments of the present disclosure, the obtaining of the second apparatus information of the apparatus may further include the following sub-steps:

[0297] Receiving the second apparatus information broadcast by the apparatus; or

[0298] Broadcasting a query request in local, and receiving the second apparatus information returned by the apparatus based on the query request.

[0299] In a preferred embodiment of embodiments of the present disclosure, the example embodiments of the present disclosure may further include the following steps:

[0300] Generating a binding request based on the second apparatus information;

[0301] Sending the binding request to the server to request the server to bind the second apparatus information and a corresponding apparatus;

[0302] Receiving a binding result returned by the server based on the binding request.

[0303] In the example embodiments of the present disclosure, after determining the target network configuration apparatus, the network configuration application connected to the online hotspot may actively obtain

the hotspot information of the online hotspot and the first apparatus information of the target network configuration apparatus, generate a network configuration request according to the first apparatus Information and the hotspot information, and send the network configuration request to the server to request the server to perform the network configuration on the apparatus according to the hotspot information of the online hotspot. The network configuration process is more automated, which simplifies user operations, reduces the amount of information input by users, thereby reducing the probability of user input error, and improving the success rate and the efficiency of network configuration.

[0304] Referring to FIG. 8, a flow chart of steps of another example embodiment of a method for performing network configuration on apparatus according to the present disclosure is shown. The example embodiments of the present disclosure are described from the server side, which may specifically include the following steps.

[0305] Step 801, receiving a network configuration request sent by a network configuration application, wherein the network configuration request includes hotspot information of an online hotspot.

[0306] Step 802, generating a hotspot switching command based on the network configuration request.

[0307] Step 803, sending the hotspot switching command to an apparatus needing network configuration through a network configuration hotspot, to

make the apparatus switch a hotspot that the apparatus currently connects to from the network configuration hotspot to the online hotspot.

[0308] In a preferred embodiment of embodiments of the present disclosure, before step 803, the example embodiments of the present disclosure may further include the following steps:

[0309] Establishing, by a server, a secure connection with the apparatus needing network configuration through the network configuration hotspot of a router;

[0310] Receiving first apparatus information sent by the apparatus and a network configuration hotspot list obtained by the apparatus;

[0311] Generating an association relationship between the first apparatus information and the network configuration hotspot list;

[0312] Saving the first apparatus information, the network configuration hotspot list, and the association relationship.

[0313] In a preferred embodiment of embodiments of the present disclosure, each network configuration hotspot in the network configuration hotspot list includes a basic service set identifier BSSID.

[0314] Before step 801, the example embodiments of the present disclosure may further include the following steps:

[0315] Establishing a secure connection with the network configuration application through the online hotspot of a router;

[0316] Receiving the hotspot information of the online hotspot sent by the network configuration application, wherein the hotspot information of the online hotspot includes the BSSID of the online hotspot;

[0317] Matching the BSSID of the online hotspot with BSSIDs in the network configuration hotspot list corresponding to all apparatuses stored in the server to obtain a to-be-network-configured apparatus list;

[0318] Sending the to-be-network-configured apparatus list to be configured to the network configuration application.

[0319] In a preferred embodiment of embodiments of the present disclosure, after 801, the example embodiments of the present disclosure may further include the following steps:

[0320] Serializing all network configuration requests received for the same apparatus;

[0321] Processing the network configuration requests for the same apparatus one by one according to a preset processing sequence; during the processing, when a certain network configuration request is approved, temporarily storing or rejecting other network configuration requests for the same apparatus within a preset duration for processing the network configuration request until the approved network configuration request is processed or timed out.

[0322] In a preferred embodiment of embodiments of the present disclosure, step 802 further includes the following sub-steps.

[0323] Sub-step 31, generating network configuration approval information when the network configuration request is approved, wherein the network

configuration approval information includes instruction information of user touch operation, and the network configuration approval information is configured to prompt the user to perform a touch operation on the apparatus.

[0324] Sub-step 32, generating a network configuration rejection information when the network configuration request is rejected, wherein the network configuration rejection information is configured to prompt the user to prohibit operating the apparatus.

[0325] Sub-step 33, generating network configuration response information based on the network configuration approval information or the network configuration rejection information, and sending the network configuration response information to the network configuration application;

[0326] Sub-step 34, receiving network configuration preparation information sent by the network configuration application based on the network configuration approval information, wherein the network configuration preparation information is information generated after the network configuration application determining that the user performs the touch operation based on the network configuration approval information.

[0327] Sub-step 35, generating the hotspot switching command according to the network configuration preparation information.

[0328] In a preferred embodiment of embodiments of the present disclosure, after the step 803, the example embodiments of the present disclosure may further include the following steps:

[0329] Receiving network configuration error information sent by the apparatus, wherein the network configuration error information is information generated when the apparatus determines that a designated network configuration condition is not met after receiving the hotspot switching command.

[0330] In a preferred embodiment of embodiments of the present disclosure, after step 803, the example embodiments of the present disclosure may further include the following steps:

[0331] Determining that the network configuration of apparatus succeeds when second apparatus information sent by the apparatus is received;

[0332] Receiving a binding request sent by the network configuration application, wherein the binding request includes second apparatus information of the apparatus;

[0333] Upon determining that the second apparatus information sent by the apparatus is consistent with the second apparatus information sent by the network configuration application, generating a binding relationship between the second apparatus information and the apparatus, and returning a binding result to the network configuration application.

[0334] In the example embodiments of the present disclosure, during the process of network configuration of apparatus, the server may establish a secure connection with the apparatus through the network configuration hotspot, and establish a secure connection with the network configuration application through the online hotspot. When receiving the network

configuration request containing the hotspot information of the online hotspot sent by the network configuration application, the server may generate a hotspot switching command according to the network configuration request and send the hotspot switching command to the apparatus to make the apparatus switch the currently connected hotspot from the network configuration hotspot to the online hotspot. The network configuration process establishes a reliable connection with the apparatus, which improves the success rate of the network configuration of the apparatus. Meanwhile, in combination with the network configuration application, the automation of the network configuration may be improved, user operations may be simplified, and the efficiency of the network configuration may be improved.

[0335] Referring to FIG. 9, a flowchart of steps of another example embodiment of a method for performing network configuration on apparatus of the present disclosure is shown. The example embodiments of the present disclosure are described from the router side, which may specifically include the following steps.

[0336] Step 901, when detecting that the apparatus is connected to a network configuration hotspot of the router, the router intercepts the connection request sent by an apparatus to a corresponding server.

[0337] Step 902, determining whether a server corresponding to the connection request meets a preset condition.

[0338] Step 903, if the server meets the preset condition, sending the connection request to the server to make the server establish a secure

connection with the apparatus and perform network configuration on the apparatus.

[0339] In a preferred embodiment of embodiments of the present disclosure, the example embodiments of the present disclosure may further include the following steps:

[0340] Discarding the connection request if the server does not meet the preset condition.

[0341] In a preferred embodiment of embodiments of the present disclosure, step 902 further includes the following sub-steps.

[0342] Sub-step S41, determining vendor information of the server corresponding to the connection request.

[0343] Sub-step S42, determining whether a vendor corresponding to the vendor information pays for a current network configuration service; if yes, determining that the server corresponding to the connection request meets the preset condition; if not, determining that the server corresponding to the connection request does not meet the preset condition.

[0344] In a preferred embodiment of embodiments of the present disclosure, before step 901, the example embodiments of the present disclosure may further include the following steps:

[0345] After the router is powered on, turning on the network configuration hotspot, and setting the network configuration hotspot as a hidden hotspot.

[0346] In the example embodiments of the present disclosure, the router may realize the network configuration service by only turning on the network

configuration hotspot, and the existing routers on the market basically do not need to be modified, making the network configuration solution of the example embodiments of the present disclosure very easy to promote.

[0347] When detecting that the apparatus is connected to the network configuration hotspot, the router may intercept the connection request sent by the apparatus to the corresponding server, and determine whether the server corresponding to the connection request meets the preset condition. When the server meets the preset condition, the router sends the connection request to the server to make the server establish a secure connection with the apparatus, and performs the network configuration on the apparatus to expand the business model of the network configuration by router.

[0348] The description of the example embodiments in FIG. 6-FIG.9 may be relatively simple since they are basically similar to the method example embodiments in FIG. 2 to FIG. 5. For related details, reference may be made to the part of the description of the method example embodiments in FIG. 2 to FIG. 5.

[0349] It should be noted that for the method example embodiments, for the sake of simple description, they are all expressed as combinations of a series of actions, but those skilled in the art should know that the example embodiments of the present disclosure are not limited by the described sequence of actions, because according to the example embodiments, some steps may be performed in other order or at the same time. In addition, those skilled in the art should also be aware that the example embodiments described in the specification are

merely preferable embodiments, and the actions involved are not necessarily required for the example embodiments of the present disclosure.

[0350] Referring to FIG. 10, a structural block diagram of an example embodiment of an apparatus for performing network configuration of the present disclosure is shown. The apparatus may specifically include the following modules:

[0351] A network configuration hotspot connection module 1001 is configured to connect to a network configuration hotspot provided by a router;

[0352] A first apparatus information sending module 1002 is configured to send a first apparatus information of the apparatus to a server through the network configuration hotspot;

[0353] A hotspot switching command receiving module 1014 is configured to receive a hotspot switching command sent by the server according to the first apparatus information, where the hotspot switching command includes hotspot information of an online hotspot;

[0354] A hotspot switching module 1004 is configured to connect to the online hotspot based on the hotspot switching command when a designated network configuration condition is met.

[0355] In a preferred embodiment of embodiments of the present disclosure, the network configuration hotspot connection module 1001 may include the following sub-modules:

[0356] A network configuration hotspot list obtaining sub-module is configured to obtain a network configuration hotspot list, where the network

configuration hotspot list includes at least one network configuration hotspot and/or the signal strength of the network configuration hotspot;

[0357] A network configuration hotspot connection sub-module is configured to connect to the network configuration hotspot with the strongest signal strength; and if the connecting fails, connect to the network configuration hotspot with a second strongest signal strength until the connecting to the network configuration hotspot succeeds.

[0358] In a preferred embodiment of embodiments of the present disclosure, the first apparatus information sending module 1002 may further include the following sub-modules:

[0359] A secure connection establishment sub-module is configured to send a connection request to the server through the network configuration hotspot to establish a secure connection with the apparatus and the server;

[0360] A first apparatus information obtaining sub-module is configured to obtain first apparatus information of the apparatus;

[0361] A first apparatus information sending sub-module is configured to send the first apparatus information and the network configuration hotspot list to the server.

[0362] In a preferred embodiment of embodiments of the present disclosure, the example embodiments of the present disclosure may also include the following modules:

[0363] A network configuration mode module is configured to enter the network configuration mode when a touch operation of a user is detected.

[0364] In a preferred embodiment of embodiments of the present disclosure, the designated network configuration conditions include at least the following condition:

[0365] The apparatus enters the network configuration mode, and the duration of entering the network configuration mode does not exceed the preset duration.

[0366] In a preferred embodiment of embodiments of the present disclosure, the example embodiments of the present disclosure may further include the following modules:

[0367] A network configuration error information generating module is configured to generate network configuration error information when the designated network configuration condition is not met; and send the network configuration error information to the server.

[0368] In a preferred embodiment of embodiments of the present disclosure, the example embodiments of the present disclosure may also include the following modules:

[0369] A second apparatus information obtaining module is configured to obtain second apparatus information of the apparatus;

[0370] A second apparatus information announcement module is configured to locally announce the second apparatus information to the outside; and/or

[0371] A second apparatus information sending module is configured to establish a secure connection with the server based on the online hotspot, and send the second apparatus information to the server.

[0372] Referring to FIG. 11, a structural block diagram of an example embodiment of a terminal for performing network configuration on apparatus of the present disclosure is shown. The terminal may specifically include the following modules:

[0373] A target network configuration apparatus determining module 1101 is configured to determine a target network configuration apparatus by using a network configuration application, wherein the target network configuration apparatus connects to a network configuration hotspot provided by a router in advance and sends first apparatus information of the target network configuration apparatus to a server;

[0374] A network configuration request generating module 1102 is configured to generate a network configuration request based on the first apparatus information and hotspot information of a currently connected online hotspot;

[0375] A network configuration request sending module 1103 is configured to send a network configuration request to the server to request the server to perform network configuration on the apparatus according to the hotspot information of the online hotspot.

[0376] In a preferred embodiment of embodiments of the present disclosure, the example embodiments of the present disclosure may further include the following modules:

[0377] A network configuration response information receiving module is configured to receive the network configuration response information returned

by the server based on the network configuration request, where the network configuration response information includes the network configuration approval information, and the network configuration approval information includes instruction information of user touch operation;

[0378] A network configuration approval information display module is configured to display the network configuration approval information;

[0379] A network configuration preparation information generating module is configured to generate network configuration preparation information upon determining that the user performs a touch operation based on the network configuration approval information;

[0380] A network configuration preparation information sending module is configured to send the network configuration preparation information to the server to notify the server to perform network configuration on the apparatus.

[0381] In a preferred embodiment of embodiments of the present disclosure, the network configuration response information further includes network configuration rejection information, and the example embodiments of the present disclosure may further include the following modules:

[0382] A network configuration rejection information display module is configured to display the network configuration rejection information to prompt the user to prohibit operating the apparatus.

[0383] In a preferred embodiment of embodiments of the present disclosure, the example embodiments of the present disclosure may further include the following modules:

[0384] An online hotspot access module is configured to connect the network configuration application to the online hotspot of the router and establish a secure connection with the server.

[0385] In a preferred embodiment of embodiments of the present disclosure, the target network configuration apparatus determining module 1101 may include the following sub-modules:

[0386] A hotspot information determining sub-module is configured to determine the hotspot information of the online hotspot;

[0387] A to-be-network-configured apparatus list obtaining sub-module is configured to obtain the to-be-network-configured apparatus list from the server side based on the hotspot information, and the to-be-network-configured apparatus list includes one or more apparatuses to be network-configured, and the first apparatus information of the apparatus;

[0388] A to-be-network-configured apparatus list display sub-module is configured to display the to-be-network-configured apparatus list; and take the apparatus in the to-be-network-configured apparatus list that is selected by the user as the target network configuration apparatus.

[0389] In a preferred embodiment of embodiments of the present disclosure, the example embodiments of the present disclosure may further include the following modules:

[0390] A second apparatus information obtaining module is configured to obtain second apparatus information of the apparatus, where the second

apparatus information is the apparatus information after the network configuration of the apparatus is successful;

[0391] A determining module configured to determine that the network configuration of the apparatus is successful based on the second apparatus information;

[0392] A network configuration success information generating module is configured to generate the network configuration success information and display the network configuration success information.

[0393] In a preferred embodiment of embodiments of the present disclosure, the second apparatus information obtaining module includes:

[0394] A second apparatus information receiving sub-module is configured to receive the second apparatus information broadcast by the apparatus; or

[0395] A query request broadcasting sub-module is configured to broadcast the query request locally and receive the second apparatus information returned by the apparatus based on the query request.

[0396] In a preferred embodiment of embodiments of the present disclosure, the example embodiments of the present disclosure may further include the following modules:

[0397] A binding request generation module is configured to generate a binding request based on the second apparatus information;

[0398] A binding request sending module is configured to send the binding request to the server to request the server to bind the second apparatus information and the corresponding apparatus;

[0399] A binding result receiving module is configured to receive the binding result returned by the server based on the binding request.

[0400] Referring to FIG. 12, a structural block diagram of an example embodiment of a server for network configuration on apparatus according to the present disclosure is shown. The server may specifically include the following modules:

[0401] A network configuration request receiving module 1201 is configured to receive a network configuration request sent by a network configuration application, wherein the network configuration request includes hotspot information of an online hotspot;

[0402] A hotspot switching command generating module 1202 is configured to generate a hotspot switching command based on the network configuration request;

[0403] A hotspot switching command sending module 1203 is configured to send the hotspot switching command to an apparatus needing network configuration through a network configuration hotspot to make the apparatus switch a hotspot that the apparatus connects to from the network configuration hotspot to the online hotspot.

[0404] In a preferred embodiment of embodiments of the present disclosure, the example embodiments of the present disclosure may further include the following modules:

[0405] A first secure connection establishment module is configured to establish a secure connection with the apparatus needing network configuration through the network configuration hotspot of the router;

[0406] A first apparatus information receiving module is configured to receive the first apparatus information sent by the apparatus and the network configuration hotspot list obtained by the apparatus;

[0407] An association relationship generating module is configured to generate an association relationship between the first apparatus information and the network configuration hotspot list;

[0408] A saving module is configured to save the first apparatus information, the network configuration hotspot list, and the association relationship.

[0409] In a preferred embodiment of embodiments of the present disclosure, each network configuration hotspot in the network configuration hotspot list includes a basic service set identifier BSSID; the example embodiments of the present disclosure may also include the following modules:

[0410] A second secure connection establishment module is configured to establish a secure connection with the network configuration application through the online hotspot of the router;

[0411] A hotspot information receiving module is configured to receive the hotspot information of the online hotspot sent by the network configuration application, where the hotspot information of the online hotspot includes the BSSID of the online hotspot;

[0412] A to-be-network-configured apparatus list obtaining module is configured to match the BSSID of the online hotspot with the BSSIDs in the network configuration hotspot list corresponding to all apparatuses stored in the server to obtain the to-be-network-configured apparatus list;

[0413] A to-be-network-configured apparatus list sending module is configured to send the to-be-network-configured apparatus list to the network configuration application.

[0414] In a preferred embodiment of embodiments of the present disclosure, the example embodiments of the present disclosure may further include the following modules:

[0415] A serialization processing module is configured to serialize all network configuration requests received for the same apparatus;

[0416] A network configuration request processing module is configured to process network configuration requests for the same apparatus one by one according to a preset processing sequence. During processing, if a certain network configuration request is approved, then within the preset duration for processing the network configuration, other network configuration requests for the same apparatus are temporarily stored or rejected until the approved network configuration request is processed or timed out.

[0417] In a preferred embodiment of embodiments of the present disclosure, the hotspot switching command generating module 1203 includes the following sub-modules:

[0418] A network configuration approval information generation sub-module is configured to generate network configuration approval information when the network configuration request is approved, where the network configuration approval information includes instruction information of user touch operation, and the network configuration approval information is configured to prompt the user to perform a touch operation on the apparatus;

[0419] A network configuration rejection information generation sub-module is configured to generate network configuration rejection information when the network configuration request is rejected, and the network configuration rejection information is configured to prompt the user to prohibit operating the apparatus;

[0420] A network configuration response information generation sub-module is configured to generate network configuration response information based on the network configuration approval information or the network configuration rejection information, and send the network configuration response information to the network configuration application;

[0421] A network configuration preparation information receiving sub-module is configured to receive network configuration preparation information sent by the network configuration application based on the network configuration approval information, where the network configuration preparation information is information that is generated after the network configuration application determines that the user performs a touch operation based on the network configuration approval information;

[0422] A hotspot switching command generation sub-module is configured to generate the hotspot switching command according to the network configuration preparation information.

[0423] In a preferred embodiment of embodiments of the present disclosure, the example embodiments of the present disclosure may also include the following modules:

[0424] A network configuration error information receiving module is configured to receive network configuration error information sent by the apparatus, where the network configuration error information is information generated after the apparatus receives the hotspot switching command and that the designated network configuration condition is not met is determined.

[0425] In a preferred embodiment of embodiments of the present disclosure, the example embodiments of the present disclosure may further include the following modules:

[0426] A second apparatus information receiving module is configured to determine that the network configuration of the apparatus is successful when the second apparatus information sent by the apparatus is received;

[0427] A binding request receiving module is configured to receive a binding request sent by a network configuration application, where the binding request includes the second apparatus information of the apparatus;

[0428] A binding module is configured to, upon determining that the second apparatus information sent by the apparatus is consistent with the second apparatus information sent by the network configuration application, generate

the second apparatus information and the binding relationship of the apparatus, and return the binding result to the network configuration application.

[0429] Referring to FIG. 13, a structural block diagram of an example embodiment of a router for performing network configuration on apparatus of the present disclosure is shown. The router may specifically include the following modules:

[0430] A connection request interception module 1301 is configured to intercept a connection request sent by an apparatus to a corresponding server when a router detects that the apparatus connects to a network configuration hotspot of the router;

[0431] A determining module 1302 is configured to determine whether a server corresponding to the connection request meets a preset condition;

[0432] A connection request sending module 1303 is configured to send the connection request to the server when the server meets the preset condition to make the server establish a secure connection with the apparatus, and perform network configuration on the apparatus.

[0433] In a preferred embodiment of embodiments of the present disclosure, the example embodiments of the present disclosure may also include the following modules:

[0434] A request discarding module is configured to discard the connection request if the server does not meet the preset condition.

[0435] In a preferred embodiment of embodiments of the present disclosure, the determining module 1302 includes:

[0436] A vendor information determining sub-module is configured to determine the vendor information of the server corresponding to the connection request;

[0437] A vendor information determining sub-module is configured to determine whether the vendor corresponding to the vendor information pays for the current network configuration service; if so, that the server corresponding to the connection request meets the preset condition is determined; if not, that the server corresponding to the connection request does not meet the preset condition is determined.

[0438] In a preferred embodiment of embodiments of the present disclosure, the example embodiments of the present disclosure may further include the following modules:

[0439] A network configuration hotspot activation module is configured to, after the router is powered on, enable the network configuration hotspot, and set the network configuration hotspot as a hidden hotspot.

[0440] The description of the example embodiments shown in FIG. 10-FIG. 13 may be relatively simple since they are basically similar to the above-mentioned method example embodiments, and for related details, reference may be made to the part of the description of the method example embodiments.

[0441] The example embodiments of the present disclosure may be implemented as a system that uses any appropriate hardware, firmware, software, or any combination thereof to perform a desired configuration. FIG.

14 schematically illustrates an exemplary system (or device) 1400 that may be used to implement the various example embodiments described in this disclosure.

[0442] For an example embodiment, FIG. 14 shows an exemplary system 1400 having one or more processors 1402, at least one system control module (chipset) 1404 coupled to at least one of the processors 1402, a system memory 1406 coupled to the system control module 1404, a non-volatile memory (NVM)/storage apparatus 1408 coupled to the system control module 1404, one or more input/output devices 1410 coupled to the system control module 1404, and a network interface 1412 coupled to the system control module 1404.

[0443] The processor 1402 may include one or more single-core or multi-core processors, and the processor 1402 may include any combination of a general-purpose processor or a dedicated processor (for example, a graphics processor, an application processor, a baseband processor, etc.). In some example embodiments, the system 1400 may serve as the data platform described in the example embodiments of the present disclosure.

[0444] In some example embodiments, the system 1400 may include one or more computer-readable media with instructions (for example, system memory 1406 or NVM/storage devices 1408) and one or more processors 1402 combined with the one or more computer-readable media to be configured to execute the instructions to implement modules to perform the actions described in this disclosure.

[0445] For example embodiments, the system control module 1404 may include any suitable interface controller to provide any suitable interface to at least one of the processor(s) 1402 and/or any suitable apparatuses or components that communicate with the system control module 1404.

[0446] The system control module 1404 may include a memory controller module to provide an interface to the system memory 1406. The memory controller module may be a hardware module, a software module, and/or a firmware module.

[0447] The system memory 1406 may be used to load and store data and/or instructions for the system 1400, for example. For an example embodiment, the system memory 1406 may include any suitable volatile memory, for example, a suitable DRAM. In some example embodiments, the system memory 1406 may include a double data rate type quad synchronous dynamic random access memory (DDR7 SDRAM).

[0448] For example embodiments, the system control module 1404 may include one or more input/output controllers to provide interfaces to the NVM/storage device(s) 1408 and the input/output apparatus 1410 (one or more).

[0449] For example, the NVM/storage device(s)1408 may be used to store data and/or instructions. The NVM/storage device(s)1408 may include any suitable non-volatile memory (e.g., flash memory) and/or may include any suitable (one or more) non-volatile storage apparatuses (e.g., one or more hard

drives (HDD), one or more compact disc (CD) drives and/or one or more digital versatile disc (DVD) drives).

[0450] The NVM/storage apparatus 1408 may include storage resources that are physically part of the apparatus on which the system 1400 is installed, or it may be accessed by the apparatus and does not have to be a part of the apparatus. For example, the NVM/storage device(s) 1408 may be accessed through the input/output device(s) 1410 through the network.

[0451] The input/output device(s) 1410 may provide an interface for the system 1400 to communicate with any other suitable apparatus. The input/output device(s) 1410 may include communication components, audio components, sensor components, and the like. The network interface 1412 may provide an interface for the system 1400 to communicate through one or more networks. The system 1400 may communicate with one or more of the wireless network standards and/or protocols according to any of the one or more wireless network standards and/or protocols. The components perform wireless communication, such as connecting to wireless networks based on communication standards, such as Wi-Fi, 2G, or 3G, or a combination of them for wireless communication.

[0452] For an example embodiment, at least one of the processor(s) 1402 may be packaged with the logic of one or more controllers of the system control module 1404 (for example, a memory controller module). For an example embodiment, at least one of the processor(s) 1402 may be packaged with the logic of one or more controllers of the system control module 1404 to

form a system in package (SiP). For an example embodiment, at least one of the processor(s) 1402 and the logic of one or more controllers of the system control module 1404 may be integrated on the same mold. For an example embodiment, at least one of the processor(s) 1402 and the logic of one or more controllers of the system control module 1404 may be integrated on the same mold to form a system on chip (SoC).

[0453] In each example embodiment, the system 1400 may be, but is not limited to a browser, a workstation, a desktop computing apparatus, or a mobile computing apparatus (for example, a laptop computing apparatus, a handheld computing apparatus, a tablet computer, a netbook, etc.). In an example embodiment, the system 1400 may have more or fewer components and/or different architectures. For example, in some example embodiments, the system 1400 includes one or more cameras, keyboards, liquid crystal display (LCD) screens (including touch screen displays), non-volatile memory ports, multiple antennas, graphics chips, application-specific integrated circuits (ASIC) and speakers.

[0454] If the display includes a touch panel, the display screen may be implemented as a touch screen display to receive input signals from the user. The touch panel includes one or more touch sensors to sense touch, sliding, and gestures on the touch panel. The touch sensor may not only sense the boundary of a touch or slide action, but also detect the duration and pressure related to the touch or slide operation.

[0455] The example embodiments of the present disclosure also provide a non-volatile readable storage medium. The storage medium stores one or more modules (programs). When the one or more modules are applied to the terminal apparatus, the terminal apparatus execute the instructions for each step of the above-mentioned method in the example embodiments of the present disclosure.

[0456] In an example, an apparatus is provided, and the apparatus includes: one or more processors; and, one or more machine-readable media having instructions stored thereon, when executed by the one or more processors, causing the apparatus to execute the instructions of each step of the above-mentioned method in the example embodiments of the present disclosure.

[0457] Each example embodiment in this manual is described in a progressive manner. Each example embodiment focuses on the difference from other example embodiments. For the same and similar parts of each example embodiment, please refer to each other.

[0458] Those skilled in the art should understand that the example embodiments of the example embodiments of the present disclosure may be provided as clients, devices, or computer program products. Therefore, the example embodiments of the present disclosure may take the form of complete hardware embodiments, complete software embodiments, or embodiments that combine software and hardware. Moreover, the example embodiments of the present disclosure may take the form of computer program products implemented on one or more computer-usable storage media (including but not

limited to disk storage, CD-ROM, optical storage, etc.) containing computer-usable program codes.

[0459] The example embodiments of the present disclosure are described with reference to the flowcharts and/or block diagrams of the client, terminal apparatus (system), and computer program products of the example embodiments of the present disclosure. It should be understood that each process and/or block in the flowchart and/or block diagram, and the combination of processes and/or blocks in the flowchart and/or block diagram may be realized by computer program instructions. These computer program instructions may be provided to the processor of a general-purpose computer, a special-purpose computer, an embedded processor or other programmable data processing terminal apparatus to generate a machine, so that the instructions executed by the processor of the computer or other programmable data processing terminal apparatus produce means for realizing the functions designated in one or more processes in the flowchart and/or one or more blocks in the block diagram.

[0460] These computer program instructions may also be stored in a computer-readable media that may guide a computer or other programmable data processing terminal apparatus to work in a manner that the instructions stored in the computer-readable media produce an article of manufacture including the instruction device. The instruction device implements the functions designated in one process or multiple processes in the flowchart and/or one block or multiple blocks in the block diagram.

[0461] These computer program instructions may also be loaded on a computer or other programmable data processing terminal apparatus, so that a series of operation steps are executed on the computer or other programmable terminal apparatus to generate computer-implemented processing, so that the instructions executed on the computer or other programmable terminal apparatus provide steps for implementing functions designated in a flow or multiple flows in the flowchart and/or a block or multiple blocks in the block diagram.

[0462] Although the preferable embodiment of the embodiments of the present disclosure have been described, those skilled in the art may make additional changes and modifications to these example embodiments once they learn the present disclosure. Therefore, the appended claims are intended to be interpreted as including the example embodiments and all changes and modifications falling within the scope of the example embodiments of the present disclosure.

[0463] Finally, it should be noted that in this disclosure, relational terms such as first and second are only used to distinguish one entity or operation from another entity or operation, and do not necessarily require or imply that there is any such actual relationship or sequence between these entities or operations. Moreover, the terms "include", "comprise" or any other variants thereof are intended to cover non-exclusive inclusion, so that a process, client, item or terminal apparatus including a series of elements not only includes those elements, but also includes those elements that are not explicitly

included. The other elements listed may also include elements inherent to this process, client, item, or terminal apparatus. Without more restrictions, the element defined by the sentence "including a..." does not exclude the existence of other same elements in the process, client, article, or terminal apparatus that includes the element.

[0464] The above provides a detailed introduction to the methods for network configuration and network configuration system for smart apparatuses provided by the present disclosure. Specific examples are used in this article to explain the principles and implementation of the present disclosure. The above description of example embodiments is only used to help understand the client and its core ideas of the present disclosure. Meanwhile, for those skilled in the art, according to the ideas of the present disclosure, there will be changes in implementations and scope of application. In summary, the content of the description should not be construed as a limitation on the present disclosure.

CLAIMS

WHAT IS CLAIMED IS:

1. A method, comprising:
 - connecting, by an apparatus, to a network configuration hotspot provided by a router;
 - sending first apparatus information of the apparatus to a server through the network configuration hotspot;
 - receiving a hotspot switching command sent by the server according to the first apparatus information, wherein the hotspot switching command includes hotspot information of an online hotspot; and
 - connecting to the online hotspot based on the hotspot switching command when a designated network configuration condition is met.
2. The method according to claim 1, wherein connecting, by the apparatus, to the network configuration hotspot provided by the router comprises:
 - obtaining a network configuration hotspot list, wherein the network configuration hotspot list includes at least one network configuration hotspot and/or signal strength of the network configuration hotspot;
 - connecting to the network configuration hotspot with the strongest signal strength; and

when the connecting fails, connecting to the network configuration hotspot with a second strongest signal strength until the connecting to the network configuration hotspot succeeds.

3. The method according to claim 2, wherein sending first apparatus information of the apparatus to the server through the network configuration hotspot comprises:

sending a connection request to the server through the network configuration hotspot to establish a secure connection between the apparatus and the server;

obtaining the first apparatus information of the apparatus; and

sending the first apparatus information and the network configuration hotspot list to the server.

4. The method according to claim 1, wherein before receiving the hotspot switching command sent by the server, the method further comprises:

entering a network configuration mode when a touch operation of a user is detected.

5. The method according to claim 4, wherein the designated network configuration condition at least includes the following condition:

the apparatus entering the network configuration mode, and duration of entering the network configuration mode does not exceed a preset duration.

6. The method according to claim 1, further comprising:
generating network configuration error information when the designated network configuration condition is not met; and
sending the network configuration error information to the server.

7. The method according to claim 1, wherein after connecting to the online hotspot based on the hotspot switching command when the designated network configuration condition is met, the method further comprises:

obtaining second apparatus information of the apparatus; and
announcing the second apparatus information to the outside locally, and/or establishing a secure connection with the server based on the online hotspot, and sending the second apparatus information to the server.

8. One or more computer-readable media, stored thereon computer-readable instructions that, when executed by one or more processors, cause the one or more processors to perform acts comprising:

determining, by a network configuration application, a target network configuration apparatus, wherein the target network configuration apparatus connects to a network configuration hotspot provided by a router in advance and sends first apparatus information of the target network configuration apparatus to a server;

generating a network configuration request based on the first apparatus information and hotspot information of a currently connected online hotspot; and

sending the network configuration request to the server to request the server to perform network configuration on the apparatus according to the hotspot information of the online hotspot.

9. The one or more computer-readable media according to claim 8, wherein after sending the network configuration request to the server to request the server to perform the network configuration on the apparatus according to the hotspot information of the online hotspot, the acts further comprises:

receiving network configuration response information returned by the server based on the network configuration request, wherein the network configuration response information includes network configuration approval information, and the network configuration approval information includes instruction information of user touch operation;

displaying the network configuration approval information;

upon determining that a user performs a touch operation based on the network configuration approval information, generating network configuration preparation information; and

sending the network configuration preparation information to the server to notify the server to perform the network configuration on the apparatus.

10. The one or more computer-readable media according to claim 9, wherein the network configuration response information further includes network configuration rejection information, and the method further comprises:

displaying the network configuration rejection information to prompt the user to prohibit operating the apparatus.

11. The one or more computer-readable media according to any one of claims 8, wherein before determining by the network configuration application the target network configuration apparatus, the method further comprises:

connecting, by the network configuration application, to the online hotspot of the router and establishing a secure connection with the server.

12. The one or more computer-readable media according to claim 11, wherein determining, by the network configuration application, the target network configuration apparatus comprises:

determining the hotspot information of the online hotspot;

obtaining a to-be-network-configured apparatus list from the server side based on the hotspot information, the to-be-network-configured apparatus list including one or more apparatus to be network-configured, and first apparatus information of the apparatus;

displaying the to-be-network-configured apparatus list; and

setting the apparatus selected by a user in the to-be-network-configured apparatus list as the target network configuration apparatus.

13. The one or more computer-readable media according to claim 8, the acts further comprising:

obtaining second apparatus information of the apparatus, wherein the second apparatus information is apparatus information after the network configuration of the apparatus succeeds;

determining that the network configuration of the apparatus succeeds based on the second apparatus information; and

generating network configuration success information, and displaying the network configuration success information.

14. The one or more computer-readable media according to claim 13, wherein obtaining the second apparatus information of the apparatus comprises:

receiving the second apparatus information broadcast by the apparatus; or
broadcasting a query request in local, and receiving the second apparatus information returned by the apparatus based on the query request.

15. The one or more computer-readable media according to claim 13, further comprising:

generating a binding request based on the second apparatus information;

sending the binding request to the server to request the server to bind the second apparatus information and a corresponding apparatus; and

receiving a binding result returned by the server based on the binding request.

16. An apparatus comprising:

one or more processors; and

memory communicatively coupled to the one or more processors, the memory storing computer-executable modules executable by the one or more processors, the computer-executable modules including:

a network configuration hotspot connection module, configured to connect to a network configuration hotspot provided by a router;

a first apparatus information sending module, configured to send a first apparatus information of the apparatus to a server through the network configuration hotspot;

a hotspot switching command receiving module, configured to receive a hotspot switching command sent by the server according to the first apparatus information, the hotspot switching command including hotspot information of an online hotspot; and

a hotspot switching module, configured to connect to the online hotspot based on the hotspot switching command when a designated network configuration condition is met.

17. The apparatus according to claim 16, wherein the network configuration hotspot connection module includes:

a network configuration hotspot list obtaining sub-module, configured to obtain a network configuration hotspot list, wherein the network configuration hotspot list includes at least one network configuration hotspot and/or signal strength of the network configuration hotspot; and

a network configuration hotspot connection sub-module, configured to connect to the network configuration hotspot with the strongest signal strength; and when the connecting fails, connect to the network configuration hotspot with a second strongest signal strength until the connecting to the network configuration hotspot succeeds.

18. The apparatus according to claim 17, the first apparatus information sending module includes:

a secure connection establishment sub-module, configured to send a connection request to the server through the network configuration hotspot to establish a secure connection with the apparatus and the server;

a first apparatus information obtaining sub-module, configured to obtain the first apparatus information of the apparatus; and

a first apparatus information sending sub-module, configured to send the first apparatus information and the network configuration hotspot list to the server.

19. The apparatus according to claim 16, the computer-executable modules further comprising:

a network configuration mode module, configured to enter a network configuration mode when a touch operation of a user is detected.

20. The apparatus according to claim 19, wherein the designated network configuration conditions include at least the following condition:

the apparatus entering the network configuration mode, and duration of entering the network configuration mode does not exceed a preset duration.