

Description

The invention generally relates to a method for transferring a photographic image from a liquid treated donor to one side of a receiver without wetting the opposite side of the receiver, as specified in the pre-characterising portion of claim 1 and to an apparatus for carrying out this method.

In photographic image transfer processes, for example, as described in US-A-4,223,991, an emulsion-bearing donor is exposed imagewise and is soaked in liquid activator to develop a latent image. The activated wet donor is placed in registration with a dry paper receiver and the two sheets are fed through a pair of rollers, where they are pressed together, beginning the diffusion transfer of the developed image from the donor to the receiver and wringing excess liquid from the donor. When image transfer is completed, usually after several minutes, the donor is peeled from the image side of the receiver to reveal a finished print.

Some of the excess liquid removed from the donor collects at the entry nip of the rollers. If such liquid, referred to as a meniscus, is allowed to remain in the entry nip after the donor and receiver are fed through the rollers, it will evaporate, leaving a corrosive residue at the entry nip, which may eventually damage the rollers or cause them to adhere to one another. When successive pairs of donors and receivers are fed through the rollers, a new meniscus will be transferred to the rollers each time a donor-receiver pair is introduced into the rollers. This causes the roller that contacts the receiver to spread activator as a non-uniform thin covering onto the back side of the receiver.

This is undesirable for a number of reasons. For example, the formation of dried activator salts on the back side of a receiver is undesirable from a cosmetic standpoint and, in view of the high alkalinity of the salts, touching of them should be avoided. Moreover, activator salts on the back side of a receiver, prevents stacking of several receivers because the salts may transfer from the back side of one receiver to the image side of an adjacent receiver, possibly damaging the image. More importantly, however, the non-uniform wetting of the back side causes a temperature difference between the wet and dry areas of the back side due to evaporative cooling of the wet areas. This temperature difference produces undesirable differences in image density between the wet and dry areas.

Therefore, the back side of each receiver should be kept dry during image-transfer processing of successive pairs of donors and receivers. To accomplish this, it has been proposed that the meniscus at the entry nip of the pressure rollers be removed immediately after a donor-receiver pair is fed through the rollers. In US-A-3,271,187, an endless web surrounds the roller that contacts the back side of each receiver. The web has a diameter substantially greater than that

of the roller it surrounds, is sufficiently rigid to retain its cylindrical shape, and includes a plurality of minute openings for entrapping the liquid comprising the meniscus as the rollers are rotated. The liquid entrapped in the openings is expelled from the openings by passing a gas through them. Unfortunately, the roller that contacts the back side of each receiver may become wet from a mist produced by gas expelling the liquid from the openings in the web.

In US-A-3,357,337, the roller that contacts the back side of each receiver includes a plurality of radial openings connected with a vacuum source. When the rollers are rotated in contact with one another, following exit of a donor and receiver from between the rollers, the liquid comprising the meniscus is drawn from the roller nip through the radial openings, leaving the rollers substantially dry. With this structure, the radial openings in the roller can produce a non-uniform surface pressure on a donor and receiver, which may undesirably affect imaging on the receiver.

More important than the technical limitations mentioned above, these prior art devices require compressed air or vacuum pumps. Such structure is not practical in the low-to-medium volume applications intended for the manually operated structure shown in US-A-4,223,991.

It is the object of the invention to provide an image transfer process in which donor-receiver pairs are fed between first and second rollers, with the first roller contacting the back of the receiver which process avoids wetting the back side of the receiver but uses apparatus simple enough for low or medium volume applications, i.e., does not require compressed air or vacuum pumps.

This object is accomplished by passing excess liquid at the entrance of the nip of the rollers through a gap between the rollers when empty of donor-receiver pairs and removing from the first roller liquid passed through the gap.

This object is also accomplished by apparatus for carrying out such method in which the first roller has a surface easily wetted by the liquid and the apparatus includes means for removing liquid from the first roller, means for rotating the first roller in the absence of a donor-receiver pair and means for providing a gap between the rollers wide enough to permit passage of the liquid when the first roller is rotated in the absence of a donor-receiver pair but narrow enough to laminate the donor and receiver when fed therebetween.

According to a preferred embodiment, the second roller has a surface which resists wetting by the liquid.

Fig. 1 is a perspective view of an image-transfer processor in accordance with a preferred embodiment of the invention;

Fig. 2 is a view similar to Fig. 1, showing an exposed donor sheet placed on a donor ramp of the processor and a receiver sheet placed on a receiver shelf of the processor;

Fig. 3 is a view similar to Fig. 1, showing how the donor is guided into a tray filled with liquid activator in the processor;

Fig. 4 is a view similar to Fig. 1, showing how the donor treated with the liquid and the dry receiver are fed between rollers, where they are pressed together, beginning the transfer of the developed image from the donor to the receiver and wringing excess liquid from the donor;

Fig. 5 is an elevational sectional view taken on the line 5—5 of Fig. 6 of the rollers and a squeegee member in the processor of Fig. 1; and

Fig. 6 is an elevational sectional view of the rollers and the squeegee member as seen in the direction of the arrows from the lines 6—6 in Fig. 5.

Referring now to Fig. 1 of the drawings, there is shown an image-transfer processor for making several size color prints from color negatives and slides. The color negatives are exposed onto a donor sheet of negative film and the slides are exposed onto a donor sheet of reversal film. Then, on the processor, the exposed donor is soaked in a water-based activator liquid to develop the latent image. After several seconds, the soaked donor is laminated to a receiver sheet of dry print paper, which begins the diffusion transfer of the developed image from the donor to the receiver. In a few minutes, the laminated donor and receiver are manually peeled apart to reveal a finished color print on the receiver.

To operate the processor, as shown in Fig. 2, a receiver P is placed image receiving, i.e., front side down on several upstanding ribs 1, which define a receiver feed shelf 3 of a pivotally mounted cover 5. A trailing edge T of the receiver P is inserted under two or more tines 7 of a receiver advance rake 9, and one longitudinal edge of the receiver is located against a fixed receiver edge guide 11. The tines 7 extend between respective pairs of the upstanding ribs 1 to hold the receiver P at its trailing edge T. A sheet of exposed donor F is placed emulsion side up on a donor loading ramp 13. The respective longitudinal edges of the donor are inserted under a fixed donor edge guide 15 and a movable donor edge guide 17. An upper edge U of the donor is inserted under two tines 19 and 21 of a donor-loading ramp slide 23. The edge guide 17 is adjustable to accommodate several size donor sheets, and the ramp slide 23 is releasably held in place by several clips, not shown, on the ramp 13. A relatively light spring, not shown, may be included to help keep the donor F from sliding down the ramp 13.

To immerse the donor F in the activator liquid in a liquid tray 25, beneath the cover 5, the ramp slide 23 is moved down the loading ramp 13, as shown in Fig. 3. This advances the donor F through a donor entry slot 27 in the cover 5, and onto a plurality of support ribs, not shown, beneath the level of the activator liquid in the tray 25. As soon as the donor is completely immersed in the activator liquid, the slide 23 may be moved back up the ramp 13, until it locks under the

holding clips, not shown. At the end of the activator soak time, e.g., 20 seconds at room temperature, or several seconds before, rotation of a hand crank 29 in a clockwise direction, as viewed in Fig. 4, is begun. This causes a first, upper lamination roller 31 and a second, lower lamination roller 33, adjacent a donor exit side of the liquid tray 25, to rotate in counterclockwise and clockwise directions, respectively, as viewed in Fig. 4. Once the soak time is complete, a donor advance rake handle 35 is moved towards the rotating rollers 31 and 33. The handle 35 is fixed to a donor advance rake, not shown, beneath the cover 5, and, as shown in Fig. 4, extends through a slot 37 in the receiver advance rake 9. After the handle 35 is moved several centimeters to one end 39 of the slot 37, it pushes the receiver advance rake 9 along the receiver feed shelf 3 in unison with movement of the donor advance rake along the liquid tray 25. Movement of the donor advance rake is begun before movement of the receiver advance rake to substantially equalize the respective paths taken by the donor and receiver into the lamination rollers. The receiver P is advanced by the receiver rake 9 through a receiver entry slot, not shown, beneath a pivotally mounted receiver feed guide 41 on the cover 5, and arrives at the rollers in registration with the donor F. After the donor F and the receiver P enter the lamination rollers 31 and 33, movement of the rake handle 35 is stopped; however, rotation of the hand crank 29 is continued until the laminated donor and receiver are completely out of a laminate exit slot 43, adjacent the rollers. As the donor and receiver are moved through the lamination rollers at a speed preferably in the range of 50 mm/sec to 250 mm/sec, they are sandwiched together, beginning the transfer of the developed image by diffusion from the donor to the receiver and wringing excess activator liquid from the donor into a catch tray, not shown, beneath the rollers. When transfer is complete, e.g., after six to fifteen minutes depending on temperature, the donor is peeled from the receiver to reveal a finished color print.

As excess activator is removed from the donor F by passage through the first and second rollers 31 and 33, in Fig. 4, some of the removed liquid collects as a meniscus between the donor and the second, lower roller. This meniscus remains at the entry nip of the rollers after the donor and receiver have exited from the rollers.

If rollers 31 and 33 are constructed according to the prior art, i.e., in contact with each other when not in use, and if successive donor-receiver pairs are advanced through the rollers, movement of a donor-receiver pair into the entry nip of the rollers causes any meniscus M of liquid left in the nip to be immediately smeared back over the dry back side B of the receiver P. The remainder of the meniscus M remains on the rollers, causing the upper roller 31, which contacts the back side B of the receiver, to spread activator liquid as a non-uniform thin covering onto the back side of

the receiver. This is undesirable for the reasons stated above.

According to the invention, which is shown in Figs. 5 and 6, such back-side wetting of the receiver is prevented by (a) passing the meniscus M through a permanent gap 63 between the rollers ahead of each pair of the donor and receiver and (b) removing the activator liquid passed through the gap from the upper roller 31, to dry that roller before contacting the back side of the next receiver. The liquid is passed through the gap 63 by the rotating action of the upper roller which is constructed of a material easily wetted by the liquid.

As shown in Fig. 5, the means for removing activator liquid from the upper roller 31 comprises a squeegee member, for example, squeegee blade 65, mounted on the cover 5 and having a free end 67 disposed in wiping contact with the upper roller. The squeegee blade 65 can be constructed from a suitable thin flexible material, such as stainless steel, and must provide enough force against the upper roller to wipe activator liquid off the roller. Typically, the viscosity of the activator liquid is close to that of water.

The means for providing the permanent gap 63 between the upper and lower rollers 31 and 33 is shown in Fig. 6 and comprises a first pair of collars or spacers 71, at opposite ends of the first upper roller, and a second pair of collars or spacers 73, at opposite ends of the second lower roller. As distinguished from the rollers 31 and 33, which are constructed of a compliant material, the collars 71 and 73 are constructed of a non-compliant material. The gap 63 is less than the combined thickness of the donor F and the receiver P and typically may vary, for example, from 0.025 mm (.001 inches) to 0.225 mm (.009 inches). The collars 71 and 73 are maintained in contact with one another by the compressive force of two springs 75 that bear against a central flexible shaft 77 of the upper roller 31, adjacent the opposite ends of the shaft, as shown in Fig. 6. A flexible central shaft 79 of the lower roller 33 is supported by two upstanding bearing ribs 81, adjacent the opposite ends of the shaft. Such an arrangement where the ends of the shafts 77 and 79 are pressed together between the springs 75 against the supporting ribs 81 causes a slight bowing of both rollers 31 and 33, as shown somewhat exaggerated in Fig. 6, making the gap 63 widest midway between the opposite ends of the rollers.

The upper roller 31 is hydrophilic, i.e., is easily wetted by the water-based activator liquid; whereas, the lower roller 33 is hydrophobic, i.e., resists wetting by the activator liquid. When the upper and lower rollers are rotated without the donor F and the receiver P between them, as depicted in Fig. 5, the meniscus M of activator liquid at the entry nip 61 will be conveyed by the upper roller through the gap 63. A portion of the liquid will remain with the upper roller 31 until removed by the free end 67 of the squeegee blade

65 the squeegee blade 65 wipes successive surface portions of the rotating roller 31 dry before they contact the back side B of the receiver P.

The remaining part of the liquid will continue to the bottom of lower roller 33 where because the roller is hydrophobic the liquid drops off into a catch tray (not shown).

An example of the invention includes a first, upper roller made of silicone rubber having additives and surface characteristics making it wettable by the liquid. One such roller is obtainable from the Ames Company, Hamburg, New Jersey, U.S.A., identified by the manufacturer as compound 7773-A. The second lower roller can be made also of silicone rubber but having additives and surface characteristics making it resistant to wetting by the liquid. One such roller is obtainable from Winfield Industries, Buffalo, New York, U.S.A., identified by the manufacturer as compound W-816. The squeegee member is made as described above. With these materials and a donor-receiver pair approximately 0.5 mm (.020 inches) thick, rollers having a gap of 0.125 mm (.005 inches) successfully laminated the donor-receiver pairs and allowed excess liquid in the nip to pass through the nip between laminations. The back of each receiver stayed dry even though thirty successive donor-receiver pairs were laminated.

Claims

1. A method of transferring images from successive liquid-treated donors (F) to the front sides of successive receivers (P) without wetting the back sides of the receivers (P), wherein successive pairs of the donors (F) and receivers (P) are fed between first (31) and second (33) rollers with the front side of each receiver (P) contacting a donor (F) and the back side of each receiver contacting the first roller (31), in the course of which excess liquid is removed from the donor (F) and after each pair exits from the rollers (31, 33) a portion of the removed liquid has a tendency to remain at an entry nip of the rollers (31, 33), characterized in that the method further includes the steps of passing said portion of the liquid through a gap (63) maintained between the rollers (31, 33) when empty of donor-receiver pairs and removing from the first roller liquid passed through the gap (63).

2. Apparatus specifically designed for carrying out the method of claim 1, characterized in that the first roller (31) has a surface which is easily wetted by the liquid, and the apparatus includes means (65) for removing liquid from the first roller (31), means for rotating the first roller in the absence of a donor-receiver pair and means for providing a gap between the rollers wide enough to permit passage of liquid when the first roller is rotated in the absence of a donor-receiver pair but narrow enough to laminate the donor and receiver when fed between the rollers (31, 33).

3. Apparatus according to claim 2, wherein the

the receiver. This is undesirable for the reasons stated above.

According to the invention, which is shown in Figs. 5 and 6, such back-side wetting of the receiver is prevented by (a) passing the meniscus M through a permanent gap 63 between the rollers ahead of each pair of the donor and receiver and (b) removing the activator liquid passed through the gap from the upper roller 31, to dry that roller before contacting the back side of the next receiver. The liquid is passed through the gap 63 by the rotating action of the upper roller which is constructed of a material easily wetted by the liquid.

As shown in Fig. 5, the means for removing activator liquid from the upper roller 31 comprises a squeegee member, for example, squeegee blade 65, mounted on the cover 5 and having a free end 67 disposed in wiping contact with the upper roller. The squeegee blade 65 can be constructed from a suitable thin flexible material, such as stainless steel, and must provide enough force against the upper roller to wipe activator liquid off the roller. Typically, the viscosity of the activator liquid is close to that of water.

The means for providing the permanent gap 63 between the upper and lower rollers 31 and 33 is shown in Fig. 6 and comprises a first pair of collars or spacers 71, at opposite ends of the first upper roller, and a second pair of collars or spacers 73, at opposite ends of the second lower roller. As distinguished from the rollers 31 and 33, which are constructed of a compliant material, the collars 71 and 73 are constructed of a non-compliant material. The gap 63 is less than the combined thickness of the donor F and the receiver P and typically may vary, for example, from 0.025 mm (.001 inches) to 0.225 mm (.009 inches). The collars 71 and 73 are maintained in contact with one another by the compressive force of two springs 75 that bear against a central flexible shaft 77 of the upper roller 31, adjacent the opposite ends of the shaft, as shown in Fig. 6. A flexible central shaft 79 of the lower roller 33 is supported by two upstanding bearing ribs 81, adjacent the opposite ends of the shaft. Such an arrangement where the ends of the shafts 77 and 79 are pressed together between the springs 75 against the supporting ribs 81 causes a slight bowing of both rollers 31 and 33, as shown somewhat exaggerated in Fig. 6, making the gap 63 widest midway between the opposite ends of the rollers.

The upper roller 31 is hydrophilic, i.e., is easily wetted by the water-based activator liquid; whereas, the lower roller 33 is hydrophobic, i.e., resists wetting by the activator liquid. When the upper and lower rollers are rotated without the donor F and the receiver P between them, as depicted in Fig. 5, the meniscus M of activator liquid at the entry nip 61 will be conveyed by the upper roller through the gap 63. A portion of the liquid will remain with the upper roller 31 until removed by the free end 67 of the squeegee blade

65 the squeegee blade 65 wipes successive surface portions of the rotating roller 31 dry before they contact the back side B of the receiver P.

The remaining part of the liquid will continue to the bottom of lower roller 33 where because the roller is hydrophobic the liquid drops off into a catch tray (not shown).

An example of the invention includes a first, upper roller made of silicone rubber having additives and surface characteristics making it wettable by the liquid. One such roller is obtainable from the Ames Company, Hamburg, New Jersey, U.S.A., identified by the manufacturer as compound 7773-A. The second lower roller can be made also of silicone rubber but having additives and surface characteristics making it resistant to wetting by the liquid. One such roller is obtainable from Winfield Industries, Buffalo, New York, U.S.A., identified by the manufacturer as compound W-816. The squeegee member is made as described above. With these materials and a donor-receiver pair approximately 0.5 mm (.020 inches) thick, rollers having a gap of 0.125 mm (.005 inches) successfully laminated the donor-receiver pairs and allowed excess liquid in the nip to pass through the nip between laminations. The back of each receiver stayed dry even though thirty successive donor-receiver pairs were laminated.

Claims

1. A method of transferring images from successive liquid-treated donors (F) to the front sides of successive receivers (P) without wetting the back sides of the receivers (P), wherein successive pairs of the donors (F) and receivers (P) are fed between first (31) and second (33) rollers with the front side of each receiver (P) contacting a donor (F) and the back side of each receiver contacting the first roller (31), in the course of which excess liquid is removed from the donor (F) and after each pair exits from the rollers (31, 33) a portion of the removed liquid has a tendency to remain at an entry nip of the rollers (31, 33), characterized in that the method further includes the steps of passing said portion of the liquid through a gap (63) maintained between the rollers (31, 33) when empty of donor-receiver pairs and removing from the first roller liquid passed through the gap (63).

2. Apparatus specifically designed for carrying out the method of claim 1, characterized in that the first roller (31) has a surface which is easily wetted by the liquid, and the apparatus includes means (65) for removing liquid from the first roller (31), means for rotating the first roller in the absence of a donor-receiver pair and means for providing a gap between the rollers wide enough to permit passage of liquid when the first roller is rotated in the absence of a donor-receiver pair but narrow enough to laminate the donor and receiver when fed between the rollers (31, 33).

3. Apparatus according to claim 2, wherein the



second roller (33) has a surface which resists wetting by the liquid.

4. Apparatus according to claim 2 or 3, wherein the first roller (31) is positioned above the second roller (33).

Revendications

1. Un procédé pour transférer des images d'organes donneurs successifs (F) traités par un liquide vers les faces frontales d'organes récepteurs successifs (P) sans mouiller les faces dorsales des organes récepteurs (P), suivant lequel des paires successives d'organes donneurs (F) et d'organes récepteurs (P) sont passées entre des premier (31) et deuxième (33) rouleaux, la face frontale de chaque organe récepteur (P) étant en contact avec un organe donneur (F) tandis que la face dorsale de chaque organe récepteur est en contact avec le premier rouleau (31), au cours duquel procédé on retire du liquide en excès de l'organe donneur (F) alors qu'après l'émergence de chaque paire au-delà des rouleaux une partie du liquide enlevé tend à rester dans le pincement d'entrée des rouleaux (31, 33), caractérisé en ce que le procédé comprend en outre les étapes suivant lesquelles on fait passer cette partie du liquide à travers un espace (63) ménagé entre les rouleaux (31, 33) lorsque cet espace est vide de paires d'organes récepteurs et donneurs et on enlève du premier rouleau le liquide qui a traversé l'espace (63).

2. Appareil particulièrement conçu pour mettre en oeuvre le procédé conforme à la revendication 1, caractérisé en ce que le premier rouleau (31) présente une surface facilement mouillée par le liquide, l'appareil comprenant un moyen (65) pour enlever du liquide du premier rouleau (31), un moyen pour faire tourner le premier rouleau en l'absence d'une paire d'organes donneur et récepteur et un moyen pour établir un espace entre les rouleaux, assez large pour permettre le passage du liquide lorsque le premier rouleau tourne en l'absence d'une paire d'organes donneur et récepteur mais assez étroit pour laminier l'organe donneur et l'organe récepteur lorsqu'ils passent entre les rouleaux (31, 33).

3. Appareil conforme à la revendication 2, dans lequel le deuxième rouleau (33) présente une surface qui résiste au mouillage par le liquide.

4. Appareil conforme à la revendication 2 ou 3, dans lequel le premier rouleau est placé au-dessus du deuxième rouleau.

Patentansprüche

1. Verfahren zum Übertragen von Bildern von aufeinanderfolgenden flüssigkeitsbehandelten Spenderelementen (F) auf die Vorderseite aufeinanderfolgender Empfängererelemente (P), ohne daß dabei die Rückseite der Empfängererelemente (P) mit Flüssigkeit benetzt wird, wobei aufeinanderfolgende Paare aus Spenderelementen (F) und Empfängererelementen (P) zwischen einer ersten Walze (31) und einer zweiten Walze (33) hindurchtransportiert werden und die Vorderseite eines jedem Empfängererelements (P) mit einem Spendererelement (F) und die Rückseite eines jeden Empfängererelements mit der ersten Walze (31) in Berührung kommen und wobei während dieses Transports überschüssige Flüssigkeit von dem Spendererelement (F) entfernt wird und nach dem jeweiligen Austreten eines Paares von Elementen ein Teil der Flüssigkeit dazu neigt, an einem Eingangsspalt der Walzen (31, 33) zu verharren, dadurch gekennzeichnet, daß in weiteren Arbeitsschritten des Verfahrens der Flüssigkeitsteil durch einen Spalt (63) geleitet wird, der zwischen den Walzen (31, 33) offen bleibt, wenn sich keine Paare von Spender- und Empfängererelementen in ihm befinden und daß durch den Spalt (63) hindurchgeleitete Flüssigkeit von der ersten Walze entfernt wird.

2. Vorrichtung zur Durchführung des Verfahrens nach Anspruch 1, dadurch gekennzeichnet, daß die erste Walze (31) eine durch die Flüssigkeit leicht benetzbare Oberfläche besitzt und die Vorrichtung Mittel (65) zum Entfernen der Flüssigkeit von der ersten Walze (31) aufweist sowie Mittel zum Drehen der ersten Walze in Abwesenheit eines Paares von Spender- und Empfängererelementen und Mittel zur Erzeugung eines Spaltes zwischen den Walzen, der so breit ist, daß Flüssigkeit durch ihn hindurchgelangen kann, wenn die erste Walze in Abwesenheit eines Paares von Spender- und Empfängererelementen gedreht wird, jedoch eng genug, um das Spendererelement und das Empfängererelement fest miteinander zu verbinden, wenn diese zwischen den Walzen (31, 33) hindurchgeführt werden.

3. Vorrichtung nach Anspruch 2, worin die zweite Walze (33) eine flüssigkeitsabweisende Oberfläche besitzt.

4. Vorrichtung nach Anspruch 2 oder 3, worin die erste Walze (31) über der zweiten Walze (33) angeordnet ist.

