



- (51) **International Patent Classification:**
E21B 34/06 (2006.01) *E21B 43/26* (2006.01)
- (21) **International Application Number:**
PCT/US2011/053344
- (22) **International Filing Date:**
27 September 2011 (27.09.2011)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (71) **Applicant (for all designated States except US):** HAL-
LIBURTON ENERGY SERVICES, INC. [US/US];
10200 Bellaire Boulevard, Houston, TX 77072 (US).
- (72) **Inventors; and**
- (75) **Inventors/Applicants (for US only):** FRANKLIN, Mat-
thew, Earl [US/US]; 650 N. Leora Lane, Apt. 11212,
Lewisville, TX 75056 (US). LOPEZ, Jean-marc [FR/US];
7308 Stoddard Lane, Plano, TX 75025 (US).
- (74) **Agent:** JORDAN, Carey, C.; McDermott Will & Emery
LLP, 600 13th Street, N.W., Washington, DC 20005-3096
(US).

- (81) **Designated States (unless otherwise indicated, for every
kind of national protection available):** AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,
CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO,
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN,
HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME,
MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ,
OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD,
SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) **Designated States (unless otherwise indicated, for every
kind of regional protection available):** ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU,
TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,
DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) **Title:** WELLBORE FLOW CONTROL DEVICES COMPRISING COUPLED FLOW REGULATING ASSEMBLIES AND METHODS FOR USE THEREOF




FIG. 2A

(57) **Abstract:** Wellbore flow control devices can be used in various subterranean operations to regulate access of formation fluids to the interior of a wellbore pipe and/or to limit the access of unwanted fluids thereto. Coupling of flow regulating assemblies to one another in the wellbore flow control devices can result in improved operational performance in regulating formation fluid flow to the interior of the wellbore pipe compared to using the flow regulating assemblies in an uncoupled state. Wellbore flow control devices can comprise a gate valve assembly that is in fluid flow communication with a flow restricting assembly, where each assembly is located on the exterior of a wellbore pipe and the flow restricting assembly is in fluid flow communication with the interior of the wellbore pipe.

